

SEMICONDUCTORS GENERAL CATALOG

ICS
TRANSISTORS
THYRISTORS
DIODES
LIGHT EMITTING DIODES



SANKEN ELECTRIC CO., LTD.

<http://www.sanken-ele.co.jp/en/index.html>

Warning

- The contents in this document are subject to changes, for improvement and other purposes, without notice. Make sure that this is the latest version of the document before use.
- The operation and circuit examples in this document are provided for reference purposes only. Sanken assumes no liability for violation of industrial property, intellectual property, or other rights of Sanken or third parties, that stem from these examples.
- The user must take responsibility for considering and determining which objects the products in this document are used with.
- Although we will continue to improve the quality and reliability of our products, semiconductor products, by their nature, have certain fault and failure rates. The user must take responsibility for designing and checking to secure the device and system so that a part failure may not lead to human injury, fire, damages, or other losses.
- The products in this document are intended for normal electronic devices (such as home appliances, office equipment, communication terminals, or measurement devices). Make delivery specifications with us before use.
If you are considering using our products for a device that requires high reliability (such as transport machines and their control units, traffic light control systems, disaster prevention, and security equipment or any kind of safety equipment), make sure that you consult our sales representative and make delivery specifications with us.
Do not use these products for devices that require extremely high reliability (such as aerospace instruments, nuclear power control units, or life support systems) without our written consent.
- The products in this document are not designed to be radiation-proof.
- The contents in this document must not be transcribed or copied without our written consent.
- Gallium arsenide (GaAs) is used in some products in this document.
Burning or breaking such products, as well as the accidental inhalation or ingestion of chemically treated liquids and gases, is extremely dangerous.

SANKEN SEMICONDUCTORS

CONTENTS

1 IC

1-1	Regulator IC	4
1-1-1	Linear Regulator IC	7
1-1-2	Switching Mode Regulator IC	63
1-1-3	Multi-Output Type Regulator IC	97
1-2	Motor Driver IC	120
1-2-1	2-Phase Stepper Motor Unipolar Driver ICs	122
1-2-2	3-Phase Stepper Motor Driver ICs	142
1-3	ICs for Switching Mode Power Supplies	144

2 Transistor

2-1	Transistor	149
2-2	MOS FET	160
2-3	Transistor and MOS FET Array	166

3 Thyristor

3-1	Thyristor	192
3-2	Triac	194
3-3	PNPN Switch Element	196

4 Diode

4-1	Rectifier Diode	207
4-2	Fast Recovery Diode	209
4-3	Ultrafast Recovery Diode	211
4-4	Schottky Barrier Diode	214
4-5	High Voltage Rectifier Diode	217
4-6	Dumper Diode	218
4-7	Avalanche Diode with Built-in Thyristor	220
4-8	Power Zener Diode	221
4-9	Silicon Varistor	222

5 LED

5-1	Visible Light LED	236
5-2	Infrared LED	251
5-3	Ultraviolet Surface Mount LED	252

Ordering Information	259
----------------------------	-----

Part Number Index in Alphanumeric Order	261
---	-----

Discontinued Products and Service Parts (NND)	273
---	-----

IC

1

1-1	Regulator IC	4
	Selection Guide	4
1-1-1	Linear Regulator IC	7
	Application Note	7
1-1-2	Switching Mode Regulator IC	63
	Application Note	63
1-1-3	Multi-Output Type Regulator IC	97
	Application Note	97
1-2	Motor Driver IC	120
	Selection Guide	120
	Application Note	121
1-2-1	2-Phase Stepper Motor Unipolar Driver ICs	122
1-2-2	3-Phase Stepper Motor Driver ICs	142
1-3	ICs for Switching Mode Power Supplies	144

Selection Guide

Linear Regulator IC (low dropout voltage, built-in overcurrent, thermal protection circuits*)

*: No thermal protection circuit in SI-3000V series.

Surface-Mount Type

Series Name	Output Current (A)	Output Voltage (V)							Variable (Reference Voltage) (V)					Package	Low Current Consumption During OFF	Output ON/OFF	Overcurrent Protection Characteristic	Page
		1.8	2.5	3.3	5	9	12	15	1.0	1.1	1.25	1.28	2.5					
		SI-3000LUS	0.25	○	○	○	○											
SI-3000LU	0.25	○	△	○	○							○		SOT89-5	○	○	Drooping	10
SI-3000HM	0.5			△	△	△	△						△	TO252-5	○	○	Foldback	12
SI-3000LSA	1.0	○	○	○	○									SOP8	○	○	Foldback	14
SI-3000KS	1.0	○	○	○								○		SOP8	○	○	Drooping	16
SI-3000KMS	1.0	○	○	○	○	○	△	△						TO252-3	–	–	Foldback*1	18
SI-3000KM	1.0	○	○	○	○	○	○	△	○			○		TO252-5	○	○	Foldback*2	20
SI-3000KD	1.0	○	○	○	○	△	△	△	○			○		TO263-5	○	○	Foldback*3	24
SI-3000LLSL	1.5								○					SOP8	○	○	Foldback	28
SI-3000ZD	3.0		○	○								○		TO263-5	○	○	Foldback	30

△: Sample available

○: Available

*1: Drooping for SI-3018KMS/3025KMS/3033KMS

*2: Drooping for SI-3012KM/3018KM/3025KM/3033KM

*3: Drooping for SI-3012KD/3018KD/3025KD/3033KD

Thru-hole Type

Series Name	Output Current (A)	Output Voltage (V)								Variable (Reference Voltage) (V)			Package	Low Current Consumption During OFF	Output ON/OFF	Overcurrent Protection Characteristic	Page	
		1.8	2.5	3.3	5	9	12	15	15.7	24	1	1.1						2.55
		SI-3000B	0.27									○						
SI-3000N	1.0				○	△	○	○						TO220F-3	–	–	Foldback	34
SI-3003N	1.0				○		○	○						TO220F-3	–	–	Drooping	36
SI-3000F	1.0				○	○	○	○	○	○			○	TO220F-5	–	○	Foldback	38
SI-3000KF	1.0	○	△	○	△	△	△	△			○			TO220F-5	○	○	Foldback	42
SI-3001N	1.5				○	○	○	○	○				○	TO220F-3	–	–	Foldback	46
SI-3000C	1.5				○	○	○	○	○				○	TO220F-5	–	○	Foldback*4	48
SI-3000R	1.5				○									TO220F-5	–	○	Drooping	52
SI-3002N	2.0				○	○	○	○						TO220F-3	–	–	Foldback	54
SI-3000V	2.0				○		○	○						TO3P	–	–	Foldback	56
SI-3000J	2.0				○	○	○	○						TO220F-5	–	○	Foldback	58
SI-3000ZF	3.0		○	○								○		TO220F-5	○	○	Foldback	60

△: Sample available

○: Available

*4: Drooping for SI-3033C

Switching Mode Regulator IC (built-in overcurrent, thermal protection circuits)

Surface-Mount Type

Series Name	Output Current (A)	Output Voltage (V)						Variable (Reference Voltage) (V)			Maximum Input Voltage (V)	Package	Low Current Consumption During OFF	Output ON/OFF	Overcurrent Protection Characteristic	Page
		2.5	3.3	5	9	12	15	1.0	1.1	1.25						
SAI	0.4				○	○					35	PS-4	–	–	Drooping	64
	0.5		○	○												
SI-8000W	0.6		○	○							35	SOP8	–	–	Drooping	66
SI-8000JD	1.5		○	○	○	○					43	TO263-5	○	○	Foldback	68
SI-8000SD	3.0		○	○							43	TO263-5	–	○	Drooping	70
SPI-8000A	3.0							○			53	HSOP16	○	○	Foldback	72
SI-8000RD	3.0		△	○							30*	TO263-5	–	○	Drooping	76

*: 21V for SI-8033RD

Thru-hole Type

Series Name	Output Current (A)	Output Voltage (V)						Variable (Reference Voltage) (V)			Maximum Input Voltage (V)	Package	Low Current Consumption During OFF	Output ON/OFF	Overcurrent Protection Characteristic	Page
		2.5	3.3	5	9	12	15	1.0	1.5	2.55						
SI-8000E	0.6			○		○					43	TO220F-5	–	–	Drooping	78
SI-8000JF	1.5	○	○	○	○	○			○		43	TO220F-5	○	○	Foldback	80
SI-8000GL	1.5							○			53	DIP8	○	○	Foldback	82
SI-8000S	3.0		○	○	○	○	○				43*	TO220F-5	–	○	Drooping	84

*: 35V for SI-8033S

Surface-Mount, Synchronous Rectifier Type

Series Name	Oscillation Frequency (kHz)	Output Voltage (V)						Variable (Reference Voltage) (V)			Maximum Input Voltage (V)	Package	Low Current Consumption During OFF	Output ON/OFF	Overcurrent Protection Characteristic	Page
		2.5	3.3	5	9	12	15	1.0	1.1	1.25						
SI-8011NVS	250								○		25	SSOP-24	–	○	Foldback	86
SI-8511NVS	400								○		25	SSOP-24	–	○	Drooping	88

Flywheel Diode (Schottky-Barrier Diode) Built-in Type

Series Name	Output Current (A)	Output Voltage (V)						Variable (Reference Voltage) (V)			Maximum Input Voltage (V)	Package	Low Current Consumption During OFF	Output ON/OFF	Overcurrent Protection Characteristic	Page
		2.5	3.3	5	6.5	12	15	1.0	1.1	2.55						
STA810M	1.5				○						43	SIP-8	○	○	Foldback	90
STA820M	3.0			○							31	SIP-8	–	○	Drooping	92

L-combined Type

Series Name	Output Current (A)	Output Voltage (V)						Variable (Reference Voltage) (V)			Maximum Input Voltage (V)	Package	Low Current Consumption During OFF	Output ON/OFF	Overcurrent Protection Characteristic	Page
		2.5	3.3	5	9	12	15	1.0	1.1	2.55						
SI-8400L	0.4					○					35	Non-package type	–	–	Drooping	94
	0.5		○	○												
SI-8500L	1.0		○	○	○	○					35	Non-package type	–	○	Drooping	94

Multi Output Type Regulator IC

2-Output Type

Series Name		Output Voltage	Output Current	Package	Regulator Type	Functions			Low Current Consumption During OFF	Remarks	Page
		(V)	(A)			Overcurrent Protection	Thermal Protection	ON/OFF Control			
STA801M	ch1	5.0	0.5	SIP-10	Step-down switching type	Drooping	○	○	-	Flywheel diode (Schottky-barrier diode)	98
	ch2	Select from 9, 11.5, 12.1 and 15.5	0.5		Step-down switching type	Drooping	○	○	-	Flywheel diode (Schottky-barrier diode)	
STA802M	ch1	9.0	0.5	SIP-10	Step-down switching type	Drooping	○	○	-	Flywheel diode (Schottky-barrier diode)	98
	ch2	Select from 9.1, 11.7, 12.1 and 15.7	0.5		Step-down switching type	Drooping	○	○	-	Flywheel diode (Schottky-barrier diode)	
SDI02	ch1	5.0	0.5	PS-16	Linear type	Vo shutdown after operation	○	○	-		100
	ch2	5.0	0.5			Vo shutdown after operation	○	○			
SPI-8001TW	ch1	Variable(1.0-16V)	1.5	HSOP-16	Step-down switching type	Foldback	○	○	○		104
	ch2	Variable(1.0-16V)	1.5			Foldback	○	○			
SPI-8002TW	ch1	Variable(1.0-24V)	1.5	HSOP-16	Step-down switching type	Foldback	○	○	○		104
	ch2	Variable(1.0-24V)	1.5			Foldback	○	○			
SI-3002KWF	ch1	3.3	1.0	TO220F-5	Linear type	Foldback	○	○	-		108
	ch2	2.5	1.0			Foldback	○	○			
SI-3002KWD	ch1	3.3	1.0	TO263-5	Linear type	Foldback	○	○	-		110
	ch2	2.5	1.0			Foldback	○	○			
SI-3002KWM	ch1	3.3	1.0	TO252-5	Linear type	Foldback	○	○	-		112
	ch2	2.5	1.0			Foldback	○	○			
SI-3003KWF	ch1	2.5	1.0	TO220F-5	Linear type	Foldback	○	○	-		108
	ch2	1.8	1.0			Foldback	○	○			
SI-3003KWD	ch1	2.5	1.0	TO263-5	Linear type	Foldback	○	○	-		110
	ch2	1.8	1.0			Foldback	○	○			
SI-3003KWM	ch1	2.5	1.0	TO252-5	Linear type	Foldback	○	○	-		112
	ch2	1.8	1.0			Foldback	○	○			

3-Output Type

Series Name		Output Voltage	Output Current	Package	Regulator Type	Functions			Low Current Consumption During OFF	Remarks	Page
		(V)	(A)			Overcurrent Protection	Thermal Protection	ON/OFF Control			
SLA3002M	ch1	5.0	0.5	SLA15Pin	Step-down switching type	Drooping	○	-	-		114
	ch2	15.7	1.0		Linear type	Foldback	○	○			
	ch3	9.0	0.4		Step-down switching type	Drooping	○	-			
SLA3004M	ch1	5.0	0.5	SLA15Pin	Step-down switching type	Drooping	○	-	-		114
	ch2	9.0	0.4		Step-down switching type	Drooping	○	-			
	ch3	9.0	0.4		Step-down switching type	Drooping	○	-			

4-Output Type

Series Name		Output Voltage	Output Current	Package	Regulator Type	Functions			Low Current Consumption During OFF	Remarks	Page
		(V)	(A)			Overcurrent Protection	Thermal Protection	ON/OFF Control			
SLA3005M	ch1	5.0	0.5	SLA18Pin	Linear type	Vo shutdown after operation	○	○	-		116
	ch2	5.0	0.5		Linear type	Vo shutdown after operation	○	○			
	ch3	5.0	0.5		Linear type	Vo shutdown after operation	○	○			
	ch4	5.0	0.5		Linear type	Vo shutdown after operation	○	○			
SLA3006M	ch1	5.0	0.5	SLA18Pin	Linear type	Drooping	○	○	-		116
	ch2	5.0	0.5		Linear type	Drooping	○	○			
	ch3	5.0	0.5		Linear type	Drooping	○	○			
	ch4	5.0	0.5		Linear type	Drooping	○	○			
SLA3007M	ch1	5.0	0.5	SLA18Pin	Linear type	Vo shutdown after operation	○	○	-		116
	ch2	5.0	0.5		Linear type	Vo shutdown after operation	○	○			
	ch3	5.0	0.5		Linear type	Vo shutdown after operation	○	○			
	ch4	3.3	0.5		Linear type	Drooping	○	○			

Application Note

Heat dissipation and Reliability

The reliability of an IC is highly dependent on its operating temperature. Please be sure to apply silicone grease to the IC and to mount it to the heatsink with a proper mounting torque. Heatsink design should pay particular attention to ensuring sufficient heat dissipation capacity. In addition, please take into account the air convection in operation.

Calculating Internal Power Dissipation(P_D)


P_D is given by the following formula:

$$P_D = I_O \cdot [V_{IN(\text{mean})} - V_O]$$

Determine the size of the heatsink according to the relationship between allowable power dissipation and ambient temperature.

Setting DC Input Voltage

The following is the waveform of a DC input voltage.



When setting the DC input voltage, please follow the instructions below:

- Make $V_{IN(\text{min})} \geq [(\text{Output voltage}) + (\text{Minimum dropout voltage})]$
- Make $V_{IN(\text{max})} \leq$ DC input voltage shown in the "Absolute Maximum Ratings"

Thermal Design

The maximum junction temperature $T_{J(\text{max})}$ given in the absolute maximum ratings is specific to each product type and must be strictly observed. Thus, thermal design must consider the maximum power dissipation $P_{D(\text{max})}$, which varies by the conditions of use, and the maximum ambient temperature $T_{a(\text{max})}$. To simplify thermal design, T_a - P_D characteristic graphs are provided herein. Please observe the following steps for heatsink design:

1. Obtain the maximum ambient temperature $T_{a(\text{max})}$.
2. Obtain the maximum power dissipation $P_{D(\text{max})}$.
3. Look for the intersection point on the T_a - P_D characteristic graph and determine the size of the heatsink.

Although the heatsink size is now obtained, in actual applications, 10-to-20% derating factor is generally introduced. Moreover, the heat dissipation capacity of a heatsink highly depends on how it is mounted. Thus, it is recommended to measure the heatsink and case temperature in the actual operating environment.

Please refer to the T_a - P_D characteristic graphs for respective product types.

Mounting Torque

SI-3000B	0.588 to 0.686 [N•m] (6.0 to 7.0 [kgf•cm])
SI-3000C	
SI-3000F	
SI-3000J	
SI-3000KF	
SI-3000N	
SI-3000R	
SI-3000ZF	
SI-3001N	
SI-3002N	
SI-3003N	0.686 to 0.882 [N•m] (7.0 to 9.0 [kgf•cm])
SI-3000V	

Recommended Silicone Grease

- Shin-Etsu Chemical Co., Ltd.: G746
- GE Toshiba Silicones Co., Ltd.: YG-6260
- Dow Corning Toray Silicones Co., Ltd.: SC102

Please select proper silicone grease carefully since the oil in some grease products may penetrate the device and result in an extremely short device life.

Others

- Devices can not be operated in parallel connection aiming for a larger current.
- Diodes for isolation purpose are provided in between input and ground, and also in between output and ground. They may be broken down if the device is reverse biased. In this case, please clamp the device with low V_f diodes to protect them.

Rectifier Diodes for Power Supplies

To rectify the AC input voltage using rectifier diodes for power supplies, please use SANKEN rectifier diodes shown in the following list. (Please use a center-tap or bridge configuration in using stand-alone type diodes.)

Series Name	Diodes
SI-3000B Series	AM01Z(Axial Type, $V_{RM}:200V, I_O:1.0A$)
SI-3000C Series	RM2Z(Axial Type, $V_{RM}:200V, I_O:1.2A$) or RBV-402(Bridge Type, $V_{RM}:200V, I_O:4.0A$)
SI-3000F Series	
SI-3000J Series	SFPM-62(Surface-Mount Stand-Alone Type, $V_{RM}:200V, I_O:1.0A$)
SI-3000ZD Series	
SI-3000KD Series	RM2Z(Axial Type, $V_{RM}:200V, I_O:1.2A$) or RBV-402(Bridge Type, $V_{RM}:200V, I_O:4.0A$)
SI-3000KF Series	
SI-3000KM Series	
SI-3000KMS Series	SFPM-62(Surface-Mount Stand-Alone Type, $V_{RM}:200V, I_O:1.0A$)
SI-3000KS Series	
SI-3000HM Series	SFPM-52(Surface-Mount Stand-Alone Type, $V_{RM}:200V, I_O:0.9A$)
SI-3000LLSL Series	
SI-3000LSA Series	RM2Z(Axial Type, $V_{RM}:200V, I_O:1.2A$) or RBV-402(Bridge Type, $V_{RM}:200V, I_O:4.0A$)
SI-3000LU Series	
SI-3000LUS Series	
SI-3000N Series	
SI-3000R Series	
SI-3000V Series	
SI-3000ZF Series	
SI-3001N Series	
SI-3002N Series	
SI-3003N Series	

SI-3000LUS Series Surface-Mount, Low Current Consumption, Low Dropout Voltage Linear Regulator IC

Features

- Compact surface-mount package (SOT-89-3)
- Output current: 250 mA
- Low dropout voltage: $V_{DIF} \leq 0.5$ V (at $I_O = 250$ mA)
- 4 types of output voltages (1.8 V, 2.5 V, 3.3 V, 5.0 V) available
- Built-in drooping-type-overcurrent and thermal protection circuits

Absolute Maximum Ratings

(T_a=25°C)

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V _{IN}	18	V
DC Output Current	I _O	250	mA
Power Dissipation	P _D ^{*1}	0.75	W
Junction Temperature	T _j ²	-40 to +135	°C
Storage Temperature	T _{stg} ^{*2}	-40 to +125	°C
Thermal Resistance (Junction to Ambient Air)	θ _{j-a} ^{*1}	146	°C/W

*1: When mounted on glass-epoxy board 40 × 40 mm (copper laminate area 2%)

*2: Thermal protection circuits may operate if the junction temperature exceeds 135°C

Applications

- Auxiliary power supplies for PC
- Battery-driven electronic equipment

Recommended Operating Conditions

Parameter	Symbol	Ratings		Unit
		min.	max.	
Input Voltage	V _{IN}	*2	V _O +2 ^{*1}	V
DC Output Current	I _O	0	250	mA
Operating Ambient Temperature	T _{op}	-20	85	°C

*1: V_{IN} (max) and I_O (max) are restricted by the relation P_D = (V_{IN} - V_O) × I_O.

Calculate these values referring to the reference data on page 9.

*2: Refer to the Dropout Voltage parameter.

Electrical Characteristics


(T_a=25°C, V_C=2V unless otherwise specified)

Parameter	Symbol	Ratings												Unit
		SI-3018LUS (Under development)			SI-3025LUS (Under development)			SI-3033LUS			SI-3050LUS (Under development)			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Output Voltage	V _O	1.764	1.800	1.836	2.450	2.500	2.550	3.234	3.300	3.366	4.900	5.000	5.100	V
	Conditions	V _{IN} =3.3V, I _O =10mA			V _{IN} =3.3V, I _O =10mA			V _{IN} =5V, I _O =10mA			V _{IN} =6V, I _O =10mA			
Dropout Voltage	V _{DIF}			0.5			0.3			0.3			0.3	V
	Conditions	I _O =100mA												
	Conditions	I _O =250mA												
Line Regulation	ΔV _{LINE}			10			10			10			10	mV
	Conditions	V _{IN} =3.3 to 5V, I _O =10mA			V _{IN} =3.3 to 5V, I _O =10mA			V _{IN} =4.5 to 8V, I _O =10mA			V _{IN} =6 to 10V, I _O =10mA			
Load Regulation	ΔV _{LOAD}			40			40			40			40	mV
	Conditions	V _{IN} =3.3V, I _O =0 to 250mA			V _{IN} =3.3V, I _O =0 to 250mA			V _{IN} =5V, I _O =0 to 250mA			V _{IN} =6V, I _O =0 to 250mA			
Temperature Coefficient of Output Voltage	ΔV _O /ΔT _a			±0.25			±0.25			±0.3			±0.3	mV/°C
	Conditions	T _j =0 to 100°C												
Ripple Rejection	R _{REJ}			55			55			55			55	dB
	Conditions	V _{IN} =3.3V, f=100 to 120Hz			V _{IN} =3.3V, f=100 to 120Hz			V _{IN} =5V, f=100 to 120Hz			V _{IN} =6V, f=100 to 120Hz			
Quiescent Circuit Current	I _q			250			250			250			250	μA
	Conditions	V _{IN} =3.3V, I _O =0mA			V _{IN} =3.3V, I _O =0mA			V _{IN} =5V, I _O =0mA			V _{IN} =6V, I _O =0mA			
Overcurrent Protection Starting Current ^{*1}	I _{S1}	260			260			260			260			mA
	Conditions	V _{IN} =3.3V			V _{IN} =3.3V			V _{IN} =5V			V _{IN} =6V			

*1: I_{S1} is specified at the 5% drop point of output voltage V_O on the condition that V_{IN}=3.3 V (5 V for SI-3033LUS, 6 V for SI-3050LUS), and I_O=10 mA.

External Dimensions


(Unit : mm)




Block Diagram



Typical Connection Diagram



Reference Data



SI-3000LU Series Surface-Mount, Low Current Consumption, Low Dropout Voltage Linear Regulator IC

■ Features

- Compact surface-mount package (SOT-89-5)
- Output current: 250 mA
- Low current consumption I_q (OFF) $\leq 1\mu\text{A}$ ($V_c = 0\text{ V}$)
- Low dropout voltage: $V_{DIF} \leq 0.5\text{ V}$ (at $I_o = 250\text{ mA}$)
- 5 types of output voltages (Adj, 1.8 V, 2.5 V, 3.3 V, 5.0 V) available
- Built-in drooping-type-overcurrent and thermal protection circuits

■ Absolute Maximum Ratings

($T_a=25^\circ\text{C}$)

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V_{IN}	18	V
Output control terminal voltage	V_c	V_{IN}	V
DC Output Current	I_o	250	mA
Power Dissipation	P_D^{*1}	0.75	W
Junction Temperature	T_J^{*2}	-40 to +135	$^\circ\text{C}$
Storage Temperature	T_{stg}^{*2}	-40 to +125	$^\circ\text{C}$
Thermal Resistance (Junction to Ambient Air)	θ_{JA}^{*1}	146	$^\circ\text{C/W}$

*1: When mounted on glass-epoxy board 40 × 40 mm (copper laminate area 2%)

*2: Thermal protection circuits may operate if the junction temperature exceeds 135 $^\circ\text{C}$

■ Applications

- Auxiliary power supplies for PC
- Battery-driven electronic equipment

■ Recommended Operating Conditions

Parameter	Symbol	Ratings		Unit
		min.	max.	
Input Voltage	V_{IN}	*2, *3	V_O+2^{*1}	V
DC Output Current	I_o	0	250	mA
Operating Ambient Temperature	T_{op}	-20	85	$^\circ\text{C}$

*1: V_{IN} (max) and I_o (max) are restricted by the relation $P_D = (V_{IN} - V_O) \times I_o$.

Calculate these values referring to the reference data on page 11.

*2: Refer to the Dropout Voltage parameter.

*3: For the SI-3012LU, set the input voltage to $V_{in} \geq 2.4\text{ V}$, and secure the minimum voltage as explained in "Setting DC Input Voltage" section in Linear Regulator Application Note on page 7.

■ Electrical Characteristics

($T_a=25^\circ\text{C}$, $V_c=2\text{V}$ unless otherwise specified)

Parameter	Symbol	Ratings															Unit	
		SI-3012LU(Variable)			SI-3018LU(Under development)			SI-3025LU(Under development)			SI-3033LU			SI-3050LU				
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.		
Output Voltage ^{*3}	$V_O(V_{ADJ})$	1.210	1.250	1.290	1.764	1.800	1.836	2.450	2.500	2.550	3.234	3.300	3.366	4.900	5.000	5.100	V	
Dropout Voltage	V_{DIF}	0.3			0.5			0.3			0.3			0.3			V	
	Conditions	$I_o=100\text{mA}(V_O=3.3\text{V})$			$I_o=100\text{mA}$			$I_o=100\text{mA}$			$I_o=100\text{mA}$			$I_o=100\text{mA}$				
	Conditions	$I_o=250\text{mA}(V_O=3.3\text{V})$			$I_o=250\text{mA}$			$I_o=250\text{mA}$			$I_o=250\text{mA}$			$I_o=250\text{mA}$				
Line Regulation	ΔV_{LINE}	10			10			10			10			15			mV	
	Conditions	$V_{IN}=V_O+1\text{ to }V_O+5\text{V}, I_o=10\text{mA}(V_O=3.3\text{V})$			$V_{IN}=2.5\text{ to }5\text{V}, I_o=10\text{mA}$			$V_{IN}=3.3\text{ to }5\text{V}, I_o=10\text{mA}$			$V_{IN}=4.5\text{ to }8\text{V}, I_o=10\text{mA}$			$V_{IN}=6\text{ to }10\text{V}, I_o=10\text{mA}$				
Load Regulation	ΔV_{LOAD}	20			20			40			40			40			mV	
	Conditions	$V_{IN}=V_O+1\text{V}, I_o=1\text{ to }250\text{mA}(V_O=3.3\text{V})$			$V_{IN}=3.3\text{V}, I_o=1\text{ to }250\text{mA}$			$V_{IN}=3.3\text{V}, I_o=0\text{ to }250\text{mA}$			$V_{IN}=5\text{V}, I_o=0\text{ to }250\text{mA}$			$V_{IN}=6\text{V}, I_o=0\text{ to }250\text{mA}$				
Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T_a$	± 0.3			± 0.2			± 0.25			± 0.3			± 0.3			mV/ $^\circ\text{C}$	
	Conditions	$T_J=0\text{ to }100^\circ\text{C}$																
Ripple Rejection	R_{REJ}	55			55			55			55			55			dB	
	Conditions	$V_{IN}=V_O+1\text{V}, f=100\text{ to }120\text{Hz}(V_O=3.3\text{V})$			$V_{IN}=3.3\text{V}, f=100\text{ to }120\text{Hz}$			$V_{IN}=3.3\text{V}, f=100\text{ to }120\text{Hz}$			$V_{IN}=5\text{V}, f=100\text{ to }120\text{Hz}$			$V_{IN}=6\text{V}, f=100\text{ to }120\text{Hz}$				
Quiescent Circuit Current	I_q	150			150			150			150			150			μA	
	Conditions	$V_{IN}=V_O+1\text{V}, I_o=0\text{mA}, V_c=2\text{V}, R_2=100\text{k}\Omega$			$V_{IN}=3.3\text{V}, I_o=0\text{mA}, V_c=2\text{V}$			$V_{IN}=3.3\text{V}, I_o=0\text{mA}, V_c=2\text{V}$			$V_{IN}=5\text{V}, I_o=0\text{mA}, V_c=2\text{V}$			$V_{IN}=6\text{V}, I_o=0\text{mA}, V_c=2\text{V}$				
Circuit Current at Output OFF	$I_q(\text{OFF})$	1			1			1			1			1			μA	
	Conditions	$V_{IN}=V_O+1\text{V}, V_c=0\text{V}$			$V_{IN}=3.3\text{V}, V_c=0\text{V}$			$V_{IN}=3.3\text{V}, V_c=0\text{V}$			$V_{IN}=5\text{V}, V_c=0\text{V}$			$V_{IN}=6\text{V}, V_c=0\text{V}$				
Overcurrent Protection Starting Current ^{*1}	I_{S1}	260			260			260			260			260			mA	
	Conditions	$V_{IN}=V_O+1\text{V}$			$V_{IN}=3.3\text{V}$			$V_{IN}=3.3\text{V}$			$V_{IN}=5\text{V}$			$V_{IN}=6\text{V}$				
V_c Terminal	Control Voltage (Output ON) ^{*2}	V_c, I_H	2.0		2.0		2.0		2.0		2.0		2.0		2.0		V	
	Control Voltage (Output OFF) ^{*2}	V_c, I_L	0.8		0.8		0.8		0.8		0.8		0.8		0.8			
	Control Current (Output ON)	I_c, I_H	40		40		40		40		40		40		40			μA
	Control Current (Output OFF)	I_c, I_L	0		0		0		0		0		0		0			
		Conditions	$V_c=0\text{V}$															


*1: I_{S1} is specified at the 5% drop point of output voltage V_O on the condition that $V_{IN} = 3.3\text{ V}$ (5 V for SI-3033LU, 6 V for SI-3050LU), and $I_o = 10\text{ mA}$.

*2: Output is OFF when the output control terminal (V_c terminal) is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.


*3: Reference voltage V_{ADJ} for SI-3012LU.

External Dimensions


(Unit : mm)




Block Diagram



Standard External Circuit



Reference Data



SI-3000HM Series Surface-Mount, Low Dropout Voltage Linear Regulator IC

■Features

- Compact surface-mount package (TO252-5)
- Output current: 0.5A
- Low dropout voltage: $V_{DIF} \leq 0.6V$ (at $I_O = 0.5A$)
- Low circuit current at output OFF: $I_Q (OFF) \leq 1\mu A$
- Built-in overcurrent and thermal protection circuits

■Absolute Maximum Ratings

($T_a=25^\circ C$)

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V_{IN}^{*1}	35	V
Output Control Terminal Input Voltage	V_C	V_{IN}	V
DC Output Current	I_O	0.5	A
Power Dissipation	P_D^{*2}	1	W
Junction Temperature	T_J	-30 to +125	$^\circ C$
Storage Temperature	T_{stg}	-40 to +125	$^\circ C$
Thermal Resistance (Junction to Ambient Air)	θ_{JA}^{*3}	95	$^\circ C/W$
Thermal Resistance (Junction to Case)	θ_{JC}	6	$^\circ C/W$

■Applications

- Secondary stabilized power supply (local power supply)

■Recommended Operating Conditions

Parameter	Symbol	Ratings					Unit
		SI-3200HM	SI-3033HM	SI-3050HM	SI-3090HM	SI-3120HM	
Input Voltage Range	V_{IN}	4.0 ^{*4} to 27 ^{*3}	4.0 to 10 ^{*3}	*4 to 15 ^{*3}	*4 to 20 ^{*3}	*4 to 25 ^{*3}	V
Output Current Range	I_O	0 to 0.5					A
Operating Ambient Temperature	T_{op}	-30 to +85					$^\circ C$
Operating Junction Temperature	T_J	-20 to +100					$^\circ C$

*1: A built-in input-Overvoltage-protection circuit shuts down the output voltage at the Input Overvoltage Shutdown Voltage of the electrical characteristics.

*2: When mounted on glass-epoxy board of 900m² (copper laminate area 4.3%)

*3: V_{IN} (max) and I_O (max) are restricted by the relation $P_D = (V_{IN} - V_O) \times I_O$. Please calculate these values referring to the relation between the copper laminate area and power dissipation.

*4: Refer to the Dropout Voltage parameter.

■Electrical Characteristics

Parameter	Symbol	Ratings															Unit
		SI-3200HM ^{*1} (Variable type: under development)			SI-3033HM(Under development)			SI-3050HM(Under development)			SI-3090HM(Under development)			SI-3120HM(Under development)			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Output Voltage ^{*3} Reference Voltage V_{ADJ} for SI-3200HM	$V_O (V_{ADJ})$	2.425	2.500	2.575	3.234	3.300	3.366	4.90	5.00	5.10	8.82	9.00	9.18	11.76	12.00	12.24	V
	Conditions	$V_{IN}=7V, I_O=0.01A$			$V_{IN}=5V, I_O=0.01A$			$V_{IN}=7V, I_O=0.01A$			$V_{IN}=11V, I_O=0.01A$			$V_{IN}=14V, I_O=0.01A$			
Line Regulation	ΔV_{OLINE}	25			17			25			45			60			mV
	Conditions	$V_{IN}=6$ to 15V, $I_O=0.01A$			$V_{IN}=5$ to 10V, $I_O=0.01A$			$V_{IN}=6$ to 15V, $I_O=0.01A$			$V_{IN}=10$ to 20V, $I_O=0.01A$			$V_{IN}=13$ to 25V, $I_O=0.01A$			
Load Regulation	ΔV_{LOAD}	50			33			50			90			120			mV
	Conditions	$V_{IN}=7V, I_O=0$ to 0.5A			$V_{IN}=5V, I_O=0$ to 0.5A			$V_{IN}=7V, I_O=0$ to 0.5A			$V_{IN}=11V, I_O=0$ to 0.5A			$V_{IN}=14V, I_O=0$ to 0.5A			
Dropout Voltage	V_{DIF}	0.3			0.7			0.3			0.3			0.3			V
	Conditions	$I_O=0.3A$			$I_O=0.3A$			$I_O=0.3A$			$I_O=0.3A$			$I_O=0.3A$			
		0.5			0.7			0.5			0.5			0.5			
	Conditions	$I_O=0.5A$			$I_O=0.5A$			$I_O=0.5A$			$I_O=0.5A$			$I_O=0.5A$			
Quiescent Circuit Current	I_Q	3			3			3			3			3			mA
	Conditions	$V_{IN}=7V, I_O=0A, V_C=2V$			$V_{IN}=5V, I_O=0A, V_C=2V$			$V_{IN}=7V, I_O=0A, V_C=2V$			$V_{IN}=11V, I_O=0A, V_C=2V$			$V_{IN}=14V, I_O=0A, V_C=2V$			
Circuit Current at Output OFF	$I_Q (OFF)$	1			1			1			1			1			μA
	Conditions	$V_{IN}=7V, V_C=0V$			$V_{IN}=5V, V_C=0V$			$V_{IN}=7V, V_C=0V$			$V_{IN}=11V, V_C=0V$			$V_{IN}=14V, V_C=0V$			
Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T_a$	± 0.5			± 0.3			± 0.5			± 1.0			± 1.5			mV/ $^\circ C$
	Conditions	$T_J=0$ to 100 $^\circ C$			$T_J=0$ to 100 $^\circ C$			$T_J=0$ to 100 $^\circ C$			$T_J=0$ to 100 $^\circ C$			$T_J=0$ to 100 $^\circ C$			
Ripple Rejection	R_{REJ}	75			78			75			72			68			dB
	Conditions	$V_{IN}=7V, f=100$ to 120Hz, $I_O=0.1A$			$V_{IN}=5V, f=100$ to 120Hz, $I_O=0.1A$			$V_{IN}=7V, f=100$ to 120Hz, $I_O=0.1A$			$V_{IN}=11V, f=100$ to 120Hz, $I_O=0.1A$			$V_{IN}=14V, f=100$ to 120Hz, $I_O=0.1A$			
Overcurrent Protection Starting Current ^{*1*4}	I_{S1}	0.6			0.6			0.6			0.6			0.6			A
	Conditions	$V_{IN}=7V$			$V_{IN}=5V$			$V_{IN}=7V$			$V_{IN}=11V$			$V_{IN}=14V$			
V_C Terminal	Control Voltage (Output ON) ^{*2}	V_C, IH	2		2		2		2		2		2		2		V
	Control Voltage (Output OFF)	V_C, IL		0.8		0.8		0.8		0.8		0.8		0.8		0.8	V
	Control Current (Output ON)	I_C, IH		40		40		40		40		40		40		40	μA
	Control Current (Output OFF)	I_C, IL	-5	0	-5	0	-5	0	-5	0	-5	0	-5	0	-5	0	μA
	Conditions	$V_C=2V$			$V_C=2V$			$V_C=2V$			$V_C=2V$			$V_C=2V$			
	Conditions	$V_C=0V$			$V_C=0V$			$V_C=0V$			$V_C=0V$			$V_C=0V$			
Input Overvoltage Shutdown Voltage	V_{OVP}	33			26			26			30			33			V
	Conditions	$I_O=0.01A$			$I_O=0.01A$			$I_O=0.01A$			$I_O=0.01A$			$I_O=0.01A$			
Output Noise Voltage	V_O noise	50			33			50			80			110			μV_{rms}
	Conditions	$V_{IN}=7V, I_O=0.1A, V_C=2V, C_O=1000\mu F$			$V_{IN}=5V, I_O=0.1A, C_O=1000\mu F$			$V_{IN}=7V, I_O=0.1A, V_C=2V, C_O=1000\mu F$			$V_{IN}=11V, I_O=0.1A, V_C=2V, C_O=1000\mu F$			$V_{IN}=14V, I_O=0.1A, V_C=2V, C_O=1000\mu F$			

*1: I_{S1} is specified at the 5% drop point of output voltage V_O under the condition of Output Voltage parameter.

*2: Output is OFF when the output control terminal V_C is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.


*3: The above ratings of SI-3200HM represents the characteristics at $V_O = 5V$ ($R_2 = 12.5k\Omega$). V_O can be set from 3.3V to 20V for SI-3200HM.

*4: These products cannot be used in the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.


- (1) Constant current load, (2) Positive and negative power supply, (3) Series-connected power supply, (4) V_O adjustment by raising ground voltage

External Dimensions


(Unit : mm)




Block Diagram



Typical Connection Diagram



Reference Data



SI-3000LSA Series Surface-Mount, Low Current Consumption, Low Dropout Voltage Linear Regulator IC

Features

- Compact surface-mount package (SOP-8)
- Output current: 1 A
- Low circuit current at output OFF: $I_{q(OFF)} \leq 1 \mu A$ ($V_C = 0 V$)
- Low dropout voltage: $V_{DIF} \leq 0.8 V$ (at $I_O = 1 A$)
 $V_{DIF} \leq 1.2 V$ ($I_O = 1 A$) for SI-3018LSA
- 4 types of output voltages (1.8 V, 2.5 V, 3.3 V, 5.0 V) available
- Output ON/OFF control terminal voltage compatible with LS-TTL
- Built-in drooping-type-overcurrent and thermal protection circuits

Absolute Maximum Ratings

($T_a = 25^\circ C$)

Parameter	Symbol	Rated	Unit
DC Input Voltage	V_{IN}	16	V
Output control terminal voltage	V_C	V_{IN}	V
DC Output Current	I_O	1	A
Power Dissipation	P_{D1}^{*1}	1.16	W
	P_{D2}^{*2}	1.1	W
Junction Temperature	T_J^{*3}	-30 to +150	$^\circ C$
Operating Ambient Temperature	T_{OP}	-30 to +150	$^\circ C$
Storage Temperature	T_{STG}	-30 to +150	$^\circ C$
Thermal Resistance (Junction to Lead (pin 8))	θ_{J-L}	36	$^\circ C/W$
Thermal Resistance (Junction to Ambient Air)	θ_{J-a}^{*2}	100	$^\circ C/W$

*1: When mounted on glass-epoxy board 56.5 x 56.5 mm (copper laminate area 100%)

*2: When mounted on glass-epoxy board 40 x 40 mm (copper laminate area 100%).

*3: Thermal protection circuits may be activated if the junction temperature exceeds 135 $^\circ C$

Applications

- Auxiliary power supplies for PC
- Battery-driven electronic equipment

Recommended Operating Conditions

Parameter	Symbol	Ratings				Unit
		SI-3018LSA	SI-3025LSA	SI-3033LSA	SI-3050LSA	
DC Input Voltage Range	V_{IN}	3.1 to 3.5 ^{*1}	^{*2} to 3.5 ^{*1}	^{*2} to 5.2 ^{*1}	^{*2} to 8.0	V
DC Output Current Range	I_O	0 to 1				A
Operating Junction Temperature	T_{JOP}	-20 to +125				$^\circ C$
Operating Ambient Temperature	T_{AOP}	-30 to +85				$^\circ C$

*1: V_{IN} (max) and I_O (max) are restricted by the relation $P_D = (V_{IN} - V_O) \times I_O$.

Please calculate these values referring to the reference data on page 15.

*2: Refer to the Dropout Voltage parameter.

Electrical Characteristics

($T_a = 25^\circ C$, $V_C = 2V$ unless otherwise specified)

Parameter	Symbol	Ratings												Unit
		SI-3018LSA			SI-3025LSA			SI-3033LSA			SI-3050LSA			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Output Voltage	V_O	1.764	1.800	1.836	2.450	2.500	2.550	3.234	3.300	3.366	4.90	5.00	5.10	V
	Conditions	$V_{IN} = 3.3V, I_O = 0.5A$			$V_{IN} = 3.3V, I_O = 0.5A$			$V_{IN} = 5V, I_O = 0.5A$			$V_{IN} = 6.5V, I_O = 0.5A$			
Dropout Voltage	V_{DIF}	-			0.4			0.4			0.4			V
	Conditions	-			$I_O \leq 0.5A$			$I_O \leq 0.5A$			$I_O \leq 0.5A$			
	Conditions	0.6	1.2				0.8			0.8			0.8	
Line Regulation	ΔV_{LINE}	2			2			3			15			mV
	Conditions	$V_{IN} = 3.1$ to $3.5V, I_O = 0.3A$			$V_{IN} = 3.1$ to $3.5V, I_O = 0.3A$			$V_{IN} = 4.5$ to $5.5V, I_O = 0.3A$			$V_{IN} = 6$ to $7V, I_O = 0.3A$			
Load Regulation	ΔV_{LOAD}	10			10			10			30			mV
	Conditions	$V_{IN} = 3.3V, I_O = 0$ to $1A$			$V_{IN} = 3.3V, I_O = 0$ to $1A$			$V_{IN} = 5V, I_O = 0$ to $1A$			$V_{IN} = 6.5V, I_O = 0$ to $1A$			
Temperature Coefficient of Output Voltage	$\Delta V_O / \Delta T_a$	± 0.3			± 0.3			± 0.3			± 0.5			mV/ $^\circ C$
	Conditions	$V_{IN} = 3.3V, I_O = 5mA, T_J = 0$ to $100^\circ C$			$V_{IN} = 3.3V, I_O = 5mA, T_J = 0$ to $100^\circ C$			$V_{IN} = 5V, I_O = 5mA, T_J = 0$ to $100^\circ C$			$V_{IN} = 6.5V, I_O = 5mA, T_J = 0$ to $100^\circ C$			
Ripple Rejection	R_{REJ}	60			57			55			55			dB
	Conditions	$V_{IN} = 3.3V, f = 100$ to $120Hz$			$V_{IN} = 3.3V, f = 100$ to $120Hz$			$V_{IN} = 5V, f = 100$ to $120Hz$			$V_{IN} = 6.5V, f = 100$ to $120Hz$			
Quiescent Circuit Current	I_q	1.7			1.7			1.7			1.7			mA
	Conditions	$V_{IN} = 3.3V, I_O = 0A$			$V_{IN} = 3.3V, I_O = 0A$			$V_{IN} = 5V, I_O = 0A$			$V_{IN} = 6.5V, I_O = 0A$			
Circuit Current at Output OFF	$I_{q(OFF)}$	1			1			1			1			μA
	Conditions	$V_{IN} = 3.3V, I_O = 0A, V_C = 0V$			$V_{IN} = 3.3V, I_O = 0A, V_C = 0V$			$V_{IN} = 5V, I_O = 0A, V_C = 0V$			$V_{IN} = 6.5V, I_O = 0A, V_C = 0V$			
Overcurrent Protection Starting Current ^{*1,3}	I_{S1}	1.2			1.2			1.2			1.2			A
	Conditions	$V_{IN} = 3.3V$			$V_{IN} = 3.3V$			$V_{IN} = 5V$			$V_{IN} = 6V$			
V_C Terminal	Control Voltage (Output ON) ^{*2}	V_C, I_H			2.0			2.0			2.0			V
	Control Voltage (Output OFF) ^{*2}	V_C, I_L			0.8			0.8			0.8			
	Control Current (Output ON)	I_C, I_H			40			40			40			μA
	Control Current (Output OFF)	I_C, I_L			0			0			0			

*1: I_{S1} is specified at the 5% drop point of output voltage V_O on the condition that $V_{IN} = 3.3 V$ (5 V for SI-3033LSA), and $I_O = 0.5 A$.


*2: Output is OFF when the output control terminal V_C is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.

*3: These products cannot be used in the following applications. Because these applications require a certain current at start-up and so the built-in foldback-type overcurrent protection may cause errors during start-up stage.

(1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_O adjustment by raising ground voltage

External Dimensions


(Unit : mm)




Block Diagram



Typical Connection Diagram



Reference Data



SI-3000KS Series Surface-Mount, Low Current Consumption, Low Dropout Voltage Linear Regulator IC

Features

- Compact surface-mount package (SOP-8)
- Output current: 1.0 A
- Compatible with low ESR capacitor
- Low circuit current at output OFF $I_q \leq 350 \mu\text{A}$ ($I_o = 0 \text{ A}$, $V_c = 2 \text{ V}$)
- Low current consumption $I_q (\text{OFF}) \leq 1 \mu\text{A}$ ($V_c = 0 \text{ V}$)
- Low dropout voltage $V_{\text{DIF}} \leq 0.6 \text{ V}$ ($I_o = 1 \text{ A}$)
- 4 types of output voltages (1.8 V, 2.5 V, 3.3 V, and variable type) available
- Output ON/OFF control terminal voltage compatible with LS-TTL
- Built-in dropping-type-overcurrent and thermal protection circuits

Absolute Maximum Ratings

($T_a=25^\circ\text{C}$)

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V_{IN}^{*1}	17	V
Output Control Terminal Voltage	V_c	V_{IN}	V
DC Output Current	I_o^{*1}	1.0	A
Power Dissipation	$P_D^{*1, *2}$	0.76	W
Junction Temperature	T_j	-40 to +125	$^\circ\text{C}$
Storage Temperature	T_{stg}	-40 to +125	$^\circ\text{C}$
Thermal Resistance (Junction to Ambient Air)	θ_{j-a}	130	$^\circ\text{C/W}$
Thermal resistance (Junction to Lead (pin 7))	θ_{j-l}	22	$^\circ\text{C/W}$

*1: V_{IN} (max) and I_o (max) are restricted by the relation $P_D = (V_{\text{IN}} - V_o) \times I_o$. Please calculate these values referring to the Copper laminate area vs. Power dissipation data as shown hereinafter.

*2: When mounted on a glass epoxy board of 1600 mm² (copper laminate area 2%).

Applications

- Local power supplies
- Battery-driven electronic equipment

Electrical Characteristics

($T_a=25^\circ\text{C}$, $V_c=2 \text{ V}$ unless otherwise specified)

Parameter	Symbol	Ratings												Unit
		SI-3012KS (variable type)			SI-3018KS			SI-3025KS			SI-3033KS			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Input Voltage	V_{IN}													
Output Voltage (Reference voltage V_{ADJ} for SI-3012KS)	$V_o (V_{\text{ADJ}})$	1.24	1.28	1.32	1.764	1.800	1.836	2.45	2.50	2.55	3.234	3.300	3.366	V
Dropout Voltage	V_{DIF}				-			0.4			0.4			V
	Conditions	$I_o=0.5\text{A} (V_o=2.5\text{V})$			-			$I_o=0.5\text{A}$			$I_o=0.5\text{A}$			
	Conditions	$I_o=1\text{A} (V_o=2.5\text{V})$			$I_o=1\text{A}$			$I_o=1\text{A}$			$I_o=1\text{A}$			
Line Regulation	ΔV_{OLINE}	10			10			10			15			mV
	Conditions	$V_{\text{IN}}=3.3 \text{ to } 8\text{V}, I_o=10\text{mA} (V_o=2.5\text{V})$			$V_{\text{IN}}=2.5 \text{ to } 6\text{V}, I_o=10\text{mA}$			$V_{\text{IN}}=3.3 \text{ to } 8\text{V}, I_o=10\text{mA}$			$V_{\text{IN}}=5 \text{ to } 10\text{V}, I_o=10\text{mA}$			
Load Regulation	ΔV_{LOAD}	40			40			40			50			mV
	Conditions	$V_{\text{IN}}=3.3\text{V}, I_o=0 \text{ to } 1\text{A} (V_o=2.5\text{V})$			$V_{\text{IN}}=2.5\text{V}, I_o=0 \text{ to } 1\text{A}$			$V_{\text{IN}}=3.3\text{V}, I_o=0 \text{ to } 1\text{A}$			$V_{\text{IN}}=5\text{V}, I_o=0 \text{ to } 1\text{A}$			
Quiescent Circuit Current	I_q	350			350			350			350			μA
	Conditions	$V_{\text{IN}}=3.3\text{V}, I_o=0\text{A}, V_c=2\text{V}, R_2=24\text{k}\Omega$			$V_{\text{IN}}=2.5\text{V}, I_o=0\text{A}, V_c=2\text{V}$			$V_{\text{IN}}=3.3\text{V}, I_o=0\text{A}, V_c=2\text{V}$			$V_{\text{IN}}=5\text{V}, I_o=0\text{A}, V_c=2\text{V}$			
Circuit Current at Output OFF	$I_q (\text{OFF})$	1			1			1			1			μA
	Conditions	$V_{\text{IN}}=3.3\text{V}, V_c=0\text{V}$			$V_{\text{IN}}=2.5\text{V}, V_c=0\text{V}$			$V_{\text{IN}}=3.3\text{V}, V_c=0\text{V}$			$V_{\text{IN}}=5\text{V}, V_c=0\text{V}$			
Temperature Coefficient of Output Voltage	$\Delta V_o/\Delta T_a$	± 0.3			± 0.3			± 0.3			± 0.3			mV/ $^\circ\text{C}$
	Conditions	$T_j=0 \text{ to } 100^\circ\text{C} (V_o=2.5\text{V})$			$T_j=0 \text{ to } 100^\circ\text{C}$			$T_j=0 \text{ to } 100^\circ\text{C}$			$T_j=0 \text{ to } 100^\circ\text{C}$			
Ripple Rejection	R_{REJ}	55			55			55			55			dB
	Conditions	$V_{\text{IN}}=3.3\text{V}, f=100 \text{ to } 120\text{Hz} (V_o=2.5\text{V})$			$V_{\text{IN}}=3.3\text{V}, f=100 \text{ to } 120\text{Hz}$			$V_{\text{IN}}=3.3\text{V}, f=100 \text{ to } 120\text{Hz}$			$V_{\text{IN}}=5\text{V}, f=100 \text{ to } 120\text{Hz}$			
Overcurrent Protection Starting Current ²	I_{S1}	1.2			1.2			1.2			1.2			A
	Conditions	$V_{\text{IN}}=3.3\text{V} (V_o=2.5\text{V})$			$V_{\text{IN}}=2.5\text{V}$			$V_{\text{IN}}=3.3\text{V}$			$V_{\text{IN}}=5\text{V}$			
Vc Terminal	Control Voltage (Output ON) ³	V_c, I_{H}			2.0			2.0			2.0			V
	Control Voltage (Output OFF)	V_c, I_{L}			0.8			0.8			0.8			
	Control Current (Output ON)	I_c, I_{H}			40			40			40			μA
	Conditions	$V_c=2\text{V}$												
Control Current (Output OFF)	I_c, I_{L}	-5	0		-5	0		-5	0		-5	0		μA
	Conditions	$V_c=0\text{V}$												


*1: Refer to the Dropout Voltage parameter.

*2: The I_{S1} is specified at the 5% drop point of output voltage V_o on the condition that $V_{\text{IN}} = V_o + 1 \text{ V}$, and $I_o = 10 \text{ mA}$.

*3: Output is OFF when the output control terminal V_c is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.

External Dimensions

(Unit : mm)




Pin Assignment


- ① V_c
- ② V_{IN}
- ③ V_O
- ④ Sence (ADJ for SI-3012KS)
- ⑤ GND
- ⑥ GND
- ⑦ GND
- ⑧ GND

Plastic Mold Package Type
 Flammability: UL 94V-0
 Product Mass: Approx. 0.1 g


Block Diagram



Typical Connection Diagram



Reference Data



SI-3000KMS Series Surface Mount, Low Current Consumption, Low Dropout Voltage Linear Regulator IC

Features

- Compact surface mount package (TO252-3)
- Output current: 1.0 A
- Low dropout voltage: $V_{DIF} \leq 0.6V$ (at $I_O=1.0A$)
- Low current consumption: $I_q \leq 450 \mu A$
($700 \mu A$ for SI-3050KMS/3090KMS/ 3120KMS/ 3150KMS)
- Built-in overcurrent and thermal protection circuits
- Compatible with low ESR capacitor application
(Except for SI-3050KMS/3090KMS/3120KMS/ 3150KMS)

Absolute Maximum Ratings

($T_a=25^\circ C$)

Parameter	Symbol	Ratings		Unit
		SI-3018KMS/3025KMS/ 3033KMS	SI-3050KMS/3090KMS 3120KMS/3150KMS	
DC Input Voltage	V_{IN}	17	35*1	V
DC Output Current	I_O	1.0		A
Power Dissipation	P_D^{*2}	1		W
Junction Temperature	T_j	-30 to +125		$^\circ C$
Storage Temperature	T_{stg}	-30 to +125		$^\circ C$
Thermal Resistance (Junction to Ambient Air)	θ_{ja}^{*2}	95		$^\circ C/W$
Thermal Resistance (Junction to case)	θ_{jc}	6		$^\circ C/W$

*1: A built-in input-overvoltage-protection circuit shuts down the output voltage at the Input Overvoltage Shutdown Voltage of the electrical characteristics.

*2: When mounted on glass-epoxy board of 900mm² (copper laminate area 4.3%).

Applications

- Secondary stabilized power supply (local power supply)

Recommended Operating Conditions

Parameter	Symbol	Ratings							Unit
		SI-3018KMS	SI-3025KMS	SI-3033KMS	SI-3050KMS	SI-3090KMS	SI-3120KMS	SI-3150KMS	
Input Voltage Range	V_{IN}	2.4*2 to 5.0*1	*2 to 5*1	*2 to 6*1	*2 to 15	*2 to 20	*2 to 25	*2 to 27	V
Output Current Range	I_O	0 to 1.0							A
Operating Ambient Temperature	T_{op}	-30 to +85							$^\circ C$
Operating Junction Temperature	T_j	-20 to +100							$^\circ C$

*1: V_{IN} (max) and I_O (max) are restricted by the relation $P_D = (V_{IN}-V_O) \times I_O$. Please calculate these values referring to the Copper laminate area vs. Power dissipation data as shown hereinafter.

*2: Refer to the Dropout Voltage parameter.

Electrical Characteristics

Parameter	Symbol	Ratings																		Unit			
		SI-3018KMS			SI-3025KMS			SI-3033KMS			SI-3050KMS			SI-3090KMS			SI-3120KMS				SI-3150KMS		
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Output Voltage	V_O	1.755	1.800	1.845	2.45	2.50	2.55	3.234	3.300	3.366	4.90	5.00	5.10	8.82	9.00	9.18	11.76	12.00	12.24	14.70	15.00	15.30	V
	Conditions	$V_{IN}=2.5V, I_O=10mA$			$V_{IN}=3.3V, I_O=10mA$			$V_{IN}=5V, I_O=10mA$			$V_{IN}=7V, I_O=10mA$			$V_{IN}=11V, I_O=10mA$			$V_{IN}=14V, I_O=10mA$			$V_{IN}=17V, I_O=10mA$			
Line Regulation	ΔV_{OLINE}	15			15			15			30			54			72			90			mV
	Conditions	$V_{IN}=2.5$ to $6V, I_O=10mA$			$V_{IN}=3.3$ to $8V, I_O=10mA$			$V_{IN}=5$ to $10V, I_O=10mA$			$V_{IN}=6$ to $11V, I_O=10mA$			$V_{IN}=10$ to $15V, I_O=10mA$			$V_{IN}=13$ to $18V, I_O=10mA$			$V_{IN}=16$ to $26V, I_O=10mA$			
Load Regulation	ΔV_{OLOAD}	40			40			60			75			135			180			225			mV
	Conditions	$V_{IN}=2.5V, I_O=0$ to $1A$			$V_{IN}=3.3V, I_O=0$ to $1A$			$V_{IN}=5V, I_O=0$ to $1A$			$V_{IN}=7V, I_O=0$ to $1A$			$V_{IN}=11V, I_O=0$ to $1A$			$V_{IN}=14V, I_O=0$ to $1A$			$V_{IN}=17V, I_O=0$ to $1A$			
Dropout Voltage	V_{DIF}	0.6			0.4			0.4			0.4			0.3			0.3			0.3			V
	Conditions	$I_O=0.5A$			$I_O=0.5A$			$I_O=0.5A$			$I_O=0.5A$			$I_O=0.5A$			$I_O=0.5A$			$I_O=0.5A$			
	Conditions	$I_O=1A$			$I_O=1A$			$I_O=1A$			$I_O=1A$			$I_O=1A$			$I_O=1A$			$I_O=1A$			
Quiescent Circuit Current	I_q	450			450			450			700			700			700			700			μA
	Conditions	$V_{IN}=2.5V, I_O=0A$			$V_{IN}=3.3V, I_O=0A$			$V_{IN}=5V, I_O=0A$			$V_{IN}=7V, I_O=0A$			$V_{IN}=11V, I_O=0A$			$V_{IN}=14V, I_O=0A$			$V_{IN}=17V, I_O=0A$			
Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T_a$	± 0.2			± 0.3			± 0.3			± 0.5			± 1.0			± 1.5			± 1.5			mV/ $^\circ C$
	Conditions	$T_j=0$ to $100^\circ C$			$T_j=0$ to $100^\circ C$			$T_j=0$ to $100^\circ C$			$T_j=0$ to $100^\circ C$			$T_j=0$ to $100^\circ C$			$T_j=0$ to $100^\circ C$			$T_j=0$ to $100^\circ C$			
Ripple Rejection	R_{REJ}	55			55			55			75			68			66			63			dB
	Conditions	$V_{IN}=2.5V, f=100$ to $120Hz$			$V_{IN}=3.3V, f=100$ to $120Hz$			$V_{IN}=5V, f=100$ to $120Hz$			$V_{IN}=7V, f=100$ to $120Hz$			$V_{IN}=11V, f=100$ to $120Hz$			$V_{IN}=14V, f=100$ to $120Hz$			$V_{IN}=17V, f=100$ to $120Hz$			
Overcurrent Protection Starting Current ²	I_{S1}	1.1			1.1			1.1			1.1			1.1			1.1			1.1			A
	Conditions	$V_{IN}=2.5V$			$V_{IN}=3.3V$			$V_{IN}=5V$			$V_{IN}=7V$			$V_{IN}=11V$			$V_{IN}=14V$			$V_{IN}=17V$			
Input Overvoltage Shutdown Voltage	V_{OVP}	26			30			33			33			33			33			V			
	Conditions	$I_O=10mA$			$I_O=10mA$			$I_O=10mA$			$I_O=10mA$			$I_O=10mA$			$I_O=10mA$						

*1: Refer to the Dropout Voltage parameter.


*2: I_{S1} is specified at the 5% drop point of output voltage V_O under the condition of Output Voltage parameter.

*3: SI-3050KMS, SI-3090KMS, SI-3120KMS and SI-3150KMS cannot be used in the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.


- (1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_O adjustment by raising ground voltage

External Dimensions


(Unit : mm)




Block Diagram



Typical Connection Diagram



Reference Data



SI-3000KM Series Surface Mount, Low Current Consumption, Low Dropout Voltage Linear Regulator IC

Features

- Compact surface mount package (TO252-5)
- Output current: 1.0 A
- Low dropout voltage: $V_{DIF} \leq 0.6 \text{ V}$ (at $I_o = 1.0 \text{ A}$)
- Low current consumption: $I_q \leq 350 \mu\text{A}$ (600 μA for SI-3010KM/SI-3050KM/SI-3090KM/SI-3120KM/SI-3150KM)
- Low circuit current at output OFF: $I_q (\text{OFF}) \leq 1 \mu\text{A}$
- Built-in overcurrent and thermal protection circuits
- Output ON/OFF control function
- Compatible with low ESR capacitors (SI-3012KM/SI-3018KM/SI-3025KM/SI-3033KM)

Absolute Maximum Ratings

($T_a=25^\circ\text{C}$)

Parameter	Symbol	Ratings		Unit
		SI-3012KM/3018KM/3025KM/3033KM	SI-3010KM/3050KM/3090KM/3120KM/3150KM	
DC Input Voltage	V_{IN}	17	35 ^{*1}	V
Output Control Terminal Voltage	V_c	V_{IN}		V
DC Output Current	I_o	1.0		A
Power Dissipation	P_D ^{*2}	1		W
Junction Temperature	T_j	-30 to +125		$^\circ\text{C}$
Storage Temperature	T_{stg}	-30 to +125		$^\circ\text{C}$
Thermal Resistance (Junction to Ambient Air)	θ_{j-a} ^{*2}	95		$^\circ\text{C/W}$
Thermal Resistance (Junction to case)	θ_{j-c}	6		$^\circ\text{C/W}$

*1: A built-in input-overvoltage-protection circuit shuts down the output voltage at the Input Overvoltage Shutdown Voltage of the electrical characteristics.

*2: When mounted on glass-epoxy board of 900mm² (copper laminate area 4.3%).

Applications

- Secondary stabilized power supply (local power supply)

Recommended Operating Conditions

Parameter	Symbol	Ratings									Unit
		SI-3012KM	SI-3018KM	SI-3025KM	SI-3033KM	SI-3010KM	SI-3050KM	SI-3090KM	SI-3120KM	SI-3150KM	
Input Voltage Range	V_{IN}	2.4 ^{*2} to 6.0 ^{*1}	2.4 ^{*2} to 5.0 ^{*1}	2.4 ^{*2} to 5 ^{*1}	^{*2} to 6 ^{*1}	2.4 ^{*2} to 15 ^{*1}	2.4 ^{*2} to 27 ^{*1}	^{*2} to 20 ^{*1}	^{*2} to 25 ^{*1}	^{*2} to 27 ^{*1}	V
Output Current Range	I_o	0 to 1.0									A
Operating Ambient Temperature	T_{op}	-30 to +85									$^\circ\text{C}$
Operating Junction Temperature	T_j	-20 to +100									$^\circ\text{C}$

*1: V_{IN} (max) and I_o (max) are restricted according to operating conditions due to the relation $P_D = (V_{IN}-V_o) \times I_o$. Please calculate these values referring to the Copper Laminate Area vs. Power Dissipation data as shown hereinafter.

*2: Refer to the Dropout Voltage parameter.

Electrical Characteristics 1 (Low V_o type compatible with low ESR output capacitor)

Parameter	Symbol	Ratings												Unit
		SI-3012KM (Variable type)			SI-3018KM			SI-3025KM			SI-3033KM			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Input Voltage	V_{IN}	2.4 ^{*1}			^{*1}			^{*1}			^{*1}			V
Output Voltage (Reference voltage V_{ADJ} for SI-3012KM)	$V_o (V_{ADJ})$	1.24	1.28	1.32	1.764	1.800	1.836	2.45	2.50	2.55	3.234	3.300	3.366	V
	Conditions	$V_{IN}=3.3\text{V}, I_o=10\text{mA}$			$V_{IN}=2.5\text{V}, I_o=10\text{mA}$			$V_{IN}=3.3\text{V}, I_o=10\text{mA}$			$V_{IN}=5\text{V}, I_o=10\text{mA}$			
Line Regulation	ΔV_{OLINE}			15			15			15			15	mV
	Conditions	$V_{IN}=3.3$ to 8V, $I_o=10\text{mA}$ ($V_o=2.5\text{V}$)			$V_{IN}=2.5$ to 6V, $I_o=10\text{mA}$			$V_{IN}=3.3$ to 8V, $I_o=10\text{mA}$			$V_{IN}=5$ to 10V, $I_o=10\text{mA}$			
Load Regulation	ΔV_{OLOAD}			40			40			40			50	mV
	Conditions	$V_{IN}=3.3\text{V}, I_o=0$ to 1A ($V_o=2.5\text{V}$)			$V_{IN}=2.5\text{V}, I_o=0$ to 1A			$V_{IN}=3.3\text{V}, I_o=0$ to 1A			$V_{IN}=5\text{V}, I_o=0$ to 1A			
Dropout Voltage	V_{DIF}			0.4			0.6			0.4			0.4	V
	Conditions	$I_o=0.5\text{A}$ ($V_o=2.5\text{V}$)			$I_o=0.5\text{A}$			$I_o=0.5\text{A}$			$I_o=0.5\text{A}$			
				0.6			0.6			0.6			0.6	
	Conditions	$I_o=1\text{A}$ ($V_o=2.5\text{V}$)			$I_o=1\text{A}$			$I_o=1\text{A}$			$I_o=1\text{A}$			
Quiescent Circuit Current	I_q			350			350			350			350	μA
	Conditions	$V_{IN}=3.3\text{V}, I_o=0\text{A}, V_c=2\text{V}, R_2=24\text{k}\Omega$			$V_{IN}=2.5\text{V}, I_o=0\text{A}, V_c=2\text{V}$			$V_{IN}=3.3\text{V}, I_o=0\text{A}, V_c=2\text{V}$			$V_{IN}=5\text{V}, I_o=0\text{A}, V_c=2\text{V}$			
Circuit Current at Output OFF	$I_q (\text{OFF})$			1			1			1			1	μA
	Conditions	$V_{IN}=3.3\text{V}, V_c=0\text{V}$			$V_{IN}=2.5\text{V}, V_c=0\text{V}$			$V_{IN}=3.3\text{V}, V_c=0\text{V}$			$V_{IN}=5\text{V}, V_c=0\text{V}$			
Temperature Coefficient of Output Voltage	$\Delta V_o/\Delta T_a$			± 0.3			± 0.3			± 0.3			± 0.3	mV/ $^\circ\text{C}$
	Conditions	$T_j=0$ to 100 $^\circ\text{C}$ ($V_c=2.5\text{V}$)			$T_j=0$ to 100 $^\circ\text{C}$			$T_j=0$ to 100 $^\circ\text{C}$			$T_j=0$ to 100 $^\circ\text{C}$			
Ripple Rejection	R_{REJ}			55			55			55			55	dB
	Conditions	$V_{IN}=3.3\text{V}, f=100$ to 120Hz ($V_o=2.5\text{V}$)			$V_{IN}=2.5\text{V}, f=100$ to 120Hz			$V_{IN}=3.3\text{V}, f=100$ to 120Hz			$V_{IN}=5\text{V}, f=100$ to 120Hz			
Overcurrent Protection Starting Current ^{*2}	I_{S1}			1.1			1.1			1.1			1.1	A
	Conditions	$V_{IN}=3.3\text{V}$			$V_{IN}=2.5\text{V}$			$V_{IN}=3.3\text{V}$			$V_{IN}=5\text{V}$			
V_c Terminal	Control Voltage (Output ON)	V_c, I_H	2.0		2.0		2.0		2.0		2.0		2.0	V
	Control Voltage (Output OFF)	V_c, I_L			0.8		0.8		0.8		0.8		0.8	
	Control Current (Output ON)	I_c, I_H			40		40		40		40		40	μA
	Control Current (Output OFF)	I_c, I_L			0		0		0		0		0	μA
	Conditions	$V_c=2\text{V}$			$V_c=2\text{V}$			$V_c=2\text{V}$			$V_c=2\text{V}$			
	Conditions	$V_c=0\text{V}$			$V_c=0\text{V}$			$V_c=0\text{V}$			$V_c=0\text{V}$			

*1: Refer to the Dropout Voltage parameter.

*2: I_{S1} is specified at the 5% drop point of output voltage V_o on the condition that V_{IN} =overcurrent protection starting current, $I_o = 10 \text{ mA}$.

*3: Output is OFF when output control terminal (V_c terminal) is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.

■Electrical Characteristics 2 (High Vo type)

Parameter	Symbol	Ratings															Unit
		SI-3010KM (Variable type)			SI-3050KM			SI-3090KM			SI-3120KM			SI-3150KM			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Input Voltage	V _{IN}	2.4 ^{*1}			*1			*1			*1			*1			V
Output Voltage (Reference voltage V _{ADJ} for SI-3010KM)	V _O (V _{ADJ})	0.98	1.00	1.02	4.90	5.00	5.10	8.82	9.00	9.18	11.76	12.00	12.24	14.70	15.00	15.30	V
Line Regulation	ΔV _{OLINE}			30			30			54			72			90	mV
	Conditions	V _{IN} =6 to 11V, I _O =10mA (V _O =5V)			V _{IN} =6 to 11V, I _O =10mA			V _{IN} =10 to 15V, I _O =10mA			V _{IN} =13 to 18V, I _O =10mA			V _{IN} =16 to 26V, I _O =10mA			
Load Regulation	ΔV _{OLOAD}			75			75			135			180			225	mV
	Conditions	V _{IN} =7V, I _O =0 to 1A (V _O =5V)			V _{IN} =7V, I _O =0 to 1A			V _{IN} =11V, I _O =0 to 1A			V _{IN} =14V, I _O =0 to 1A			V _{IN} =17V, I _O =0 to 1A			
Dropout Voltage	V _{DIF}			0.3			0.3			0.3			0.3			0.3	V
	Conditions	I _O =0.5A (V _O =5V)			I _O =0.5A			I _O =0.5A			I _O =0.5A			I _O =0.5A			
	Conditions	I _O =1A (V _O =5V)			I _O =1A			I _O =1A			I _O =1A			I _O =1A			
Quiescent Circuit Current	I _q			600			600			600			600			600	μA
	Conditions	V _{IN} =7V, I _O =0A, V _C =2V, R ₂ =10kΩ			V _{IN} =7V, I _O =0A, V _C =2V			V _{IN} =11V, I _O =0A, V _C =2V			V _{IN} =14V, I _O =0A, V _C =2V			V _{IN} =17V, I _O =0A, V _C =2V			
Circuit Current at Output OFF	I _q (OFF)			1			1			1			1			1	μA
	Conditions	V _{IN} =7V, V _C =0V			V _{IN} =7V, V _C =0V			V _{IN} =11V, V _C =0V			V _{IN} =14V, V _C =0V			V _{IN} =17V, V _C =0V			
Temperature Coefficient of Output Voltage	ΔV _O /ΔT _a			±0.5			±0.5			±1.0			±1.5			±1.5	mV/°C
	Conditions	T _j =0 to 100°C (V _O =5V)			T _j =0 to 100°C			T _j =0 to 100°C			T _j =0 to 100°C			T _j =0 to 100°C			
Ripple Rejection	R _{REJ}			75			75			68			66			63	dB
	Conditions	V _{IN} =7V, f=100 to 120Hz (V _O =5V)			V _{IN} =7V, f=100 to 120Hz			V _{IN} =11V, f=100 to 120Hz			V _{IN} =14V, f=100 to 120Hz			V _{IN} =17V, f=100 to 120Hz			
Overcurrent Protection Starting Current ^{*2}	I _{S1}	1.1			1.1			1.1			1.1			1.1			A
	Conditions	V _{IN} =7V			V _{IN} =7V			V _{IN} =11V			V _{IN} =14V			V _{IN} =17V			
V _C Terminal	Control Voltage (Output ON)	V _C , I _H	2.0			2.0			2.0			2.0			2.0		V
	Control Voltage (Output OFF)	V _C , I _L			0.8			0.8			0.8			0.8			V
	Control Current (Output ON)	I _C , I _H			40			40			40			40			μA
	Control Current (Output OFF)	I _C , I _L	-5	0		-5	0		-5	0		-5	0		-5	0	μA
Input Overvoltage Shutdown Voltage	V _{OVP}	33			26			30			33			33			V
	Conditions	I _O =10mA			I _O =10mA			I _O =10mA			I _O =10mA			I _O =10mA			

*1: Refer to the Dropout Voltage parameter.

*2: I_{S1} is specified at the 5% drop point of output voltage V_O on the condition that V_{IN}=overcurrent protection starting current, I_O = 10 mA.

*3: Output is OFF when output control terminal (V_C terminal) is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.


*4: SI-3010KM, SI-3050KM, SI-3090KM, SI-3120KM and SI-3150KM cannot be used in the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.

(1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_O adjustment by raising ground voltage


*5: V_{IN} (max) and I_O (max) are restricted by the relation P_D = (V_{IN} - V_O) × I_O. Please calculate these values referring to the Copper Laminate Area vs. Power Dissipation data as shown hereinafter.

■External Dimensions


(Unit : mm)




■Block Diagram



■Typical Connection Diagram



■Reference Data



SI-3000KD Series Surface-Mount, Low Current Consumption, Low Dropout Voltage Linear Regulator IC

Features

- Compact surface-mount package (TO263-5)
- Output current: 1.0A
- Low dropout voltage: $V_{DIF} \leq 0.6V$ (at $I_o = 1.0A$)
- Low circuit current consumption: $I_q \leq 350 \mu A$ (600 μA for SI-3010KD, SI-3050KD, SI-3090KD, SI-3120KD and SI-3150KD)
- Low circuit current at output OFF: $I_q (OFF) \leq 1 \mu A$
- Built-in overcurrent, thermal protection circuits
- Compatible with low ESR capacitors (SI-3012KD, SI-3018KD, SI-3025KD and SI-3033KD)

Absolute Maximum Ratings

($T_a = 25^\circ C$)

Parameter	Symbol	Ratings		Unit
		SI-3012KD/3018KD/3025KD/3033KD	SI-3010KD/3050KD/3090KD/3120KD/3150KD	
DC Input Voltage	V_{IN}	17	35 ¹	V
DC Output Current	I_o	1.0		A
Power Dissipation	P_D ²	3		W
Junction Temperature	T_j	-30 to +125		$^\circ C$
Storage Temperature	T_{stg}	-30 to +125		$^\circ C$
Thermal Resistance (Junction to Ambient Air)	θ_{j-a}	33.3		$^\circ C/W$
Thermal Resistance (Junction to Case)	θ_{j-c}	3		$^\circ C/W$

*1: A built-in input-overvoltage-protection circuit shuts down the output voltage at the Input Overvoltage Shutdown Voltage of the electrical characteristics.

*2: When mounted on glass-epoxy board of 1600m² (copper laminate area 100%)

Applications

- Secondary stabilized power supply (local power supply)

Electrical Characteristics 1 (Low V_o type compatible with low ESR output capacitor)

($T_a = 25^\circ C$, $V_c = 2V$ unless otherwise specified)

Parameter	Symbol	Ratings												Unit
		SI-3012KD (Variable type)			SI-3018KD			SI-3025KD			SI-3033KD			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Input Voltage	V_{IN}	2.4 ³		4	3		4	3		4	3		4	V
Output Voltage (Reference Voltage for SI-3012KD)	$V_o (V_{ADJ})$	1.24	1.28	1.32	1.764	1.800	1.836	2.45	2.50	2.55	3.234	3.300	3.366	V
Line Regulation	ΔV_{OLINE}	$V_{IN} = 3.3V, I_o = 10mA$			$V_{IN} = 2.5V, I_o = 10mA$			$V_{IN} = 3.3V, I_o = 10mA$			$V_{IN} = 5V, I_o = 10mA$			mV
	Conditions	$V_{IN} = 3.3$ to 8V, $I_o = 10mA$ ($V_o = 2.5V$)			$V_{IN} = 2.5$ to 6V, $I_o = 10mA$			$V_{IN} = 3.3$ to 8V, $I_o = 10mA$			$V_{IN} = 5$ to 10V, $I_o = 10mA$			mV
Load Regulation	ΔV_{OLOAD}	$V_{IN} = 3.3V, I_o = 0$ to 1A ($V_o = 2.5V$)			$V_{IN} = 2.5V, I_o = 0$ to 1A			$V_{IN} = 3.3V, I_o = 0$ to 1A			$V_{IN} = 5V, I_o = 0$ to 1A			mV
	Conditions	$I_o = 0.5A$ ($V_o = 2.5V$)			$I_o = 0.5A$			$I_o = 0.5A$			$I_o = 0.5A$			V
Dropout Voltage	V_{DIF}	$I_o = 0.5A$			$I_o = 0.5A$			$I_o = 0.5A$			$I_o = 0.5A$			V
	Conditions	$I_o = 1A$ ($V_o = 2.5V$)			$I_o = 1A$			$I_o = 1A$			$I_o = 1A$			V
Quiescent Circuit Current	I_q	350			350			350			350			μA
	Conditions	$V_{IN} = 3.3V, I_o = 0A, V_c = 2V, R_2 = 2.4k\Omega$			$V_{IN} = 2.5V, I_o = 0A, V_c = 2V$			$V_{IN} = 3.3V, I_o = 0A, V_c = 2V$			$V_{IN} = 5V, I_o = 0A, V_c = 2V$			μA
Circuit Current at Output OFF	$I_q (OFF)$	1			1			1			1			μA
	Conditions	$V_{IN} = 3.3V, V_c = 0V$			$V_{IN} = 2.5V, V_c = 0V$			$V_{IN} = 3.3V, V_c = 0V$			$V_{IN} = 5V, V_c = 0V$			μA
Temperature Coefficient of Output Voltage	$\Delta V_o / \Delta T_a$	± 0.3			± 0.3			± 0.3			± 0.3			mV/ $^\circ C$
	Conditions	$T_j = 0$ to 100 $^\circ C$ ($V_o = 2.5V$)			$T_j = 0$ to 100 $^\circ C$			$T_j = 0$ to 100 $^\circ C$			$T_j = 0$ to 100 $^\circ C$			mV/ $^\circ C$
Ripple Rejection	R_{REJ}	55			55			55			55			dB
	Conditions	$V_{IN} = 3.3V, f = 100$ to 120Hz, $I_o = 0.1A$ ($V_o = 2.5V$)			$V_{IN} = 2.5V, f = 100$ to 120Hz, $I_o = 0.1A$			$V_{IN} = 3.3V, f = 100$ to 120Hz, $I_o = 0.1A$			$V_{IN} = 5V, f = 100$ to 120Hz, $I_o = 0.1A$			dB
Overcurrent Protection Starting Current ¹	I_{S1}	1.1			1.1			1.1			1.1			A
	Conditions	$V_{IN} = 3.3V$			$V_{IN} = 2.5V$			$V_{IN} = 3.3V$			$V_{IN} = 5V$			A
Vc Terminal	Control Voltage (Output ON) ²	2			2			2			2			V
	Control Voltage (Output OFF)	V_c, I_L			0.8			0.8			0.8			V
	Control Current (Output ON)	I_c, I_H			40			40			40			μA
	Control Current (Output OFF)	I_c, I_L			-5			-5			-5			μA
	Conditions	$V_c = 2V$			$V_c = 2V$			$V_c = 2V$			$V_c = 2V$			μA
	Conditions	$V_c = 0V$			$V_c = 0V$			$V_c = 0V$			$V_c = 0V$			μA

*1: I_{S1} is specified at the 5% drop point of output voltage V_o under the condition of Output Voltage parameter.

*2: Output is OFF when the output control terminal (V_c terminal) is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.

*3: Refer to the Dropout Voltage parameter.

*4: $V_{IN} (max)$ and $I_o (max)$ are restricted by the relation $P_D = (V_{IN} - V_o) \times I_o$. Please calculate these values referring to the Copper laminate area vs. Power dissipation data.

■Electrical Characteristics 2 (High Vo Type)

Parameter	Symbol	Ratings															Unit
		SI-3010KD (Variable type)			SI-3050KD			SI-3090KD			SI-3120KD			SI-3150KD			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Input Voltage	V _{IN}	2.4 ^{*1}		27 ^{*5}	^{*1}		15 ^{*5}	^{*1}		20 ^{*5}	^{*1}		25 ^{*5}	^{*1}		27 ^{*5}	V
Output Voltage (Reference Voltage V _{ADJ} for SI-3010KD)	V _O (V _{ADJ})	0.98	1.00	1.02	4.90	5.00	5.10	8.82	9.00	9.18	11.76	12.00	12.24	14.70	15.00	15.30	V
Line Regulation	ΔV _{OLINE}			30			30			54			72			90	mV
	Conditions	V _{IN} =6 to 11V, I _O =10mA (V _O =5V)			V _{IN} =6 to 11V, I _O =10mA			V _{IN} =10 to 15V, I _O =10mA			V _{IN} =13 to 18V, I _O =10mA			V _{IN} =16 to 26V, I _O =10mA			
Load Regulation	ΔV _{OLOAD}			75			75			135			180			225	mV
	Conditions	V _{IN} =7V, I _O =0 to 1A (V _O =5V)			V _{IN} =7V, I _O =0 to 1A			V _{IN} =11V, I _O =0 to 1A			V _{IN} =14V, I _O =0 to 1A			V _{IN} =17V, I _O =0 to 1A			
Dropout Voltage	V _{DIF}			0.3			0.3			0.3			0.3			0.3	V
	Conditions	I _O =0.5A (V _O =5V)			I _O =0.5A			I _O =0.5A			I _O =0.5A			I _O =0.5A			
	Conditions	I _O =1A (V _O =5V)			I _O =1A			I _O =1A			I _O =1A			I _O =1A			
Quiescent Circuit Current	I _q			600			600			600			600			600	μA
	Conditions	V _{IN} =7V, I _O =0A, V _C =2V, R ₂ =10kΩ			V _{IN} =7V, I _O =0A, V _C =2V			V _{IN} =11V, I _O =0A, V _C =2V			V _{IN} =14V, I _O =0A, V _C =2V			V _{IN} =17V, I _O =0A, V _C =2V			
Circuit Current at Output OFF	I _q (OFF)			1			1			1			1			1	μA
	Conditions	V _{IN} =7V, V _C =0V			V _{IN} =7V, V _C =0V			V _{IN} =11V, V _C =0V			V _{IN} =14V, V _C =0V			V _{IN} =17V, V _C =0V			
Temperature Coefficient of Output Voltage	ΔV _O /ΔT _a			±0.5			±0.5			±1.0			±1.5			±1.5	mV/°C
	Conditions	T _J =0 to 100°C (V _O =5V)			T _J =0 to 100°C			T _J =0 to 100°C			T _J =0 to 100°C			T _J =0 to 100°C			
Ripple Rejection	R _{REJ}			75			75			68			66			63	dB
	Conditions	V _{IN} =7V, f=100 to 120Hz, I _O =0.1A (V _O =5V)			V _{IN} =7V, f=100 to 120Hz, I _O =0.1A			V _{IN} =11V, f=100 to 120Hz, I _O =0.1A			V _{IN} =14V, f=100 to 120Hz, I _O =0.1A			V _{IN} =17V, f=100 to 120Hz, I _O =0.1A			
Overcurrent Protection Starting Current ^{*2}	I _{s1}	1.1			1.1			1.1			1.1			1.1			A
	Conditions	V _{IN} =7V			V _{IN} =7V			V _{IN} =11V			V _{IN} =14V			V _{IN} =17V			
V _C Terminal	Control Voltage (Output ON) ^{*3}	V _C , IH	2.0			2.0			2.0			2.0			2.0		V
	Control Voltage (Output OFF) ^{*3}	V _C , IL			0.8			0.8			0.8			0.8		0.8	
	Control Current (Output ON)	I _C , IH			40			40			40			40		40	μA
	Control Current (Output OFF)	I _C , IL	-5	0		-5	0		-5	0		-5	0		-5	0	μA
	Conditions	V _C =0V			V _C =0V			V _C =0V			V _C =0V			V _C =0V			
Input Overvoltage Shutdown Voltage	V _{OV} P	33			26			30			33			33			V
	Conditions	I _O =10mA			I _O =10mA			I _O =10mA			I _O =10mA			I _O =10mA			

*1: Refer to the Dropout Voltage parameter.

*2: I_{s1} is specified at the 5% drop point of output voltage V_O under the condition of Output Voltage parameter.

*3: Output is OFF when the output control terminal (V_C terminal) is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.


*4: SI-3010KD, SI-3050KD, SI-3090KD, SI-3120KD and SI-3150KD cannot be used in the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.

(1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_O adjustment by raising ground voltage


*5: V_{IN} (max) and I_O (max) are restricted by the relation P_D = (V_{IN} - V_O) × I_O. Please calculate these values referring to the Copper laminate area vs. Power dissipation data as shown hereinafter.

■External Dimensions


(unit : mm)




■Block Diagram



■Typical Connection Diagram



■Reference Data



SI-3000LLSL Series Surface-Mount, Low Current Consumption, Low Dropout Voltage Dropper Linear Regulator IC

■ Features

- Low input voltage (1.3V) and low output voltage (1.0V)
- Compact surface-mount package (SOP8)
- Low dropout voltage: $V_{DIF} \leq 0.3V$ (at $I_o = 1.5A$)
- Built-in overcurrent, input-overvoltage and thermal protection circuits
- Built-in ON/OFF function (OFF state circuit current: $1\mu A$ max.)
- Compatible with low ESR capacitors

■ Absolute Maximum Ratings

(T_a=25°C)

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V _{IN}	10	V
DC Bias Voltage	V _B	10	V
Output Control Terminal Voltage	V _C	V _{IN}	V
DC Output Current	I _o	1.5	A
Power Dissipation	P _D *1	1.1	W
Junction Temperature	T _J	-30 to +125	°C
Operating Ambient Temperature	T _{OP}	-30 to +100	°C
Storage Temperature	T _{stg}	-30 to +125	°C
Thermal Resistance (Junction to Lead (Pin 8))	θ _(j-l)	36	°C/W
Thermal Resistance (Junction to Ambient Air)	θ _(j-a) *1	100	°C/W

*1: When mounted on glass-epoxy board of 40 × 40mm (copper laminate area 100%)

■ Applications

- On-board local power supply
- For stabilization of the secondary-side output voltage of switching power supplies

■ Recommended Operating Conditions

Parameter	Symbol	Ratings		Unit
		SI-3010LLSL		
Input Voltage	V _{IN}	1.4 to 3.6*1		V
Bias Voltage	V _B	3.3 to 5.5		
Output Current	I _o	0 to 1.5*1		A
Operating Ambient Temperature	T _{OP}	-20 to +85*1		°C

*1: V_{IN} (max) and I_o (max) are restricted by the relation P_D = (V_{IN} - V_o) × I_o.

■ Electrical Characteristics


(T_a=25°C, V_C=2V, V_{IN}=1.8V, V_B=3.3V, V_o=1.5V unless otherwise specified)

Parameter	Symbol	Ratings			Unit
		SI-3010LLSL			
		min.	typ.	max.	
Reference Voltage	V _{ADJ}	0.980	1.000	1.020	V
	Conditions	I _o =10mA			
Line Regulation	ΔV _{OLINE}			10	mV
	Conditions	V _{IN} =1.7 to 2.5V, I _o =10mA			
Load Regulation	ΔV _{OLOAD}			30	mV
	Conditions	V _{IN} =1.8V, I _o =0 to 1.5A			
Dropout Voltage	V _{DIF}			0.3	V
	Conditions	I _o =1.0A			
Quiescent Circuit Current	I _q		500	800	μA
	Conditions	I _o =0A, R ₂ =10kΩ			
Circuit Current at Output OFF	I _{q(OFF)}			1	μA
	Conditions	V _C =0V			
Temperature Coefficient of Output Voltage	ΔV _o /ΔT _a		±0.2		mV/°C
	Conditions	T _J =0 to 100°C			
Overcurrent Protection Starting Current*1	I _{S1}	1.6			A
	Conditions	V _{IN} =1.8V, V _B =3.3V			
V _C Terminal	Control Voltage (Output ON)*2	V _{C, IH}	2		V
	Control Voltage (Output OFF)	V _{C, IL}		0.8	V
	Control Current (Output ON)	I _{C, IH}		50	μA
	Control Current (Output ON)	Conditions	V _C =2.7V		
	Control Current (Output OFF)	I _{C, IL}		10	μA
	Control Current (Output OFF)	Conditions	V _C =0.4V		

*1: I_{S1} is specified at the 5% drop point of output voltage V_o on the condition that V_{IN} = overcurrent protection starting current, I_o = 10 mA.*2: Output is OFF when the output control terminal (V_C terminal) is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.

External Dimensions

(unit : mm)




Pin Assignment

- ① V_O
- ② ADJ
- ③ V_B
- ④ V_C
- ⑤ GND
- ⑥ GND
- ⑦ V_{IN}
- ⑧ V_{IN}

Plastic Mold Package Type
 Flammability: UL94V-0
 Product Mass: Approx. 0.1g

Typical Connection Diagram/Block Diagram



C_{IN}, C_B: Input and bias capacitors (Approx. 0.1 to 10μF)

Required when the input line contains inductance or when the wiring is long.

C_O: Output capacitor (47μF or larger)

SI-3010LLSL is designed to use a low ESR capacitor (such as a ceramic capacitor) for the output capacitor. The recommended ESR value for an output capacitor is 500mΩ or less (at room temperature).

R1, R2: Output voltage setting resistors

The output voltage can be set by connecting R1 and R2 as shown at left.

The recommended value for R2 is 10kΩ.


$$R1 = (V_O - V_{ADJ}) / (V_{ADJ} / R2)$$

C_{SS}: Soft start capacitor

The rising time of the output voltage can be set by connecting C_{SS} between V_{OUT} and ADJ.

Reference Data

Copper Laminate Area - Power Dissipation



SI-3000ZD Series Surface-Mount, Low Dropout Voltage Linear Regulator IC

■Features

- Compact surface-mount package (TO263-5)
- Output current: 3.0A
- Low dropout voltage: $V_{DIF} \leq 0.6V$ (at $I_o = 3.0A$)
- Low circuit current at output OFF: $I_q (OFF) \leq 1\mu A$
- Built-in overcurrent and thermal protection circuits

■Applications

- Secondary stabilized power supply (local power supply)

■Absolute Maximum Ratings

($T_a=25^\circ C$)

Parameter	Symbol	Rated	Unit
DC Input Voltage	V_{IN}^{*1}	10	V
Output Control Terminal Voltage	V_c	6	V
DC Output Current	I_o^{*1}	3.0	A
Power Dissipation	P_D^{*3}	3	W
Junction Temperature	T_j	-30 to +125	$^\circ C$
Operating Ambient Temperature	T_{op}	-30 to +85	$^\circ C$
Storage Temperature	T_{stg}	-40 to +125	$^\circ C$
Thermal Resistance (Junction to Ambient Air)	θ_{ja}	33.3	$^\circ C/W$
Thermal Resistance (Junction to Case)	θ_{jc}	3	$^\circ C/W$

■Recommended Operating Conditions

Parameter	Symbol	Rated	Unit	Remarks
Input Voltage	V_{IN}	*2 to 6^{*1}	V	
Output Current	I_o	0 to 3	A	
Operating Ambient Temperature	$T_{op(a)}$	-20 to +85	$^\circ C$	
Operating Junction Temperature	$T_{op(j)}$	-20 to +100	$^\circ C$	
Output Voltage Variable Range	V_{OAdj}	1.2 to 5	V	Only for SI-3011ZD. Refer to the block diagram.

*1: $V_{IN} (max)$ and $I_o (max)$ are restricted by the relation $P_D = (V_{IN} - V_o) \times I_o$.

*2: Set the input voltage to 2.4V or higher when setting the output voltage to 2.0V or lower (SI-3011ZD).

*3: When mounted on glass-epoxy board of 40 × 40mm (copper laminate area 100%)

■Electrical Characteristics

($T_a=25^\circ C$, $V_c=2V$ unless otherwise specified)

Parameter	Symbol	Ratings									Unit
		SI-3011ZD (Variable type)			SI-3025ZD			SI-3033ZD			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Output Voltage (Reference Voltage V_{ADJ} for SI-3011ZD)	$V_o (V_{ADJ})$	1.078	1.100	1.122	2.45	2.50	2.55	3.234	3.300	3.366	V
	Conditions	$V_{IN}=V_o+1V, I_o=10mA$			$V_{IN}=3.3V, I_o=10mA$			$V_{IN}=5V, I_o=10mA$			
Line Regulation	ΔV_{OLINE}			10			10			10	mV
	Conditions	$V_{IN}=3.3$ to $5V, I_o=10mA (V_o=2.5V)$			$V_{IN}=3.3$ to $5V, I_o=10mA$			$V_{IN}=4.5$ to $5.5V, I_o=10mA$			
Load Regulation	ΔV_{OLOAD}			40			40			40	mV
	Conditions	$V_{IN}=3.3V, I_o=0$ to $3A (V_o=2.5V)$			$V_{IN}=3.3V, I_o=0$ to $3A$			$V_{IN}=5V, I_o=0$ to $3A$			
Dropout Voltage	V_{DIF}			0.6			0.6			0.6	V
	Conditions	$I_o=3A (V_o=2.5V)$			$I_o=3A$			$I_o=3A$			
Quiescent Circuit Current	I_q		1	1.5		1	1.5		1	1.5	mA
	Conditions	$V_{IN}=V_o+1V, I_o=0A, V_c=2V$			$V_{IN}=3.3V, I_o=0A, V_c=2V$			$V_{IN}=5V, I_o=0A, V_c=2V$			
Circuit Current at Output OFF	$I_q (OFF)$			1			1			1	μA
	Conditions	$V_{IN}=V_o+1V, V_c=0V$			$V_{IN}=3.3V, V_c=0V$			$V_{IN}=5V, V_c=0V$			
Temperature Coefficient of Output Voltage	$\Delta V_o/\Delta T_a$		± 0.3			± 0.3			± 0.3		mV/ $^\circ C$
	Conditions	$T_j=0$ to $100^\circ C$			$T_j=0$ to $100^\circ C$			$T_j=0$ to $100^\circ C$			
Ripple Rejection	R_{REJ}		60			60			60		dB
	Conditions	$V_{IN}=V_o+1V, f=100$ to $120Hz, I_o=0.1A$			$V_{IN}=3.3V, f=100$ to $120Hz, I_o=0.1A$			$V_{IN}=5V, f=100$ to $120Hz, I_o=0.1A$			
Overcurrent Protection Starting Current ^{*2}	I_{S1}	3.2			3.2			3.2			A
	Conditions	$V_{IN}=V_o+1V$			$V_{IN}=3.3V$			$V_{IN}=5V$			
V_c Terminal	Control Voltage (Output ON) ^{*3}	V_c, IH	2		2			2			V
	Control Voltage (Output OFF) ^{*3}	V_c, IL					0.8			0.8	
	Control Current (Output ON)	I_c, IH			100			100		100	μA
	Control Current (Output OFF)	I_c, IL	-5	0		-5	0		-5	0	μA
	Conditions	$V_c=2.7V$			$V_c=2.7V$			$V_c=2.7V$			
	Conditions	$V_c=0V$			$V_c=0V$			$V_c=0V$			

*1: Set the input voltage to 2.4V or higher when setting the output voltage to 2.0V or lower.

*2: I_{S1} is specified at the -5% drop point of output voltage V_o under the condition of Output Voltage parameter.


*3: Output is OFF when the output control terminal (V_c terminal) is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.

*4: These products cannot be used for the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.

- (1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_o adjustment by raising ground voltage

External Dimensions

(Unit : mm)



Notes

- 1) The dimensions do not include mold burrs.
- 2) Values in parentheses are for reference.
- 3) Values in square brackets are the dimensions after lead forming.
- 4) Backside Flatness: 0.8mm max.
- 5) Unit: mm


Pin Assignment

- ① Vc
 - ② VIN
 - ③ GND (Common to the rear side of product)
 - ④ Vo
 - ⑤ Sense
- (ADJ for SI-3011ZD)

Plastic Mold Package Type
 Flammability: UL94V-0
 Product Mass: Approx. 1.48g

Block Diagram

SI-3011ZD




CIN: Input capacitor (Approx. 10μF)

Co: Output capacitor (47μF or larger)

The output voltage may oscillate if a low ESR type capacitor (such as a ceramic capacitor) is used for the output capacitor in the SI-3000ZD Series.

SI-3025ZD, SI-3033ZD



R1, R2: Output voltage setting resistors

The output voltage can be set by connecting R1 and R2 as shown at left.


The recommended value for R2 is 10kΩ or 11kΩ.

$$R1 = (Vo - V_{ADJ}) / (V_{ADJ} / R2)$$

*: Insert R3 in case of setting Vo to Vo ≤ 1.8V. The recommended value for R3 is 10kΩ.

Reference Data

Copper Laminate Area (on Glass-Epoxy Board) vs. Thermal Resistance (from Junction to Ambient Temperature) (Typical Value)



- A higher heat radiation effect can be achieved by enlarging the copper laminate area connected to the inner frame to which a monolithic IC is mounted.
- Obtaining the junction temperature
 Measure GND terminal temperature Tc with a thermocouple, etc. Then substitute this value in the following formula to obtain the junction temperature.

$$T_j = P_D \times \theta_{j-a} + T_c \quad P_D = (V_{IN} - V_O) \cdot I_{OUT}$$

SI-3000B Series 5-Terminal, Full-Mold, Low Dropout Linear Regulator IC

■Features

- Compact full-mold package (equivalent to TO220)
- Output current: 0.27A
- Low dropout voltage: $V_{DIF} \leq 0.5V$ (at $I_O=0.27A$)
- Output ON/OFF control terminal is compatible with LS-TTL. (It can be driven directly by LS-TTL or standard CMOS logic.)
- Built-in foldback overcurrent and thermal protection circuits
- Accuracy of overcurrent protection starting current
 SI-3157B : 0.3 to 0.7A ($V_{IN}=18V$)
 SI-3025B : 0.3 to 0.7A
 (When $V_{IN}=18V$, at $V_O=15.7V$)
 0.3 to 0.75A
 (When $V_{IN}=18V$, at $V_O=11.7V$)
- Variable output voltage type (SI-3025B) also available

■Absolute Maximum Ratings

(Ta=25°C)

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V_{IN}	35	V
Output Control Terminal Voltage	V_C	V_{IN}	V
DC Output Current	I_O	0.27^{*1}	A
Power Dissipation	P_{D1}	14(With infinite heatsink)	W
	P_{D2}	1.5(Without heatsink, stand-alone operation)	W
Junction Temperature	T_J	-40 to +125	°C
Operating Ambient Temperature	T_{OP}	-30 to +100	°C
Storage Temperature	T_{stg}	-40 to +125	°C
Thermal Resistance (junction to case)	θ_{j-c}	7.0	°C/W
Thermal Resistance (junction to ambient air)	θ_{j-a}	66.7(Without heatsink, stand-alone operation)	°C/W

■Applications

- For BS and CS antenna power supplies
- Electronic equipment

■Electrical Characteristics

(Ta=25°C unless otherwise specified)

Parameter	Symbol	Ratings						Unit	
		SI-3157B			SI-3025B				
		min.	typ.	max.	min.	typ.	max.		
Input Voltage	V_{IN}	^{*2}		27^{*1}	$6^{*2,6}$		27^{*1}	V	
Output Voltage (Reference Voltage V_{ADJ} for SI-3025B)	V_O (V_{ADJ})	14.92	15.70	16.48	2.448	2.550	2.652	V	
	Conditions	$V_{IN}=18V, I_O=0.2A$			$V_{IN}=V_O+3V, I_O=0.2A$				
Dropout Voltage	V_{DIF}			0.5			0.5	V	
	Conditions	$I_O \leq 0.27A$			$I_O \leq 0.27A$				
Line Regulation	ΔV_{OLINE}		30	90			10	mV	
	Conditions	$V_{IN}=17$ to $27V, I_O=0.2A$			$V_{IN}=(V_O+1)$ to $27V, I_O=0.27A$				
Load Regulation	ΔV_{OLOAD}		120	300			10	mV	
	Conditions	$V_{IN}=18V, I_O=0$ to $0.27A$			$V_{IN}=V_O+3V, I_O=0$ to $0.27A$				
Temperature Coefficient of Output Voltage (Reference Voltage V_{ADJ} : Temperature Coefficient of Reference Voltage)	$\Delta V_O/\Delta T_a$ ($\Delta V_{ADJ}/\Delta T_a$)		± 1.5			± 0.5		mV/°C	
	Conditions	$V_{IN}=18V, I_O=5mA, T_J=0$ to $100^\circ C$			$V_{IN}=V_O+3V, I_O=5mA, T_J=0$ to $100^\circ C$				
Ripple Rejection	R_{REJ}		54			54		dB	
	Conditions	$V_{IN}=18V, f=100$ to $120Hz$			$V_{IN}=V_O+3V, f=100$ to $120Hz$				
Quiescent Circuit Current	I_q		3	10		3	10	mA	
	Conditions	$V_{IN}=18V, I_O=0A$			$V_{IN}=V_O+3V, I_O=0A$				
Overcurrent Protection Starting Current ^{*3,4}	I_{S1}	0.3		0.7	0.3		0.75	A	
	Conditions	$V_{IN}=18V$			$V_{IN}=18V$, at $V_O=11.7V$				
	Conditions				0.3 $V_{IN}=18V$, at $V_O=15.7V$				
V_C Terminal ^{*5}	Control Voltage (Output ON)	V_C : IH	2.0		2.0			V	
	Control Voltage (Output OFF)	V_C : IL					0.8		
	Control Current (Output ON)	I_C : IH			20			20	μA
	Conditions	$V_C=2.7V$			$V_C=2.7V$				
	Control Current (Output OFF)	I_C : IL			-0.3			-0.3	mA
	Conditions	$V_C=0.4V$			$V_C=0.4V$				

*1: $V_{IN(max)}$ and $I_{O(max)}$ are restricted by the relation $P_{D(max)}=(V_{IN}-V_O) \cdot I_O=14(W)$.

*2: Refer to the Dropout Voltage parameter. (Refer to Setting DC Input Voltage on page 7.)

*3: I_{S1} is specified at the 5% drop point of output voltage V_O on the condition that $V_{IN}=V_O+3V, I_O=0.2A$.

*4: These products cannot be used in the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.

(1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_O adjustment by raising ground voltage*5: Output is ON even when output control terminal V_C is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.

*6: When setting output voltage to 5V or lower, input voltage needs to be set to 6V or higher to operate stably.

External Dimensions

(Unit : mm)

a. Part Number
b. Lot Number


Pin Assignment

SI-3157B	SI-3025B
① GND	① GND
② Vc	② Vc
③ Vo	③ Vo
④ Sense	④ ADJ
⑤ VIN	⑤ VIN

Plastic Mold Package Type
Flammability: UL94V-0
Product Mass: Approx. 2.3g

Forming No. 1101

Block Diagram



Typical Connection Diagram


SI-3157B

SI-3025B

C_0 : Output capacitor (47 to 100 μ F)
 $*1 C_1$ } : Oscillation prevention capacitor
 C_2 } (Approx. C_1 : 47 μ F, C_2 : 0.33 μ F)
 These capacitors are required if the input line contains inductance or the wiring is long. Especially at low temperatures, tantalum capacitors are recommended for C_1 and C_0 .
 $*2 D_1$: Protection diode
 This diode is required for protection against reverse biasing of the input and output. Sanken EU2Z is recommended.
 $*3 R_1$ } : External resistor for setting output voltage
 R_2 } The relation between output voltage V_o and external resistors R_1 and R_2 is as follows.

$$V_o = V_{ADJ} \cdot \left(1 + \frac{R_1}{R_2} \right) \quad (V_{ADJ} = 2.55V(\text{typ.}))$$
 R_2 must be 2.55k Ω for stable operation.

Ta-Pd Characteristics



SI-3000N Series 3-Terminal, Full-Mold, Low Dropout Voltage Linear Regulator IC

Features

- Compact full-mold package (equivalent to TO220)
- Output current: 1.0A
- Low dropout voltage: $V_{DIF} \leq 1V$ (at $I_o=1.0A$)
- Built-in foldback-overcurrent, input-overvoltage and thermal protection circuits

Applications

- For stabilization of the secondary-side output voltage of switching power supplies.
- Electronic equipment

Absolute Maximum Ratings

(T_a=25°C)

Parameter	Symbol	Ratings			Unit
		SI-3050N	SI-3090N/3120N	SI-3150N	
DC Input Voltage	V _{IN}	25	30	35	V
DC Output Current	I _o	1.0 ²			A
Power Dissipation	P _{D1}	14(With infinite heatsink)			W
	P _{D2}	1.5(Without heatsink, stand-alone operation)			W
Junction Temperature	T _J	-40 to +125			°C
Operating Ambient Temperature	T _{op}	-30 to +100			°C
Storage Temperature	T _{stg}	-40 to +125			°C
Thermal Resistance (junction to case)	θ _{J-C}	7.0			°C/W
Thermal Resistance (junction to ambient air)	θ _{J-A}	66.7(Without heatsink, stand-alone operation)			°C/W

Electrical Characteristics

(T_a=25°C unless otherwise specified)

Parameter	Symbol	Ratings												Unit		
		SI-3050N			SI-3090N			SI-3120N			SI-3150N					
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.			
Input Voltage	V _{IN}	6 ³			10 ³			13 ³			16 ³			V		
Output Voltage	V _o	4.80			8.64			11.52			14.40			V		
		5.00			9.00			12.00			15.00					
Dropout Voltage	V _{DIF}	Conditions			V _{IN} =8V, I _o =0.5A			V _{IN} =12V, I _o =0.5A			V _{IN} =15V, I _o =0.5A			V _{IN} =18V, I _o =0.5A		
		Conditions			I _o ≤0.5A			I _o ≤0.5A			I _o ≤0.5A			I _o ≤0.5A		
		Conditions			I _o ≤1.0A			I _o ≤1.0A			I _o ≤1.0A			I _o ≤1.0A		
		Conditions			I _o ≤1.0A			I _o ≤1.0A			I _o ≤1.0A			I _o ≤1.0A		
Line Regulation	ΔV _{OLINE}	10			18			24			30			mV		
		30			48			64			90					
Load Regulation	ΔV _{OLOAD}	Conditions			V _{IN} =6 to 15V, I _o =0.5A			V _{IN} =10 to 20V, I _o =0.5A			V _{IN} =13 to 25V, I _o =0.5A			V _{IN} =16 to 27V, I _o =0.5A		
		40			70			93			120			300		
Temperature Coefficient of Output Voltage	ΔV _O /ΔT _a	±0.5			±1.0			±1.5			±1.5			mV/°C		
		Conditions			V _{IN} =8V, I _o =5mA, T _J =0 to 100°C			V _{IN} =12V, I _o =5mA, T _J =0 to 100°C			V _{IN} =15V, I _o =5mA, T _J =0 to 100°C				V _{IN} =18V, I _o =5mA, T _J =0 to 100°C	
Ripple Rejection	R _{REJ}	54			54			54			54			dB		
		Conditions			V _{IN} =8V, f=100 to 120Hz			V _{IN} =12V, f=100 to 120Hz			V _{IN} =15V, f=100 to 120Hz				V _{IN} =18V, f=100 to 120Hz	
Quiescent Circuit Current	I _q	3			3			3			3			mA		
		10			10			10			10					
Overcurrent Protection Starting Current ^{4,5}	I _{S1}	1.2			1.2			1.2			1.2			A		
		Conditions			V _{IN} =8V			V _{IN} =12V			V _{IN} =15V				V _{IN} =18V	

*1: In some cases, "A" may be printed on the right of the marking.

*2: V_{IN(max)} and I_{o(max)} are restricted by the relation P_{D(max)}=(V_{IN}-V_o)•I_o≤14(W).

*3: Refer to the Dropout Voltage parameter. (Refer to Setting DC Input Voltage on page 7.)


*4: I_{S1} is specified at the 5% drop point of output voltage V_o on the condition that V_{IN}=V_o+3V, I_o=0.5A.

*5: These products cannot be used in the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.


(1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_o adjustment by raising ground voltage

External Dimensions


(Unit : mm)




Block Diagram



Typical Connection Diagram



T_a-P_d Characteristics



SI-3003N Series 3-Terminal, Full-Mold, Low Dropout Voltage Linear Regulator IC

Features

- Compact full-mold package (equivalent to TO220)
- Output current: 1.0A
- Low dropout voltage: $V_{DIF} \leq 0.5V$ (at $I_o=1.0A$)
- Built-in drooping-overcurrent, input-overvoltage and thermal protection circuits
- Supports constant current load and positive and negative power supplies.

Applications

- For stabilization of the secondary-side output voltage of switching power supplies.
- Electronic equipment

Absolute Maximum Ratings

(T_a=25°C)

Parameter	Symbol	Ratings			Unit
		SI-3053N	SI-3123N	SI-3153N	
DC Input Voltage	V _{IN}	25	30	30	V
DC Output Current	I _o	1.0 ^{*1}			A
Power Dissipation	P _{D1}	20(With infinite heatsink)			W
	P _{D2}	1.5(Without heatsink, stand-alone operation)			W
Junction Temperature	T _J	-40 to +125			°C
Operating Ambient Temperature	T _{OP}	-30 to +100			°C
Storage Temperature	T _{STG}	-40 to +125			°C
Thermal Resistance (junction to case)	θ _{J-C}	5.0			°C/W
Thermal Resistance (junction to ambient air)	θ _{J-A}	66.7(Without heatsink, stand-alone operation)			°C/W

Electrical Characteristics

(T_a=25°C unless otherwise specified)

Parameter	Symbol	Ratings									Unit
		SI-3053N			SI-3123N			SI-3153N			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Input Voltage	V _{IN}	6 ^{*2}		15 ^{*1}	13 ^{*2}		22 ^{*1}	16 ^{*2}		25 ^{*1}	V
Output Voltage	V _o	4.90	5.00	5.10	11.76	12.00	12.24	14.70	15.00	15.30	V
	Conditions	V _{IN} =8V, I _o =1.0A			V _{IN} =15V, I _o =1.0A			V _{IN} =18V, I _o =1.0A			
Dropout Voltage	V _{DIF}			0.5			0.5			0.5	V
	Conditions	I _o ≤1.0A									
Line Regulation	ΔV _{OLINE}		10	30		24	64		30	90	mV
	Conditions	V _{IN} =6V to 15V, I _o =1.0A			V _{IN} =13V to 22V, I _o =1.0A			V _{IN} =16V to 25V, I _o =1.0A			
Load Regulation	ΔV _{OLOAD}		20	50		40	120		50	150	mV
	Conditions	V _{IN} =8V, I _o =0 to 1.0A			V _{IN} =15V, I _o =0 to 1.0A			V _{IN} =18V, I _o =0 to 1.0A			
Temperature Coefficient of Output Voltage	ΔV _O /ΔT _a		±0.5			±1.5			±1.5		mV/°C
	Conditions	V _{IN} =8V, I _o =5mA, T _J =0 to 100°C			V _{IN} =15V, I _o =5mA, T _J =0 to 100°C			V _{IN} =18V, I _o =5mA, T _J =0 to 100°C			
Ripple Rejection	R _{REJ}		54			54			54		dB
	Conditions	V _{IN} =8V, f=100 to 120Hz			V _{IN} =15V, f=100 to 120Hz			V _{IN} =18V, f=100 to 120Hz			
Quiescent Circuit Current	I _q		3	10		3	10		3	10	mA
	Conditions	V _{IN} =8V, I _o =0A			V _{IN} =15V, I _o =0A			V _{IN} =18V, I _o =0A			
Overcurrent Protection Starting Current ^{4,5}	I _{S1}	1.2			1.2			1.2			A
	Conditions	V _{IN} =8V			V _{IN} =15V			V _{IN} =18V			
Current Limit at Output Short Circuit	I _{S2}	1.2			1.2			1.2			A
	Conditions	V _{IN} =8V, V _O =0A			V _{IN} =15V, V _O =0A			V _{IN} =18V, V _O =0A			


*1: V_{IN(max)} and I_{O(max)} are restricted by the relation P_{D(max)}=(V_{IN}-V_O)•I_o≤20(W).

*2: Refer to the dropout voltage parameter. (Refer to Setting DC Input Voltage on page 7.)


*3: I_{S1} is specified at the 5% drop point of output voltage V_o on the condition that V_{IN}=V_O+3V, I_o=1A.

External Dimensions


(Unit : mm)




Block Diagram



Typical Connection Diagram



Ta-Pd Characteristics



SI-3000F Series 5-Terminal, Full-Mold, Low Dropout Voltage Linear Regulator IC

Features

- Compact full-mold package (equivalent to TO220)
- Output current: 1.0A
- Low dropout voltage: $V_{DIF} \leq 1V$ (at $I_o=1.0A$)
- Variable output voltage (rise only)
Available for remote sensing (excluding SI-3025F)
- Output ON/OFF control terminal is compatible with LS-TTL. (It can be driven directly by LS-TTL or standard CMOS logic.)
- Built-in foldback-overcurrent, input-overvoltage and thermal protection circuits
- Variable output voltage type (SI-3025F) also available

Absolute Maximum Ratings

($T_a=25^\circ C$)

Parameter	Symbol	Ratings					Unit
		SI-3050F	SI-3090F/3120F	SI-3150F/3157F	SI-3240F	SI-3025F	
DC Input Voltage	V_{IN}	25	30	35	45	30	V
Output Control Terminal Voltage	V_c	V_{IN}					V
DC Output Current	I_o	1.0^{*2}					A
Power Dissipation	P_{D1}	14**(With infinite heatsink)					W
	P_{D2}	1.5(Without heatsink, stand-alone operation)					W
Junction Temperature	T_j	-40 to +125					$^\circ C$
Operating Ambient Temperature	T_{op}	-30 to +100					$^\circ C$
Storage Temperature	T_{stg}	-40 to +125					$^\circ C$
Thermal Resistance (junction to case)	θ_{j-c}	7.0***					$^\circ C/W$
Thermal Resistance (junction to ambient air)	θ_{j-a}	66.7(Without heatsink, stand-alone operation)					$^\circ C/W$

** SI-3240F: 18

*** SI-3240F: 5.5

Applications

- For stabilization of the secondary-side output voltage of switching power supplies.
- Electronic equipment

Electrical Characteristics (except SI-3025F)

($T_a=25^\circ C$ unless otherwise specified)

Parameter	Symbol	Ratings															Unit				
		SI-3050F			SI-3090F			SI-3120F			SI-3150F			SI-3157F				SI-3240F			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.		min.	typ.	max.	
Input Voltage	V_{IN}	6 ³		15 ²	10 ³		20 ²	13 ³		25 ²	16 ³		27 ²	16.7 ³		27 ²	25 ³		40 ²	V	
Output Voltage	V_o	SI-3000F *1			SI-3000FA															V	
		4.80	5.00	5.20	8.64	9.00	9.36	11.52	12.00	12.48	14.40	15.00	15.60	14.92	15.70	16.48	23.04	24.00	24.96		
Dropout Voltage	V_{DIF}	Conditions $V_{IN}=8V, I_o=0.5A$			Conditions $V_{IN}=12V, I_o=0.5A$			Conditions $V_{IN}=15V, I_o=0.5A$			Conditions $V_{IN}=18V, I_o=0.5A$			Conditions $V_{IN}=19V, I_o=0.5A$			Conditions $V_{IN}=27V, I_o=0.5A$			V	
		0.5			0.5			0.5			0.5			0.5							
		Conditions $I_o \leq 0.5A$			Conditions $I_o \leq 0.5A$			Conditions $I_o \leq 0.5A$			Conditions $I_o \leq 0.5A$			Conditions $I_o \leq 0.5A$			Conditions $I_o \leq 0.5A$				
Line Regulation	ΔV_{OLINE}	10			18			24			30			30			48			mV	
		30			48			64			90			90			128				
		Conditions $V_{IN}=8V$ to 15V, $I_o=0.5A$			Conditions $V_{IN}=10V$ to 20V, $I_o=0.5A$			Conditions $V_{IN}=13V$ to 25V, $I_o=0.5A$			Conditions $V_{IN}=16V$ to 27V, $I_o=0.5A$			Conditions $V_{IN}=17V$ to 27V, $I_o=0.5A$			Conditions $V_{IN}=25V$ to 38V, $I_o=0.5A$				
Load Regulation	ΔV_{OLOAD}	40			70			93			120			120			120			mV	
		100			180			240			300			300			300				
Temperature Coefficient of Output Voltage	$\Delta V_o/\Delta T_a$	± 0.5			± 1.0			± 1.5			± 1.5			± 1.5			± 2.5			mV/ $^\circ C$	
		Conditions $V_{IN}=8V, I_o=5mA, T_j=0$ to 100 $^\circ C$			Conditions $V_{IN}=12V, I_o=5mA, T_j=0$ to 100 $^\circ C$			Conditions $V_{IN}=15V, I_o=5mA, T_j=0$ to 100 $^\circ C$			Conditions $V_{IN}=18V, I_o=5mA, T_j=0$ to 100 $^\circ C$			Conditions $V_{IN}=19V, I_o=5mA, T_j=0$ to 100 $^\circ C$			Conditions $V_{IN}=27V, I_o=5mA, T_j=0$ to 100 $^\circ C$				
Ripple Rejection	RREJ	54			54			54			54			54			54			dB	
		Conditions $V_{IN}=8V, f=100$ to 120Hz			Conditions $V_{IN}=12V, f=100$ to 120Hz			Conditions $V_{IN}=15V, f=100$ to 120Hz			Conditions $V_{IN}=18V, f=100$ to 120Hz			Conditions $V_{IN}=19V, f=100$ to 120Hz			Conditions $V_{IN}=27V, f=100$ to 120Hz				
Quiescent Circuit Current	I_q	3			3			3			3			3			5			mA	
		10			10			10			10			10			10				
Overcurrent Protection Starting Current ^{4,7}	I_{S1}	1.2			1.2			1.2			1.2			1.2			1.2			A	
		Conditions $V_{IN}=8V$			Conditions $V_{IN}=12V$			Conditions $V_{IN}=15V$			Conditions $V_{IN}=18V$			Conditions $V_{IN}=19V$			Conditions $V_{IN}=27V$				
Vc Terminal ⁵	Control Voltage (Output ON)	V_c IH	2.0		2.0		2.0		2.0		2.0		2.0		2.0		2.0		2.0	V	
	Control Voltage (Output OFF)	V_c IL		0.8		0.8		0.8		0.8		0.8		0.8		0.8		0.8		0.8	
	Control Current (Output ON)	I_c IH		20		20		20		20		20		20		20		20		20	μA
	Control Current (Output OFF)	I_c IL		-0.3		-0.3		-0.3		-0.3		-0.3		-0.3		-0.3		-0.3		-0.3	mA
	Conditions	$V_c=2.7V$																			
Conditions	$V_c=0.4V$																				

*1: In some cases, "A" may be printed on the right of the marking.

*2: $V_{IN(max)}$ and $I_{O(max)}$ are restricted by the relation $P_{D(max)}=(V_{IN}-V_o) \cdot I_o=14W$ (SI-3240F: 18W).

*3: Refer to the Dropout Voltage parameter. (Refer to Setting DC Input Voltage on page 7.)

*4: I_{S1} is specified at the 5% drop point of output voltage V_o on the condition that $V_{IN}=V_o+3V, I_o=0.5A$.

*5: Output is ON even when output control terminal VC is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.

*6: When setting output voltage to 5V or lower, input voltage needs to be set to 6V or higher to operate stably.

*7: These products cannot be used in the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.

(1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_o adjustment by raising ground voltage


■Electrical Characteristics (SI-3025F)

(T_a=25°C unless otherwise specified)


Parameter	Symbol	Ratings			Unit	
		SI-3025F				
		min.	typ.	max.		
Input Voltage	V _{IN}	6 ^⑥		25 ^②	V	
Output Voltage	V _O	3		24	V	
Reference Voltage	V _{REF}	2.45	2.55	2.65	V	
Dropout Voltage	V _{ADJ}			0.5	V	
	Conditions	I _O ≤0.5A				
	Conditions	I _O ≤1.0A				
Line Regulation	ΔV _{OLINE}			10	mV/V	
	Conditions	V _{IN} =V _O +1 to 25V, I _O =0.5A				
Load Regulation	ΔV _{OLOAD}			20	mV/V	
	Conditions	V _{IN} =V _O +3V, I _O =0 to 1.0A				
Temperature Coefficient of Reference Voltage	ΔV _{REF} /ΔT _a		±0.5		mV/°C	
	Conditions	V _{IN} =V _O +3V, I _O =5mA, T _J =0 to 100°C				
Ripple Rejection	R _{REJ}		54		dB	
	Conditions	V _{IN} =V _O +3V, f=100 to 120Hz				
Quiescent Circuit Current	I _q		3	10	mA	
	Conditions	V _{IN} =V _O +3V, I _O =0A				
Overcurrent Protection Starting Current ^{4,7}	I _{S1}	1.2			A	
	Conditions	V _{IN} =V _O +3V				
V _c Terminal ⁵	Control Voltage (Output ON)	V _c IH	2.0		V	
	Control Voltage (Output OFF)	V _c IL		0.8		
	Control Current (Output ON)	I _c IH			20	μA
		Conditions	V _C =2.7V			
	Control Current (Output OFF)	I _c IL			-0.3	mA
		Conditions	V _C =0.4V			

■External Dimensions


(Unit : mm)




■Block Diagram



■Typical Connection Diagram



■ T_a - P_d Characteristics



SI-3000KF Series Low Current Consumption, Low Dropout Voltage Linear Regulator IC

Features

- Compact full-mold package (equivalent to TO220)
- Output current: 1.0A
- Low dropout voltage: $V_{DIF} \leq 0.5V$ (at $I_o = 1.0A$)
- High ripple rejection: 75 to 80dB
- Low circuit current at output OFF: $I_q (OFF) \leq 1\mu A$
- Built-in overcurrent and thermal protection circuits

Applications

- Secondary stabilized power supply (local power supply)

Absolute Maximum Ratings

($T_a=25^\circ C$)

Parameter	Symbol	Ratings		Unit	Remarks
		SI-3018KF/3025KF/3033KF	SI-3010KF/3050KF/3090KF/3120KF/3150KF		
DC Input Voltage	V_{IN}	20	35 ¹	V	
Output Control Terminal Voltage	V_c	V_{IN}		V	
DC Output Current	I_o	1.0		A	
Power Dissipation	P_{D1}	16.6		W	With infinite heatsink
	P_{D2}	1.5			Without heatsink, stand-alone operation
Junction Temperature	T_j	-30 to +125		$^\circ C$	
Storage Temperature	T_{stg}	-30 to +125		$^\circ C$	
Operating Ambient Temperature	T_{op}	-30 to +100		$^\circ C$	
Thermal Resistance (Junction to Case)	θ_{j-c}	6.0		$^\circ C/W$	
Thermal Resistance (Junction to Ambient Air)	θ_{j-a}	66.7		$^\circ C/W$	Without heatsink, stand-alone operation

*1: A built-in input-overvoltage-protection circuit shuts down the output voltage at the Input Overvoltage Shutdown Voltage of the electrical characteristics.

Recommended Operating Conditions

Parameter	Symbol	Ratings								Unit
		SI-3010KF	SI-3018KF	SI-3025KF	SI-3033KF	SI-3050KF	SI-3090KF	SI-3120KF	SI-3150KF	
Input Voltage Range	V_{IN}	2.4 ² to 27 ¹	2.4 ² to 10 ¹	² to 10 ¹	² to 10 ¹	² to 15 ¹	² to 20 ¹	² to 25 ¹	² to 27 ¹	V
Output Current Range	I_o	0 to 1.0 ¹								A
Output Voltage Variable Range	V_{oADJ}	1.2 to 16	-							V
Operating Ambient Temperature	T_{op}	-30 to +85								$^\circ C$
Operating Junction Temperature	T_j	-20 to +100								$^\circ C$

*1: V_{IN} (max) and I_o (max) are restricted by the relationship P_D (max) = $(V_{IN} - V_o) \times I_o = 16.6W$.

*2: Refer to the Dropout Voltage parameter.

Electrical Characteristics

Parameter	Symbol	Ratings									Unit
		SI-3018KF			SI-3025KF			SI-3033KF			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Output Voltage (Reference Voltage for SI-3010KD)	$V_o (V_{ADJ})$	1.764	1.800	1.836	2.45	2.50	2.55	3.234	3.300	3.366	V
Line Regulation	ΔV_{OLINE}	15			20			30			mV
	Conditions	$V_{IN}=2.5V, I_o=0.01A, V_c=2V$			$V_{IN}=3.3V, I_o=0.01A, V_c=2V$			$V_{IN}=5V, I_o=0.01A, V_c=2V$			
Load Regulation	ΔV_{OLOAD}	36			40			50			mV
	Conditions	$V_{IN}=2.5V, I_o=0$ to 1A, $V_c=2V$			$V_{IN}=3.3V, I_o=0$ to 1A, $V_c=2V$			$V_{IN}=5V, I_o=0$ to 1A, $V_c=2V$			
Dropout Voltage	V_{DIF}	0.6			0.3			0.3			V
	Conditions	$I_o \leq 0.5A, V_c=2V$			$I_o \leq 0.5A, V_c=2V$			$I_o \leq 0.5A, V_c=2V$			
	Conditions	$I_o \leq 1.0A, V_c=2V$			$I_o \leq 1.0A, V_c=2V$			$I_o \leq 1.0A, V_c=2V$			
Quiescent Circuit Current	I_q	500			500			500			μA
	Conditions	$V_{IN}=2.5V, I_o=0A, V_c=2V$			$V_{IN}=3.3V, I_o=0A, V_c=2V$			$V_{IN}=5V, I_o=0A, V_c=2V$			
Circuit Current at Output OFF	$I_q (OFF)$	1			1			1			μA
	Conditions	$V_{IN}=2.5V, V_c=0V$			$V_{IN}=3.3V, V_c=0V$			$V_{IN}=5V, V_c=0V$			
Temperature Coefficient of Output Voltage	$\Delta V_o/\Delta T_a$	± 0.2			± 0.3			± 0.3			mV/ $^\circ C$
	Conditions	$V_{IN}=2.5V, I_o=0.01A, V_o=2V, T_j=0$ to 100 $^\circ C$			$V_{IN}=3.3V, I_o=0.01A, V_o=2V, T_j=0$ to 100 $^\circ C$			$V_{IN}=5V, I_o=0.01A, V_o=2V, T_j=0$ to 100 $^\circ C$			
Ripple Rejection	R_{REJ}	80			79			76			dB
	Conditions	$V_{IN}=2.5V, I_o=0.1A, V_c=2V, f=100$ to 120Hz			$V_{IN}=3.3V, I_o=0.1A, V_c=2V, f=100$ to 120Hz			$V_{IN}=5V, I_o=0.1A, V_c=2V, f=100$ to 120Hz			
Overcurrent Protection Starting Current ³	I_{S1}	1.1			1.1			1.1			A
	Conditions	$V_{IN}=2.5V, V_c=2V$			$V_{IN}=3.3V, V_c=2V$			$V_{IN}=5V, V_c=2V$			
V_c Terminal	Control Voltage (Output ON) ⁴	V_c, I_H	2		2		2				V
		Conditions	$V_{IN}=2.5V$		$V_{IN}=3.3V$		$V_{IN}=5V$				
	Control Voltage (Output OFF)	V_c, I_L	0.8		0.8		0.8				V
		Conditions	$V_{IN}=2.5V$		$V_{IN}=3.3V$		$V_{IN}=5V$				
Control Current (Output ON)	I_c, I_H	40		40		40				μA	
	Conditions	$V_{IN}=2.5V, V_c=2V$		$V_{IN}=3.3V, V_c=2V$		$V_{IN}=5V, V_c=2V$					
Control Current (Output OFF)	I_c, I_L	-5		-5		-5				μA	
	Conditions	$V_{IN}=2.5V, V_c=0V$		$V_{IN}=3.3V, V_c=0V$		$V_{IN}=5V, V_c=0V$					

*3: I_{S1} is specified at the 5% drop point of output voltage V_o on the condition that V_{IN} = overcurrent protection starting current, $I_o = 10$ mA.

*4: Output is OFF when the output control terminal V_c is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.

*5: SI-3000KF cannot be used in the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.

- (1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_o adjustment by raising ground voltage

Electrical Characteristics

Parameter	Symbol	Ratings															Unit	
		SI-3010KF			SI-3050KF			SI-3090KF			SI-3120KF			SI-3150KF				
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.		
Output Voltage (Reference Voltage for SI-3010KD)	V_O (V_{ADJ})	0.98	1.00	1.02	4.90	5.00	5.10	8.82	9.00	9.18	11.76	12.00	12.24	14.70	15.00	15.30	V	
	Conditions	$V_{IN}=7V, I_O=0.01A, V_C=2V, V_O=5A$			$V_{IN}=7V, I_O=0.01A, V_C=2V$			$V_{IN}=11V, I_O=0.01A, V_C=2V$			$V_{IN}=14V, I_O=0.01A, V_C=2V$			$V_{IN}=17V, I_O=10mA$				
Line Regulation	ΔV_{OLINE}			30			30			54			72			90	mV	
	Conditions	$V_{IN}=6$ to 15V, $I_O=0.01A, V_C=2V, V_O=5A$			$V_{IN}=6$ to 15V, $I_O=0.01A, V_C=2V$			$V_{IN}=10$ to 20V, $I_O=0.01A, V_C=2V$			$V_{IN}=13$ to 25V, $I_O=0.01A, V_C=2V$			$V_{IN}=16$ to 26V, $I_O=10mA$				
Load Regulation	ΔV_{LOAD}			75			75			135			180			225	mV	
	Conditions	$V_{IN}=7V, I_O=0$ to 1A, $V_C=2V, V_O=5A$			$V_{IN}=7V, I_O=0$ to 1A, $V_C=2V$			$V_{IN}=11V, I_O=0$ to 1A, $V_C=2V$			$V_{IN}=14V, I_O=0$ to 1A, $V_C=2V$			$V_{IN}=17V, I_O=0$ to 1A				
Dropout Voltage	V_{DIF}			0.3			0.3			0.3			0.3			0.3	V	
	Conditions	$I_O=0.5A, V_C=2V, V_O=5V$			$I_O=0.5A, V_C=2V$			$I_O=0.5A, V_C=2V$			$I_O=0.5A, V_C=2V$			$I_O=0.5A$				
				0.5			0.5			0.6			0.5			0.6		
	Conditions	$I_O=1.0A, V_C=2V, V_O=5V$			$I_O=1.0A, V_C=2V$			$I_O=1.0A, V_C=2V$			$I_O \leq 1.0A, V_C=2V$			$I_O=1A$				
Quiescent Circuit Current	I_q			600			600			600			600			600	μA	
	Conditions	$V_{IN}=7V, I_O=0A, V_C=2V$			$V_{IN}=7V, I_O=0A, V_C=2V$			$V_{IN}=11V, I_O=0A, V_C=2V$			$V_{IN}=14V, I_O=0A, V_C=2V$			$V_{IN}=17V, I_O=0A, V_C=2V$				
Circuit Current at Output OFF	I_q (OFF)			1			1			1			1			1	μA	
	Conditions	$V_{IN}=7V, V_C=0V$			$V_{IN}=7V, V_C=0V$			$V_{IN}=11V, V_C=0V$			$V_{IN}=14V, V_C=0V$			$V_{IN}=17V, V_C=0V$				
Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T_a$			± 0.5			± 0.5			± 1.0			± 1.5			± 1.5	mV/ $^{\circ}C$	
	Conditions	$V_{IN}=7V, I_O=0.01A, V_C=2V, T_J=0$ to 100 $^{\circ}C, V_O=2.5V$			$V_{IN}=7V, I_O=0.01A, V_C=2V, T_J=0$ to 100 $^{\circ}C$			$V_{IN}=11V, I_O=0.01A, V_C=2V, T_J=0$ to 100 $^{\circ}C$			$V_{IN}=14V, I_O=0.01A, V_C=2V, T_J=0$ to 100 $^{\circ}C$			$T_J=0$ to 100 $^{\circ}C$				
Ripple Rejection	RREJ			75			75			68			66			63	dB	
	Conditions	$V_{IN}=7V, I_O=0.1A, V_C=2V, f=100$ to 120Hz, $V_O=2.5V$			$V_{IN}=7V, I_O=0.1A, V_C=2V, f=100$ to 120Hz			$V_{IN}=11V, I_O=0.1A, V_C=2V, f=100$ to 120Hz			$V_{IN}=14V, I_O=0.1A, V_C=2V, f=100$ to 120Hz			$V_{IN}=17V, I_O=0.1A, f=100$ to 120Hz				
Overcurrent Protection Starting Current ^{*3}	I_{S1}			1.1			1.1			1.1			1.1			1.1	A	
	Conditions	$V_{IN}=7V, V_C=2V$			$V_{IN}=7V, V_C=2V$			$V_{IN}=11V, V_C=2V$			$V_{IN}=14V, V_C=2V$			$V_{IN}=17V$				
V _C Terminal	Control Voltage (Output ON) ^{*4}	V_C, I_H			2			2			2			2			V	
		Conditions	$V_{IN}=7V$			$V_{IN}=7V$			$V_{IN}=11V$			$V_{IN}=14V$						
	Control Voltage (Output OFF)	V_C, I_L			0.8			0.8			0.8			0.8			0.8	V
		Conditions	$V_{IN}=7V$			$V_{IN}=7V$			$V_{IN}=11V$			$V_{IN}=14V$						
	Control Current (Output ON)	I_C, I_H			40			40			40			40			40	μA
		Conditions	$V_{IN}=7V, V_C=2V$			$V_{IN}=7V, V_C=2V$			$V_{IN}=11V, V_C=2V$			$V_{IN}=14V, V_C=2V$			$V_C=2V$			
Control Current (Output OFF)	I_C, I_L			-5			0			-5			0			-5	μA	
	Conditions	$V_{IN}=7V, V_C=0V$			$V_{IN}=7V, V_C=0V$			$V_{IN}=11V, V_C=0V$			$V_{IN}=14V, V_C=0V$			$V_C=0V$				
Input Overvoltage Shutdown Voltage	V_{OVP}			33			26			30			33			-33	V	
	Conditions	$I_O=0.01A$			$I_O=0.01A$			$I_O=0.01A$			$I_O=0.01A$			$I_O=10mA$				


*3: I_{S1} is specified at the 5% drop point of output voltage V_O on the condition that V_{IN} = overcurrent protection starting current, $I_O = 10$ mA.

*4: Output is OFF when the output control terminal V_C is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.

*5: SI-3000KF cannot be used in the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.

(1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_O adjustment by raising ground voltage

■Block Diagram



■Typical Connection Diagram

●SI-3018KF/SI-3025KF/SI-3033KF/
SI-3050KF/SI-3090KF/SI-3120KF/
SI-3150KF

C_{IN} : Input capacitor (22 μ F or larger)
 C_o : Output capacitor (47 μ F or larger)
 If a low ESR capacitor (such as a ceramic capacitor) is used for the output capacitor, oscillation may occur.

*1. D1: Reverse bias protection diode
 This diode is required for protection against reverse biasing between the input and output.
 (Sanken SFPL-52 is recommended.)
 This diode is not required at $V_o \leq 3.3V$.


●SI-3010KF

R1, R2: Output voltage setting resistors
 The output voltage can be adjusted by connecting R1 and R2 as shown above.
 The recommended value for R2 is 10k Ω .

$$R1 = (V_o - V_{ADJ}) \times (V_{ADJ} / R2)$$


*2: For SI-3010KF, insert R3 in case of setting V_o to $V_o \leq 1.5V$.
 The recommended value for R3 is 10k Ω .

■Ta-Pd Characteristics



■External Dimensions

(Unit : mm)



SI-3001N Series 3-Terminal, Full-Mold, Low Dropout Voltage Linear Regulator IC

Features

- Compact full-mold package (equivalent to TO220)
- Output current: 1.5A
- Low dropout voltage: $V_{DIF} \leq 1V$ (at $I_o=1.5A$)
- Built-in foldback overcurrent, overvoltage and thermal protection circuits

Applications

- For stabilization of the secondary-side output voltage of switching power supplies.
- Electronic equipment

Absolute Maximum Ratings

(T_a=25°C)

Parameter	Symbol	Ratings			Unit
		SI-3051N/3091N	SI-3121N/3151N	SI-3241N	
DC Input Voltage	V _{IN}	35	35	45	V
DC Output Current	I _o	1.5 ²			A
Power Dissipation	P _{D1}	18(With infinite heatsink)			W
	P _{D2}	1.5(Without heatsink, stand-alone operation)			W
Junction Temperature	T _J	-40 to +125			°C
Operating Ambient Temperature	T _{op}	-30 to +100			°C
Storage Temperature	T _{stg}	-40 to +125			°C
Thermal Resistance (junction to case)	θ _{J-C}	5.5			°C/W
Thermal Resistance (junction to ambient air)	θ _{J-A}	66.7(Without heatsink, stand-alone operation)			°C/W

Electrical Characteristics

(T_a=25°C unless otherwise specified)

Parameter	Symbol	Ratings												Unit				
		SI-3051N			SI-3091N			SI-3121N			SI-3151N				SI-3241N			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.		min.	typ.	max.	
Input Voltage	V _{IN}	6 ³		30 ²	10 ³		30 ²	13 ³		30 ²	16 ³		30 ²	25 ³		40 ²	V	
Output Voltage	V _o	SI-3000N *1	4.80	5.00	5.20	8.64	9.00	9.36	11.52	12.00	12.48	14.40	15.00	15.60	23.04	24.00	24.96	V
		SI-3000NA	4.90	5.00	5.10	8.82	9.00	9.18	11.76	12.00	12.24	14.70	15.00	15.30	23.52	24.00	24.48	
Dropout Voltage	V _{DIF}	Conditions	V _{IN} =8V, I _o =1.0A			V _{IN} =12V, I _o =1.0A			V _{IN} =15V, I _o =1.0A			V _{IN} =18V, I _o =1.0A			V _{IN} =27V, I _o =1.0A			V
					0.5			0.5			0.5			0.5			0.5	
		Conditions	I _o ≤1.0A															
					1.0			1.0			1.0			1.0			1.0	
Line Regulation	ΔV _{OLINE}		10	30		18	48		24	64		30	90		48	128	mV	
		Conditions	V _{IN} =6V to 15V, I _o =1.0A			V _{IN} =10V to 20V, I _o =1.0A			V _{IN} =13V to 25V, I _o =1.0A			V _{IN} =16V to 27V, I _o =1.0A			V _{IN} =25V to 38V, I _o =1.0A			
Load Regulation	ΔV _{OLOAD}		40	100		70	180		93	240		120	300		120	300	mV	
		Conditions	V _{IN} =8V, I _o =0 to 1.5A			V _{IN} =12V, I _o =0 to 1.5A			V _{IN} =15V, I _o =0 to 1.5A			V _{IN} =18V, I _o =0 to 1.5A			V _{IN} =27V, I _o =0 to 1.5A			
Temperature Coefficient of Output Voltage	ΔV _O /ΔT _a		±0.5			±1.0			±1.5			±1.5			±2.5		mV/°C	
		Conditions	V _{IN} =8V, I _o =5mA, T _J =0 to 100°C			V _{IN} =12V, I _o =5mA, T _J =0 to 100°C			V _{IN} =15V, I _o =5mA, T _J =0 to 100°C			V _{IN} =18V, I _o =5mA, T _J =0 to 100°C			V _{IN} =27V, I _o =5mA, T _J =0 to 100°C			
Ripple Rejection	R _{REJ}		54			54			5			54			54		dB	
		Conditions	V _{IN} =8V, f=100 to 120Hz			V _{IN} =12V, f=100 to 120Hz			V _{IN} =15V, f=100 to 120Hz			V _{IN} =18V, f=100 to 120Hz			V _{IN} =27V, f=100 to 120Hz			
Quiescent Circuit Current	I _q		5	10		5	10		5	10		5	10		5	10	mA	
		Conditions	V _{IN} =8V, I _o =0A			V _{IN} =12V, I _o =0A			V _{IN} =15V, I _o =0A			V _{IN} =18V, I _o =0A			V _{IN} =27V, I _o =0A			
Overcurrent Protection Starting Current ^{4,5}	I _{S1}		1.6			1.6			1.6			1.6			1.6		A	
		Conditions	V _{IN} =8V			V _{IN} =12V			V _{IN} =15V			V _{IN} =18V			V _{IN} =27V			

*1: In some cases, "A" may be printed on the right of the marking.

*2: V_{IN(max)} and I_{O(max)} are restricted by the relation P_{D(max)}=(V_{IN}-V_o)•I_o=18(W).

*3: Refer to the Dropout Voltage parameter. (Refer to Setting DC Input Voltage on page 7.)


*4: I_{S1} is specified at the 5% drop point of output voltage V_o on the condition that V_{IN}=V_o+3V, I_o=1A.

*5: These products cannot be used in the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.


(1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_o adjustment by raising ground voltage

External Dimensions


(Unit : mm)




Block Diagram



Typical Connection Diagram



Ta-Pd Characteristics



SI-3000C Series 5-Terminal, Full-Mold, Low Dropout Voltage Linear Regulator IC

Features

- Compact full-mold package (equivalent to TO220)
- Output current: 1.5A
- Low dropout voltage: $V_{DIF} \leq 1V$ (at $I_O=1.5A$)
- Variable output voltage (rise only)
Available for remote sensing
- Output ON/OFF control terminal is compatible with LS-TTL.
(It can be driven directly by LS-TTL or standard CMOS logic.)
- Built-in foldback overcurrent (SI-3033C: Drooping type overcurrent), input-overvoltage and thermal protection circuits

Absolute Maximum Ratings

(T_a=25°C)

Parameter	Symbol	Ratings				Unit
		SI-3033C	SI-3050C/3090C	SI-3120C/3150C	SI-3240C	
DC Input Voltage	V _{IN}	20	35	35	45	V
Output Control Terminal Voltage	V _c	V _{IN}				V
DC Output Current	I _O	1.5 ²				A
Power Dissipation	P _{D1}	18(With infinite heatsink)				W
	P _{D2}	1.5(Without heatsink, stand-alone operation)				W
Junction Temperature	T _j	-40 to +125				°C
Operating Ambient Temperature	T _{op}	-30 to +100				°C
Storage Temperature	T _{stg}	-40 to +125				°C
Thermal Resistance (junction to case)	θ _{jc}	5.5				°C/W
Thermal Resistance (junction to ambient air)	θ _{ja}	66.7(Without heatsink, stand-alone operation)				°C/W

Applications

- For stabilization of the secondary-side output voltage of switching power supplies.
- Electronic equipment

Electrical Characteristics

(T_a=25°C unless otherwise specified)

Parameter	Symbol	Ratings									Unit				
		SI-3033C			SI-3050C			SI-3090C							
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.					
Input Voltage	V _{IN}	*3			6 ⁻³			30 ⁻²			V				
Output Voltage	V _O	SI-3000C ^{*1}	3.168	3.300	3.432	4.80	5.00	5.20	8.64	9.00	9.36	V			
		SI-3000CA	3.234	3.300	3.366	4.90	5.00	5.10	8.82	9.00	9.18				
Dropout Voltage	V _{DIF}	Conditions			V _{IN} =5V, I _O =1.0A			V _{IN} =8V, I _O =1.0A			V _{IN} =12V, I _O =1.0A			V	
	Conditions	I _O ≤1.0A			0.5			0.5			0.5				
		I _O ≤1.5A			1.0			1.0			1.0				
Line Regulation	ΔV _{OLINE}	10			30			18			48			mV	
	Conditions	V _{IN} =4.5 to 12V, I _O =1.0A			V _{IN} =6 to 15V, I _O =1.0A			V _{IN} =10 to 20V, I _O =1.0A							
Load Regulation	ΔV _{LOAD}	40			100			70			180			mV	
	Conditions	V _{IN} =5V, I _O =0 to 1.5A			V _{IN} =8V, I _O =0 to 1.5A			V _{IN} =12V, I _O =0 to 1.5A							
Temperature Coefficient of Output Voltage	ΔV _O /ΔT _a	±0.5			±0.5			±1.0						mV/°C	
	Conditions	V _{IN} =5V, I _O =5mA, T _j =0 to 100°C			V _{IN} =8V, I _O =5mA, T _j =0 to 100°C			V _{IN} =12V, I _O =5mA, T _j =0 to 100°C							
Ripple Rejection	R _{REJ}	54			54			54						dB	
	Conditions	V _{IN} =5V, f=100 to 120Hz			V _{IN} =8V, f=100 to 120Hz			V _{IN} =12V, f=100 to 120Hz							
Quiescent Circuit Current	I _q	3			10			5			10			mA	
	Conditions	V _{IN} =5V, I _O =0A			V _{IN} =8V, I _O =0A			V _{IN} =12V, I _O =0A							
Overcurrent Protection Starting Current ^{4,6}	I _{S1}	1.6			1.6			1.6						A	
	Conditions	V _{IN} =5V			V _{IN} =8V			V _{IN} =12V							
V _c Terminal ⁵	Control Voltage (Output ON)	V _c IH	2.0			2.0			2.0						V
	Control Voltage (Output OFF)	V _c IL	0.8			0.8			0.8						
	Control Current (Output ON)	I _c IH	20			20			20						μA
		Conditions	V _c =2.7V												
	Control Current (Output OFF)	I _c IL	-0.3			-0.3			-0.3						mA
Conditions		V _c =0.4V													

*1: In some cases, "A" may be printed on the right of the marking.

*2: V_{IN(max)} and I_{O(max)} are restricted by the relation P_{D(max)}=(V_{IN}-V_O)•I_O=18(W).

*3: Refer to the Dropout Voltage parameter. (Refer to Setting DC Input Voltage on page 7.)

*4: I_{S1} is specified at the 5% drop point of output voltage V_O on the condition that V_{IN}=V_O+3V, I_O=1A.*5: Output is ON even when output control terminal V_c is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.

*6: These products (except for SI-3033C) cannot be used in the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.

(1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_O adjustment by raising ground voltage

Electrical Characteristics

(T_a=25°C unless otherwise specified)

Parameter	Symbol	Ratings									Unit	
		SI-3120C			SI-3150C			SI-3240C				
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.		
Input Voltage	V _{IN}	13 ³		30 ²	16 ³		30 ²	25 ³		40 ²	V	
Output Voltage	SI-3000C *1	11.52	12.00	12.48	14.40	15.00	15.60	23.04	24.00	24.96	V	
	SI-3000CA	11.76	12.00	12.24	14.70	15.00	15.30	23.52	24.00	24.48		
Dropout Voltage	Conditions	V _{IN} =15V, I _O =1.0A			V _{IN} =18V, I _O =1.0A			V _{IN} =27V, I _O =1.0A			V	
	V _{DIF}			0.5			0.5			0.5		
	Conditions	I _O ≤1.0A										
	Conditions			1.0			1.0			1.0		
Line Regulation	ΔV _{OLINE}		24	64		30	90		48	128	mV	
	Conditions	V _{IN} =13 to 25V, I _O =1.0A			V _{IN} =16 to 25V, I _O =1.0A			V _{IN} =25 to 38V, I _O =1.0A				
Load Regulation	ΔV _{OLOAD}		93	240		120	300		120	300	mV	
	Conditions	V _{IN} =15V, I _O =0 to 1.5A			V _{IN} =18V, I _O =0 to 1.5A			V _{IN} =27V, I _O =0 to 1.5A				
Temperature Coefficient of Output Voltage	ΔV _O /ΔT _a		±1.5			±1.5			±2.5		mV/°C	
	Conditions	V _{IN} =15V, I _O =5mA, T _j =0 to 100°C			V _{IN} =18V, I _O =5mA, T _j =0 to 100°C			V _{IN} =27V, I _O =5mA, T _j =0 to 100°C				
Ripple Rejection	R _{REJ}		54			54			54		dB	
	Conditions	V _{IN} =15V, f=100 to 120Hz			V _{IN} =18V, f=100 to 120Hz			V _{IN} =27V, f=100 to 120Hz				
Quiescent Circuit Current	I _q		5	10		5	10		5	10	mA	
	Conditions	V _{IN} =15V, I _O =0A			V _{IN} =18V, I _O =0A			V _{IN} =27V, I _O =0A				
Overcurrent Protection Starting Current*4,6	I _{S1}	1.6			1.6			1.6			A	
	Conditions	V _{IN} =15V			V _{IN} =18V			V _{IN} =27V				
V _C Terminal ⁵	Control Voltage (Output ON)	V _C . IH	2.0		2.0			2.0			V	
	Control Voltage (Output OFF)	V _C . IL					0.8			0.8		
	Control Current (Output ON)	I _C . IH			20			20			20	μA
		Conditions	V _C =2.7V									
	Control Current (Output OFF)	I _C . IL			-0.3			-0.3			-0.3	mA
		Conditions	V _C =0.4V									

*1: In some cases, "A" may be printed on the right of the marking.

*2: V_{IN(max)} and I_{O(max)} are restricted by the relation P_{D(max)}=(V_{IN}-V_O)•I_O=18(W).

*3: Refer to the Dropout Voltage parameter. (Refer to Setting DC Input Voltage on page 7.)


*4: I_{S1} is specified at the 5% drop point of output voltage V_O on the condition that V_{IN}=V_O+3V, I_O=1A.*5: Output is ON even when output control terminal V_C is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.

*6: These products cannot be used in the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.

(1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_O adjustment by raising ground voltage

External Dimensions

(unit : mm)




- a. Part Number
- b. Lot Number

Pin Assignment


- ① GND
- ② V_c
- ③ V_o
- ④ V_{os}
- ⑤ V_{IN}

Plastic Mold Package Type
 Flammability: UL94V-0
 Product Mass: Approx. 2.3g

Block Diagram




■ Typical Connection Diagram



- C_0 : Output capacitor (47 to 100 μ F)
- *1 C_1 } : Oscillation prevention capacitor
 C_2 } (Approx. C_1 : 47 μ F, C_2 : 0.33 μ F)
 These capacitors are required if the input line contains inductance or the wiring is long. Especially at low temperatures, tantalum capacitors are recommended for C_1 and C_0 .
- *2 D_1 : Protection diode
 This diode is required for protection against reverse biasing of the input and output. Sanken EU2Z is recommended.

■ T_a - P_D Characteristics



SI-3000R Series 5-Terminal, Built-in Reset Function, Full-Mold, Low Dropout Voltage Linear Regulator IC

■Features

- Reset signal output (When the output voltage rises, a reset signal is output to secure the normal operation of the system. When the output voltage decreases, the reset signal is also output to protect the system.)
- Reset signal detection output voltage level V_{oth} is 92% of output voltage in the standard specification. Models with different setting values for different needs are scheduled to be added to the series.
- Delay time for reset signal can be set freely by external capacitor.
- Compact full-mold package (equivalent to TO220)
- Output current: 1.5A
- Low dropout voltage : $V_{DIF} \leq 1V$ (at $I_O=1.5A$)
Applicable to battery driven equipment with built-in microcomputer.
- Built-in drooping-type-overcurrent, input-overvoltage and thermal protection circuits
- Low circuit current $I_D=typ.1.5mA$ ($I_O=0A$)

■Absolute Maximum Ratings

(T_a=25°C)

Parameter	Symbol	Ratings		Unit
		SI-3050R		
DC Input Voltage	V _{IN}	35		V
Voltage of Rest Signal Output Terminal	V _{RST}	V _{IN}		V
DC Output Current	I _O	1.5 ^{*1}		A
Power Dissipation	P _{D1}	18(With infinite heatsink)		W
	P _{D2}	1.5(Without heatsink, stand-alone operation)		W
Junction Temperature	T _j	-30 to +125		°C
Operating Ambient Temperature	T _{OP}	-30 to +100		°C
Storage Temperature	T _{stg}	-30 to +125		°C
Thermal Resistance (junction to case)	θ _{J-C}	5.5		°C/W
Thermal Resistance (junction to ambient air)	θ _{J-A}	66.7(Without heatsink, stand-alone operation)		°C/W

■Applications

- Microcomputer-controlled equipment
- Battery-driven micro-computer-controlled equipment

■Electrical Characteristics

(T_a=25°C unless otherwise specified)

Parameter	Symbol	Ratings			Unit
		SI-3050R			
		min.	typ.	max.	
Input Voltage	V _{IN}	6 ^{*2}		30 ^{*1}	V
Output Voltage	V _O	4.80	5.00	5.20	V
	Conditions	V _{IN} =8V, I _O =1.0A			
Dropout Voltage	V _{DIF}			0.5	V
	Conditions	I _O ≤1.0A			
	Conditions	I _O ≤1.5A			
Line Regulation	ΔV _{OLINE}			30	mV
	Conditions	V _{IN} =6 to 15V, I _O =1.0A			
Load Regulation	ΔV _{OLOAD}			100	mV
	Conditions	V _{IN} =8V, I _O =0 to 1.5A			
Ripple Rejection	R _{REJ}		54		dB
	Conditions	V _{IN} =8V, f=100 to 120Hz			
Quiescent Circuit Current	I _q		1.5	5.0	mA
	Conditions	V _{IN} =8V, I _O =0A			
Overcurrent Protection Starting Current (Drooping Type)	I _{S1}	1.6			A
	Conditions	V _{IN} =8V			
Current Limit at Output Short Circuit	I _{S2}	1.6			A
	Conditions	V _{IN} =8V			
DLY Terminal	Threshold	V _{DLYth}	2.7	3.1	V
	Source	I _{DLY}	25	45	μA
Reset Threshold Voltage Level (V _{oth} : Threshold Output Voltage)	V _{oth} /V _O	90	92	94	%
Reset Threshold Voltage Hysteresis	ΔV _{oth}	50	100	150	mV
V _C Terminal ^{*4}	H-level Output Voltage	V _{RSTH}	V _{CC} -1		V
	L-level Output Voltage	V _{RSTL}		0.8	V
	Sink Current at H level	I _{RSTH}		-20	μA
	Source Current at L level	I _{RSTL}	-16		mA


*1: V_{IN(max)} and I_{O(max)} are restricted by the relation P_{D(max)}=(V_{IN}-V_O)•I_O=18(W).

*2: Refer to the Dropout Voltage parameter. (Refer to Setting Dc Input Voltage on page 7.)


*3: I_{S1} is specified at the 5% drop point of output voltage V_O on the condition that V_{IN}=8V, I_O=1.0A.

*4: Reset signal output terminal V_{RST} is an open-collector output. Use a pull-up resistor when connecting it to a logic circuit.


■Block Diagram




■Ta-Pd Characteristics



■Typical Connection Diagram




■Reset Signal Output Timing Chart



■External Dimensions

(unit : mm)



SI-3002N Series 3-Terminal, Full-Mold, Low Dropout Voltage Linear Regulator IC

■Features

- Compact full-mold package (equivalent to TO220)
- Output current: 2.0A
- Low dropout voltage: $V_{DIF} \leq 1V$ (at $I_o=2.0A$)
- Built-in foldback-overcurrent, input-overvoltage and thermal protection circuits

■Applications

- For stabilization of the secondary stage of switching power supplies
- Electronic equipment

■Absolute Maximum Ratings

(T_a=25°C)

Parameter	Symbol	Ratings			Unit
		SI-3052N	SI-3092N	SI-3122N/3152N	
DC Input Voltage	V _{IN}	25	30	35	V
DC Output Current	I _o	2.0 ¹			A
Power Dissipation	P _{D1}	20(With infinite heatsink)			W
	P _{D2}	1.5(Without heatsink, stand-alone operation)			W
Junction Temperature	T _J	-40 to +125			°C
Operating Ambient Temperature	T _{op}	-30 to +100			°C
Storage Temperature	T _{stg}	-40 to +125			°C
Thermal Resistance (junction to case)	θ _{J-c}	5.0			°C/W
Thermal Resistance (junction to ambient air)	θ _{J-a}	66.7(Without heatsink, stand-alone operation)			°C/W

■Electrical Characteristics

(T_a=25°C unless otherwise specified)

Parameter	Symbol	Ratings												Unit
		SI-3052N			SI-3092N			SI-3122N			SI-3152N			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Input Voltage	V _{IN}	6 ²		15 ¹	10 ²		25 ¹	13 ²		27 ¹	16 ²		27 ¹	V
Output Voltage	V _o	4.90	5.00	5.10	8.82	9.00	9.18	11.76	12.00	12.24	14.70	15.00	15.30	V
	Conditions	V _{IN} =8V, I _o =1.0A			V _{IN} =12V, I _o =1.0A			V _{IN} =15V, I _o =1.0A			V _{IN} =18V, I _o =1.0A			
Dropout Voltage	V _{DIF}			0.5			0.5			0.5			0.5	V
	Conditions	I _o ≤1.5A												
	Conditions			1.0			1.0			1.0			1.0	
Line Regulation	ΔV _{OLINE}		10	30		18	48		24	64		30	90	mV
	Conditions	V _{IN} =6 to 15V, I _o =1.0A			V _{IN} =10 to 20V, I _o =1.0A			V _{IN} =13 to 25V, I _o =1.0A			V _{IN} =16 to 25V, I _o =1.0A			
	Conditions	V _{IN} =8V, I _o =0 to 2.0A			V _{IN} =12V, I _o =0 to 2.0A			V _{IN} =15V, I _o =0 to 2.0A			V _{IN} =18V, I _o =0 to 2.0A			
Load Regulation	ΔV _{OLOAD}		40	100		70	180		93	240		120	300	mV
	Conditions	V _{IN} =8V, I _o =0 to 2.0A			V _{IN} =12V, I _o =0 to 2.0A			V _{IN} =15V, I _o =0 to 2.0A			V _{IN} =18V, I _o =0 to 2.0A			
Temperature Coefficient of Output Voltage	ΔV _o /ΔT _a		±0.5			±1.0			±1.5			±1.5		mV/°C
	Conditions	V _{IN} =8V, I _o =5mA, T _J =0 to 100°C			V _{IN} =12V, I _o =5mA, T _J =0 to 100°C			V _{IN} =15V, I _o =5mA, T _J =0 to 100°C			V _{IN} =18V, I _o =5mA, T _J =0 to 100°C			
Ripple Rejection	R _{REJ}		54			54			54			54		dB
	Conditions	V _{IN} =8V, f=100 to 120Hz			V _{IN} =12V, f=100 to 120Hz			V _{IN} =15V, f=100 to 120Hz			V _{IN} =18V, f=100 to 120Hz			
Quiescent Circuit Current	I _q		3	10		3	10		3	10		3	10	mA
	Conditions	V _{IN} =8V, I _o =0A			V _{IN} =12V, I _o =0A			V _{IN} =15V, I _o =0A			V _{IN} =18V, I _o =0A			
Overcurrent Protection Starting Current ^{3,4}	I _{s1}	2.1			2.1			2.1			2.1			A
	Conditions	V _{IN} =8V			V _{IN} =12V			V _{IN} =15V			V _{IN} =18V			

*1: V_{IN(max)} and I_{o(max)} are restricted by the relation P_{D(max)}=(V_{IN}-V_o)•I_o≤20(W).

*2: Refer to the Dropout Voltage parameter. (Refer to Setting DC Input Voltage on page 7.)


*3: I_{s1} is specified at the 5% drop point of output voltage V_o on the condition that V_{IN}=V_o+3V, I_o=1.0A.

*4: These products cannot be used in the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.


(1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_o adjustment by raising ground voltage

External Dimensions


(unit : mm)



Block Diagram



Typical Connection Diagram



T_a-P_d Characteristics



SI-3000V Series 3-Terminal, Low Dropout Voltage Linear Regulator IC

■Features

- TO-3P package 3-terminal regulator
- Output current: 2.0A
- Low dropout voltage: $V_{DIF} \leq 1V$ (at $I_O=2.0A$)
- Built-in foldback-overcurrent protection circuit

■Applications

- For stabilization of the secondary-side output voltage of switching power supplies.
- Electronic equipment

■Absolute Maximum Ratings

($T_a=25^\circ C$)

Parameter	Symbol	Ratings		Unit
		SI-3052V	SI-3122V/3152V	
DC Input Voltage	V_{IN}	25	30	V
DC Output Current	I_O	2.0		A
Power Dissipation	P_{D1}	50($T_c=25^\circ C$)		W
	P_{D2}	1.6(Without heatsink, stand-alone operation)		W
Junction Temperature	T_J	-30 to +125		$^\circ C$
Operating Ambient Temperature	T_{op}	-20 to +100		$^\circ C$
Storage Temperature	T_{stg}	-30 to +125		$^\circ C$
Thermal Resistance (junction to case)	θ_{j-c}	2.0		$^\circ C/W$

■Electrical Characteristics

($T_a=25^\circ C$)

Parameter	Symbol	Ratings									unit
		SI-3052V			SI-3122V			SI-3152V			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Input Voltage	V_{IN}	6		15	13		25	16		25	V
Output Voltage	V_O	4.9	5.0	5.1	11.8	12.0	12.2	14.8	15.0	15.2	V
	Conditions	$V_{IN}=8V, I_O=1.0A$			$V_{IN}=16V, I_O=1.0A$			$V_{IN}=20V, I_O=1.0A$			
Dropout Voltage	V_{DIF}			0.5			0.5			0.5	V
	Conditions	$I_O=1.0A$									
	Conditions			1.0			1.0			1.0	
Line Regulation	ΔV_{OLINE}		10	30		20	60		20	60	mV
	Conditions	$V_{IN}=6$ to 15V, $I_O=1.0A$			$V_{IN}=13$ to 25V, $I_O=1.0A$			$V_{IN}=16$ to 25V, $I_O=1.0A$			
Load Regulation	ΔV_{OLOAD}		40	100		80	200		80	200	mV
	Conditions	$V_{IN}=8V, I_O=0$ to 2.0A			$V_{IN}=16V, I_O=0$ to 2.0A			$V_{IN}=20V, I_O=0$ to 2.0A			
Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T_a$		± 0.5			+1.5			± 1.5		mV/ $^\circ C$
Ripple Rejection	R_{REJ}		54			54			54		dB
	Conditions	$f=100$ to 120Hz									
Overcurrent Protection Starting Current	I_{S1}	2.4			2.4			2.4			A
	Conditions	$V_{IN}=8V$			$V_{IN}=16V$			$V_{IN}=20V$			


The following are also available: SI-3522V(5.2V), SI-3062V(6V), SI-3082V(8V), SI-3922V(9.2V), SI-3102V(10V), SI-3132V(13.1V), SI-3182V(18V), SI-3202V(20V).

*1: These products cannot be used in the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.

(1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_O adjustment by raising ground voltage

*2: I_{S1} is specified at the 5% drop point of output voltage V_O . (where $V_O=V_{IN} + 3V$)

External Dimensions




- a. Part Number
- b. Lot Number

Pin Assignment


- ① GND
- ② Vo (backside of case)
- ③ Vin

Plastic Mold Package Type (TO-3P)
 Flammability: UL94V-0
 Product Mass: Approx. 6g

Block Diagram



Typical Connection Diagram



C1: Oscillation prevention capacitor (approx. 0.33μF)

Connect C1 to terminal 3 as close as possible.

C2: Output capacitor (47 to 100μF)

Connect C2 to terminal 2 as close as possible.

D1: Protection diode (RM1Z)

This diode is required for protection against reverse biasing of the input and output.


Note 1: Prevention of oscillation at low temperatures

At low temperatures, oscillation may occur unless an output capacitor with good tanδ is used. Be sure to connect a tantalum capacitor (approx. 10μF) in parallel with output capacitor C2.

Note 2: Isolation type diodes are provided in between input and ground, and also in between output and ground. These may be destroyed if the device is reverse biased. In this case, use diodes with low Vf to protect them.

Note 3: The output voltage cannot be adjusted by raising the ground voltage (using a diode or resistor).

Ta-Pd Characteristics



SI-3000J Series 5-Terminal, Full-Mold, Low Dropout Voltage Linear Regulator IC

Features

- Compact full-mold package (equivalent to TO220)
- Output current: 2.0A
- Low dropout voltage: $V_{DIF} \leq 1V$ (at $I_o=2.0A$)
- Variable output voltage (rise only) Available for remote sensing used for remote sensing.
- Output ON/OFF control terminal is compatible with LS-TTL.
(It can be driven directly by LS-TTL or standard CMOS logic.)
- Built-in foldback-overcurrent, input-overvoltage and thermal protection circuits

Absolute Maximum Ratings

(T_a=25°C)

Parameter	Symbol	Ratings			Unit
		SI-3050J	SI-3090J	SI-3120J/3150J	
DC Input Voltage	V _{IN}	25	30	35	V
Output Control Terminal Voltage	V _c	V _{IN}			V
DC Output Current	I _o	2.0 ¹			A
Power Dissipation	P _{D1}	20(With infinite heatsink)			W
	P _{D2}	1.5(Without heatsink, stand-alone operation)			W
Junction Temperature	T _j	-40 to +125			°C
Operating Ambient Temperature	T _{op}	-30 to +100			°C
Storage Temperature	T _{stg}	-40 to +125			°C
Thermal Resistance (junction to case)	θ _{J-C}	5.0			°C/W
Thermal Resistance (junction to ambient air)	θ _{J-A}	66.7(Without heatsink, stand-alone operation)			°C/W

Applications

- For stabilization of the secondary-side output voltage of switching power supplies.
- Electronic equipment

Electrical Characteristics

(T_a=25°C unless otherwise specified)

Parameter	Symbol	Ratings												Unit
		SI-3050J			SI-3090J			SI-3120J			SI-3150J			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Input Voltage	V _{IN}	6 ²		15 ¹	10 ²		25 ¹	13 ²		27 ¹	16 ²		27 ¹	V
Output Voltage	V _o	4.90	5.00	5.10	8.82	9.00	9.18	11.76	12.00	12.24	14.70	15.00	15.30	V
	Conditions	V _{IN} =8V, I _o =1.0A			V _{IN} =12V, I _o =1.0A			V _{IN} =15V, I _o =1.0A			V _{IN} =18V, I _o =1.0A			
Dropout Voltage	V _{DIF}			0.5			0.5			0.5			0.5	V
	Conditions	I _o ≤1.5A												
	Conditions			1.0			1.0			1.0			1.0	
Line Regulation	ΔV _{OLINE}		10	30		18	48		24	64		30	90	mV
	Conditions	V _{IN} =6 to 15V, I _o =1.0A			V _{IN} =10 to 20V, I _o =1.0A			V _{IN} =13 to 25V, I _o =1.0A			V _{IN} =16 to 25V, I _o =1.0A			
Load Regulation	ΔV _{OLOAD}		40	100		70	180		93	240		120	300	mV
	Conditions	V _{IN} =8V, I _o =0 to 2.0A			V _{IN} =12V, I _o =0 to 2.0A			V _{IN} =15V, I _o =0 to 2.0A			V _{IN} =18V, I _o =0 to 2.0A			
Temperature Coefficient of Output Voltage	ΔV _o /ΔT _a		±0.5			±1.0			±1.5			±1.5		mV/°C
	Conditions	V _{IN} =8V, I _o =5mA, T _j =0 to 100°C			V _{IN} =12V, I _o =5mA, T _j =0 to 100°C			V _{IN} =15V, I _o =5mA, T _j =0 to 100°C			V _{IN} =18V, I _o =5mA, T _j =0 to 100°C			
Ripple Rejection	R _{REJ}		54			54			54			54		dB
	Conditions	V _{IN} =8V, f=100 to 120Hz			V _{IN} =12V, f=100 to 120Hz			V _{IN} =15V, f=100 to 120Hz			V _{IN} =18V, f=100 to 120Hz			
Quiescent Circuit Current	I _q		3	10		3	10		3	10		3	10	mA
	Conditions	V _{IN} =8V, I _o =0A			V _{IN} =12V, I _o =0A			V _{IN} =15V, I _o =0A			V _{IN} =18V, I _o =0A			
	I _q (off)		0.5	1.0		0.5	1.0		0.5	1.0		0.5	1.0	
Overcurrent Protection Starting Current ^{3,5}	I _{S1}		2.1			2.1			2.1			2.1		A
	Conditions	V _{IN} =8V			V _{IN} =12V			V _{IN} =15V			V _{IN} =18V			
V _c Terminal ⁴	Control Voltage (Output ON)	V _c IH	2.0			2.0			2.0			2.0		V
	Control Voltage (Output OFF)	V _c IL			0.8			0.8			0.8		0.8	
	Control Current (Output ON)	I _c IH			20			20			20		20	μA
	Control Current (Output ON)	Conditions	V _c =2.7V											
	Control Current (Output OFF)	I _c IL			-0.3			-0.3			-0.3			-0.3
Control Current (Output OFF)	Conditions	V _c =0.4V												

*1: V_{IN(max)} and I_{o(max)} are restricted by the relation P_{D(max)}=(V_{IN}-V_o)•I_o≤20(W).

*2: Refer to the Dropout Voltage parameter. (Refer to Setting DC Input Voltage on page 7.)


*3: I_{S1} is specified at the 5% drop point of output voltage V_o on the condition that V_{IN}=V_o+3V, I_o=1A.*4: Output is ON even when output control terminal V_c is open. Each input level is equivalent to LS-TTL level. Therefore, it can be driven directly by LS-TTLs.

*5: These products cannot be used in the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.

(1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_o adjustment by raising ground voltage

External Dimensions

(unit : mm)




- a. Part Number
- b. Lot Number

Pin Assignment


- ① GND
- ② Vc
- ③ Vo
- ④ Sense
- ⑤ VIN

Plastic Mold Package Type
 Flammability: UL94V-0
 Product Mass: Approx. 2.3g

Block Diagram




Typical Connection Diagram



- C₀ : Output capacitor (47 to 100μF)
- *1 C₁ } Oscillation prevention capacitor
 C₂ } (Approx. C₁: 47μF, C₂: 0.33μF)
 These capacitors are required if the input line contains inductance or the wiring is long. Especially at low temperatures, tantalum capacitors are recommended for C₁ and C₀.
- *2 D₁ : Protection diode
 This diode is required for protection against reverse biasing of the input and output. Sanken EU2Z is recommended.

T_a-P_d Characteristics



$$P_D = I_O \cdot [V_{IN}(\text{mean}) - V_O]$$

SI-3000ZF Series 5-Terminal, Low Dropout Voltage Linear Regulator IC

■Features

- Compact full-mold package (equivalent to TO220)
- Output current: 3.0A
- Low dropout voltage: $V_{DIF} \leq 0.7V$ (at $I_o = 3.0A$)
- Low circuit current at output OFF: I_q (OFF) $\leq 1\mu A$
- Built-in overcurrent and thermal protection circuits

■Applications

- Secondary stabilized power supply (local power supply)

■Absolute Maximum Ratings

(Ta = 25°C)

Parameter	Symbol	Rated	Unit
DC Input Voltage	V_{IN}^{*1}	10	V
Output Control Terminal Voltage	V_C	6	V
DC Output Current	I_o^{*1}	3.0	A
Power Dissipation	P_{D1}	20 (With infinite heatsink)	W
	P_{D2}	1.5 (Without heatsink, stand-alone operation)	W
Junction Temperature	T_j	-30 to +125	°C
Operating Ambient Temperature	T_{op}	-30 to +100	°C
Storage Temperature	T_{stg}	-30 to +125	°C
Thermal Resistance (Junction to Case)	θ_{j-c}	5.0	°C/W
Thermal Resistance (Junction to Ambient Air)	θ_{j-a}	66.7 (Without heatsink, stand-alone operation)	°C/W

■Recommended Operating Conditions

Parameter	Symbol	Rated	Unit	Remarks
Input Voltage	V_{IN}	*2 to 6 *1	V	
Output Current	I_o	0 to 3	A	
Operating Ambient Temperature	T_{op} (a)	-20 to +85	°C	
Operating Junction Temperature	T_{op} (j)	-20 to +100	°C	
Output Voltage Variable Range	V_{OADJ}	1.2 to 5	V	Only for SI-3011ZF. Refer to the Typical Connection Diagram

*1: V_{IN} (max) and I_o (max) are restricted by the relationship $P_D = (V_{IN} - V_o) \times I_o$.

*2: Set the input voltage to 2.4V or higher when setting the output voltage to 2.0V or lower (SI-3011ZF).

■Electrical Characteristics

(Ta = 25°C, $V_C = 2V$ unless otherwise specified)

Parameter	Symbol	Rated									Unit
		SI-3011ZF			SI-3025ZF			SI-3033ZF			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Output Voltage (Reference Voltage for SI-3011ZF)	V_O (V_{AJD})	1.078	1.100	1.122	2.45	2.50	2.55	3.234	3.300	3.366	V
Line Regulation	ΔV_{OLINE}	10			10			10			mV
	Conditions	$V_{IN}=V_O+1V, I_o=10mA$			$V_{IN}=3.3V, I_o=10mA$			$V_{IN}=5V, I_o=10mA$			
Load Regulation	ΔV_{OLOAD}	40			40			40			mV
	Conditions	$V_{IN}=3.3V, I_o=0$ to 3A ($V_O=2.5V$)			$V_{IN}=3.3V, I_o=0$ to 3A			$V_{IN}=5V, I_o=0$ to 3A			
Dropout Voltage	V_{DIF}	0.7			0.7			0.7			V
	Conditions	$I_o=3A$ ($V_O=2.5V$)			$I_o=3A$			$I_o=3A$			
Quiescent Circuit Current	I_q	1			1			1			mA
	Conditions	$V_{IN}=V_O+1V, I_o=0A, V_C=2V$			$V_{IN}=3.3V, I_o=0A, V_C=2V$			$V_{IN}=5V, I_o=0A, V_C=2V$			
Circuit Current at Output OFF	I_q (OFF)	1			1			1			μA
	Conditions	$V_{IN}=V_O+1V, V_C=0V$			$V_{IN}=3.3V, V_C=0V$			$V_{IN}=5V, V_C=0V$			
Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T_a$	± 0.3			± 0.3			± 0.3			mV/°C
	Conditions	$T_j=0$ to 100°C			$T_j=0$ to 100°C			$T_j=0$ to 100°C			
Ripple Rejection	R_{REJ}	60			60			60			dB
	Conditions	$V_{IN}=V_O+1V, f=100$ to 120Hz, $I_o=0.1A$			$V_{IN}=3.3V, f=100$ to 120Hz, $I_o=0.1A$			$V_{IN}=5V, f=100$ to 120Hz, $I_o=0.1A$			
Overcurrent Protection Starting Current ^{*2}	I_{S1}	3.2			3.2			3.2			A
	Conditions	$V_{IN}=V_O+1V$			$V_{IN}=3.3V$			$V_{IN}=5V$			
V_C Terminal	Control Voltage (Output ON) ^{*3}	2			2			2			V
	Control Voltage (Output OFF) ^{*3}	0.8			0.8			0.8			V
	Control Current (Output ON)	100			100			100			μA
	Control Current (Output OFF)	-5			-5			-5			μA
	Conditions	$V_C=2.7V$			$V_C=2.7V$			$V_C=2.7V$			
	Conditions	$V_C=0V$			$V_C=0V$			$V_C=0V$			

*1: Set the input voltage to 2.4V or higher when setting the output voltage to 2.0V or lower.

*2: I_{S1} is specified at the 5% drop point of output voltage V_o under the Output Voltage parameter conditions.

*3: Output is OFF when the output control terminal V_C is open. Each input level is equivalent to LS-TTL level. Therefore, the device can be driven directly by LS-TTLs.

*4: These products cannot be used in the following applications because the built-in foldback-type overcurrent protection may cause errors during start-up stage.

(1) Constant current load (2) Positive and negative power supply (3) Series-connected power supply (4) V_o adjustment by raising ground voltage

External Dimensions

(unit : mm)

a. Part Number
b. Lot number

Pin Assignment
① V_c
② V_{IN}
③ GND
④ V_o
⑤ Sense
(ADJ for SI-3011ZF)

Plastic Mold Package Type
Flammability: UL94V-0
Product Mass: Approx. 2.3g

Forming No. 1101

Typical Connection Diagram/Block Diagram

SI-3011ZF

SI-3025ZF, SI-3033ZF

C_{IN}: Input capacitor (Approx. 10μF)
This capacitor is required when the input line contains inductance or when the wiring is long.


C_o: Output capacitor (47μF or higher)
The output voltage may oscillate if a low ESR type capacitor (such as a ceramic capacitor) is used for the output capacitor in SI-3000ZF.

R₁, R₂: Output voltage setting resistors
The output voltage can be set by connecting R₁ and R₂ as shown at left.
The recommended value for R₂ is 10kΩ or 11kΩ.

$$R1 = (Vo - V_{ADJ}) / (V_{ADJ} / R2)$$

*: Insert R₃ in case of setting V_o to V_o ≤ 1.8V. The recommended value for R₃ is 10kΩ.

T_a-P_d Characteristics



Application Note

Heat Dissipation and Reliability

The reliability of an IC is highly dependent on its operating temperature. Please be sure to apply silicone grease to the IC and to mount it to the heatsink with a proper mounting torque.

Heatsink design should pay particular attention to ensuring sufficient heat dissipation capacity.

In addition, please take into account the air convection in operation.

The reliability of discrete components such as capacitors and coils is closely related to temperature. A high operating temperature may reduce the service life. Exceeding the allowable temperature may burn the coils or damage capacitors. It is important to make sure that the temperature of output smoothing coils and input/output capacitors do not exceed their allowable levels during operation. With an adequate derating for the coils, minimize heat emission as far as possible. (For discrete components, refer to the individual user manuals.)

Internal Power Dissipation

P_D can be obtained from the following formula.

- For the device with built-in flywheel diode:
(SI-8000L series)

$$P_D = V_O \cdot I_O \left(\frac{100}{\eta \chi} - 1 \right)$$

- For the device with external flywheel diode:
(SAI series, SI-8000E series, SI-8000S series, SI-8000SD series, SI-8000JD series, SI-8000JF series)

$$P_D = V_O \cdot I_O \left(\frac{100}{\eta \chi} - 1 \right) - V_F \cdot I_O \left(1 - \frac{V_O}{V_{IN}} \right)$$

Efficiency $\eta \chi$ depends on the input/output conditions. Please refer to the efficiency characteristics of the devices. (Posted on the Web site.)

V_O : Output voltage
 V_{IN} : Input voltage
 I_O : Output current
 $\eta \chi$: Efficiency(%)
 V_F : Diode forward voltage

Thermal Design

The maximum junction temperature $T_{j(max)}$ given in the Absolute Maximum Ratings is specific to each product type and must be strictly observed.

Thus, thermal design must consider the maximum power dissipation $P_{D(max)}$, which varies by the conditions of use, and the maximum ambient temperature $T_{a(max)}$.

To simplify thermal design, T_a - P_D characteristic graphs are provided herein. Please observe the following steps for heatsink design:

- Obtain the maximum ambient temperature $T_{a(max)}$.
- Obtain the maximum power dissipation $P_{D(max)}$.
- Look for the intersection point on the T_a - P_D characteristic graph and determine the size of the heatsink.

Although the heatsink size is now obtained, in actual applications, 10-to-20% derating factor is generally introduced. Moreover, the heat dissipation capacity of a heatsink highly depends on how it is mounted. Thus, it is recommended to measure the heatsink and case temperature in the actual operating environment.

Please refer to the T_a - P_D characteristic graphs for respective product types.

Mounting Torque

SI-8000E	} 0.588 to 0.686[N•m] (6.0 to 7.0[kgf•cm])
SI-8000JF	
SI-8000S	

Recommended Silicone Grease

- Shin-Etsu Chemical Co., Ltd.: G746
- GE Toshiba Silicones Co., Ltd.: YG-6260
- Dow Corning Toray Silicone Co., Ltd.: SC102

Please select proper silicone grease carefully since the oil in some grease products may penetrate the device and result in an extremely short device life.

Others

- Devices can not be operated in parallel connection aiming for a larger current.
- Not applicable for the current boost or voltage step-up use.

Rectifier Diodes for Power Supplies

To rectify the AC input using rectifier diodes in power supplies, please use SANKEN rectifier diodes shown in the following list. (Please use a center-tap or bridge configuration in using stand-alone type diodes.)

Series Name	Diodes
SAI Series	SFPM-62 (Surface-Mount Stand-Alone Type, $V_{RM}=200V, I_O=1.0A$)
SI-8000E Series	AM01Z (Axial Type, $V_{RM}=200V, I_O=1.0A$)
SI-8000GL Series	RM10Z (Axial Type, $V_{RM}=200V, I_O=1.5A$)
SI-8000JD Series	
SI-8000JF Series	
SI-8000RD Series	RM4Z (Axial Type, $V_{RM}=200V, I_O=3.0A$) or RBV-402 (Bridge Type, $V_{RM}=200V, I_O=4.0A$)
SI-8000S Series	
SI-8000SD Series	
SI-8000W Series	AM01Z (Axial Type, $V_{RM}=200V, I_O=1.0A$)
SI-8011NVS Series	RM4Z (Axial Type, $V_{RM}=200V, I_O=3.0A$) or RBV-402 (Bridge Type, $V_{RM}=200V, I_O=4.0A$)
SI-8400L Series	AM01Z (Axial Type, $V_{RM}=200V, I_O=1.0A$)
SI-8500L Series	RM10Z (Axial Type, $V_{RM}=200V, I_O=1.5A$)
SI-8511NVS Series	
SPI-8000A Series	RM4Z (Axial Type, $V_{RM}=200V, I_O=3.0A$) or RBV-402 (Bridge Type, $V_{RM}=200V, I_O=4.0A$)
STA810M Series	RM10Z (Axial Type, $V_{RM}=200V, I_O=1.5A$)
STA820M Series	RM4Z (Axial Type, $V_{RM}=200V, I_O=3.0A$) or RBV-402 (Bridge Type, $V_{RM}=200V, I_O=4.0A$)

SAI Series Surface-Mount, Separate Excitation Step-down Switching Mode Regulator IC

■ Features

- Surface-mount power package
- Output current: 0.4 to 0.5A
- High efficiency: 75 to 89%
- Requires only 4 discrete components
- Internally-adjusted phase correction and output voltage
- Built-in reference oscillator (60kHz)
- Built-in overcurrent and thermal protection circuits

■ Line up

Part Number	SAI01	SAI02	SAI03	SAI06
V _o (V)	5.0	3.3	12.0	9.0
I _o (A)	0.5		0.4	

■ Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V _{IN}	35	V
Power Dissipation	P _D	0.75	W
Junction Temperature	T _J	+125	°C
Storage Temperature	T _{stg}	-40 to +125	°C
Thermal Resistance(junction to case)	θ _{J-C}	20	°C/W

■ Applications

- Power supplies for telecommunication equipment
- Onboard local power supplies

■ Recommended Operating Conditions

Parameter	Symbol	Ratings				Unit
		SAI01	SAI02	SAI03	SAI06	
DC Input Voltage Range	V _{IN}	7 to 33	5.3 to 28	15 to 33	12 to 33	V
Output Current Range	I _o	0 to 0.5		0 to 0.4		A
Operating Junction Temperature Range	T _{jop}	-30 to +125				°C


■ Electrical Characteristics

(T_a=25°C)

Parameter	Symbol	Ratings												Unit
		SAI01			SAI02			SAI03			SAI06			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Output Voltage	V _o	4.80	5.00	5.20	3.17	3.30	3.43	11.40	12.00	12.60	8.55	9.00	9.45	V
Conditions		V _{IN} =20V, I _o =0.3A			V _{IN} =15V, I _o =0.3A			V _{IN} =24V, I _o =0.3A			V _{IN} =21V, I _o =0.3A			
Efficiency	η	80			75			88			86			%
Conditions		V _{IN} =20V, I _o =0.3A			V _{IN} =15V, I _o =0.3A			V _{IN} =24V, I _o =0.3A			V _{IN} =21V, I _o =0.3A			
Oscillation Frequency	f	60			60			60			60			kHz
Conditions		V _{IN} =20V, I _o =0.3A			V _{IN} =15V, I _o =0.3A			V _{IN} =24V, I _o =0.3A			V _{IN} =21V, I _o =0.3A			
Line Regulation	ΔV _{OLINE}	80			60			100			90			mV
Conditions		V _{IN} =10 to 30V, I _o =0.3A			V _{IN} =8 to 28V, I _o =0.3A			V _{IN} =18 to 30V, I _o =0.3A			V _{IN} =15 to 30V, I _o =0.3A			
Load Regulation	ΔV _{OLOAD}	30			20			70			50			mV
Conditions		V _{IN} =20V, I _o =0.1 to 0.4A			V _{IN} =15V, I _o =0.1 to 0.4A			V _{IN} =24V, I _o =0.1 to 0.4A			V _{IN} =21V, I _o =0.1 to 0.4A			
Temperature Coefficient of Output Voltage	ΔV _o /ΔT _a	±0.5			±0.5			±1.5			±1.0			mV/°C
Conditions		45			45			45			45			
Ripple Rejection	R _{REJ}	45			45			45			45			dB
Conditions		f=100 to 120Hz			f=100 to 120Hz			f=100 to 120Hz			f=100 to 120Hz			
Overcurrent Protection Starting Current	I _{s1}	0.55			0.55			0.45			0.45			A
Conditions		V _{IN} =10V			V _{IN} =8V			V _{IN} =18V			V _{IN} =15V			

External Dimensions

(unit : mm)




- a. Part Number
- b. Lot Number
- Ⓐ Case temperature measuring point

Pin Assignment


- ① VIN
- ② SWOUT
- ③ Vos
- ④ GND

Plastic Mold Package Type
 Flammability: UL94V-0
 Product Mass: Approx. 0.22g


Block Diagram



Typical Connection Diagram



Ta-Pd Characteristics



$$P_D = V_O \cdot I_O \left(\frac{100}{\eta\chi} - 1 \right) - V_F \cdot I_O \left(1 - \frac{V_O}{V_{IN}} \right)$$

The efficiency depends on the input voltage and the output current. Therefore, obtain the value from the efficiency graph and substitute the percentage in the formula above.

- VO : Output voltage
- IO : Output current
- ηχ : Efficiency (%)
- VF : Diode D1 forward voltage
SFPB54-0.3V

Thermal design for D1 must be considered separately.

SI-8000W Series Surface-Mount, Separate Excitation Step-down Switching Mode Regulator IC

■Features

- Surface-mount package (SOP8)
- Output current: 0.6A
- High efficiency: 75 to 80%
- Requires only 4 discrete components
- Internally-adjusted phase correction and output voltage adjustment performed internally
- Built-in reference oscillator (60kHz)
- Built-in overcurrent and thermal protection circuits

■Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V_{IN}	35	V
Power Dissipation	P_D	1	W
Junction Temperature	T_j	-30 to +125	°C
Storage Temperature	T_{stg}	-40 to +125	°C
Thermal Resistance (Junction to 7-Pin Lead)	θ_{j-L}	22	°C/W
Thermal Resistance (Junction to Ambient Air)*1	θ_{j-a}	100	°C/W

*1: Glass-epoxy board of 40 × 40mm (copper laminate area 4.3%)

■Applications

- Power supplies for telecommunication equipment
- Onboard local power supplies

■Recommended Operating Conditions

Parameter	Symbol	Ratings		Unit
		SI-8033W	SI-8050W	
DC Input Voltage Range	V_{IN}	5.3 to 28	7 to 33	V
Output Current Range	I_O	0 to 0.6		A
Operating Junction Temperature Range	T_{jop}	-30 to +125		°C

■Electrical Characteristics

($T_a=25^\circ\text{C}$)

Parameter	Symbol	Ratings						Unit
		SI-8033W			SI-8050W			
		min.	typ.	max.	min.	typ.	max.	
Output Voltage	V_O	3.17	3.30	3.43	4.80	5.00	5.20	V
	Conditions	$V_{IN}=15\text{V}, I_O=0.3\text{A}$			$V_{IN}=20\text{V}, I_O=0.3\text{A}$			
Efficiency	η	75			80			%
	Conditions	$V_{IN}=15\text{V}, I_O=0.3\text{A}$			$V_{IN}=20\text{V}, I_O=0.3\text{A}$			
Oscillation Frequency	f	60			60			kHz
	Conditions	$V_{IN}=15\text{V}, I_O=0.3\text{A}$			$V_{IN}=20\text{V}, I_O=0.3\text{A}$			
Line Regulation	ΔV_{OLINE}	60			80			mV
	Conditions	$V_{IN}=8\text{ to }28\text{V}, I_O=0.3\text{A}$			$V_{IN}=10\text{ to }30\text{V}, I_O=0.3\text{A}$			
Load Regulation	ΔV_{OLOAD}	20			30			mV
	Conditions	$V_{IN}=15\text{V}, I_O=0.1\text{ to }0.4\text{A}$			$V_{IN}=20\text{V}, I_O=0.1\text{ to }0.4\text{A}$			
Temperature Coefficient of Output Voltage	$\Delta V_O/\Delta T_a$	± 0.5			± 0.5			mV/°C
Ripple Rejection	R_{REJ}	45			45			dB
	Conditions	$f=100\text{ to }120\text{Hz}$			$f=100\text{ to }120\text{Hz}$			
Overcurrent Protection Starting Current	I_{S1}	0.61			0.61			A
	Conditions	$V_{IN}=15\text{V}$			$V_{IN}=20\text{V}$			

External Dimensions


(Unit : mm)

Pin Assignment


- ① VIN
- ② N.C
- ③ SWout
- ④ Vos
- ⑤ GND
- ⑥ GND
- ⑦ GND
- ⑧ GND

Plastic Mold Package Type
 Flammability: UL94V-0
 Product Mass: Approx. 0.1g


Block Diagram



Typical Connection Diagram



Reference Data



SI-8000JD Series Surface-Mount, Separate Excitation Step-down Switching Mode Regulator IC

■Features

- Surface-mount package (TO263-5)
- Output current: 1.5A
- High efficiency: 77 to 86%
- Requires only 4 discrete components
- Internally-adjusted phase correction and output voltage
- Capable of downsizing a choke-coil due to IC's high switching frequency (125 kHz). (Compared with conventional Sanken devices)
- Built-in foldback-overcurrent and thermal protection circuits
- Output ON/OFF available (Circuit current at output OFF: 200 μ A max)
- Soft start available by ON/OFF pin Conditions

■Lineup

Part Number	SI-8033JD	SI-8050JD	SI-8090JD	SI-8120JD
Vo(V)	3.3	5.0	9.0	12.0
Io(A)	1.5			

■Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit	Conditions
DC Input Voltage	V _{IN}	43	V	
Output Current	I _o	1.5	A	
Power Dissipation*	P _d	3	W	When mounted on glass-epoxy board 40 × 40 mm (copper area 100%)
Junction Temperature	T _j	+125	°C	
Storage Temperature	T _{stg}	-40 to +125	°C	
Thermal Resistance (Junction to Case)	θ_{j-c}	3	°C/W	
Thermal Resistance (Junction to Ambient Air)	θ_{j-a}	33.3	°C/W	When mounted on glass-epoxy board 40 × 40 mm (copper area 100%)

*: Limited by thermal protection circuit

■Applications

- Power supplies for telecommunication equipment
- Onboard local power supplies, etc.

■Recommended Operating Conditions

Parameter	Symbol	Ratings				Unit	Conditions
		SI-8033JD	SI-8050JD	SI-8090JD	SI-8120JD		
DC Input Voltage Range	V _{IN1}	5.3 to 6.3	7 to 8	11 to 12	14 to 15	V	I _o =0 to 1A
	V _{IN2}	6.3 to 40	8 to 40	12 to 40	15 to 40		I _o =0 to 1.5A
DC Output Current Range*	I _o	0 to 1.5				A	V _{IN} =V _O +3V
Operating Junction Temperature Range	T _{TOP}	-30 to +125				°C	
Operating Temperature Range*	T _{OP}	-30 to +125				°C	

*: Limited by Ta-Pd characteristics

■Electrical Characteristics

(T_a=25°C)

Parameter	Symbol	Ratings												Unit
		SI-8033JD			SI-8050JD			SI-8090JD			SI-8120JD			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Output Voltage	V _o	3.234	3.30	3.366	4.90	5.00	5.10	8.82	9.00	9.18	11.76	12.00	12.24	V
	Conditions	V _{IN} =15V, I _o =0.5A			V _{IN} =20V, I _o =0.5A			V _{IN} =21V, I _o =0.5A			V _{IN} =24V, I _o =0.5A			
Efficiency	η	77			82			86			88			%
	Conditions	V _{IN} =15V, I _o =0.5A			V _{IN} =20V, I _o =0.5A			V _{IN} =21V, I _o =0.5A			V _{IN} =24V, I _o =0.5A			
Oscillation Frequency	f	125			125			125			125			kHz
	Conditions	V _{IN} =15V, I _o =0.5A			V _{IN} =20V, I _o =0.5A			V _{IN} =21V, I _o =0.5A			V _{IN} =24V, I _o =0.5A			
Line Regulation	Δ V _{OLINE}	25 80			40 100			50 120			60 130			mV
	Conditions	V _{IN} =8 to 30V, I _o =0.5A			V _{IN} =10 to 30V, I _o =0.5A			V _{IN} =15 to 30V, I _o =0.5A			V _{IN} =18 to 30V, I _o =0.5A			
Load Regulation	Δ V _{OLOAD}	10 30			10 40			10 40			10 40			mV
	Conditions	V _{IN} =15V, I _o =0.2 to 0.8A			V _{IN} =20V, I _o =0.2 to 0.8A			V _{IN} =21V, I _o =0.2 to 0.8A			V _{IN} =24V, I _o =0.2 to 0.8A			
Temperature Coefficient of Output Voltage	Δ V _o /ΔT _a	±0.5			±0.5			±1.0			±1.0			mV/°C
Overcurrent Protection Starting Current	I _{st}	1.6			1.6			1.6			1.6			A
	Conditions	V _{IN} =15V			V _{IN} =20V			V _{IN} =21V			V _{IN} =24V			
ON/OFF* Pin	Low Level Voltage	V _S SSL			0.5			0.5			0.5			V
	Outflow Current at Low Voltage	I _S SSL			100			100			100			
Quiescent Circuit Current	I _q	7			7			7			7			mA
		Conditions	V _{IN} =15V, I _o =0A			V _{IN} =20V, I _o =0A			V _{IN} =21V, I _o =0A			V _{IN} =24V, I _o =0A		
	I _{q(OFF)}	200			200			200			200			μ A
		Conditions	V _{IN} =15V, V _{ON/OFF} =0.3V			V _{IN} =20V, V _{ON/OFF} =0.3V			V _{IN} =21V, V _{ON/OFF} =0.3V			V _{IN} =24V, V _{ON/OFF} =0.3V		

*: Pin 5 is the ON/OFF pin. Soft start at power on can be performed with a capacitor connected to this pin.


The output can also be turned ON/OFF with this pin.

The output is stopped by setting the voltage of this pin to V_SSSL or lower.


ON/OFF-pin voltage can be changed with an open-collector drive circuit of a transistor.

When using both the soft-start and ON/OFF functions together, the discharge current from C₃ flows into the ON/OFF control transistor. Therefore, limit the current securely to protect the transistor if C₃ capacitance is large.


The ON/OFF pin is pulled up to the power supply in the IC, so applying the external voltage is prohibited.



V_{OUT. ON/OFF}




Soft Start




Soft Start + V_{OUT. ON/OFF}

External Dimensions


(Unit : mm)




Block Diagram




Typical Connection Diagram



Reference Data



Ta-Pd Characteristics



SI-8000SD Series Surface Mount, Separate Excitation Step-down Switching Mode Regulator IC

Features

- Surface-mount package (TO263-5)
- Output current: 3.0A
- High efficiency: 79% typ. (SI-8033SD), 84% typ. (SI-8050SD)
- Requires only 4 discrete external components
- Internally-adjusted phase correction and output voltage
- Built-in reference oscillator (60kHz)
- Built-in overcurrent and thermal protection circuits
- Output ON/OFF available
- Soft start available by S.S pin

Lineup

Part Number	SI-8033SD	SI-8050SD
Vo (V)	3.3	5.0
Io (A)	3	

Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit	Conditions
DC Input Voltage	V _{IN}	43*1	V	
Power Dissipation*2	P _D	3	W	When mounted on glass-epoxy board 40 x 40 mm (copper area: 100%)
Junction Temperature	T _j	+125	°C	
Storage Temperature	T _{stg}	-40 to +125	°C	
Thermal Resistance (Junction to Case)	θ _{J-C}	3	°C/W	
Thermal Resistance (Junction to Ambient Air)	θ _{J-A}	33.3	°C/W	When mounted on glass-epoxy board 40 x 40 mm (copper area: 100%)

*1: 35V for SI-8033SD

*2: Limited by thermal protection circuit.

Applications

- Power supplies for telecommunication equipment
- Onboard local power supplies

Recommended Operating Conditions

Parameter	Symbol	Ratings		Unit
		SI-8033SD	SI-8050SD	
DC Input Voltage Range	V _{IN1}	5.5 to 28	7 to 40	V
Output Current Range*	I _O	0 to 3.0		A
Operating Junction Temperature Range	T _{jop}	-30 to +125		°C
Operating Temperature Range*	T _{op}	-30 to +125		°C

*: Limited by Ta-Pd characteristics.

Electrical Characteristics

(T_a=25°C)

Parameter	Symbol	Ratings						Unit	
		SI-8033SD			SI-8050SD				
		min.	typ.	max.	min.	typ.	max.		
Output Voltage	V _O	3.17	3.3	3.43	4.8	5.0	5.2	V	
	Conditions	V _{IN} =15V, I _O =1A			V _{IN} =20V, I _O =1A				
Efficiency	η		79			84		%	
	Conditions	V _{IN} =15V, I _O =1A			V _{IN} =20V, I _O =1A				
Oscillation Frequency	f		60			60		kHz	
	Conditions	V _{IN} =15V, I _O =1A			V _{IN} =20V, I _O =1A				
Line Regulation	ΔV _{O(LINE)}		25	80		40	100	mV	
	Conditions	V _{IN} =8 to 28V, I _O =1A			V _{IN} =10 to 30V, I _O =1A				
Load Regulation	ΔV _{O(LOAD)}		10	30		10	40	mV	
	Conditions	V _{IN} =15V, I _O =0.5 to 1.5A			V _{IN} =20V, I _O =0.5 to 1.5A				
Temperature Coefficient of Output Voltage	ΔV _O /ΔT _a		±0.5			±0.5		mV/°C	
Overcurrent Protection Starting Current	I _{S1}	3.1			3.1			A	
	Conditions	V _{IN} =15V			V _{IN} =20V				
Soft Start Pin*	Low-Level Voltage	V _{SSL}	0.2			0.2		V	
	Outflow Current at Low Voltage	I _{SSL}	20	30	40	20	30		40
		Conditions	V _{SSL} =0.2V						μA

* Pin 5 is a soft start pin. Soft start at power on can be performed with a capacitor connected to this pin.

The output can also be turned ON/OFF with this pin.


The output is stopped by setting the voltage of this pin to V_{SSL} or lower.

Soft-start pin voltage can be changed with an open-collector drive circuit of a transistor.


When using both the soft-start and ON/OFF functions together, the discharge current from C₃ flows into the ON/OFF control transistor. Therefore, limit the current securely to protect the transistor if C₃ capacitance is large.

The ON/OFF pin is pulled up to the power supply in the IC, so applying the external voltage is prohibited.


If this pin is not used, leave it open.



V_{OUT}. ON/OFF




Soft start



Soft start + V_{OUT}. ON/OFF



External Dimensions

(Unit : mm)




Block Diagram

Reference Data



Typical Connection Diagram



SPI-8000A Series Surface Mount, Separate Excitation Step-down Switching Mode Regulator IC

Features

- Surface-mount 16 pin package
- Output current: 3.0A
- High efficiency: 91% (at $V_{IN} = 10V$, $I_o = 1A$, $V_o = 5V$)
- Capable of downsizing a choke-coil due to IC's high switching frequency (125kHz). (Compared with conventional Sanken devices)
- The output-voltage-variable type can vary its output voltage from 1V to 24V because of its low reference voltage (V_{ref}) of 1V.
- Wide Input Voltage Range (8 to 50V)
- Output ON/OFF available
- Built-in overcurrent and thermal protection circuits

Absolute Maximum Ratings

($T_a=25^\circ C$)

Parameter	Symbol	Rated	Unit
DC Input Voltage	V_{IN}	53	V
Power Dissipation	$P_D^{*1, *2}$	2.4	W
Junction Temperature	T_j	+125	$^\circ C$
Storage Temperature	T_{stg}	-40 to +125	$^\circ C$
Thermal Resistance (junction to case)	θ_{j-c}^{*2}	18	$^\circ C/W$
Thermal Resistance (junction to ambient air)	θ_{j-a}^{*2}	50	$^\circ C/W$

*1: Limited due to thermal protection.

*2: When mounted on glass-epoxy board 700cm² (copper laminate area 30.8cm²)

Applications

- Onboard local power supplies
- OA equipment
- For stabilization of the secondary-side output voltage of switching power supplies

Recommended Operating Conditions

Parameter	Symbol	Ratings	
		SPI-8010A	
DC Input Voltage Range	V_{IN}	(8 or V_o+3) ^{*1} to 50	
Output Voltage Range	V_o	1 to 24	
Output Current Range	I_o	0.02 to 3.0	
Operating Junction Temperature Range	T_{jop}	-30 to +125	
Operating Temperature Range	T_{op}	-30 to +125	


*1: The minimum value of an input voltage range is the higher of either 8V or V_o+3V .

Electrical Characteristics

($T_a=25^\circ C$)


Parameter	Symbol	Rating			Unit
		SPI-8010A (Variable type)			
		min.	typ.	max.	
Output Voltage (Reference Voltage for SPI-8010A)	$V_o(V_{ADJ})$	0.97	1.00	1.03	V
Efficiency	Eff	$V_{IN}=12V, I_o=1A$			%
	Conditions	$V_{IN}=20V, I_o=1A, V_o=5V$			
Oscillation Frequency	F_{osc}	250			kHz
	Conditions	$V_{IN}=12V, I_o=1A$			
Line Regulation	ΔV_{OLINE}	20	40		mV
	Conditions	$V_{IN}=10$ to 30V, $I_o=1A$			
Load Regulation	ΔV_{OLOAD}	10	30		mV
	Conditions	$V_{IN}=12V, I_o=0.1$ to 1.5A			
Temperature Coefficient of Output Voltage (Temperature Coefficient of Reference Voltage for SPI-8010A)	$\Delta V_o/\Delta T_a$ $\Delta V_{ADJ}/\Delta T_a$	± 0.5			$mV/^\circ C$
Overcurrent Protection Starting Current	I_s	3.1			A
	Conditions	$V_{IN}=12V$			
Quiescent Circuit Current	I_q	7			mA
	Conditions	$V_{IN}=12V, I_o=0A$			
Circuit Current at Output OFF	$I_{q(off)}$		400		μA
	Conditions	$V_{IN}=12V, V_{ON/OFF}=0.3V$			
CE/SS Terminal	Low Level Voltage	V_{SSL}	0.5		V
	Outflow Current at Low Voltage	I_{SSL}	50		μA
	Conditions	$V_{SSL}=0V$			

* Pin 4 is the CE/SS pin. Soft start at power on can be performed with a capacitor connected to this pin. The output can also be turned ON/OFF with this pin. The output is stopped by setting the voltage of this pin to V_{SSL} or lower. CE/SS-pin voltage can be changed with an open-collector drive circuit of a transistor. When using both the soft-start and ON/OFF functions together, the discharge current from C_4 flows into the ON/OFF control transistor. Therefore, limit the current securely to protect the transistor if C_3 capacitance is large. The CE/SS pin is pulled up to the power supply in the IC, so applying the external voltage is prohibited.




External Dimensions


(Unit : mm)



Block Diagram



■ Typical Connection Diagram



Diode D1

- Be sure to use a Schottky-barrier diode for D1. If other diodes like fast recovery diodes are used, IC may be destroyed because of the reverse voltage generated by the recovery voltage or ON voltage.

Choke coil L1

- If the winding resistance of the choke coil is too high, the efficiency may drop below the rated value.
- As the overcurrent protection starting current is about 4.5A, take care concerning heat radiation from the choke coil caused by magnetic saturation due to overload or short-circuited load.

Capacitors C1, C2

- As large ripple currents flow through C1 and C2, use high-frequency and low-impedance capacitors aiming for switching-mode-power-supply use. Especially when the impedance of C2 is high, the switching waveform may become abnormal at low temperatures. For C2, do not use a capacitor with an extremely low equivalent series resistance (ESR) such as an OS capacitor or a tantalum capacitor, which may cause an abnormal oscillation.


Resistors R2, R3

- R2 and R3 are the resistors to set the output voltage. Set their values so that I_{REF} becomes approx. 2mA. Obtain R2 and R3 values by the following formula:

$$R2 = \frac{(V_{OUT} - V_{REF})}{I_{REF}} = \frac{(V_{OUT} - 1)}{2 \times 10^{-3}} (\Omega), R3 = \frac{V_{REF}}{I_{REF}} = \frac{1}{2 \times 10^{-3}} \cong 500(\Omega)$$

©To create the optimum operating conditions, place the components as close as possible to each other.

■ T_a-P_d Characteristics



$$P_D = V_O \cdot I_O \left(\frac{100}{\eta\%} - 1 \right) - V_F \cdot I_O \left(1 - \frac{V_O}{V_{IN}} \right)$$

Note 1: The efficiency depends on the input voltage and the output current. Therefore, obtain the value from the efficiency graph and substitute the percentage in the formula above.

Note 2: Thermal design for D1 must be considered separately.

- V_O : Output voltage
- V_{IN} : Input voltage
- I_O : Output current
- η% : Efficiency (%)
- V_F : Diode D1 forward voltage
 SPB-G56S...0.4V(I_O=2A)

SI-8000RD Series Surface Mount, Separate Excitation Step-down Switching Mode Regulator IC

Features

- Surface-mount package (TO263-5)
- Output current: 3.0A
- Capable of downsizing a choke-coil due to IC's high switching frequency (110kHz). (Compared with conventional Sanken devices)
- High efficiency: 80% typ (SI-8033RD), 84% typ (SI-8050RD)
- Requires only 4 discrete components
- Built-in overcurrent and thermal protection circuits
- Built-in soft start circuit (output ON/OFF available)

Applications

- Power supplies for telecommunication equipment
- Onboard local power supplies
- For stabilization of the secondary-side output voltage of a switching regulators

Lineup

Product Name	SI-8033RD	SI-8050RD
V _o (V)	3.3	5.0
I _o (A)	3.0	

Absolute Maximum Ratings^{*1}

Parameter	Symbol	Ratings		Unit
		SI-8033RD	SI-8050RD	
Input Voltage	V _{IN}	21	30	V
Power Dissipation ^{*2, *3}	P _D	3.0		W
Junction Temperature	T _J	+125		°C
Storage Temperature	T _{stg}	-40 to +125		°C
Thermal Resistance (Junction to Case) ^{*2}	θ _{J-C}	3.0		°C/W
Thermal Resistance (Junction to Ambient Air) ^{*2}	θ _{J-A}	33.3		°C/W

*1: The absolute maximum ratings show the destructive limit. No parameter should exceed the ratings in transient or normal operations.

*2: When mounted on glass-epoxy board of 40 × 40mm (copper laminate area 100%)

*3: Limited by thermal protection.

Recommended Operating Conditions^{*1}

Parameter	Symbol	Ratings				Unit
		SI-8033RD		SI-8050RD		
		min.	max.	min.	max.	
Input Voltage Range	V _{IN}	5.5	20	7	28	V
Output Current Range ^{*2}	I _o	0	3.0	0	3.0	A
Operating Junction Temperature Range	T _{JOP}	-30	+125	-30	+125	°C
Operating Temperature Range ^{*2}	T _{OP}	-30	+125	-30	+125	°C

*1: The recommended operating conditions show the operating conditions required for the normal circuit function described in the electrical characteristics. These conditions must be followed in actual use.

*2: Limited by T_a-P_D characteristics.

Electrical Characteristics^{*1}

(T_a=25°C)


Parameter	Symbol	Ratings						Unit
		SI-8033RD			SI-8050RD			
		min.	typ.	max.	min.	typ.	max.	
Output Voltage	V _o	3.17	3.30	3.43	4.8	5.0	5.2	V
Efficiency ^{*2}	η	V _{IN} =15V, I _o =1A			V _{IN} =20V, I _o =1A			%
	Conditions	80			84			
Oscillation Frequency	f	V _{IN} =15V, I _o =1A			V _{IN} =20V, I _o =1A			kHz
	Conditions	110			110			
Line Regulation	θV _{OLINE}	25			40			mV
	Conditions	V _{IN} =8 to 20V, I _o =1A			V _{IN} =10 to 30V, I _o =1A			
Load Regulation	θV _{OLOAD}	10			10			mV
	Conditions	V _{IN} =15V, I _o =0.5 to 1.5A			V _{IN} =20V, I _o =0.5 to 1.5A			
Temperature Coefficient of Output Voltage	θV _o /θT _a	±0.5			±0.5			mV/°C
Overcurrent Protection Starting Current	I _{SI}	3.1			3.1			A
	Conditions	V _{IN} =15V			V _{IN} =20V			
Soft Start ^{*3} Terminal	Low Level Voltage	V _{S5L}			0.2			V
	Outflow Current at Low Voltage	I _{SSL}	15	25	35	15	25	
								μA
								V _{S5L} =0.2V

*1: The electrical characteristics show the characteristics ratings guaranteed when operating the IC under the measurement conditions described in the above table in the circuit shown in the measurement circuit diagram.

*2: Efficiency is calculated from the following formula.


$$\eta(\%) = \frac{V_o \cdot I_o}{V_{IN} \cdot I_{IN}} \times 100$$

*3: Pin 5 is a soft start pin. Soft start at power on can be performed with a capacitor connected to this pin. The output can also be turned ON/OFF with this pin. The output is stopped by setting the voltage of this pin to V_{S5L} or lower. Soft-start pin voltage can be changed with an open-collector drive circuit of a transistor. When using both the soft-start and ON/OFF functions together, the discharge current from C₃ flows into the ON/OFF control transistor. Therefore, limit the current securely to protect the transistor if C₃ capacitance is large. The ON/OFF pin is pulled up to the power supply in the IC, so applying the voltage externally is prohibited. If this pin is not used, leave it open.




External Dimensions


(Unit : mm)




Block Diagram




Typical Connection Diagram



Reference Data



Ta-Pd Characteristics



SI-8000E Series Full-Mold, Separate Excitation Step-down Switching Mode Regulator IC

■Features

- Compact full-mold package (equivalent to TO220)
- High efficiency: 80 to 88%
- Requires only 4 discrete components
- Internally-adjusted phase correction and output voltage
- Built-in reference oscillator (60kHz)
- Built-in overcurrent and thermal protection circuits

■Applications

- Power supplies for telecommunication equipment
- Onboard local power supplies

■Lineup

Part Number	SI-8050E	SI-8120E
Vo(V)	5.0	12.0
Io(A)	0.6	

■Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V _{IN}	43	V
Power Dissipation	P _{D1}	14(With infinite heatsink)	W
	P _{D2}	1.5(Without heatsink, stand-alone operation)	W
Junction Temperature	T _J	+125	°C
Storage Temperature	T _{Stg}	-40 to +125	°C
Thermal Resistance(junction to case)	θ _{J-c}	7.0	°C/W
Thermal Resistance(junction to ambient air)	θ _{J-a}	66.7	°C/W

■Recommended Operating Conditions

Parameter	Symbol	Ratings		Unit
		SI-8050E	SI-8120E	
DC Input Voltage Range	V _{IN}	7 to 40	14 to 40	V
Output Current Range	I _O	0 to 0.6		A
Operating Junction Temperature Range	T _{JO}	-30 to +125		°C
Operating Temperature Range	T _{OP}	-30 to +125		°C


■Electrical Characteristics

(T_a=25°C)


Parameter	Symbol	Ratings						Unit
		SI-8050E			SI-8120E			
		min.	typ.	max.	min.	typ.	max.	
Output Voltage	V _O	4.80	5.00	5.20	11.52	12.00	12.48	V
	Conditions	V _{IN} =20V, I _O =0.3A			V _{IN} =24V, I _O =0.3A			
Efficiency	η		80			88		%
	Conditions	V _{IN} =20V, I _O =0.3A			V _{IN} =24V, I _O =0.3A			
Oscillation Frequency	f		60			60		kHz
	Conditions	V _{IN} =20V, I _O =0.3A			V _{IN} =24V, I _O =0.3A			
Line Regulation	ΔV _{OLINE}		80	100		100	130	mV
	Conditions	V _{IN} =10 to 30V, I _O =0.3A			V _{IN} =17 to 30V, I _O =0.3A			
Load Regulation	ΔV _{OLOAD}		30	40		70	95	mV
	Conditions	V _{IN} =20V, I _O =0.1 to 0.4A			V _{IN} =24V, I _O =0.1 to 0.4A			
Temperature Coefficient of Output Voltage	ΔV _O /ΔT _a		±0.5			±1.5		mV/°C
Overcurrent Protection Starting Current	I _{SI}	0.61			0.61			A
	Conditions	V _{IN} =10V			V _{IN} =17V			

External Dimensions


(Unit : mm)




Block Diagram



Typical Connection Diagram



Ta-Pd Characteristics



SI-8000JF Series Full-Mold, Separate Excitation Step-down Switching Mode Regulator IC

Features

- Compact full-mold package (equivalent to TO220)
- Output current: 1.5A
- High efficiency: 79 to 91%
- Requires only 4 discrete components
- Internally-adjusted phase correction and output voltage
- Capable of downsize a choke-coil due to IC's high switching frequency (125kHz). (Compared with conventional Sanken devices)
- Built-in foldback-overcurrent and thermal protection circuits
- Output ON/OFF available (circuit current at output OFF: 200 μ A max.)
- Soft start available by ON/OFF pin

Lineup

Part Number	SI-8015JF	SI-8025JF	SI-8033JF	SI-8050JF	SI-8090JF	SI-8120JF
Vo (V)	1.59	2.5	3.3	5.0	9.0	12.0
Io (A)	1.5					

Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V _{IN}	43	V
Power Dissipation	P _{D1}	16.6 (with infinite heatsink)	W
	P _{D2}	1.5 (without heatsink, standalone operation)	W
Junction Temperature	T _j	+125	°C
Storage Temperature	T _{stg}	-40 to +125	°C
Thermal Resistance (Junction to Case)	θ_{j-c}	6.0	°C/W

Applications

- Power supplies for telecommunication equipment
- Onboard local power supplies

Recommended Operating Conditions

Parameter	Symbol	Ratings						Unit	Conditions
		SI-8015JF*	SI-8025JF	SI-8033JF	SI-8050JF	SI-8090JF	SI-8120JF		
DC Input Voltage Range	V _{IN1}	Vo+2 to Vo+3	4.5 to 5.5	5.3 to 6.3	7 to 8	11 to 12	14 to 15	V	Io=0 to 1A
	V _{IN2}	Vo+3 to 40	5.5 to 40	6.3 to 40	8 to 40	12 to 40	15 to 40	V	Io=0 to 1.5A
Output Current Range	Io	0 to 1.5						A	V _{IN} ≥Vo+3V
Operating Junction Temperature Range	T _{top}	-30 to +125						°C	

* SI-8015JF is a variable output voltage type. The variable output voltage range is from 2.5 V to 24 V.

Electrical Characteristics

(T_a=25°C)

Parameter	Symbol	Ratings															Unit			
		SI-8015JF			SI-8025JF			SI-8033JF			SI-8050JF			SI-8090JF				SI-8120JF		
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Output Voltage ¹	V _O ²	1.558	1.59	1.622	2.45	2.50	2.55	3.234	3.30	3.366	4.90	5.00	5.10	8.82	9.00	9.18	11.76	12.00	12.24	V
	Conditions	V _{IN} =12V, I _O =0.5A			V _{IN} =12V, I _O =0.5A			V _{IN} =15V, I _O =0.5A			V _{IN} =20V, I _O =0.5A			V _{IN} =21V, I _O =0.5A			V _{IN} =24V, I _O =0.5A			
Efficiency	η	67			74			77			82			86			88			%
	Conditions	V _{IN} =12V, I _O =0.5A			V _{IN} =12V, I _O =0.5A			V _{IN} =15V, I _O =0.5A			V _{IN} =20V, I _O =0.5A			V _{IN} =21V, I _O =0.5A			V _{IN} =24V, I _O =0.5A			
Oscillation Frequency	f	125			125			125			125			125			125			kHz
	Conditions	V _{IN} =12V, I _O =0.5A			V _{IN} =12V, I _O =0.5A			V _{IN} =15V, I _O =0.5A			V _{IN} =20V, I _O =0.5A			V _{IN} =21V, I _O =0.5A			V _{IN} =24V, I _O =0.5A			
Line Regulation	ΔV_{OLINE}	25 80			25 80			25 80			40 100			50 120			60 130			mV
	Conditions	V _{IN} =8 to 30V, I _O =0.5A			V _{IN} =7 to 30V, I _O =0.5A			V _{IN} =8 to 30V, I _O =1.0A			V _{IN} =10 to 30V, I _O =1.0A			V _{IN} =15 to 30V, I _O =1.0A			V _{IN} =18 to 30V, I _O =1.0A			
Load Regulation	ΔV_{LOAD}	10 30			10 30			10 30			10 40			10 40			10 40			mV
	Conditions	V _{IN} =12V, I _O =0.2 to 0.8A			V _{IN} =12V, I _O =0.2 to 0.8A			V _{IN} =15V, I _O =0.5 to 1.5A			V _{IN} =20V, I _O =0.5 to 1.5A			V _{IN} =21V, I _O =0.5 to 1.5A			V _{IN} =24V, I _O =0.5 to 1.5A			
Temperature Coefficient of Output Voltage ³	$\Delta V_O/\Delta T_a$ ⁴	±0.5			±0.5			±1.0			±1.0									mV/°C
Overcurrent Protection	I _{S1}	1.6			1.6			1.6			1.6			1.6			1.6			A
Starting Current	Conditions	V _{IN} =12V			V _{IN} =12V			V _{IN} =15V			V _{IN} =20V			V _{IN} =21V			V _{IN} =24V			
ON/OFF ⁵ Terminal	Low Level Voltage	V _{SSL}	0.5		0.5		0.5		0.5		0.5		0.5		0.5		0.5		V	
	Outflow Current at Low Voltage	I _{SSL}	100		100		100		100		100		100		100		100		μ A	
Quiescent Circuit Current	I _q	7			7			7			7			7			7			mA
	Conditions	V _{IN} =12V, I _O =0A			V _{IN} =12V, I _O =0A			V _{IN} =15V, I _O =0A			V _{IN} =20V, I _O =0A			V _{IN} =21V, I _O =0A			V _{IN} =24V, I _O =0A			
	I _{q(OFF)}	200			200			200			200			200			200			μ A
Conditions	V _{IN} =12V, V _{ON/OFF} =0.3V			V _{IN} =12V, V _{ON/OFF} =0.3V			V _{IN} =15V, V _{ON/OFF} =0.3V			V _{IN} =20V, V _{ON/OFF} =0.3V			V _{IN} =21V, V _{ON/OFF} =0.3V			V _{IN} =24V, V _{ON/OFF} =0.3V				

*1: Reference voltage for SI-8015JF


*3: Temperature Coefficient of Reference Voltage for SI-8015JF

*2: V_{REF} for SI-8015JF

*4: $\Delta V_{REF}/\Delta T_a$ for SI-8015JF

*5: Pin 5 is the ON/OFF pin. Soft start at power on can be performed with a capacitor connected to this pin.

The output can also be turned ON/OFF with this pin. The output is stopped by setting the voltage of this pin to V_{SSL} or lower. ON/OFF-pin voltage can be changed with an open-collector drive circuit of a transistor. When using both the soft-start and ON/OFF functions together, the discharge current from C₃ flows into the ON/OFF control transistor. Therefore, limit the current securely to protect the transistor if C₃ capacitance is large. The ON/OFF pin is pulled up to the power supply in the IC, so applying the external voltage is prohibited. If this pin is not used, leave it open.




V_{OUT}. ON/OFF

Soft start


Soft start +V_{OUT}. ON/OFF

External Dimensions


(Unit : mm)



Block Diagram



Typical Connection Diagram



SI-8000GL Series Compact, Separate Excitation Step-down Switching Mode Regulator IC

■Features

- DIP 8 pin package
- Output current: 1.5A
- High efficiency: 91% (at $V_{IN} = 10V$, $I_o = 1A$, $V_o = 5V$)
- Capable of downsize a choke-coil due to IC's high switching frequency (125kHz). (Compared with conventional Sanken devices)
- The output-voltage-variable type can vary its output voltage from 1V to 24V because of its low reference voltage (V_{ref}) of 1V.
- Wide Input Voltage Range (8 to 50V)
- Output ON/OFF available
- Built-in overcurrent protection and thermal protection circuits

■Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V_{IN}	53	V
Power Dissipation	P_D^{*1}	1	W
Junction Temperature	T_j	+125	°C
Storage Temperature	T_{stg}	-40 to +125	°C
Thermal Resistance (junction to case)	θ_{j-c}	28	°C/W
Thermal Resistance (junction to ambient air)	θ_{j-a}	100	°C/W

*1: Limited by thermal protection.

■Applications

- Onboard local power supplies
- OA equipment
- For stabilization of the secondary-side output voltage of switching power supplies

■Recommended Operating Conditions

Parameter	Symbol	Ratings	
		SI-8010GL	
DC Input Voltage Range	V_{IN}	(8 or V_o+3)*1 to 50	
Output Voltage Range	V_o	1 to 24	
Output Current Range	I_o	0.02 to 1.5	
Operating Junction Temperature Range	T_{jop}	-30 to +125	
Operating Temperature Range	T_{op}	-30 to +125	


*1: The minimum value of an input voltage range is the higher of either 8V or V_o+3V .

■Electrical Characteristics

($T_a=25^\circ C$)


Parameter	Symbol	Ratings			Unit
		SI-8010GL (Variable type)			
		min.	typ.	max.	
Output Voltage (Reference Voltage for SI-8010GL)	$V_o(V_{REF})$	0.97	1.00	1.03	V
Efficiency	Eff	$V_{IN}=12V, I_o=1A$			%
	Conditions	$V_{IN}=20V, I_o=1A, V_o=5V$			
Oscillation Frequency	F_{OSC}	250			kHz
	Conditions	$V_{IN}=12V, I_o=1A$			
Line Regulation	ΔV_{OLINE}	20			mV
	Conditions	$V_{IN}=10$ to $30V, I_o=1A$			
Load Regulation	ΔV_{OLOAD}	10			mV
	Conditions	$V_{IN}=12V, I_o=0.1$ to $1.5A$			
Temperature Coefficient of Output Voltage (Temperature Coefficient of Reference Voltage for SI-8010GL)	$\Delta V_o/\Delta T_a$ $\Delta V_{REF}/\Delta T_a$	± 0.5			mV/°C
Overcurrent Protection Starting Current	I_s	1.6			A
	Conditions	$V_{IN}=12V$			
Quiescent Circuit Current	I_q	7			mA
	Conditions	$V_{IN}=12V, I_o=0A$			
Circuit Current at Output OFF	$I_q(OFF)$	400			μA
	Conditions	$V_{IN}=12V, V_{ON/OFF}=0.3V$			
CE/SS Terminal	Low Level Voltage	V_{SSL}	0.5		V
	Terminal Outflow Current at Low Voltage	I_{SSL}	50		
		Conditions	$V_{SSL}=0V$		μA

*: Pin 2 is the CE/SS pin. Soft start at power on can be performed with a capacitor connected to this pin. The output can also be turned ON/OFF with this pin. The output is stopped by setting the voltage of this pin to V_{SSL} or lower. CE/SS-pin voltage can be changed with an open-collector drive circuit of a transistor. When using both the soft-start and ON/OFF functions together, the discharge current from C_4 flows into the ON/OFF control transistor. Therefore, limit the current securely to protect the transistor if C_3 capacitance is large. The CE/SS pin is pulled up to the power supply in the IC, so applying the external voltage is prohibited.




External Dimensions


(Unit: mm)




Block Diagram



Ta-Pd Characteristics



Typical Connection Diagram



SI-8000S Series Full-Mold, Separate Excitation Step-down Switching Mode Regulator IC

Features

- Compact full-mold package (equivalent to TO220)
- Output current: 3.0A
- High efficiency: 79 to 91%
- Requires only 4 discrete components
- Internally-adjusted phase correction and output voltage
- Built-in reference oscillator (60kHz)
- Built-in overcurrent and thermal protection circuits
- Built-in soft start circuit (Output ON/OFF available)

Lineup

Part Number	SI-8033S	SI-8050S	SI-8090S	SI-8120S	SI-8150S
V _o (V)	3.3	5.0	9.0	12.0	15.0
I _o (A)	3.0				

Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V _{IN}	43*	V
Power Dissipation	P _{D1}	18(With infinite heatsink)	W
	P _{D2}	1.5(Without heatsink, stand-alone operation)	W
Junction Temperature	T _j	+125	°C
Storage Temperature	T _{stg}	-40 to +125	°C
SW Terminal Applied Reverse Voltage	V _{SW}	-1	V
Thermal Resistance(junction to case)	θ _{J-C}	5.5	°C/W

*35V for SI-8033S

Applications

- Power supplies for telecommunication equipment
- Onboard local power supplies

Recommended Operating Conditions

Parameter	Symbol	Ratings					Unit
		SI-8033S	SI-8050S	SI-8090S	SI-8120S	SI-8150S	
DC Input Voltage Range	V _{IN}	5.5 to 28	7 to 40	12 to 40	15 to 40	18 to 40	V
Output Current Range	I _o	0 to 3.0					A
Operating Junction Temperature Range	T _{top}	-30 to +125					°C

Electrical Characteristics


(T_a=25°C)

Parameter	Symbol	Ratings															Unit
		SI-8033S			SI-8050S			SI-8090S			SI-8120S			SI-8150S			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Output Voltage	SI-8000S*1	3.17	3.30	3.43	4.80	5.00	5.20	8.55	9.00	9.45	11.50	12.00	12.50	14.25	15.00	15.75	V
	SI-8000SS	3.234	3.30	3.366	4.90	5.00	5.10	8.73	9.00	9.27	-----			-----			
	Conditions	V _{IN} =15V, I _o =1.0A			V _{IN} =20V, I _o =1.0A			V _{IN} =21V, I _o =1.0A			V _{IN} =24V, I _o =1.0A			V _{IN} =25V, I _o =1.0A			
Efficiency	η	79			84			88			90			91			%
	Conditions	V _{IN} =15V, I _o =1.0A			V _{IN} =20V, I _o =1.0A			V _{IN} =21V, I _o =1.0A			V _{IN} =24V, I _o =1.0A			V _{IN} =25V, I _o =1.0A			
Oscillation Frequency	f	60			60			60			60			60			kHz
	Conditions	V _{IN} =15V, I _o =1.0A			V _{IN} =20V, I _o =1.0A			V _{IN} =21V, I _o =1.0A			V _{IN} =24V, I _o =1.0A			V _{IN} =25V, I _o =1.0A			
Line Regulation	ΔV _{OLINE}	25 80			40 100			50 120			60 130			60 130			mV
	Conditions	V _{IN} =8 to 28V, I _o =1.0A			V _{IN} =10 to 30V, I _o =1.0A			V _{IN} =15 to 30V, I _o =1.0A			V _{IN} =18 to 30V, I _o =1.0A			V _{IN} =21 to 30V, I _o =1.0A			
Load Regulation	ΔV _{OLOAD}	10 30			10 40			10 40			10 40			10 40			mV
	Conditions	V _{IN} =15V, I _o =0.5 to 1.5A			V _{IN} =20V, I _o =0.5 to 1.5A			V _{IN} =21V, I _o =0.5 to 1.5A			V _{IN} =24V, I _o =0.5 to 1.5A			V _{IN} =25V, I _o =0.5 to 1.5A			
Temperature Coefficient of Output Voltage	ΔV _o /ΔT _a	±0.5			±0.5			±1.0			±1.0			±1.0			mV/°C
Overcurrent Protection Starting Current	I _{st}	3.1			3.1			3.1			3.1			3.1			A
	Conditions	V _{IN} =15V			V _{IN} =20V			V _{IN} =21V			V _{IN} =24V			V _{IN} =25V			

*1: "S" may be printed to the right of the marking (except SI-8120S, SI-8150S)

External Dimensions

(Unit : mm)



Forming No. 1101


- a. Part Number
- b. Lot Number
- c. Logo Mark

Pin Assignment


- ① VIN
- ② SWout
- ③ GND
- ④ Vos
- ⑤ S.S

Plastic Mold Package Type
 Flammability: UL94V-0
 Product Mass: Approx. 2.3g

Block Diagram




Typical Connection Diagram



- C_{1,2} : 1000μF
- L₁ : 150μH
- D₁ : RK46(Sanken)

T_a-P_d Characteristics



$$P_D = V_o \cdot I_o \left(\frac{100}{\eta \chi} - 1 \right) - V_F \cdot I_o \left(1 - \frac{V_o}{V_{IN}} \right)$$

The efficiency depends on the input voltage and the output current. Therefore, obtain the value from the efficiency graph and substitute the percentage in the formula above.

- V_o : Output voltage
- V_{IN} : Input voltage
- I_o : Output current
- ηχ : Efficiency (%)
- V_F : Diode D₁ forward voltage
0.5V(RK46)

Thermal design for D₁ must be considered separately.

SI-8011NVS Surface-Mount, Synchronous Rectifier Step-down Switching Mode Regulator Control IC

■ Features

- Surface-mount package (TSSOP24)
- High efficiency due to synchronous rectification: 93% (at $V_{IN} = 5V$, $I_o = 1A$, $V_o = 2.5V$)
- Capable of downsize a choke-coil due to IC's high switching frequency (125kHz typ, On Time Control). (Compared with conventional Sanken devices)
- Low reference voltage (V_{ref}) of 1.1V. The output voltage is variable from 1.1V to 6V.
- High-speed response to a load
- Compatible with low ESR capacitors
- Soft start and output ON/OFF available
- Built-in overcurrent protection circuit
- PWRGD function to indicate the output voltage status
- High precision reference voltage: $1.1V \pm 1.2\%$

■ Absolute Maximum Ratings

($T_a = 25^\circ C$)

Parameter	Symbol	Ratings	Unit
Control-System DC Input Voltage	V_{CC}	7	V
DC Input Voltage	V_{IN}	25	V
Boost Block Input Voltage	V_H	30	V
EN Terminal Input Voltage	V_{EN}	V_{CC}	V
PWRGD Terminal Applied Voltage	V_{PWRGD}	7	V
Junction Temperature	T_j	+150	$^\circ C$
Storage Temperature	T_{stg}	-40 to +150	$^\circ C$

■ Applications

- Power supplies for notebook PCs and mobile devices
- Onboard local power supplies
- OA equipment
- For stabilization of the secondary-side output voltage of switching power supplies

■ Recommended Operating Conditions

Parameter	Symbol	Ratings	Unit
Control System Input Voltage Range	V_{CC}	4.5 to 5.5	V
Input Voltage Range	V_{IN}	3 to 18	V
Output Voltage Range	V_o	1.1 to 6	V
Operating Temperature Range	T_{op}	-20 to +85	$^\circ C$


■ Electrical Characteristics

($T_a = 25^\circ C$ unless otherwise specified)

Parameter	Symbol	Ratings			Unit	Conditions	
		min.	typ.	max.			
Dynamic Characteristics	Output Voltage	V_o	-1.2%	1.1	+1.2%	V	$V_{IN}=5V$, $V_{CC}=5V$, VSNS connected to V_o , $I_o=0A$
	Temperature Coefficient of Output Voltage	$\Delta V_o/\Delta T$		± 0.03		mV/ $^\circ C$	$V_{IN}=5V$, $V_{CC}=5V$, VSNS connected to V_o , $I_o=0A$, $T_a=0$ to $85^\circ C$
Circuit Current	Circuit Current (V_{CC} Terminal)	I_{op}			6	mA	$V_{CC}=5V$, EN=H, FADJ:open
	Circuit Current (V_{IN} Terminal)	I_{op}			1	mA	$V_{IN}=5V$, EN=H
	Standby Current 1 (V_{CC} Terminal)	I_{std1}			100	μA	$V_{CC}=5V$, EN=L
	Standby Current 2 (V_{IN} Terminal)	I_{std2}			50	μA	$V_{IN}=5V$, EN=L
Undervoltage Lockout	UVLO Operating Voltage 1 (V_{CC} Terminal)	V_{uvlo1}	3.7		4.4	V	$V_{IN}=5V$
	UVLO Operating Voltage 2 (V_{IN} Terminal)	V_{uvlo2}	2.5		2.9	V	$V_{CC}=5V$
On Time Control	On Time	T_{on}			2	μS	$V_{CC}=5V$, $V_{IN}=5V$, $V_o=2.5V$
	Minimum Off Time	T_{off}			1	μS	$V_{CC}=5V$
	REF Terminal Voltage	V_{ref}	1.1	1.2	1.3	V	$V_{CC}=5V$
	REF Terminal Source Current	I_{ref}			100	μA	$V_{CC}=5V$
High Side Drive	On Resistance (high side)	R_{onHH}			5.5	Ω	VH-VLIN=5V
	On Resistance (low side)	R_{onHL}			5.5	Ω	VH-VLIN=5V
Low Side Drive	On Resistance (high side)	R_{onLH}			5.5	Ω	$V_{CC}=5V$
	On Resistance (low side)	R_{onLL}			5.5	Ω	$V_{CC}=5V$
Bootstrap	Bootstrap Voltage	VH-VLIN	4.5	5	5.5	V	
Protection System	Current for Current Limit Detection	I_{lim}	90	100	110	μA	$V_{CC}=5V$, $V_{IN}=5V$
	Soft Start Terminal Current	I_{ss}		± 20		μA	$V_{CC}=5V$
	EN Low Level Voltage	V_{ceLo}	0		0.8	V	$V_{CC}=5V$
	EN High Level Voltage	V_{ceHi}	2.4		V_{CC}	V	$V_{CC}=5V$
	EN Bias Level Current	ICE			5	μA	$V_{CC}=5V$, EN=5V
	PWRGD Good Voltage (high side)	V_{sens}		1.32		V	$V_{CC}=5V$
	PWRGD Good Voltage (low side)	V_{sens}		0.88		V	$V_{CC}=5V$
	PWRGD Low Output Voltage	V_{pwrGD}			0.4	V	$V_{CC}=5V$, $I_{pwrGD}=120\mu A$
	PWRGD Terminal Current	I_{pwrGD}			120	μA	$V_{CC}=5V$, $V_{pwrGD}=0.4V$
	PWRGD Leakage Current	I_{pwrGD}			5	μA	$V_{pwrGD}=5V$


External Dimensions

(Unit : mm)




Plastic Mold Package Type
Flammability: UL94V-0
Product Mass: Approx. 1.36g

Block Diagram (Pin Assignment)



Typical Connection Diagram



MOS FET Q1, Q2

- Be sure to use logic type MOS FET as Q1 and Q2.
- If you use a normal power MOS FET type, the ON resistance may not drop to a satisfactory level due to a shortage of V_{GS}. This may deteriorate the efficiency and cause overheating.

Diode D1

- Be sure to use a Schottky-barrier diode for D1.
- If other diodes like fast recovery diodes are used, IC may be destroyed because of the reverse voltage generated by the recovery voltage or ON voltage.

Choke coil L1

- If the winding resistance of the choke coil is too high, the efficiency may drop below the rated value.
- Take care concerning heat radiation from the choke coil caused by magnetic saturation due to overload or short-circuit load.

Capacitor C1, C2

- As large ripple currents flow through C1 and C2, use high-frequency and low-impedance capacitors aiming for switching-mode-power-supply use. Especially when the impedance of C2 is high, the switching waveform may become abnormal at low temperatures. For C2, do not use a capacitor with an extremely low equivalent series resistance (ESR) such as a ceramic capacitor, which may cause an abnormal oscillation.

* To create the optimum operating conditions, place the components as close as possible to each other.

SI-8511NVS Surface-Mount, Synchronous Rectifier Step-down Switching Mode Regulator Control IC

■ Features

- Surface-mount package (TSSOP24)
- High efficiency due to synchronous rectification: 92% (at $V_{IN} = 5V$, $I_o = 1A$, $V_o = 2.5V$)
- Capable of downsize a choke-coil due to IC's high switching frequency (400kHz typ, On Time Control). (Compared with conventional Sanken devices)
- Low reference voltage (V_{ref}) of 1.1V. The output voltage is variable from 1.1V to 6V.
- High-speed response to a load
- Compatible with low ESR capacitors
- Soft start and output ON/OFF available
- Built-in overcurrent and output-overvoltage protection circuits
- PWRGD function to indicate the output voltage status
- High precision reference voltage: $1.1V \pm 1.2\%$

■ Absolute Maximum Ratings

(Ta=25°C)

Parameter	Symbol	Ratings	Unit
Control-System DC Input Voltage	V_{CC}	7	V
DC Input Voltage	V_{IN}	25	V
Boost Block Input Voltage	V_H	30	V
EN Terminal Input Voltage	V_{EN}	V_{CC}	V
PWRGD Terminal Applied Voltage	V_{PWRGD}	7	V
Junction Temperature	T_j	+150	°C
Storage Temperature	T_{stg}	-40 to +150	°C

■ Applications

- Power supplies for notebook PCs and mobile devices
- Onboard local power supplies
- OA equipment
- For stabilization of the secondary-side output voltage of switching power supplies

■ Recommended Operating Conditions

Parameter	Symbol	Ratings	Unit
Control System Input Voltage Range	V_{CC}	4.5 to 5.5	V
Input Voltage Range	V_{IN}	3 to 18	V
Output Voltage Range	V_o	1.1 to 6	V
Operating Temperature Range	T_{op}	-20 to +85	°C

■ Electrical Characteristics

(Ta=25°C unless otherwise specified)

Parameter	Symbol	Ratings			Unit	Conditions	
		min.	typ.	max.			
Dynamic Characteristics	Output Voltage	V_o	-1.2%	1.1	+1.2%	V	$V_{IN}=5V$, $V_{CC}=5V$, VSNS connected to V_o , $I_o=0A$
	Temperature Coefficient of Output Voltage	$\Delta V_o/\Delta T$		± 0.03		mV/°C	$V_{IN}=5V$, $V_{CC}=5V$, VSNS connected to V_o , $I_o=0A$, $T_a=0$ to 85°C
Circuit Current	Circuit Current (V_{CC} Terminal)	I_{op}			6	mA	$V_{CC}=5V$, EN=H, FADJ:open
	Circuit Current (V_{IN} Terminal)	I_{op}			1	mA	$V_{IN}=5V$, EN=H
	Standby Current 1 (V_{CC} Terminal)	I_{std1}			100	μA	$V_{CC}=5V$, EN=L
	Standby Current 2 (V_{IN} Terminal)	I_{std2}			50	μA	$V_{IN}=5V$, EN=L
Undervoltage Lockout	UVLO Operating Voltage 1 (V_{CC} Terminal)	V_{uvlo1}	3.7		4.45	V	$V_{IN}=5V$
	UVLO Operating Voltage 2 (V_{IN} Terminal)	V_{uvlo2}	2.5		2.9	V	$V_{CC}=5V$
On Time Control	On Time	T_{on}		1.27		μS	$V_{CC}=5V$, $V_{IN}=5V$, $V_o=2.5V$
	Minimum Off Time	T_{off}		0.7		μS	$V_{CC}=5V$
	REF Terminal Voltage	V_{ref}	1.1	1.2	1.3	V	$V_{CC}=5V$
	REF Terminal Source Current	I_{ref}			100	μA	$V_{CC}=5V$
High Side Drive	On Resistance (high side)	R_{onHH}		5.5		Ω	VH-VLIN=5V
	On Resistance (low side)	R_{onHL}		5.5		Ω	VH-VLIN=5V
Low Side Drive	On Resistance (high side)	R_{onLH}		5.5		Ω	$V_{CC}=5V$
	On Resistance (low side)	R_{onLL}		5.5		Ω	$V_{CC}=5V$
Bootstrap	Bootstrap Voltage	VH-VLIN	4.5	5	5.5	V	
Protection System	Current for Current Limit Detection	I_{lim}	90	100	110	μA	$V_{CC}=5V$, $V_{IN}=5V$
	Soft Start Terminal Current	I_{ss}		± 20		μA	$V_{CC}=5V$
	EN Low Level Voltage	V_{cshl}	0		0.8	V	$V_{CC}=5V$
	EN High Level Voltage	V_{cshi}	2.4		V_{CC}	V	$V_{CC}=5V$
	EN Bias Level Current	ICE			5	μA	$V_{CC}=5V$, EN=5V
	PWRGD Good Voltage (high side)	V_{sens}		1.32		V	$V_{CC}=5V$
	PWRGD Good Voltage (low side)	V_{sens}		0.88		V	$V_{CC}=5V$
	PWRGD Low Output Voltage	V_{pwrpd}			0.4	V	$V_{CC}=5V$, $I_{pwrpd}=120\mu A$
	PWRGD Terminal Current	I_{pwrpd}			120	μA	$V_{CC}=5V$, $V_{pwrpd}=0.4V$
	PWRGD Leakage Current	I_{pwrpd}			5	μA	$V_{pwrpd}=5V$

STA810M Series Separate Excitation Switching Mode Regulator IC with Flywheel Diode

Features

- Output current: 1.5A
- High efficiency: TYP83% (STA811M)
- Built-in flywheel diode (schottky-barrier diode)
- Requires only 3 discrete components: output coil, input and output capacitors
- Phase correction and output voltage adjustment performed internally
- Built-in reference oscillator (125kHz)
- Built-in foldback-overcurrent and thermal protection circuits
- Built-in ON/OFF circuit (soft start available)

Applications

- Power supplies for telecommunication equipment
- Onboard local power supplies
- OA equipment
- For stabilization of the secondary-side output voltage of switching power supplies

Lineup

Part Number	Output Voltage (V)
STA811M	6.5

Output voltage: 2.5V, 3.3V, 5V, 9V, 12V and adjustable types are projected.

Absolute Maximum Ratings*1

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V _{IN}	43	V
Output Current	I _O	1.5	A
Power Dissipation*2	P _{D1}	18.2 (With infinite heatsink)	W
	P _{D2}	2.7 (Without heatsink, stand-alone operation)	W
Junction Temperature	T _J	+125	°C
Storage Temperature	T _{Stg}	-40 to +125	°C
Thermal Resistance (junction to case)	θ _{J-C}	5.5	°C/W
Thermal Resistance (junction to ambient air)	θ _{J-A}	37	°C/W

*1: Absolute maximum ratings show the destructive limit. No parameter should exceed the ratings in transient or normal operations.

*2: Limited by thermal protection.

Recommended Operating Conditions*1

Parameter	Symbol	Ratings		Unit	Conditions
		STA811M			
		min.	max.		
DC Input Voltage Range	V _{IN1}	8.5	9.5	V	I _O =0 to 1A
	V _{IN2}	9.5	40	V	I _O =0 to 1.5A
Output Current Range*2	I _O	0	1.5	A	V _{IN} ≥ 9.5V
Operating Junction Temperature Range	T _{JOP}	-30	+125	°C	
Operating Temperature Range*2	T _{OP}	-30	+80	°C	

*1: Recommended operating conditions show operating conditions required for normal circuit function described in the electrical characteristics.

These conditions must be followed in actual use.

*2: Limited by T_a-P_D characteristics.

Electrical Characteristics


(T_a=25°C)

Parameter	Symbol	Ratings			Unit
		STA811M			
		min.	typ.	max.	
Output Voltage	V _O	6.37	6.5	6.63	V
	Conditions	V _{IN} =28V, I _O =1A			
Efficiency*1	η		83		%
	Conditions	V _{IN} =28V, I _O =1A			
Oscillation Frequency	f _O		125		kHz
	Conditions	V _{IN} =28V, I _O =1A			
Line Regulation	V _{Line}		40	100	mV
	Conditions	V _{IN} =10 to 30V, I _O =1A			
Load Regulation	V _{Load}		10	40	mV
	Conditions	V _{IN} =28V, I _O =0.2 to 1A			
Temperature Coefficient of Output Voltage	ΔV _O /ΔT		±0.5		mV/°C
Overcurrent Protection Starting Current	I _S	1.6			A
	Conditions	V _{IN} =28V			
ON/OFF Terminal*2	Low Level Voltage	V _{SSL}		0.5	V
	Outflow Current at Low Voltage	I _{SSL}		100	
Quiescent Circuit Current 1	I _q		7		mA
	Conditions	V _{IN} =28V, I _O =0A			
Quiescent Circuit Current 2	I _{q(OFF)}			200	μA
	Conditions	V _{IN} =28V, V _{ON/OFF} =0.3A			

*1: Efficiency is calculated from the following formula.


$$\eta (\%) = \frac{V_O \cdot I_O}{V_{IN} \cdot I_{IN}} \times 100$$

*2: Pin 7 is the ON/OFF pin. Soft start at power on can be performed by connecting a capacitor to this pin. The output can also be turned ON/OFF with this pin. The output is stopped by setting the voltage of this pin to V_{SSL} or lower. ON/OFF-pin voltage can be changed with an open-collector drive circuit of a transistor. When using both the soft-start and ON/OFF functions together, the discharge current from C₃ flows into the ON/OFF control transistor. Therefore, limit the current securely to protect the transistor if C₃ capacitance is large. The ON/OFF pin is pulled up to the power supply in the IC, so applying the external voltage is prohibited. If this pin is not used, leave it open.




External Dimensions


(Unit : mm)




Block Diagram



Typical Connection Diagram



Thermal Derating



STA820M Series Separate Excitation Switching Mode Regulator IC with Flywheel Diode

Features

- Output current: 3A
- High efficiency: TYP 83% (STA821M)
- Built-in flywheel diode (Schottky-barrier diode)
- Requires only 3 discrete components: output coil, input and output capacitors
- Phase correction and output voltage adjustment performed internally
- Built-in reference oscillator (110kHz)
- Built-in foldback-overcurrent and thermal protection circuits
- Built-in ON/OFF circuit (soft start available)

Applications

- Power supplies for telecommunication equipment
- On-board local power supplies
- OA equipment
- For stabilization of the secondary-side output voltage of switching power supplies

Lineup

Part Number	Output Voltage (V)
STA821M	5

Output voltage: 3.3V, 9V, 12V; adjustable types currently being planned

Absolute Maximum Ratings*1

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V _{IN}	31	V
Output Current	I _o	3	A
Power Dissipation*2	P _{D1}	18.2 (With infinite heatsink)	W
	P _{D2}	2.7 (Without heatsink, stand-alone operation)	W
Junction Temperature	T _j	+125	°C
Storage Temperature	T _{stg}	-40 to +125	°C
Thermal Resistance (Junction to Case)	θ _{j-c}	5.5	°C/W
Thermal Resistance (Junction to Ambient Air)	θ _{j-a}	37	°C/W

*1: The absolute maximum ratings show the destructive limit. No parameter should exceed the ratings in transient or normal operations.

*2: Limited by thermal protection.

Recommended Operating Conditions*1

Parameter	Symbol	Ratings		Unit
		STA821M		
		min.	max.	
DC Input Voltage Range	V _{IN}	7	30	V
Output Current Range*2	I _o	0	3	A
Operating Junction Temperature Range	T _{top}	-30	+125	°C
Ambient Temperature Range*2	T _{op}	-30	+80	°C

*1: The recommended operating conditions show the operating conditions required for the normal circuit function described in the electrical characteristics. These conditions must be followed in actual use.

*2: Limited by T_a-P_D characteristics.

Electrical Characteristics


(T_a=25°C)

Parameter	Symbol	Ratings			Unit
		STA821M			
		min.	typ.	max.	
Output Voltage	V _o	4.8	5.0	5.2	V
	Conditions	V _{IN} =20V, I _o =1A			
Efficiency*1	η		83		%
	Conditions	V _{IN} =20V, I _o =1A			
Oscillation Frequency	f _o		110		kHz
	Conditions	V _{IN} =20V, I _o =1A			
Line Regulation	V _{Line}		40	100	mV
	Conditions	V _{IN} =10 to 30V, I _o =1A			
Load Regulation	V _{Load}		10	40	mV
	Conditions	V _{IN} =20V, I _o =0.5 to 1.5A			
Temperature Coefficient of Output Voltage	ΔV _o /ΔT		±0.5		mV/°C
Overcurrent Protection Starting Current	I _s	3.1			A
	Conditions	V _{IN} =20V			
ON/OFF Terminal*2	Low Level Voltage	V _{SSL}	0.2		V
	Outflow Current at Low Voltage	I _{SSL}	25	35	
		Conditions	V _{SSL} =0.2V		
Quiescent Circuit Current	I _q		4		μA
	Conditions	V _{IN} =20V, I _o =0A			

*1: Efficiency is calculated from the following formula.


$$\eta(\%) = \frac{V_o \cdot I_o}{V_{IN} \cdot I_{IN}} \times 100$$

*2: Pin 7 is the ON/OFF pin. Soft start at power on can be performed by connecting a capacitor to this pin. The output can also be turned ON/OFF with this pin. The output is stopped by setting the voltage of this pin to V_{SSL} or lower. ON/OFF-pin voltage can be changed with an open-collector drive circuit of a transistor. When using both the soft-start and ON/OFF functions together, the discharge current from C₃ flows into the ON/OFF control transistor. Therefore, limit the current securely to protect the transistor if C₃ capacitance is large. The ON/OFF pin is pulled up to the power supply in the IC, so applying the external voltage is prohibited. If this pin is not used, leave it open.




External Dimensions


(Unit : mm)




Block Diagram



Typical Connection Diagram



Ta-Pd Characteristics



SI-8400L/8500L Series Separate Excitation Switching Mode Regulator IC with Coil

■Features

- Switching IC/Coil combined type
- Requires only 2 discrete components
- Low switching noise
- No heatsink required
- Built-in overcurrent and thermal protection circuits
- Built-in soft start circuit (Output ON/OFF available)...SI-8500L Series

■Applications

- Telephone power supplies
- Onboard local power supplies

■Lineup

Part Number	SI-8401L	SI-8402L	SI-8403L	SI-8501L	SI-8502L	SI-8503L	SI-8504L
V _o (V)	5.0	12.0	3.3	5.0	12.0	3.3	9.0
I _o (A)	0.5	0.4	0.5	1.0			

■Absolute Maximum Ratings

Parameter	Symbol	Ratings		Unit
		SI-8400L	SI-8500L	
DC Input Voltage	V _{IN}	35		V
Power Dissipation	P _D	1.25	3	W
Junction Temperature	T _j	+100		°C
Storage Temperature	T _{stg}	-25 to +85		°C

■Recommended Operating Conditions

Parameter	Symbol	Ratings			Unit
		SI-8401L	SI-8402L	SI-8403L	
DC Input Voltage Range	V _{IN}	7 to 33	15 to 33	5.3 to 33	V
Output Current Range	I _o	0 to 0.5	0 to 0.4	0 to 0.5	A
Operating Temperature Range	T _{op}	-20 to +85			°C

Parameter	Symbol	Ratings				Unit
		SI-8501L	SI-8502L	SI-8503L	SI-8504L	
DC Input Voltage Range	V _{IN}	7 to 33	15 to 33	5.3 to 33	12 to 33	V
Output Current Range	I _o	0 to 1.0				A
Operating Temperature Range	T _{op}	-20 to +85				°C

■Electrical Characteristics

(T_a=25°C)


Parameter	Symbol	Ratings									Unit
		SI-8401L			SI-8402L			SI-8403L			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Output Voltage	V _o	4.80	5.00	5.20	11.40	12.00	12.60	3.17	3.30	3.43	V
	Conditions	V _{IN} =20V, I _o =0.3A			V _{IN} =24V, I _o =0.3A			V _{IN} =15V, I _o =0.3A			
Efficiency	η	80			88			75			%
	Conditions	V _{IN} =20V, I _o =0.3A			V _{IN} =24V, I _o =0.3A			V _{IN} =15V, I _o =0.3A			
Oscillation Frequency	f	60			60			60			kHz
	Conditions	V _{IN} =20V, I _o =0.3A			V _{IN} =24V, I _o =0.3A			V _{IN} =15V, I _o =0.3A			
Line Regulation	ΔV _{OLINE}	80	100		100	130		60	80		mV
	Conditions	V _{IN} =10 to 30V, I _o =0.3A			V _{IN} =18 to 30V, I _o =0.3A			V _{IN} =8 to 30V, I _o =0.3A			
Load Regulation	ΔV _{LOAD}	30	40		70	95		20	30		mV
	Conditions	V _{IN} =20V, I _o =0.1 to 0.4A			V _{IN} =24V, I _o =0.1 to 0.4A			V _{IN} =15V, I _o =0.1 to 0.4A			
Temperature Coefficient of Output Voltage	ΔV _o /ΔT _a	±0.5			±1.5			±0.5			mV/°C
Switching Ripple Voltage (C ₂ =470μF)	ΔV _r	20			35	70		15			mV _{P-P}
	Conditions	V _{IN} =20V, I _o =0.3A			V _{IN} =24V, I _o =0.3A			V _{IN} =15V, I _o =0.3A			
Overcurrent Protection Starting Current	I _{s1}	0.55			0.45			0.55			A
	Conditions	V _{IN} =10V			V _{IN} =18V			V _{IN} =8V			

(T_a=25°C)


Parameter	Symbol	Ratings												Unit
		SI-8501L			SI-8502L			SI-8503L			SI-8504L			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Output Voltage	V _o	4.80	5.00	5.20	11.40	12.00	12.60	3.17	3.30	3.43	8.55	9.00	9.45	V
	Conditions	V _{IN} =20V, I _o =0.5A			V _{IN} =24V, I _o =0.5A			V _{IN} =15V, I _o =0.5A			V _{IN} =21V, I _o =0.5A			
Efficiency	η	83			89			79			87			%
	Conditions	V _{IN} =20V, I _o =0.5A			V _{IN} =24V, I _o =0.5A			V _{IN} =15V, I _o =0.5A			V _{IN} =21V, I _o =0.5A			
Oscillation Frequency	f	60			60			60			60			kHz
	Conditions	V _{IN} =20V, I _o =0.5A			V _{IN} =24V, I _o =0.5A			V _{IN} =15V, I _o =0.5A			V _{IN} =21V, I _o =0.5A			
Line Regulation	ΔV _{OLINE}	70	130		70	130		50	80		70	130		mV
	Conditions	V _{IN} =10 to 30V, I _o =0.5A			V _{IN} =18 to 30V, I _o =0.5A			V _{IN} =8 to 30V, I _o =0.5A			V _{IN} =15 to 30V, I _o =0.5A			
Load Regulation	ΔV _{LOAD}	30	30	55	30	30	55	20	20	45	30	30	55	mV
	Conditions	V _{IN} =20V, I _o =0.2 to 0.8A			V _{IN} =24V, I _o =0.2 to 0.8A			V _{IN} =15V, I _o =0.2 to 0.8A			V _{IN} =21V, I _o =0.2 to 0.8A			
Temperature Coefficient of Output Voltage	ΔV _o /ΔT _a	±0.5			±1.5			±0.5			±1.0			mV/°C
Switching Ripple Voltage (C ₂ =470μF)	ΔV _r	45			30			15			25			mV _{P-P}
	Conditions	V _{IN} =20V, I _o =0.5A			V _{IN} =24V, I _o =0.5A			V _{IN} =15V, I _o =0.5A			V _{IN} =21V, I _o =0.5A			
Overcurrent Protection Starting Current	I _{s1}	1.1			1.1			1.1			1.1			A
	Conditions	V _{IN} =18V			V _{IN} =24V			V _{IN} =12V			V _{IN} =21V			

External Dimensions


(Unit : mm)




Block Diagram



Typical Connection Diagram



Ta-Pd Characteristics



Application Note

■ Heat Dissipation and Reliability

The reliability of an IC is highly dependent on its operating temperature. Please be sure to apply silicone grease to the IC and to mount it to the heatsink with a proper mounting torque.

Heatsink design should pay particular attention to ensuring sufficient heat dissipation capacity.

In addition, please take into account the air convection in operation.

The reliability of discrete components such as capacitors and coils is closely related to temperature. A high operating temperature may reduce the service life. Exceeding the allowable temperature may burn the coils or damage capacitors. It is important to make sure that the temperature of output smoothing coils and input/output capacitors do not exceed their allowable levels during operation. With an adequate derating for the coils, minimize heat emission as far as possible. (For discrete components, refer to the individual user manuals.)

■ Thermal Design

The maximum junction temperature $T_{j(max)}$ given in the Absolute Maximum Ratings is specific to each product type and must be strictly observed.

Thus, thermal design must consider the maximum power dissipation $P_{D(max)}$, which varies by the conditions of use, and the maximum ambient temperature $T_{a(max)}$.

To simplify the thermal design, T_a - P_D characteristic graphs are provided herein. Please observe the following steps for heatsink design:

1. Obtain the maximum ambient temperature $T_{a(max)}$.
2. Obtain the maximum power dissipation $P_{D(max)}$.
3. Look for the intersection point on the T_a - P_D characteristic graph and determine the size of the heatsink.

Although the heatsink size is now obtained, in actual applications, 10-to-20% derating factor is generally introduced. Moreover, the heat dissipation capacity of a heatsink highly depends on how it is mounted. Thus, it is recommended to measure the heatsink or case temperature in the actual operating environment.

Please refer to the T_a - P_D characteristic graphs for respective product types.

■ Mounting Torque

STA800M Series (when mounted by using a spring)

0.588 to 0.784 [N•m] (6.0 to 8.0 [kgf•cm])

SLA3000M Series

0.588 to 0.784 [N•m] (6.0 to 8.0 [kgf•cm])

■ Recommended Silicone Grease

- Shin-Etsu Chemical Co., Ltd.: G746
- GE Toshiba Silicones Co., Ltd.: YG-6260
- Dow Corning Toray Silicone Co., Ltd.: SC102

Please select proper silicone grease carefully since the oil in some grease products may penetrate the device and result in an extremely short device life.

STA801M/802M 2-Output Separate Excitation Switching Mode Regulator IC

■Features

- 2 regulators combined in 1 package
- Compact inline package
- Output current (0.5A × 2 outputs)
- Output voltage of Ch2 selectable from 4 levels
- Built-in flywheel diode (Schottky barrier diode)
- Requires only 7 discrete components (2 outputs)
- Internally-adjusted phase corrections and output voltages
- Built-in reference oscillator (125kHz) - Enables to downsize a choke-coil due to IC's high oscillating frequency. (Compared with conventional Sanken devices)
- Built-in overcurrent and thermal protection circuits
- Built-in soft start circuits (Output ON/OFF available)

■Lineup

Part Number	Output Voltage (V)	
	Ch1	Ch2(Select one output)
STA801M	5	9.0 / 11.5 / 12.1 / 15.5
STA802M	9	9.1 / 11.7 / 12.1 / 15.7

■Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V _{IN}	43	V
Power Dissipation	P _{D1}	6.7(With infinite heatsink)	W
	P _{D2}	1.6(Without heatsink, stand-alone operation)	W
Junction Temperature	T _J	+125	°C
Storage Temperature	T _{stg}	-40 to +125	°C

■Applications

- For BS and CS antenna power supplies
- For stabilization of the secondary stage of switching power supplies
- Electronic equipment

■Recommended Operating Conditions

Parameter	Symbol	Ratings		Unit
		min.	max.	
DC Input Voltage Range	V _{IN}	Ch2 V _{Omax} +2	40	V
Output Current Range per Channel	I _O	0	0.5	A
Operating Temperature Range	T _{OP}	-20	+125	°C

■Electrical Characteristics

(T_a=25°C)


	Parameter	Symbol	Ratings						Unit
			STA801M			STA802M			
			min.	typ.	max.	min.	typ.	max.	
Ch1	Output voltage 1	V _{O1}	4.80	5.00	5.20	8.64	9.00	9.36	V
		Conditions	V _{IN} =20V, I _O =0.3A			V _{IN} =20V, I _O =0.3A			
	Efficiency *	η ₁		80			86		%
		Conditions	V _{IN} =20V, I _O =0.3A			V _{IN} =20V, I _O =0.3A			
	Temperature Coefficient of Output Voltage	ΔV _O /ΔT _{a1}		±0.5			±1.0		mV/°C
	Line Regulation	ΔV _O /LINE1		30	90		35	110	mV
Conditions		V _{IN} =10 to 30V, I _O =0.3A			V _{IN} =14 to 30V, I _O =0.3A				
Load Regulation	ΔV _O /LOAD1		10	40		20	80	mV	
	Conditions	V _{IN} =20V, I _O =0.1 to 0.4A			V _{IN} =20V, I _O =0.1 to 0.4A				
Ch2 (Select one output)	Output voltage 2-1	V _{O2-1}	8.64	9.00	9.36	8.74	9.10	9.46	V
		Conditions	V _{IN} =20V, I _O =0.3A			V _{IN} =20V, I _O =0.3A			
	Output voltage 2-2	V _{O2-2}	11.04	11.50	11.96	11.24	11.70	12.16	V
		Conditions	V _{IN} =20V, I _O =0.3A			V _{IN} =20V, I _O =0.3A			
	Output voltage 2-3	V _{O2-3}	11.62	12.10	12.58	11.62	12.10	12.58	V
		Conditions	V _{IN} =20V, I _O =0.3A			V _{IN} =20V, I _O =0.3A			
	Output voltage 2-4	V _{O2-4}	14.88	15.50	16.12	15.08	15.70	16.32	V
		Conditions	V _{IN} =20V, I _O =0.3A			V _{IN} =20V, I _O =0.3A			
	Vo2-4	Efficiency*	η		89			89	%
			Conditions	V _{IN} =20V, I _O =0.3A			V _{IN} =20V, I _O =0.3A		
		Temperature Coefficient of Output Voltage	ΔV _O /ΔT _a		±2.0			±2.0	mV/°C
		Line Regulation	ΔV _O /LINE		40	130		40	130
	Conditions		V _{IN} =20 to 30V, I _O =0.3A			V _{IN} =20 to 30V, I _O =0.3A			
	Load Regulation	ΔV _O /LOAD		30	120		30	120	mV
Conditions		V _{IN} =20V, I _O =0.1 to 0.4A			V _{IN} =20V, I _O =0.1 to 0.4A				
Common	No-load Circuit Current	I _{CC}		15			15	mA	
	Oscillation Frequency	f		125			125	kHz	
	Overcurrent Protection Starting Current	I _{S1}	0.51	0.7		0.51	0.7	A	

* Efficiency indicates the value when only one channel is active. The value can be calculated as shown below. 7.5mA is deducted for the no-load circuit current of $\frac{I_{CC}}{2}$ at unused output.

$$\eta = \frac{V_O \cdot I_O}{V_{IN} \cdot (I_{IN} - 0.0075)} \times 100(\%)$$

External Dimensions

(Unit : mm)




- a. Part Number
- b. Lot Number


Pin Assignment

- | | |
|------------|----------------------------|
| ① VO2 Cont | ⑧ SS2 |
| ② VOS1 | ⑨ VOS2-2 |
| ③ SS1 | ⑩ VOS2-1 |
| ④ SWOUT1 | |
| ⑤ GND | Plastic Mold Package Type |
| ⑥ VIN | Flammability: UL94V-0 |
| ⑦ SWOUT2 | Product Mass: Approx. 2.5g |

Block Diagram




Typical Connection Diagram



For how to connect VOS2-1 and VOS2-2 of Channel 2, refer to the output selection method on the Sanken web site.

Ta-Pd Characteristics



SDI02 2-Output, Low Dropout Voltage Linear Regulator IC for USB

■Features

- Two 5V/0.5A output regulators in one package
- Surface-mount 16 pin package
- Low dropout voltage: $V_{DIF} \leq 0.5V$ (at $I_o = 0.5A$)
- Independent Output ON/OFF control terminals compatible with LS-TTL (Active High)
- Independent built in overcurrent and thermal protection circuits
- Open collector flag-output terminals built in to output OCP operation to each output terminal (Active Low)
- Built-in anti-malfunction delay circuit: Delay time can be set with an external capacitor

■Applications

- USB power supplies
- Electronic equipment

■Recommended Operating Conditions

Parameter	Symbol	Ratings	Unit
DC Input Voltage Range	V_{IN}	5.5*1 to 8.0	V
Output Current Range	I_o	0 to +0.5	A
Operating Ambient Temperature	T_{aop}	-10 to +85	°C
Operating Junction Temperature	T_{jop}	-10 to +100	°C

*1: $V_{IN(min)}$ must be no less than the sum of output voltage and dropout voltage.

■Electrical Characteristics

Parameter	Symbol	Ratings			Unit	
		min.	typ.	max.		
Output Voltage	V_o	4.85	5.00	5.15	V	
	Conditions	$V_{IN}=7V, I_o=0.1A$				
Dropout Voltage	V_{DIF}			0.5	V	
	Conditions	$I_o \leq 0.5A$				
Line Regulation	ΔV_{OLINE}			30	mV	
	Conditions	$V_{IN}=6$ to $15V, I_o=0.1A$				
Load Regulation	ΔV_{OLOAD}			50	mV	
	Conditions	$V_{IN}=7V, I_o=0$ to $0.5A$				
Temperature Coefficient of Output Voltage	$\Delta V_o/\Delta T_a$		± 0.5		mV/°C	
	Conditions	$V_{IN}=7V, I_o=5mA, T_j=-10$ to $100^\circ C$				
Quiescent Circuit Current	I_q			12*1	mA	
	Conditions	$V_{IN}=7V, I_o=0A$				
Quiescent Circuit Current (Output OFF)	$I_q(OFF)$			0.25 *1	mA	
	Conditions	$V_{IN}=7V, V_c1$ and $2=0V$				
Overcurrent Protection Starting Current*1	I_{S1}	0.75		0.96	A	
	Conditions	$V_{IN}=7V$				
Vc Terminal*3	Control Voltage (Output ON)	2.0			V	
	Control Voltage (Output OFF)			0.7		
	Control Current (Output ON)			50		
	Conditions	$V_c=2.7V$				
Control Current (Output OFF)	I_c, IL			-100	μA	
	Conditions	$V_c=0V$				
OCP Detection Voltage	V_{oth}	3.7	4.0	4.3	V	
DLY Threshold Voltage	V_{DLYth}	2.1	2.3	2.5	V	
DLY Terminal Outflow Current	I_{DLY}	35	50	65	μA	
FLG Output Voltage	Before OCP Detection	V_{FLGh}	$V_{IN}-0.4$		V	
		Conditions	With R_{FLG} connected between FLG and V_{IN} pins			
	After OCP Detection	V_{FLGi}				0.5
		Conditions	$I_{FLG}=1mA$			
FLG Reset Time *4	t_{Reset}		1.2		μS	

*1: Total of two circuits

*2: I_{S1} is specified at the 5% drop point of output voltage V_o on the condition that $V_{IN}=7V, I_o=0.1A$.

*3: Output is ON even when output control terminal V_c is open. Each input level is equivalent to LS-TTL.

Therefore, the device can be driven directly by LS-TTLs.

*4: Refer to timing chart on p.102

■Absolute Maximum Ratings

($T_a=25^\circ C$)

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V_{IN}	18	V
Output Control Terminal Voltage	V_c	V_{IN}	V
DC Output Current	I_o	0.5	A
Power Dissipation	P_D	3.1*1	W
Junction Temperature	T_j	-30 to +125	°C
Operating Ambient Temperature	T_{OP}	-30 to +100	°C
Storage Temperature	T_{Stg}	-30 to +125	°C
Thermal Resistance (junction to ambient air)	$\theta_{j-a 1}$	42*2	°C/W
	$\theta_{j-a 2}$	32*1	°C/W
	$\theta_{j-1 1}$	11*3	°C/W
Thermal Resistance (junction to lead)	$\theta_{j-1 1}$	14*4	°C/W


*1: With simultaneous operation of both two channels when mounted on glass-epoxy board 56.5mm x 56.5mm (copper laminate area 50%).

*2: With operation of one channel when mounted on glass-epoxy board 56.5mm x 56.5mm (copper laminate area 50%).

*3: Junction - to - pin 14 (CH1)

*4: Junction - to - pin 10 (CH2)

External Dimensions




- a. Part Number
b. Lot Number

Pin Assignment


① FLG1	⑨ GND2
② DLY1	⑩ GND2
③ Vo1	⑪ Vc2
④ VIN1	⑫ Vc2
⑤ FLG2	⑬ GND1
⑥ DLY2	⑭ GND1
⑦ Vo2	⑮ Vc1
⑧ VIN2	⑯ Vc1

Plastic Mold Package Type
Flammability: UL94V-0
Product Mass: Approx. 1.05g

Block Diagram




Typical Connection Diagram



- *1 C_{IN} : Input capacitor (Approx. $47\mu F$)
This capacitor is required if the input line contains inductance or the wiring is long.
- *2 C_o : Output capacitor (47 to $220\mu F$)
Use a capacitor of $100\mu F$ or higher or a tantalum capacitor at low temperatures ($-10^{\circ}C$ or lower).
- *3 C_d : Delay time setting capacitor ($0.1\mu F$ or higher)
 C_d determines the delay time (t_{DLY}) from when a low V_o level due to OCP operation is detected until a flag signal is output.
It prevents a rush current from causing malfunction at start-up.
Approximate calculation: $t_{DLY} \approx (C_d \times V_{DLYth}) / I_{DLY} [\text{sec}]$
Especially when the start-up requires some time for such as soft-start on V_{IN} or large C_{IN} capacitance, be sure to set t_{DLY} long enough for the output voltage to rise sufficiently.
Be sure to connect C_d and do not short-circuit the C_d in the application.

Timing chart




With R_{FLG} connected between FLG and V_{IN} pins

FLG output is latched after the time t_{DLY} has elapsed (the time set by DLY) after OCP is detected. The latch can be reset by making V_c or V_{IN} low. Allow a time lag of $C_d \times 600$ [sec] or more between setting and restarting.

- *4 $D1, 2$: Reverse biasing protection diode.
This diode is required for protection against reverse biasing of the input and output.
- *5 R_{FLG} : Set the value so as to limit the inflow current into the FLG terminal to 1mA or lower.

Ta-Pd Characteristics



SPI-8001TW/SPI-8002TW 2-Output, Step-down Switching Mode Regulator IC

■ Features

- 2 regulators combined in one package
- Output current: 1.5A × 2 (HSOP 16 Pin Surface mount package)
- High efficiency: TYP80% (SPI-8001TW), TYP78% (SPI-8002TW)
- Variable output voltage: 1.0 to 16V (SPI-8001TW), 1.0 to 24V (SPI-8002TW)
- Built-in reference oscillator (250kHz): Enables to downsize a choke-coil
- Low circuit current consumption: $\leq 1\mu\text{A}$ (at output OFF)
- High accuracy reference voltage: $\pm 1\%$
- Built-in foldback-overcurrent and thermal protection circuits
- Built-in ON/OFF circuit (soft start available) – per output

■ Applications

- Onboard local power supplies
- OA equipment
- For stabilization of the secondary-side output voltage of switching power supplies

■ Absolute Maximum Ratings*1

Parameter	Symbol	Ratings		Unit
		SPI-8001TW	SPI-8002TW	
Input Voltage	V_{IN}	21	40	V
	V_{CC}	21	40	
	$V_{C/E}$	21	40	
Power Dissipation*2, *3	P_D	3.0		W
Junction Temperature	T_J	+135		°C
Storage Temperature	T_{stg}	-40 to +135		°C
Thermal Resistance (junction to case)*2	θ_{j-c}	9.0		°C/W
Thermal Resistance (junction to ambient air)*2	θ_{j-a}	35.8		°C/W

*1: Absolute maximum ratings show the destructive limit. No parameter should exceed the ratings in transient or normal operations.

*2: When mounted on glass-epoxy board 70cm² (copper laminate area 30.8cm²).

*3: Limited by thermal protection.

■ Recommended Operating Conditions*1

Parameter	Symbol	Ratings				Unit
		SPI-8001TW		SPI-8002TW		
		Min	Max	Min	Max	
Input Voltage Range	V_{IN}	V_{O+3}	20	V_{O+3}	38	V
	V_{CC}	4.5	20	4.5	38	V
	$V_{C/E}$		20		38	V
Output Voltage Range	V_O	1	16	1	24	V
Output Current Range	I_O		1.5		1.5	A
Operating Junction Temperature Range	T_{jop}	-30	+135	-30	+135	°C
Operating Temperature Range	T_{op}	-30	+135	-30	+135	°C

*1: Recommended operating conditions show the operating conditions required for the normal circuit function described in the electrical characteristics. These conditions must be followed in actual use.

Electrical Characteristics*1

(Ta=25°C)

Parameter	Symbol	Ratings						Unit	
		SPI-8001TW			SPI-8002TW				
		min.	typ.	max.	min.	typ.	max.		
Reference Voltage	V _{REF}	0.996	1.006	1.016	0.996	1.006	1.016	V	
	Conditions	V _{IN} =10V, V _O =1V, I _O =0.1A							
Temperature Coefficient of Reference Voltage	ΔV _{REF} /ΔT		±0.1			±0.1		mV/°C	
	Conditions	V _{IN} =10V, V _O =1V, I _O =0.1A, T _a =-30 to +135°C							
Efficiency 1 ²	Eff1		80			78		%	
	Conditions	V _{IN} =V _{CC} =15V, V _O =5V, I _O =0.5A, I _{IN} : including I _{CC}							
Efficiency 2 ²	Eff2		83			81		%	
	Conditions	V _{IN} =15V, V _O =5V, I _O =0.5A, V _{CC} =5V, I _{IN} : excluding I _{CC}							
Oscillation Frequency	f _{osc}		250		215	250	285	kHz	
	Conditions	V _{IN} =V _{CC} =15V, V _O =5V, I _O =0.5A							
Line Regulation	V _{Line}		30	60		30	60	mV	
	Conditions	V _{IN} =V _{CC} =10 to 20V, V _O =5V, I _O =1A							
Load Regulation	V _{Load}		10	40		10	40	mV	
	Conditions	V _{IN} =V _{CC} =15V, V _O =5V, I _O =0.2 to 1.5A							
Overcurrent Protection Starting Current	I _S	1.6			1.6			A	
	Conditions	V _{IN} =V _{CC} =15V							
Quiescent Circuit Current 1	I _{IN}		4			4		mA	
	Conditions	V _{IN} =15V, V _{CC} =5V, I _O =0V, V _O ≤12V							
Quiescent Circuit Current 2	I _{CC}		8.5			8.5		mA	
	Conditions	V _{CC} =15V, I _O =0A							
Quiescent Circuit Current 3	I _{IN (off)}			1			1	μA	
	Conditions	V _{IN} =15V, V _{CE} =0V or Open							
Quiescent Circuit Current 4	I _{CC (off)}			1			1	μA	
	Conditions	V _{CC} =15V, V _{CE} =0V or Open							
C/E Terminal	High Level Voltage	V _{CEH}	2		2			V	
		Conditions	V _{IN} =V _{CC} =15V						
	Low Level Voltage	V _{CEL}			0.8			0.8	V
		Conditions	V _{IN} =V _{CC} =15V						
Inflow Current at High	I _{CEH}		95			95		μA	
	Conditions	V _{CE} =20V							
SS Terminal ³	Low Level Voltage	V _{SSL}			0.5		0.5	V	
		Conditions	V _{IN} =V _{CC} =15V						
	Inflow Current at Low	I _{SSL}		60	80		60	80	μA
		Conditions	V _{SSL} =0V, V _{IN} =V _{CC} =15V						

*1: Electrical characteristics show the characteristic ratings guaranteed when operating the IC under the measurement conditions described in the above table.

*2: Efficiency is calculated from the following formula.


$$\eta (\%) = \frac{V_O \cdot I_O}{V_{IN} \cdot I_{IN}} \times 100$$

*3: Pin 6 and pin 11 are the SS pins. Soft start at power on can be performed with capacitors connected to these pins. The outputs can also be turned ON/OFF with these pins. The outputs are stopped by setting the voltages of these pins to V_{SSL} or lower. SS-pin voltages can be changed with open-collector drive circuits of transistors.


When using both the soft-start and ON/OFF functions together, the discharge currents from C₄ and C₅ flow into the ON/OFF control transistors respectively. Therefore, limit the currents securely to protect the transistors if C₄ and C₅ capacitances are large. The SS pins are pulled up to the power supply in the IC, so applying the external voltages are prohibited.

External Dimensions


(Unit : mm)



Block Diagram



■Typical Connection Diagram



- C1 : 220 μF/50V
- C2, C3 : 470 μF/25V
- C4, C5 : 1 μF
- C6, C7, C8 : 0.1 μF
- R5, R6 : 1kΩ
- L1, L2 : 47 μH
- Di1, Di2 : SFPB-66 (Sanken)

Diodes Di1, Di2

- Be sure to use a Schottky-barrier diodes for Di1 and Di2.

If other diodes like fast recovery diodes are used, IC may be destroyed because of the reverse voltage generated by the recovery voltage or ON voltage.

Choke coils L1, L2

- If the winding resistance of the choke coil is too high, the efficiency may drop below the rated value.
- As the overcurrent protection starting current is about 2.0A, take care concerning heat radiation from the choke coil caused by magnetic saturation due to overload or short-circuited load.
- Use a closed-magnetic-path coil to prevent interference between the channels SW_{out1} and SW_{out2}.

Capacitors C1, C2, C3

- As large ripple currents flow through C1, C2 and C3, use high-frequency and low-impedance capacitors suitable for switching mode power supplies. Especially when the impedance of C2 and C3 are high, the switching waveforms may become abnormal at low temperatures. For C2 and C3, do not use capacitors with extremely low equivalent series resistance (ESR) such as OS capacitors or tantalum capacitors, which may cause abnormal oscillation.


Resistors R1, R2, R3, R4

- R1, R2, R3 and R4 are resistors for setting output voltages. Set the resistors so that I_{REF} is approx. 1 mA. For example, R1 and R2 can be calculated as shown below.

$$R1 = \frac{(VO1 - VREF1)}{IREF1} = \frac{(VO1 - V)}{1 \times 10^{-3}} (\Omega), R2 = \frac{VREF1}{IREF1} = \frac{1}{1 \times 10^{-3}} \approx 1(K\Omega)$$

© To create the optimum operating conditions, place the components as close as possible to each other.

■T_a-P_d Characteristics



$$P_D = VO \cdot IO \left(\frac{100}{\eta\chi} - 1 \right) - VF \cdot IO \left(1 - \frac{VO}{VIN} \right)$$

- VO : Output Voltage
- VIN : Input Voltage
- IO : Output Current
- ηχ : Efficiency (%)
- VF : D1 Forward Voltage
SFPB-66...0.45V (IO=1A)

Note 1: The efficiency depends on the input voltage and the output current. Therefore, obtain the value from the efficiency graph and substitute the percentage in the formula above.

Note 2: Thermal design for D1 must be considered separately.

SI-3000KWF Series 2-Output, Low Dropout Voltage Linear Regulator IC

■Features

- Compact full-mold package (equivalent to TO220F)
- Output current: 1.0A × 2
- Low dropout voltage: $V_{DIF} \leq 0.6V$ (at $I_o = 1A$)
- Built-in overcurrent and thermal protection circuits

■Applications

- Secondary stabilized power supply (local power supply)

■Absolute Maximum Ratings

($T_a=25^\circ C$)

Parameter	Symbol	Ratings		Unit
		SI-3002KWF/SI-3003KWF		
DC Input Voltage	V_{IN}^{*1}	18		V
Output Control Terminal Voltage	V_c	6		V
Output Current ^{*1}	I_{o1}	1.0		A
	I_{o2}	1.0		
Power Dissipation (with two outputs ON)	P_D^{*2}	14		W
Junction Temperature	T_j	-30 to +125		$^\circ C$
Operating Ambient Temperature	T_{op}	-30 to +85		$^\circ C$
Storage Temperature	T_{stg}	-40 to +125		$^\circ C$
Thermal Resistance (Junction to Ambient Air)	θ_{j-a}	66.7		$^\circ C/W$
Thermal Resistance (Junction to Lead)	θ_{j-c}	7		$^\circ C/W$

*1: V_{IN} (max), I_{o1} (max) and I_{o2} (max) are restricted by the relation $P_D = (V_{IN} - V_{O1}) \times I_{o1} + (V_{IN} - V_{O2}) \times I_{o2}$.

*2: $T_c = 25^\circ C$ (With infinite heatsink)

Thermal protection may operate when the junction temperature exceeds 135 $^\circ C$.

■Electrical Characteristics

Parameter	Symbol	Ratings						Unit	
		SI-3002KWF			SI-3003KWF				
		min.	typ.	max.	min.	typ.	max.		
Output Voltage	V_{O1}	3.234	3.300	3.366	2.450	2.500	2.550	V	
	Conditions	$V_{IN}=5V, I_o=10mA$			$V_{IN}=3.3V, I_o=10mA$				
	V_{O2}	2.450	2.500	2.550	1.764	1.800	1.836		
	Conditions	$V_{IN}=5V, I_o=10mA$			$V_{IN}=3.3V, I_o=10mA$				
Line Regulation	ΔV_{OLINE1}			20			20	mV	
	Conditions	$V_{IN}=4.5$ to 10V, $I_o=10mA$			$V_{IN}=3.2$ to 5V, $I_o=10mA$				
	ΔV_{OLINE2}			20			20		
	Conditions	$V_{IN}=4.5$ to 10V, $I_o=10mA$			$V_{IN}=3.2$ to 5V, $I_o=10mA$				
Load Regulation	ΔV_{OLOAD1}			30			30	mV	
	Conditions	$V_{IN}=5V, I_o=0$ to 1A			$V_{IN}=3.3V, I_o=0$ to 1A				
	ΔV_{OLOAD2}			30			30		
	Conditions	$V_{IN}=5V, I_o=0$ to 1A			$V_{IN}=3.3V, I_o=0$ to 1A				
Dropout Voltage	V_{DIF1}			0.6			0.6	V	
	Conditions	$I_o=1A$			$I_o=1A$				
Temperature Coefficient of Output Voltage	$\Delta V_{O1}/\Delta T_a$		± 0.3			± 0.3		mV/ $^\circ C$	
	Conditions	$T_j=0$ to 100 $^\circ C$			$T_j=0$ to 100 $^\circ C$				
	$\Delta V_{O2}/\Delta T_a$		± 0.3			± 0.3			
	Conditions	$T_j=0$ to 100 $^\circ C$			$T_j=0$ to 100 $^\circ C$				
Ripple Rejection	R_{REJ1}		60			60		dB	
	Conditions	$V_{IN}=5V, f=100$ to 120Hz			$V_{IN}=3.3V, f=100$ to 120Hz				
	R_{REJ2}		60			60			
	Conditions	$V_{IN}=5V, f=100$ to 120Hz			$V_{IN}=3.3V, f=100$ to 120Hz				
Overcurrent Protection Starting Current ^{*1}	$I_{S1 1}$	1.2			1.2			A	
	Conditions	$V_{IN}=5V$			$V_{IN}=3.3V$				
	$I_{S1 2}$	1.2			1.2				
	Conditions	$V_{IN}=5V$			$V_{IN}=3.3V$				
Quiescent Circuit Current	I_q		1	1.5		1	1.5	mA	
	Conditions	$V_{IN}=5V, I_o=0A, V_c=2V$			$V_{IN}=3.3V, I_o=0A, V_c=2V$				
Circuit Current at Output OFF	$I_q(OFF)$			0.5			0.5	mA	
	Conditions	$V_{IN}=5V, V_c=0V$			$V_{IN}=3.3V, V_c=0V$				
VC Terminal	Control Voltage (Output ON) ^{*2}	V_c, IH	2		2			V	
	Control Voltage (Output OFF)	V_c, IL		0.8			0.8	V	
	Control Current (Output ON)	I_c, IH			5			5	μA
	Control Current (Output OFF)	I_c, IL	-100			-100			μA
	Conditions	$V_c=2.7V$			$V_c=2.7V$				
	Conditions	$V_c=0.4V$			$V_c=0.4V$				


*1: $I_{S1 1}$ and $I_{S1 2}$ are specified at the 5% drop points of output voltages V_{O1} and V_{O2} on the condition that V_{IN} = the condition of overcurrent protection starting current, $I_o = 10 mA$.

*2: Output is OFF when the output control terminal V_c is open. Each input level is equivalent to LS-TTL. Therefore, the device can be driven directly by LS-TTLs.


Channels 1 and 2 are turned on or off at the same time.

External Dimensions


(Unit : mm)



Block Diagram



Ta-Pd Characteristics



SI-3000KWD Series 2-Output, Surface-Mount, Low Dropout Voltage Linear Regulator IC

■ Features

- Surface-mount package (SOT263-5)
- Output current: $1.0\text{A} \times 2$
- Low dropout voltage: $V_{DIF} \leq 0.6\text{V}$ (at $I_o = 1\text{A}$)
- Built-in overcurrent and thermal protection circuits

■ Applications

- Secondary stabilized power supply (local power supply)

■ Absolute Maximum Ratings

(T_a=25°C)

Parameter	Symbol	Ratings		Unit
		SI-3002KWD/SI-3003KWD		
DC Input Voltage	V _{IN} ^{*1}	18		V
Output Control Terminal Voltage	V _c	6		V
Output Current ^{*1}	I _{o1}	1.0		A
	I _{o2}	1.0		
Power Dissipation (with two outputs ON)	P _D ^{*2}	3		W
Junction Temperature	T _j	-30 to +125		°C
Operating Ambient Temperature	T _{op}	-30 to +85		°C
Storage Temperature	T _{stg}	-40 to +125		°C
Thermal Resistance (Junction to Ambient Air)	θ _{ja}	33.3		°C/W
Thermal Resistance (Junction to Lead)	θ _{jc}	3		°C/W

*1: V_{IN} (max), I_{o1} (max) and I_{o2} (max) are restricted by the relation $P_D = (V_{IN} - V_{O1}) \times I_{O1} + (V_{IN} - V_{O2}) \times I_{O2}$.

*2: When mounted on glass-epoxy board of 40 × 40mm² (copper laminate area 100%)

Thermal protection may operate when the junction temperature exceeds 135°C.

■ Electrical Characteristics

Parameter	Symbol	Ratings						Unit	
		SI-3002KWD			SI-3003KWD				
		min.	typ.	max.	min.	typ.	max.		
Output Voltage	V _{O1}	3.234	3.300	3.366	2.450	2.500	2.550	V	
	Conditions	V _{IN} =5V, I _o =10mA			V _{IN} =3.3V, I _o =10mA				
	V _{O2}	2.450	2.500	2.550	1.764	1.800	1.836	V	
	Conditions	V _{IN} =5V, I _o =10mA			V _{IN} =3.3V, I _o =10mA				
Line Regulation	ΔV _{OLINE1}			20			20	mV	
	Conditions	V _{IN} =4.5 to 10V, I _o =10mA			V _{IN} =3.2 to 5V, I _o =10mA				
	ΔV _{OLINE2}			20			20	mV	
	Conditions	V _{IN} =4.5 to 10V, I _o =10mA			V _{IN} =3.2 to 5V, I _o =10mA				
Load Regulation	ΔV _{OLOAD1}			30			30	mV	
	Conditions	V _{IN} =5V, I _o =0 to 1A			V _{IN} =3.3V, I _o =0 to 1A				
	ΔV _{OLOAD2}			30			30	mV	
	Conditions	V _{IN} =5V, I _o =0 to 1A			V _{IN} =3.3V, I _o =0 to 1A				
Dropout Voltage	V _{DIF1}			0.6			0.6	V	
	Conditions	I _o =1A			I _o =1A				
Temperature Coefficient of Output Voltage	ΔV _{O1} /ΔT _a		±0.3			±0.3		mV/°C	
	Conditions	T _j =0 to 100°C			T _j =0 to 100°C				
	ΔV _{O2} /ΔT _a		±0.3			±0.3		mV/°C	
	Conditions	T _j =0 to 100°C			T _j =0 to 100°C				
Ripple Rejection	R _{REJ1}		60			60		dB	
	Conditions	V _{IN} =5V, f=100 to 120Hz			V _{IN} =3.3V, f=100 to 120Hz				
	R _{REJ2}		60			60		dB	
	Conditions	V _{IN} =5V, f=100 to 120Hz			V _{IN} =3.3V, f=100 to 120Hz				
Overcurrent Protection Starting Current ^{*1}	I _{S1 1}	1.2			1.2			A	
	Conditions	V _{IN} =5V			V _{IN} =3.3V				
	I _{S1 2}	1.2			1.2			A	
	Conditions	V _{IN} =5V			V _{IN} =3.3V				
Quiescent Circuit Current	I _q		1	1.5		1	1.5	mA	
	Conditions	V _{IN} =5V, I _o =0A, V _c =2V			V _{IN} =3.3V, I _o =0A, V _c =2V				
Circuit Current at Output OFF	I _q (OFF)			0.5			0.5	mA	
	Conditions	V _{IN} =5V, V _c =0V			V _{IN} =3.3V, V _c =0V				
VC Terminal	Control Voltage (Output ON) ^{*2}	V _c , IH	2		2			V	
	Control Voltage (Output OFF)	V _c , IL			0.8		0.8	V	
	Control Current (Output ON)	I _c , IH			5		5	μA	
	Control Current (Output OFF)	I _c , IL	-100			-100			μA
	Conditions	V _c =0.4V			V _c =0.4V				


*1: I_{S1 1} and I_{S1 2} are specified at the 5% drop points of output voltages V_{O1} and V_{O2} on the condition that V_{IN} = the condition of overcurrent protection starting current, I_o = 10 mA.

*2: Output is OFF when the output control terminal V_c is open. Each input level is equivalent to LS-TTL. Therefore, the devices can be driven directly by LS-TTLs.


Channels 1 and 2 are turned on or off at the same time.

External Dimensions


(Unit : mm)



Block Diagram



Ta-Pd Characteristics



SI-3000KWM Series 2-Output, Surface-Mount, Low Dropout Voltage Linear Regulator IC

■Features

- Compact surface-mount package (SOT252-5)
- Output current: 1.0A × 2
- Low dropout voltage: $V_{DIF} \leq 0.6V$ (at $I_o = 1A$)
- Built-in overcurrent and thermal protection circuits

■Applications

- Secondary stabilized power supply (local power supply)

■Absolute Maximum Ratings

($T_a=25^\circ C$)

Parameter	Symbol	Ratings		Unit
		SI-3002KWM/SI-3003KWM		
DC Input Voltage	V_{IN}^{*1}	18		V
Output Control Terminal Voltage	V_c	6		V
Output Current ^{*1}	I_{o1}	1.0		A
	I_{o2}	1.0		
Power Dissipation (with two outputs ON)	P_D^{*2}	1		W
Junction Temperature	T_j	-30 to +125		$^\circ C$
Operating Ambient Temperature	T_{op}	-30 to +85		$^\circ C$
Storage Temperature	T_{stg}	-40 to +125		$^\circ C$
Thermal Resistance (Junction to Ambient Air)	θ_{j-a}	95		$^\circ C/W$
Thermal Resistance (Junction to Lead)	θ_{j-c}	6		$^\circ C/W$

*1: V_{IN} (max), I_{o1} (max) and I_{o2} (max) are restricted by the relation $P_D = (V_{IN} - V_{O1}) \times I_{o1} + (V_{IN} - V_{O2}) \times I_{o2}$.

*2: When mounted on glass-epoxy board of $30 \times 30mm^2$ (copper laminate area 4.3%)

Thermal protection may operate when the junction temperature exceeds $135^\circ C$.

■Electrical Characteristics


Parameter	Symbol	Ratings						Unit	
		SI-3002KWM			SI-3003KWM				
		min.	typ.	max.	min.	typ.	max.		
Output Voltage	V_{O1}	3.234	3.300	3.366	2.450	2.500	2.550	V	
	Conditions	$V_{IN}=5V, I_o=10mA$			$V_{IN}=3.3V, I_o=10mA$				
	V_{O2}	2.450	2.500	2.550	1.764	1.800	1.836		
	Conditions	$V_{IN}=5V, I_o=10mA$			$V_{IN}=3.3V, I_o=10mA$				
Line Regulation	ΔV_{OLINE1}			20			20	mV	
	Conditions	$V_{IN}=4.5$ to $10V, I_o=10mA$			$V_{IN}=3.2$ to $5V, I_o=10mA$				
	ΔV_{OLINE2}			20			20		
	Conditions	$V_{IN}=4.5$ to $10V, I_o=10mA$			$V_{IN}=3.2$ to $5V, I_o=10mA$				
Load Regulation	ΔV_{OLOAD1}			30			30	mV	
	Conditions	$V_{IN}=5V, I_o=0$ to $1A$			$V_{IN}=3.3V, I_o=0$ to $1A$				
	ΔV_{OLOAD2}			30			30		
	Conditions	$V_{IN}=5V, I_o=0$ to $1A$			$V_{IN}=3.3V, I_o=0$ to $1A$				
Dropout Voltage	V_{DIF1}			0.6			0.6	V	
	Conditions	$I_o=1A$			$I_o=1A$				
Temperature Coefficient of Output Voltage	$\Delta V_{O1}/\Delta T_a$		± 0.3			± 0.3		mV/ $^\circ C$	
	Conditions	$T_j=0$ to $100^\circ C$			$T_j=0$ to $100^\circ C$				
	$\Delta V_{O2}/\Delta T_a$		± 0.3			± 0.3			
	Conditions	$T_j=0$ to $100^\circ C$			$T_j=0$ to $100^\circ C$				
Ripple Rejection	R_{REJ1}		60			60		dB	
	Conditions	$V_{IN}=5V, f=100$ to $120Hz$			$V_{IN}=3.3V, f=100$ to $120Hz$				
	R_{REJ2}		60			60			
	Conditions	$V_{IN}=5V, f=100$ to $120Hz$			$V_{IN}=3.3V, f=100$ to $120Hz$				
Overcurrent Protection Starting Current ^{*1}	$I_{S1 1}$	1.2			1.2			A	
	Conditions	$V_{IN}=5V$			$V_{IN}=3.3V$				
	$I_{S1 2}$	1.2			1.2				
	Conditions	$V_{IN}=5V$			$V_{IN}=3.3V$				
Quiescent Circuit Current	I_q		1	1.5		1	1.5	mA	
	Conditions	$V_{IN}=5V, I_o=0A, V_c=2V$			$V_{IN}=3.3V, I_o=0A, V_c=2V$				
Circuit Current at Output OFF	$I_q(OFF)$			0.5			0.5	mA	
	Conditions	$V_{IN}=5V, V_c=0V$			$V_{IN}=3.3V, V_c=0V$				
VC Terminal	Control Voltage (Output ON) ^{*2}	V_c, IH	2		2			V	
	Control Voltage (Output OFF)	V_c, IL					0.8	V	
	Control Current (Output ON)	I_c, IH			5			5	μA
	Control Current (Output OFF)	I_c, IL	-100			-100			μA
	Conditions	$V_c=2.7V$			$V_c=2.7V$				
	Conditions	$V_c=0.4V$			$V_c=0.4V$				

*1: $I_{S1 1}$ and $I_{S1 2}$ are specified at the 5% drop points of output voltages V_{O1} and V_{O2} on the condition that V_{IN} = the condition of protection starting current, $I_o = 10 mA$.


*2: Output is OFF when the output control terminal V_c is open. Each input level is equivalent to LS-TTL. Therefore, the devices can be driven directly by LS-TTLs. Channels 1 and 2 are turned on or off at the same time.

External Dimensions

(Unit : mm)



Block Diagram



SLA3002M/3004M 3-Output Linear/Switching Type Regulator IC

Features

- 3 regulator ICs combined in 1 package
- Insulated single inline package
- Can be used with Linear and switching type
- 3 independent circuits for input and output respectively. Internal dissipation can be reduced since different input voltages can be applied.
- Linear regulator IC is low-dropout voltage type with input/output voltage difference of 1V. Output ON/OFF control, variable output voltage (rise only) function
- Switching type: built-in separate excitation (60kHz), high efficiency of 80% or over
- Each regulator has overcurrent protection and thermal protection circuit.

Lineup

Part Number	SLA3002M			SLA3004M		
	Type	Vo (V)	Io(A)	Type	Vo (V)	Io (A)
Regulator 1	Switching	5	0.5	Switching	5	0.5
Regulator 2	Linear	15.7	1.0	Switching	9	0.4
Regulator 3	Switching	9	0.4	Switching	9	0.4

Absolute Maximum Ratings

Parameter	Symbol	Ratings						Unit
		SLA3002M			SLA3004M			
		Reg1	Reg2	Reg3	Reg1	Reg2	Reg3	
DC Input Voltage	V _{IN}		35			35	V	
Voltage of Output Control Terminal	V _C		V _{IN}				V	
Reverse Voltage applied to SW Terminal	V _{SW}	-1		-1		-1	V	
Power Dissipation	P _D	37.5(T _C =25°C)			37.5(T _C =25°C)			W
Junction Temperature	T _J	+150			+150			°C
Storage Temperature	T _{stg}	-40 to +150			-40 to +150			°C
Operating Ambient Temperature	T _{op}	-30 to +85			-30 to +85			°C
Thermal Resistance(junction-to-case)	θ _{J-C}	10			10			°C/W

Applications

- For stabilization of the secondary-side output voltage of switching power supplies
- Electronic equipment

Electrical Characteristics

(T_a=25°C unless otherwise specified)


Regulator	Parameter	Symbol	Ratings						Unit	
			SLA3002M			SLA3004M				
			min.	typ.	max.	min.	typ.	max.		
Regulator 1	Recommended DC Input Voltage	V _{IN1}	7		33	7		33	V	
	Output Voltage	V _{O1}	4.75		5.25	4.75		5.25	V	
		Conditions	V _{IN} =20V, I _O =0.3A			V _{IN} =20V, I _O =0.3A				
	Dropout Voltage	V _{DIF1}							V	
		Conditions								
	Efficiency	η ₁	80			80			%	
		Conditions	V _{IN} =20V, I _O =0.3A			V _{IN} =20V, I _O =0.3A				
	Line Regulation	ΔV _{OLINE1}	80			110			mV	
		Conditions	V _{IN} =10 to 30V, I _O =0.3A			V _{IN} =10 to 30V, I _O =0.3A				
	Load Regulation	ΔV _{OLOAD1}	30			40			mV	
Conditions		V _{IN} =20V, I _O =0.1 to 0.4A			V _{IN} =20V, I _O =0.1 to 0.4A					
Switching Frequency	f ₁	60			60			kHz		
	Conditions	V _{IN} =20V, I _O =0.3A			V _{IN} =20V, I _O =0.3A					
Overcurrent Protection Starting Current ¹	I _{S1, 1}	0.55				0.55			A	
	Conditions	V _{IN} =10V			V _{IN} =10V					
V _C Terminal ²	Control Voltage (Output ON)	V _{CIH, 1}							V	
	Control Voltage (Output OFF)	V _{CIL, 1}							V	
Regulator 2	Recommended DC Input Voltage	V _{IN2}	17		30	12		33	V	
	Output Voltage	V _{O2}	14.92		16.48	8.55		9.45	V	
		Conditions	V _{IN} =19V, I _O =0.5A			V _{IN} =21V, I _O =0.3A				
	Dropout Voltage	V _{DIF2}							V	
		Conditions	I _O =1.0A							
	Efficiency	η ₂				85			%	
		Conditions				V _{IN} =21V, I _O =0.3A				
	Line Regulation	ΔV _{OLINE2}	90			110			mV	
		Conditions	V _{IN} =17 to 25V, I _O =0.5A			V _{IN} =14 to 30V, I _O =0.3A				
	Load Regulation	ΔV _{OLOAD2}	120			80			mV	
Conditions		V _{IN} =19V, I _O =0 to 0.1A			V _{IN} =21V, I _O =0.1 to 0.4A					
Switching Frequency	f ₂				60			kHz		
	Conditions				V _{IN} =21V, I _O =0.3A					
Overcurrent Protection Starting Current ¹	I _{S1, 2}	1.2				0.45			A	
	Conditions	V _{IN} =19V			V _{IN} =14V					
V _C Terminal ²	Control Voltage (Output ON)	V _{CIH, 2}	2.0							V
	Control Voltage (Output OFF)	V _{CIL, 2}							V	
Regulator 3	Recommended DC Input Voltage	V _{IN3}	12		33	12		33	V	
	Output Voltage	V _{O3}	8.55		9.45	8.64		9.36	V	
		Conditions	V _{IN} =21V, I _O =0.3A			V _{IN} =21V, I _O =0.3A				
	Dropout Voltage	V _{DIF3}							V	
		Conditions								
	Efficiency	η ₃	85			85			%	
		Conditions	V _{IN} =21V, I _O =0.3A			V _{IN} =21V, I _O =0.3A				
	Line Regulation	ΔV _{OLINE3}	90			110			mV	
		Conditions	V _{IN} =14 to 30V, I _O =0.3A			V _{IN} =14 to 30V, I _O =0.3A				
	Load Regulation	ΔV _{OLOAD3}	50			80			mV	
Conditions		V _{IN} =21V, I _O =0.1 to 0.4A			V _{IN} =21V, I _O =0.1 to 0.4A					
Switching Frequency	f ₃	60			60			kHz		
	Conditions	V _{IN} =21V, I _O =0.3A			V _{IN} =21V, I _O =0.3A					
Overcurrent Protection Starting Current ¹	I _{S1, 3}	0.45				0.45			A	
	Conditions	V _{IN} =14V			V _{IN} =14V					
V _C Terminal ²	Control Voltage (Output ON)	V _{CIH, 3}							V	
	Control Voltage (Output OFF)	V _{CIL, 3}							V	

*1: I_{S1} of Linear Regulator is specified at the 5% drop point of output voltage V_O. I_{S1} of Switching Type is specified at the 10% drop point of output voltage V_O.


*2: Output is ON when V_C terminal is open.

External Dimensions


(Unit : mm)



Block Diagram



Typical Connection Diagram



SLA3005M/3006M/3007M 4-Output, Low Dropout Voltage Linear Regulator IC for USB Hub

Features

- 4 regulators combined in one package
- Insulated single inline package
- SLA 3005M/3006M have four 5V/0.5A outputs. SLA3007M has three 5V/0.5A output and ch4 is a 3.3V/0.5A output for USB-IC
- Low dropout voltage: $V_{DIF} \leq 0.5V$ (at $I_o=0.5A$)
- Output-independent ON/OFF control terminal compatible with LS-TTL (Active High)
- Output-independent overcurrent and thermal protection circuits built in ($T_a=25^\circ C$)

Absolute Maximum Ratings

($T_a=25^\circ C$)

Parameter	Symbol	Ratings		Unit
		SLA3005M/3006M	SLA3007M	
DC Input Voltage	V_{IN}	20	18	V
Output Control Terminal Voltage	V_c	V_{IN}		V
DC Output Current	I_o	0.5		A
Power Dissipation	P_{D1}	30(With infinite heatsink)		W
	P_{D2}	3.36(Without heatsink, stand-alone operation)		W
Junction Temperature	T_j	-30 to +125		$^\circ C$
Operating Ambient Temperature	T_{OP}	-30 to +100		$^\circ C$
Storage Temperature	T_{stg}	-30 to +125		$^\circ C$
Thermal Resistance (junction to case)	θ_{j-c}	9.0		$^\circ C/W$
Thermal Resistance (junction to ambient air)	θ_{j-a}	29.8(Without heatsink, stand-alone operation)		$^\circ C/W$

4-Output, Low Dropout Voltage Linear Regulator for USB Hub SLA3005M/3006M/3007M

- Open collector flag-output terminals built in to output OCP operation to each output terminal (Active Low) – excluding SLA3007M ch4
- SLA3005M/3007M (excluding ch4) for V_o shutdown after OCP operation and SLA3006M for continuous OCP operation
- Built-in anti-malfunction delay circuit whose time can be set with an external capacitor

Applications

- USB hub power supplies
- Electronic equipment

Recommended Operating Conditions

Parameter	Symbol	Ratings	Unit
DC Input Voltage Range	V_{IN}	5.5 to 10	V
Output Current Range	I_o	0 to 0.5	A
Operating Junction Temperature Range	T_{jop}	-20 to +100	$^\circ C$
Operating Ambient Temperature Range	T_{aop}	-20 to +85	$^\circ C$

Electrical Characteristics

($T_a=25^\circ C$ unless otherwise specified)

Parameter	Symbol	Ratings											Unit	
		SLA3005M			SLA3006M			SLA3007M						
		min.	typ.	max.	min.	typ.	max.	ch1, 2, 3		ch4				
Output Voltage	V_o	4.85	5.00	5.15	4.85	5.00	5.15	4.85	5.00	5.15	3.234	3.300	3.366	V
	Conditions	$V_{IN}=7V, I_o=0.1A$			$V_{IN}=7V, I_o=0.1A$			$V_{IN}=7V, I_o=0.1A$		$V_{IN}=7V, I_o=0.1A$				
Dropout Voltage	V_{DIF}			0.5			0.5			0.5			2.0	V
	Conditions	$I_o \leq 0.5A$			$I_o \leq 0.5A$			$I_o \leq 0.5A$		$I_o \leq 0.5A$				
Line Regulation	ΔV_{OLINE}			30			30			30			30	mV
	Conditions	$V_{IN}=6$ to 15V, $I_o=0.1A$			$V_{IN}=6$ to 15V, $I_o=0.1A$			$V_{IN}=6$ to 15V, $I_o=0.1A$		$V_{IN}=6$ to 15V, $I_o=0.1A$				
Load Regulation	ΔV_{OLOAD}			50			50			50			30	mV
	Conditions	$V_{IN}=7V, I_o=0$ to 0.5A			$V_{IN}=7V, I_o=0$ to 0.5A			$V_{IN}=7V, I_o=0$ to 0.5A		$V_{IN}=7V, I_o=0$ to 0.2A				
Temperature Coefficient of Output Voltage	$\Delta V_o/\Delta T_a$		± 0.5			± 0.5			± 0.5			± 0.3		mV/ $^\circ C$
	Conditions	$V_{IN}=7V, I_o=5mA, T_j=-10$ to $100^\circ C$			$V_{IN}=7V, I_o=5mA, T_j=-10$ to $100^\circ C$			$V_{IN}=7V, I_o=5mA, T_j=-10$ to $100^\circ C$		$V_{IN}=7V, I_o=5mA, T_j=-10$ to $100^\circ C$				
Quiescent Circuit Current ³	I_q			20			20			20				mA
	Conditions	$V_{IN}=7V, I_o=0A$			$V_{IN}=7V, I_o=0A$			$V_{IN}=7V, I_o=0A$		-				
Quiescent Circuit Current (Output OFF) ³	$I_{q(OFF)}$			0.5			0.5			0.5				mA
	Conditions	$V_{IN}=7V, V_c1$ to 4=0V			$V_{IN}=7V, V_c1$ to 4=0V			$V_{IN}=7V, V_c1$ to 4=0V		-				
Overcurrent Protection Starting Current ¹	I_{S1}	0.55		0.65	0.75		0.96	0.55		0.65	0.55		0.65	A
	Conditions	$V_{IN}=7V$			$V_{IN}=7V$			$V_{IN}=7V$		$V_{IN}=7V$				
Vc Terminal ²	Control Voltage (Output ON)	V_c IH	2.0		2.0			2.0			2.0			V
	Control Voltage (Output OFF)	V_c IL			0.7		0.7			0.7			0.7	
	Control Current (Output ON)	I_c IH			50		50			50			50	
	Control Current (Output ON)	Conditions	$V_c=2.7V$			$V_c=2.7V$			$V_c=2.7V$		$V_c=2.7V$			
	Control Current (Output OFF)	I_c IL			-100		-100			-100			-100	
OCP Detection Voltage	V_{oth}	3.7	4.0	4.3	3.7	4.0	4.3	3.7	4.0	4.3				V
DLY Threshold Voltage	V_{DLYth}	2.1	2.3	2.5	2.1	2.3	2.5	2.1	2.3	2.5				V
DLY Terminal Outflow Current	I_{DLY}	35	50	65	35	50	65	35	50	65				μA
FLG Output Voltage	Before OCP Detection	V_{FLGh}	$V_{IN}-0.4$		$V_{IN}-0.4$			$V_{IN}-0.4$						V
	Conditions	With R_{FLG} connected between FLG and V_{IN}			With R_{FLG} connected between FLG and V_{IN}			With R_{FLG} connected between FLG and V_{IN}		-				
	After OCP Detection	V_{FLGi}		0.5		0.5			0.5					
Conditions	$I_{FLG}=1mA$			$I_{FLG}=1mA$			$I_{FLG}=1mA$		-					

*1 I_{S1} is specified at the 5% drop point of output voltage V_o on the condition that $V_{IN} = 7V, I_o = 0.1A$.


*2 Output is ON even when output control terminal V_c is open. Each input level is equivalent to LS-TTL. Therefore, the device can be driven directly by LS-TTLs.

*3 Total of four circuits

* The FLG output is latched after the delay time has elapsed after OCP detection. (SLA3005M/SLA3007M (ch1 to 3) shut down the output voltages simultaneously at latching.) Set the V_{IN} or V_c to low level in order to reset latching. Leave a time lag of $C_d \times 600s$ or more before restart.

** SLA3007Mch4 does not have the FLG output function.

External Dimensions



- a. Part Number
- b. Lot Number


Pin Assignment

- | | |
|-------------------|-----------------------|
| ① V _{C1} | ⑩ FLG3 |
| ② FLG1 | ⑪ DLY3 |
| ③ DLY1 | ⑫ Vo3 |
| ④ Vo1 | ⑬ GND |
| ⑤ V _{C2} | ⑭ V _{C4} |
| ⑥ FLG2 | ⑮ FLG4 (SLA3007M: NC) |
| ⑦ DLY2 | ⑯ DLY4 (SLA3007M: NC) |
| ⑧ Vo2 | ⑰ Vo4 |
| ⑨ V _{C3} | ⑱ V _{IN} |


Plastic Mold Package Type
 Flammability: UL94V-0
 Product Mass: Approx. 6g

Block Diagram


SLA3005M




SLA3006M



SLA3007M




■ Typical Connection Diagram




- *1 C_{IN} : Input capacitor (Approx. 47μF)
This capacitor is required if the input line contains inductance or the wiring is long.
- *2 C_O : Output capacitor (47 to 220μF)
Use a capacitor of 100μF or higher or a tantalum capacitor at the temperatures lower than -10°C.
- *3 C_d : Delay time setting capacitor (0.1μF or higher)
C_d determines the delay time (t_{DLY}) from when a low V_O level due to OCP operation is detected until a flag signal is output.
It prevents a rush current from causing malfunction at start-up.
Approximate calculation: $t_{DLY} \approx (C_d \times V_{DLYth}) / I_{DLY} [\text{sec}]$
Especially when the start-up requires some time for such as soft-start on V_{IN} or large C_{IN} capacitance, be sure to set t_{DLY} long enough for the output voltage to rise sufficiently.
Be sure to connect C_d and do not short-circuit the C_d in the application.
- *4 D₁ to D₄ : Reverse biasing protection diodes
These diodes are required for protection against reverse biasing of the respective inputs and outputs.
- *5 R_{FLG} : Set the value so as to limit the inflow current into the FLG terminal to 1mA or lower.

■ Ta-Pd Characteristics



■ Timing Chart



1-2 Motor Driver IC

Selection Guide

2-Phase Stepper Motor Unipolar Driver IC

Excitation Method	Output Current (A)					Motor Supply Voltage (V)	Package	Remarks	Page
	1.0	1.2	1.5	2.0	3.0				
2-Phase Excitation	SLA7022MU		SLA7029M			to 46	ZIP15Pin with Heatsink		122
	SMA7022MU		SMA7029M			to 46	ZIP15Pin		122
			SMA7036M			to 46	ZIP15Pin		124
2-Phase/1-2 Phase Excitation	SDK03M					to 46	SMD16Pin	Two ICs are used to drive a single motor.	132
	SLA7027MU		SLA7024M		SLA7026M	to 46	ZIP18Pin with Heatsink		126
	SLA7031M		SLA7032M		SLA7033M	to 46	ZIP18Pin with Heatsink		128
2W, 1-2 Phase Excitation μ Step Support	SLA7050M			SLA7051M	SLA7052M	to 46	ZIP18Pin with Heatsink	Built-in sequencer	130
		SLA7042M			SLA7044M	to 46	ZIP18Pin with Heatsink		134
4W, 1-2 Phase Excitation μ Step Support	SLA7065M			SLA7066M	SLA7067M	to 46	ZIP21Pin with Heatsink	Built-in sequencer	136
	SLA7060M			SLA7061M	SLA7062M	to 46	ZIP21Pin with Heatsink	Built-in sequencer	138

Serial Signal Generator for SLA704x

Part Number	Power Supply Voltage (V)	Package	Page
PG001M	4.5 to 5.5	DIP16Pin	140

3-Phase Stepper Motor Driver IC

Excitation Method	Part Number	Power Supply Voltage (V)	Output Current (A)	Package	Remarks	Page
2-Phase/2-3 Phase Excitation	SLA7611M	to 36	3.0	ZIP18Pin with Heatsink		142

Application Note

■ Setup Precautions

- Recommended mounting torque
0.588 to 0.784 [N•m](6.0 to 8.0 [kgf•cm])
- Recommended silicone grease
Shin-Etsu Chemical Co., Ltd.: G746
GE Toshiba Silicones Co., Ltd.: YG-6260
Dow Corning Toray Silicone Co., Ltd.: SC102
Please select proper silicone grease carefully since the oil in some grease products may penetrate the device and result in an extremely short device life.

■ Handling Precautions

When using the following products that use C-MOS circuits for input terminals, observe the following.

SMA7036M/SLA7031M/SLA7032M/SLA7033M

SLA7050M/SLA7051M/SLA7052M

SLA7060M/SLA7061M/SLA7062M

SLA7065M/SLA7066M/SLA7067M

- Carefully control the humidity of the room to prevent the buildup of static electricity. Since static electricity is particularly a problem during the winter, be sure to take sufficient precautions.

Take care to make sure that static electricity is not applied to the IC during wiring and assembly. Take precautions such as shorting the terminals of the printed circuit board to ensure that they are at the same electrical potential.

SLA7022MU/SLA7029M/SMA7022MU/SMA7029M 2-Phase Excitation

■ Absolute Maximum Ratings

(T_a=25°C)


Parameter	Symbol	Ratings				Units
		SLA7022MU	SLA7029M	SMA7022MU	SMA7029M	
Motor supply voltage	V _{CC}	46				V
FET Drain-Source voltage	V _{DSS}	100				V
Control supply voltage	V _S	46				V
TTL input voltage	V _{IN}	7				V
Reference voltage	V _{REF}	2				V
Output current	I _O	1	1.5	1	1.5	A
Power dissipation	P _{D1}	4.5 (Without Heatsink)		4.0 (Without Heatsink)		W
	P _{D2}	35 (T _C =25°C)				28 (T _C =25°C)
Channel temperature	T _{ch}	+150				°C
Storage temperature	T _{stg}	-40 to +150				°C

■ Electrical Characteristics


(T_a=25°C)

Parameter	Symbol	Ratings												Units
		SLA7022MU			SLA7029M			SMA7022MU			SMA7029M			
		min	typ	max	min	typ	max	min	typ	max	min	typ	max	
Control supply current	I _S	10			10			10			10			mA
	Condition	V _S =44V			V _S =44V			V _S =44V			V _S =44V			
Control supply voltage	V _S	10	24	44	10	24	44	10	24	44	10	24	44	V
FET Drain-Source voltage	V _{DSS}	100			100			100			100			V
FET ON voltage	V _{DS}	0.85			0.6			0.85			0.6			V
	Condition	I _D =1A, V _S =14V			I _D =1A, V _S =14V			I _D =1A, V _S =14V			I _D =1A, V _S =14V			
FET drain leakage current	I _{loss}	4			4			4			4			mA
	Condition	V _{DSS} =100V, V _S =44V			V _{DSS} =100V, V _S =44V			V _{DSS} =100V, V _S =44V			V _{DSS} =100V, V _S =44V			
FET diode forward voltage	V _{SD}	1.2			1.1			1.2			1.1			V
	Condition	I _D =1A			I _D =1A			I _D =1A			I _D =1A			
TTL input current	I _{IH}	40			40			40			40			μA
	Condition	V _{IH} =2.4V, V _S =44V			V _{IH} =2.4V, V _S =44V			V _{IH} =2.4V, V _S =44V			V _{IH} =2.4V, V _S =44V			
	I _{IL}	-0.8			-0.8			-0.8			-0.8			mA
Condition	V _{IL} =0.4V, V _S =44V			V _{IL} =0.4V, V _S =44V			V _{IL} =0.4V, V _S =44V			V _{IL} =0.4V, V _S =44V				
TTL input voltage (Active High)	V _{IH}	2			2			2			2			V
	Condition	I _D =1A			I _D =1A			I _D =1A			I _D =1A			
	V _{IL}	0.8			0.8			0.8			0.8			
TTL input voltage (Active Low)	V _{IH}	2			2			2			2			V
	Condition	V _{DSS} =100V			V _{DSS} =100V			V _{DSS} =100V			V _{DSS} =100V			
	V _{IL}	0.8			0.8			0.8			0.8			
Switching time	T _r	0.5			0.5			0.5			0.5			μs
	Condition	V _S =24V, I _D =0.8A			V _S =24V, I _D =1A			V _S =24V, I _D =0.8A			V _S =24V, I _D =1A			
	T _{stg}	0.7			0.7			0.7			0.7			
	Condition	V _S =24V, I _D =0.8A			V _S =24V, I _D =1A			V _S =24V, I _D =0.8A			V _S =24V, I _D =1A			
	T _f	0.1			0.1			0.1			0.1			
	Condition	V _S =24V, I _D =0.8A			V _S =24V, I _D =1A			V _S =24V, I _D =0.8A			V _S =24V, I _D =1A			

Internal Block Diagram




Typical Connection Diagram (Recommended component values)



External Dimensions

(Unit:mm)



SMA7036M 2-Phase Excitation


Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
Motor supply voltage	V_{CC}	46	V
Control supply voltage	V_S	46	V
FET Drain-Source voltage	V_{DSS}	100	V
TTL input voltage	V_{IN}	-0.3 to +7	V
SYNC terminal voltage	V_{SYNC}	-0.3 to +7	V
Reference voltage	V_{REF}	-0.3 to +7	V
Sense voltage	V_{RS}	-5 to +7	V
Output current	I_O	1.5	A
Power dissipation	P_{D1}	4.0 ($T_a=25^\circ\text{C}$)	W
	P_{D2}	28 ($T_c=25^\circ\text{C}$)	W
Channel temperature	T_{ch}	150	$^\circ\text{C}$
Storage temperature	T_{stg}	-40 to +150	$^\circ\text{C}$
Operating ambient temperature	T_a	-20 to +85	$^\circ\text{C}$


Electrical Characteristics

Parameter	Symbol	Ratings			Units	
		min	typ	max		
Control supply current	I_S		10	15	mA	
	Condition		$V_S=44\text{V}$			
Control supply voltage	V_S	10	24	44	V	
	V_{DSS}	100				
FET Drain-Source voltage	V_{DS}				V	
	Condition		$V_S=44\text{V}, I_{SS}=250\mu\text{A}$			
FET ON voltage	V_{DS}			0.6	V	
	Condition		$I_D=1\text{A}, V_S=10\text{V}$			
FET diode forward voltage	V_{SD}			1.1	V	
	Condition		$I_{SD}=1\text{A}$			
FET drain leakage current	I_{DSS}			250	μA	
	Condition		$V_{DSS}=100\text{V}, V_S=44\text{V}$			
IN terminal	Active H	V_{IH}	2		V	
		Condition		$I_D=1\text{A}$		
		V_{IL}		0.8		
	Active L	Condition		$V_{DSS}=100\text{V}$		
		V_{IH}	2			
		Condition		$V_{DSS}=100\text{V}$		
Input current	I_I			± 1	μA	
	Condition		$V_S=44\text{V}, V_I=0 \text{ or } 5\text{V}$			
SYNC terminal	Input voltage	V_{SYNCH}	4.0		V	
		Condition		Synchronous chopping mode		
		V_{SYNCL}				0.8
	Input current	Condition		Asynchronous chopping mode		
		I_{SYNCH}			0.1	
		Condition		$V_S=44\text{V}, V_{YS}=5\text{V}$		
REF terminal	Input voltage	I_{SYNCL}		-0.1	mA	
		Condition		$V_S=44\text{V}, V_{YS}=0\text{V}$		
		V_{REF}	0			2.0
	Input current	Condition		Reference voltage input		
		V_{REF}	4.0		5.5	
		Condition		Output FET OFF		
Internal resistance	I_{REF}			± 1	μA	
	Condition		No synchronous trigger			
R _{REF}	R_{REF}		40		Ω	
	Condition		Resistance between GND and REF terminal at synchronous trigger			
Switching time	T _{ON}	T_{ON}		1.5	μs	
		Condition		$V_S=24\text{V}, I_D=1\text{A}$		
		T_r		0.5		
	T _{stg}	Condition		$V_S=24\text{V}, I_D=1\text{A}$		
		T_{stg}		0.9		
		Condition		$V_S=24\text{V}, I_D=1\text{A}$		
T _f	T_f		0.1			
	Condition		$V_S=24\text{V}, I_D=1\text{A}$			
Chopping OFF time	T_{OFF}		12		μs	
	Condition		$V_S=24\text{V}$			

Internal Block Diagram




Typical Connection Diagram (Recommended component values)



External Dimensions

(Unit : mm)



SLA7027MU/SLA7024M/SLA7026M 2-Phase/1-2 Phase Excitation

Absolute Maximum Ratings


(Ta=25°C)

Parameter	Symbol	Ratings			Units
		SLA7027MU	SLA7024M	SLA7026M	
Motor supply voltage	V _{CC}	46			V
FET Drain-Source voltage	V _{DSS}	100			V
Control supply voltage	V _S	46			V
Input voltage	V _{IN}	7			V
Reference voltage	V _{REF}	2			V
Output current	I _O	1	1.5	3	A
Power dissipation	P _{D1}	4.5 (Without Heatsink)			W
	P _{D2}	35 (T _C =25°C)			W
Channel temperature	T _{ch}	+150			°C
Storage temperature	T _{stg}	-40 to +150			°C


Electrical Characteristics

Parameter	Symbol	Ratings									Units
		SLA7027MU			SLA7024M			SLA7026M			
		min	typ	max	min	typ	max	min	typ	max	
Control supply current	I _S	10			10			15			mA
	Condition	V _S =44V									
Control supply voltage	V _S	10	24	44	10	24	44	10	24	44	V
FET Drain-Source voltage	V _{DSS}	100			100			100			V
	Condition	V _S =44V, I _{DSS} =250μA									
FET ON voltage	V _{DS}	0.85			0.6			0.85			V
	Condition	I _D =1A, V _S =14V									
FET drain leakage current	I _{DSS}	4			4			4			mA
	Condition	V _{DSS} =100V, V _S =44V									
FET diode forward voltage	V _{SD}	1.2			1.1			2.3			V
	Condition	I _D =1A									
TTL input current	I _{IH}	40			40			40			μA
	Condition	V _{IH} =2.4V, V _S =44V									
	I _{IL}	-0.8			-0.8			-0.8			mA
Condition	V _{IL} =0.4V, V _S =44V										
TTL input voltage (Active High)	V _{IH}	2			2			2			V
	Condition	I _D =1A									
	V _{IL}			0.8			0.8			0.8	
TTL input voltage (Active Low)	V _{IH}	2			2			2			V
	Condition	V _{DSS} =100V									
	V _{IL}			0.8			0.8			0.8	
Switching time	T _r	0.5			0.5			0.5			μs
	Condition	V _S =24V, I _D =0.8A									
	T _{stg}	0.7			0.7			0.7			
	Condition	V _S =24V, I _D =0.8A									
	T _f	0.1			0.1			0.1			
Condition	V _S =24V, I _D =1A										

Internal Block Diagram




Typical Connection Diagram (Recommended component values)



External Dimensions

(Unit : mm)



SLA7031M/SLA7032M/SLA7033M

2-Phase/1-2 Phase Excitation

■ Absolute Maximum Ratings

(T_a=25°C)

Parameter	Symbol	Ratings			Units
		SLA7031M	SLA7032M	SLA7033M	
Motor supply voltage	V _{CC}	46			V
Control supply voltage	V _S	46			V
FET Drain-Source voltage	V _{DSS}	100			V
Input voltage	V _{IN}	-0.3 to +7			V
	V _{SYNC}	-0.3 to +7			
Reference voltage	V _{REF}	-0.3 to +7			V
Sense voltage	V _{RS}	-5 to +7			V
Output current	I _O	1	1.5	3	A
	P _{D1}	4.5(Without Heatsink)			W
Power dissipation	P _{D2}	35(T _c =25°C)			W
Channel temperature	T _{ch}	+150			°C
Operating ambient temperature	T _a	-20 to +85			°C
Storage temperature	T _{stg}	-40 to +150			°C


■ Recommended Operating Conditions

Parameter	Symbol	Ratings		Unit	Remarks
		min	max		
Motor Supply Voltage	V _M		44	V	
Control Supply Voltage	V _S	10	44	V	
REF Input Voltage	V _{REF}	0.1	1.0	V	The control current precision is degraded at 0.1V or lower.
	V _{REF(dis)}	4.0	5.5	V	Output MOS FET OFF
Case Temperature	T _C		100	°C	Temperature of 4(15)-Pin Lead(without heatsink)


■ Electrical Characteristics

Parameter	Symbol	Ratings									Units				
		SLA7031M			SLA7032M			SLA7033M							
		min	typ	max	min	typ	max	min	typ	max					
Control supply current	I _S	10			15			10			15			mA	
	Condition	V _S =44V													
Control supply voltage	V _S	10	24	44	10	24	44	10	24	44	V				
FET Drain-Source voltage	V _{DSS}	100									V				
	Condition	V _S =44V, I _{OSS} =250μA													
FET ON voltage	V _{DS}	0.85			0.6			0.85			V				
	Condition	I _D =1A, V _S =10V													
FET diode forward voltage	V _{SD}	1.2			1.1			2.3			V				
	Condition	I _{SD} =1A													
FET drain leakage current	I _{DSS}	250			250			250			μA				
	Condition	V _{DSS} =100V, V _S =44V													
IN terminal	Input voltage (Active High)	V _{IH}	2.0			2.0			2.0			V			
		Condition	I _D =1A												
		V _{IL}	0.8			0.8			0.8						
	Input voltage (Active Low)	V _{IH}	2.0			2.0			2.0			V			
		Condition	V _{DSS} =100V												
		V _{IL}	0.8			0.8			0.8						
Input current	I _I	±1			±1			±1			μA				
	Condition	V _S =44V, V _I =0 or 5V													
SYNC terminal	Input voltage	V _{SYNC}	4.0			4.0			4.0			V			
		Condition	Synchronous chopping mode												
		V _{SYNC}	0.8			0.8			0.8						
	Input current	Condition	Asynchronous chopping mode												
		I _{SYNC}	0.1			0.1			0.1			mA			
		Condition	V _S =44V, V _{SYNC} =5V												
I _{SYNC}	-0.1			-0.1			-0.1								
REF terminal	Input current	V _{REF}	0			2.0			0			2.0			V
		Condition	Reference voltage input												
		V _{REF}	4.0			5.5			4.0			5.5			
	Input current	Condition	Output FET OFF												
		I _{REF}	±1			±1			±1			μA			
		Condition	No synchronous trigger												
Internal resistance	R _{REF}	40			40			40			Ω				
	Condition	Resistance between GND and REF terminal at synchronous trigger													
Sense Voltage	V _{RS}	V _{REF}			V _{REF}			V _{REF}			V				
Switching time	T _r	0.5			0.5			0.5			μs				
	T _{sg}	0.7			0.7			0.7							
	T _f	0.1			0.1			0.1							
	Condition	V _S =24V, I _D =0.8A													
Chopping OFF time	T _{OFF}	12			12			12			μs				
	Condition	V _S =24V													

Internal Block Diagram




Typical Connection Diagram (Recommended component values)



External Dimensions

(Unit : mm)



SLA7050M/SLA7051M/SLA7052M 2-Phase/1-2 Phase Excitation, Built-in Sequencer

Absolute Maximum Ratings

(T_a=25°C)

Parameter	Symbol	Ratings			Unit
		SLA7050M	SLA7051M	SLA7052M	
Motor Supply Voltage	V _M	46			V
Load Supply Voltage	V _S	46			V
Logic Supply Voltage	V _{CC}	7			V
Output Current	I _O	1	2	3	A
Logic Input Voltage	V _{IN}	-0.3 to V _{CC} +0.3			V
REF Input Voltage	V _{REF}	-0.3 to V _{CC} +0.3			V
Sense Voltage	V _{RS}	-2 to +2			V
Power Dissipation	P _{D1}	4 (Without Heatsink)			W
	P _{D2}	20 (T _C =25°C)			W
Junction Temperature	T _J	+150			°C
Operating Ambient Temperature	T _a	-20 to +85			°C
Storage Temperature	T _{stg}	-30 to +150			°C

Recommended Operating Conditions

Parameter	Symbol	Ratings		Unit	Remarks
		min.	max.		
Motor Supply Voltage	V _M		44	V	
Load Supply Voltage	V _S	10	44	V	
Logic Supply Voltage	V _{CC}	3.0	5.5	V	The V _{CC} surge voltage should be 0.5V or lower.
REF Input Voltage	V _{REF}	0.1	1.0	V	The control current precision is degraded at 0.1V or lower.
Case Temperature	T _C		100	°C	Temperature at pin-10 Lead (Without heatsink)

Electrical Characteristics

(V_{CC} = 5V, V_S = 24V, T_a = 25°C, unless otherwise specified)

Parameter	Symbol	Ratings									Unit
		SLA7050M			SLA7051M			SLA7052M			
		min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	
Main Supply Current	I _{SS}			15			15			15	mA
	Conditions	Normal operation			Normal operation			Normal operation			
	I _S			100			100			100	μA
	Conditions	Sleep mode			Sleep mode			Sleep mode			
Logic Supply Current	I _{CC}			3			3			3	mA
Output MOSFET Breakdown Voltage	V _{DSS}	100			100			100			V
	Conditions	V _S =44V, I _{DSS} =1mA			V _S =44V, I _{DSS} =1mA			V _S =44V, I _{DSS} =1mA			
Output MOSFET ON Resistance	R _{DS(ON)}			0.85			0.5			0.27	Ω
	Conditions	I _D =1A			I _D =1A			I _D =3A			
Output MOSFET Diode Forward Voltage	V _{SD}			1.2			1.1			2.3	V
	Conditions	I _{SD} =1A			I _{SD} =1A			I _{SD} =3A			
Maximum Clock Frequency	F _{clock}			100			100			100	kHz
Logic Input Voltage	V _{IL}			V _{CC} -0.25			V _{CC} -0.25			V _{CC} -0.25	V
	V _{IH}	V _{CC} -0.75			V _{CC} -0.75			V _{CC} -0.75			
Logic Input Current	I _{IL}		±1			±1			±1		μA
	I _{IH}		±1			±1			±1		
REF Input Voltage	V _{REF}	0		1.5	0		1.5	0		1.5	V
	Conditions	Normal-operation current control			Normal-operation current control			Normal-operation current control			
	V _{REFS}	2		V _{CC}	2		V _{CC}	2		V _{CC}	
	Conditions	Output OFF (sleep)			Output OFF (sleep)			Output OFF (sleep)			
REF Input Current	I _{REF}		±10			±10			±10		μA
Sense Voltage	V _{RS}		V _{REF}			V _{REF}			V _{REF}		V
PWM OFF Time	T _{OFF}		12			12			12		μS
PWM Minimum ON Time	T _{ON(min)}		5			5			5		μS
Sleep - Enable Recovery Time	T _{SE}	100			100			100			μS
	Conditions	V _{REF} : 2.0→1.5V, I _O : 0.75A			V _{REF} : 2.0→1.5V, I _O : 1.5A			V _{REF} : 2.0→1.5V, I _O : 2.0A			
Switching Time	T _{ONC}		2.5			2.5			2.5		μS
	Conditions	Clock→Out			Clock→Out			Clock→Out			
	T _{OFFC}		2.0			2.0			2.0		
	Conditions	Clock→Out			Clock→Out			Clock→Out			

Internal Block Diagram and Pin Assignment

Pin No.	Symbol	Function
1	OutA	Phase A output
2	NC	No Connection
3	OutA̅	Phase A̅ output
4	GA	No Connection
5	Vcc	Logic supply
6	SenseA	Phase A current sense
7	Clock	Step Clock input
8	Sync	Synchronous PWM control signal input
9	Ref	Control current setting & output OFF
10	GND	Device GND
11	CW/CCW	Normal/reverse control input
12	Full/Half	Full/Half Step control input
13	SenseB	Phase B current sense
14	Vs	Load supply (motor supply)
15	GB	No Connection
16	OutB̅	Phase B̅ output
17	NC	No Connection
18	OutB	Phase B output

Truth Table

	L	H
CW/CCW	CW	CCW
Full/Half	Full	Half
REF	Enable	Disable
Sync	Asynchronous	Synchronous
Clock		

* REF terminal turns into normal operation at VREF < 1.5V.
The output is disabled (Output OFF) at VREF > 2V.

Typical Connection Diagram

Rs=0.1 to 2Ω (Power dissipation should be: $P=I_o^2 \times R_s$)
 R1=10kΩ CA=100µF/50V
 R2=5.1kΩ (VR) CB=10µF/10V
 Q1:T.B.D

- * Vcc line noise precaution:
The device may malfunction if the Vcc line noise exceeds 0.5V.
- * Be sure to connect the unused logic input terminals (CW/CCW, F/H, Sync) to Vcc or GND. If they are open, the device will malfunction.
- * GND pattern precaution:
Separating the Vcc system GND (S-GND) and Vs system GND (P-GND) from the device GND (10-Pin) helps to reduce noise.

External Dimensions

(Unit : mm)

Forming No. No.871

Forming No. No.872

SDK03M 2-Phase/1-2 Phase Excitation


Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
Motor supply voltage	V_{CC}	46	V
FET Drain-Source voltage	V_{DSS}	100	V
Control supply voltage	V_S	46	V
TTL input voltage	V_{IN}	7	V
Reference voltage	V_{REF}	2	V
Output current	I_O	1	A
Power dissipation	P_D	2.5 (Without Heatsink)	W
Channel temperature	T_{ch}	+150	°C
Storage temperature	T_{stg}	-40 to +150	°C

Electrical Characteristics

Parameter	Symbol	Ratings			Units
		min	typ	max	
Control supply current	I_S		5	7.5	mA
	Condition	$V_S=44V$			
Control supply voltage	V_S	10	24	44	V
FET Drain-Source voltage	V_{DSS}	100			V
	Condition	$V_S=44V, I_{OSS}=250\mu A$			
FET ON voltage	V_{DS}			0.85	V
	Condition	$I_D=1A, V_S=14V$			
FET drain leakage current	I_{DSS}			4	mA
	Condition	$V_{DSS}=100V, V_S=44V$			
FET diode forward voltage	V_{SD}			1.2	V
	Condition	$I_D=1A$			
TTL input current	I_{IH}			40	μA
	Condition	$V_{IH}=2.4V, V_S=44V$			
	I_{IL}			-0.8	mA
Condition	$V_{IL}=0.4V, V_S=44V$				
TTL input voltage (Active High)	V_{IH}	2			V
	Condition	$I_D=1A$			
	V_{IL}			0.8	
TTL input voltage (Active Low)	V_{IH}	2			V
	Condition	$V_{DSS}=100V$			
	V_{IL}			0.8	
Switching time	T_r		0.5		μs
	Condition	$V_S=24V, I_D=0.8A$			
	T_{stg}		0.7		
	Condition	$V_S=24V, I_D=0.8A$			
	T_f		0.1		
Condition	$V_S=24V, I_D=0.8A$				

Internal Block Diagram



1,8,9,16pin Description of pins

	Excitation input signal	
	Active H	Active L
Pin 1	OUT ₁	OUT ₂
Pin 16	OUT ₁	OUT ₂
Pin 8	OUT ₂	OUT ₁
Pin 9	OUT ₂	OUT ₁

■Typical Connection Diagram (Recommended component values)

Active High

Excitation signal time chart
2-phase excitation

Phase	clock	0	1	2	3	0	1
Phase A	IN ₁	H	L	L	H	H	L
	IN ₂	L	H	H	L	L	H
Phase B	IN ₁	H	H	L	L	H	H
	IN ₂	L	L	H	H	L	L

r₁ : 510Ω
 r₂ : 100Ω (VR)
 r₃ : 47kΩ
 r₄ : 47kΩ
 r₅ : 2.4kΩ
 r₆ : 2.4kΩ
 C₁ : 470pF
 C₂ : 470pF
 C₃ : 2200pF
 C₄ : 2200pF
 R_S : 1.8Ω typ
 (1 to 2W)

Active Low

Excitation signal time chart
2-phase excitation

Phase	clock	0	1	2	3	0	1
Phase A	IN ₁	L	H	H	L	L	H
	IN ₂	H	L	L	H	H	L
Phase B	IN ₁	L	L	H	H	L	L
	IN ₂	H	H	L	L	H	H


r₁ : 510Ω
 r₂ : 100Ω (VR)
 r₃ : 47kΩ
 r₄ : 47kΩ
 r₅ : 2.4kΩ
 r₆ : 2.4kΩ
 C₁ : 470pF
 C₂ : 470pF
 C₃ : 2200pF
 C₄ : 2200pF
 R_S : 1.8Ω typ
 (1 to 2W)

1-2-phase excitation

Phase	clock	0	1	2	3	4	5	6	7	0	1	2	3
Phase A	IN ₁	H	H	L	L	L	L	H	H	H	L	L	L
	IN ₂	L	L	H	H	H	H	L	L	L	L	L	H
Phase B	IN ₁	L	H	H	H	L	L	L	L	L	H	H	H
	IN ₂	L	L	L	L	L	H	H	H	L	L	L	L

■External Dimensions

(Unit : mm)



SLA7042M/SLA7044M 2W1-2 Phase Excitation/Micro-step Support


Absolute Maximum Ratings

Parameter	Symbol	Ratings		Units
		SLA7042M	SLA7044M	
Motor supply voltage	V _{CC}	46		V
FET Drain-Source voltage	V _{DSS}	100		V
Control supply voltage	V _{DD}	7		V
Input voltage	V _{IN}	-0.5 to V _{DD} +0.5		V
Output current	I _O	1.2	3.0	A
Power dissipation	P _D	4.5 (Without Heatsink)		W
Channel temperature	T _{ch}	+150		°C
Storage temperature	T _{stg}	-40 to +150		°C


Electrical Characteristics

Parameter	Symbol	Ratings						Units	
		SLA7042M			SLA7044M				
		min	typ	max	min	typ	max		
Control supply current	I _{DD}			7			7	mA	
	Conditions	V _{DD} =5.5V			V _{DD} =5.5V				
Control supply voltage	V _{DD}	4.5	5	5.5	4.5	5	5.5	V	
	V _{IH}	3.5		5	3.5		5		
Terminals DATA, CLOCK and STROBE	Input voltage	Conditions	V _{DD} =5V			V _{DD} =5V			V
		V _{IL}	0		1.5	0		1.5	
		Conditions	V _{DD} =5V			V _{DD} =5V			
	Input hysteresis voltage	V _H	1			1			V
		Conditions	V _{DD} =5V			V _{DD} =5V			
	Input current	I _I			±1			±1	µA
Conditions		V _{DD} =5V, V _I =0 or 5V			V _{DD} =5V, V _I =0 or 5V				
REF terminal	Input voltage	V _{REF}	0.4		2.5	0.4		2.5	V
		Conditions	V _{DD} =5V			V _{DD} =5V			
	V _{DISABLE}	V _{DD} -1		V _{DD}	V _{DD} -1		V _{DD}		
	Conditions	V _{DD} =5V			V _{DD} =5V				
Input current	I _{REF}			±1			±1	µA	
	Conditions	V _{DD} =5V, V _I =0 or 5V			V _{DD} =5V, V _I =0 or 5V				
Step reference current ratio	V _{ref}	0			0			%	
	Conditions	MODE 0			MODE 0				
	V _{ref}	20			20				
	Conditions	MODE 1			MODE 1				
	V _{ref}	40			40				
	Conditions	MODE 2			MODE 2				
	V _{ref}	55.5			55.5				
	Conditions	MODE 3			MODE 3				
	V _{ref}	71.4			71.4				
	Conditions	MODE 4			MODE 4				
	V _{ref}	83			83				
	Conditions	MODE 5			MODE 5				
	V _{ref}	91			91				
	Conditions	MODE 6			MODE 6				
V _{ref}	100			100					
Conditions	MODE 7			MODE 7					
FET ON voltage	V _{DS}			0.8			1.4	V	
	Conditions	I _D =1.2A, V _{DD} =4.75V			I _D =3.0A, V _{DD} =4.75V				
FET Drain-Source voltage	V _{DSS}	100			100			V	
	Conditions	I _{DSS} =4mA, V _{DD} =5V			I _{DSS} =4mA, V _{DD} =5V				
FET drain leakage current	I _{DSS}			4			4	mA	
	Conditions	V _{DSS} =100V, V _{DD} =5V			V _{DSS} =100V, V _{DD} =5V				
FET diode forward voltage	V _{SD}			1.2			2.3	V	
	Conditions	I _D =1.2A			I _D =3A				
Chopper off time	T _{OFF}	7			7			µs	
	Conditions	MODE 1, 2			MODE 1, 2				
	T _{OFF}	9			9				
	Conditions	MODE 3, 4, 5			MODE 3, 4, 5				
	T _{OFF}	11			11				
	Conditions	MODE 6, 7			MODE 6, 7				
Switching time	T _r	0.5			0.5			µs	
	Conditions	V _{DD} =5V, I _D =1A			V _{DD} =5V, I _D =1A				
	T _{stg}	0.7			0.7				
	Conditions	V _{DD} =5V, I _D =1A			V _{DD} =5V, I _D =1A				
	T _f	0.1			0.1				
Conditions	V _{DD} =5V, I _D =1A			V _{DD} =5V, I _D =1A					
Data setup time "A"	t _{SDAT}	75			75			ns	
Conditions	Data active time before clock ↓			Data active time before clock ↓					
Data hold time "B"	t _{HDAT}	75			75				
Conditions	Data active time before clock ↓			Data active time before clock ↓					
Data pulse time "C"	t _{WDAT}	150			150				
Conditions									
Clock pulse width "D"	t _{WHCLK}	100			100				
Conditions									
Strobe stability time "E"	t _{SSSTB}	100			100				
Conditions	Time from clock ↓ to Strobe ↓			Time from clock ↓ to Strobe ↓					
Strobe pulse H width "F"	t _{WHSTB}	100			100				
Conditions									

Internal Block Diagram




Serial Data Pattern



Successively output this serial data and set any current. Then, determine the step time of the reference voltage Vref with STROBE signal intervals.

Diagram of Standard External Circuit




Output Current Formula

$$I_{O} = \frac{K}{3} \cdot \frac{V_{REF}}{R_s}$$

K: Reference voltage setting ratio by serial signal (See the internal block diagram)

External Dimensions

(Unit : mm)



Forming No. No.871

Forming No. No.872

SLA7065M/SLA7066M/SLA7067M 2-Phase/2W 1-2 Phase Excitation Support, Built-in Sequencer

Features

- Main supply voltage VBB: 46V (max), 10 to 44V recommended
- Logic supply voltage VDD: 3.0 to 5.5V support
- Lineup of output current Io: 1A, 2A, 3A (maximum set current)
- Supporting the clock-input-method micro-step drive (built-in sequencer)
- 2-phase excitation to 2W 1-2 phase excitation support
- Self-excitation PWM current control method
- Built-in synchronous chopping function to prevent the audible motor noise in the hold state
- ZIP type 21-Pin mold package (SLA package)

Absolute Maximum Ratings

(Ta=25°C)

Parameter	Symbol	Ratings			Unit
		SLA7065M	SLA7066M	SLA7067M	
Motor Supply Voltage	V _M	46			V
Driver Supply Voltage	V _{BB}	46			V
Logic Supply Voltage	V _{DD}	7			V
Output Current	I _o	1.0	2.0	3.0	A
Logic Input Voltage	V _{IN}	-0.3 to V _{DD} +0.3			V
REF Input Voltage	V _{REF}	-0.3 to V _{DD} +0.3			V
Sense Voltage	V _{RS}	-2 to +2 (tw >1μs)			V
Power Dissipation	P _d	3.5 (Without Heatsink)			W
Junction Temperature	T _j	+150			°C
Operating Ambient Temperature	T _a	-20 to +85			°C
Storage Temperature	T _{stg}	-30 to +150			°C

Recommended Operating Conditions

Parameter	Symbol	Ratings		Unit	Remarks
		min	max		
Motor Supply Voltage	V _M		44	V	
Driver Supply Voltage	V _{BB}	10	44	V	
Logic Supply Voltage	V _{DD}	3.0	5.5	V	The V _{DD} surge voltage should be 0.5V or lower.
REF Input Voltage	V _{REF}	0.1	1.0	V	The control current precision is degraded at 0.1V or lower.
Case Temperature	T _C		90	°C	Temperature at pin-11 Lead (Without heatsink)


Electrical Characteristics

(VDD=5V, VBB=24V, Ta=25°C, unless otherwise specified)

Parameter	Symbol	Ratings									Unit
		SLA7065M			SLA7066M			SLA7067M			
		min	typ	max	min	typ	max	min	typ	max	
Main Supply Current	I _{BB}			15			15			15	mA
	Conditions	In operation			In operation			In operation			
	I _{BBs}			100			100			100	
Logic Supply Current	I _{DD}			4			4			4	mA
	Conditions	Sleep mode			Sleep mode			Sleep mode			
Output MOSFET Breakdown Voltage	V _{(BR) DS}	100			100			100			V
	Conditions	V _{BB} =44V, I _D =1mA			V _{BB} =44V, I _D =1mA			V _{BB} =44V, I _D =1mA			
Output MOSFET ON Resistance	R _{DS (ON)}		0.7			0.25			0.18		Ω
	Conditions	I _D =1A			I _D =2A			I _D =3A			
Output MOSFET Diode Forward Voltage	V _F		0.85			0.95			0.95		V
	Conditions	I _F =1A			I _F =2A			I _F =3A			
Maximum Clock Frequency	f _{clk}	250			250			250			kHz
	Conditions	When Clock Duty = 50%			When Clock Duty = 50%			When Clock Duty = 50%			
Logic Input Voltage	V _{IL}	V _{DD} -0.75		V _{DD} -0.25	V _{DD} -0.75		V _{DD} -0.25	V _{DD} -0.75		V _{DD} -0.25	V
	V _{IH}		±1			±1			±1		
Logic Input Current	I _{IL}		±1			±1			±1		μA
	Conditions	Clock, Reset, CW/CCW, Sync			Clock, Reset, CW/CCW, Sync			Clock, Reset, CW/CCW, Sync			
	I _{ILM}		-50			-50			-50		
	I _{IH}		±1			±1			±1		
REF Input Voltage	V _{REF}	0		1.5	0		1.5	0		1.5	V
	Conditions	Normal-operation current control			Normal-operation current control			Normal-operation current control			
	V _{REFS}	2		V _{DD}	2		V _{DD}	2		V _{DD}	
REF Input Current	I _{REF}		±10			±10			±10		μA
	Conditions	Output OFF (sleep)			Output OFF (sleep)			Output OFF (sleep)			
Mo Output Voltage	V _{MoL}			1.25			1.25			1.25	V
	Conditions	I _{MoL} =1.5mA			I _{MoL} =1.5mA			I _{MoL} =1.5mA			
	V _{MoH}	V _{DD} -1.25			V _{DD} -1.25			V _{DD} -1.25			
Mo Output Current	I _{MoL}			3			3			3	mA
	I _{MoH}	-3			-3			-3			
Sense Terminal Inflow Current	I _{SENSE}		±10			±10			±10		μA
Sense Voltage	V _{SENSE}	0.95	1.00	1.05	0.95	1.00	1.05	0.95	1.00	1.05	V
	Conditions	When V _{REF} = 1V in Mode F			When V _{REF} = 1V in Mode F			When V _{REF} = 1V in Mode F			
	Mode F		100			100			100		
Step Reference Current Ratio	Mode E		98.1			98.1			98.1		%
	Mode C		92.4			92.4			92.4		
	Mode A		83.1			83.1			83.1		
	Mode 8		70.7			70.7			70.7		
	Mode 6		55.5			55.5			55.5		
	Mode 4		38.2			38.2			38.2		
	Mode 2		19.5			19.5			19.5		
	Conditions	V _{REF} =V _{SENSE} =100%, V _{REF} =0.1 to 1.0V			V _{REF} =V _{SENSE} =100%, V _{REF} =0.1 to 1.0V			V _{REF} =V _{SENSE} =100%, V _{REF} =0.1 to 1.0V			
Switching Time	T _{ONC}		2.0			2.0			2.0		μs
	Conditions	Clock→OutON			Clock→OutON			Clock→OutON			
	T _{OFFC}		1.5			1.5			1.5		
PWM Minimum ON Time	Conditions	Clock→OutOFF			Clock→OutOFF			Clock→OutOFF			
	T _{ON (min)}		1.8			1.8			1.8		μs
	Conditions	Mode 2 to F			Mode 2 to F			Mode 2 to F			
t _{OFF1}		12			12			12			
Chopping OFF Time	Conditions	Mode 8 to F			Mode 8 to F			Mode 8 to F			
	t _{OFF2}		9			9			9		μs
	Conditions	Mode 4 to 6			Mode 4 to 6			Mode 4 to 6			
t _{OFF3}		7			7			7			
Chopping OFF Time	Conditions	Mode 2			Mode 2			Mode 2			
	t _{OFF4}										

The direction in which current flows out of the device is regarded as negative.


Internal Block Diagram



Pin Assignment


Pin No.	Symbol	Function
1	OutA	Phase A output
2		
3	OutA $\bar{}$	Phase A $\bar{}$ output
4		
5	SenseA	Phase A current sense
6	V _{DD}	Logic supply
7	REF	Control current setting & output OFF control input
8	Reset	Internal logic reset input
9	CW/CCW	Normal/reverse control input
10	Clock	Step Clock input
11	GND	Device GND
12	M2	Excitation mode setting input
13	M1	
14	M ₀	2-phase excitation state monitor output
15	Sync	PWM control signal input
16	V _{BB}	Driver supply (motor supply)
17	SenseB	Phase B current sense
18	OutB $\bar{}$	Phase B $\bar{}$ output
19		
20	OutB	Phase B output
21		

Typical Connection Diagram



External Dimensions

(Unit : mm)



SLA7060M/SLA7061M/SLA7062M 1-2 Phase to 4W 1-2 Phase Excitation Support, Built-in Sequencer

Features

- Main supply voltage V_{BB} : 46V (max), 10 to 44V recommended
- Logic supply voltage V_{DD} : 3.0 to 5.5V support
- Lineup of output current I_o : 1A, 2A, 3A (maximum set current)
- Supporting the clock-input-method micro-step drive (built-in sequencer)
- 1-2 phase excitation to 4W 1-2 phase excitation support
- Self-excitation PWM current control method
- Built-in synchronous chopping function to prevent the audible motor noise in the hold state
- ZIP type 21-Pin mold package (SLA package)

Absolute Maximum Ratings

($T_a=25^\circ\text{C}$)

Parameter	Symbol	Ratings			Unit
		SLA7060M	SLA7061M	SLA7062M	
Motor Supply Voltage	V_M	46			V
Driver Supply Voltage	V_{BB}	46			V
Logic Supply Voltage	V_{DD}	7			V
Output Current	I_o	1.0	2.0	3.0	A
Logic Input Voltage	V_{IN}	-0.3 to $V_{DD}+0.3$			V
REF Input Voltage	V_{REF}	-0.3 to $V_{DD}+0.3$			V
Sense Voltage	V_{RS}	-2 to +2 (tw > 1 μs)			V
Power Dissipation	P_d	3.5 (Without Heatsink)			W
Junction Temperature	T_j	+150			$^\circ\text{C}$
Operating Ambient Temperature	T_a	-20 to +85			$^\circ\text{C}$
Storage Temperature	T_{stg}	-30 to +150			$^\circ\text{C}$

Recommended Operating Conditions

Parameter	Symbol	Ratings		Unit	Remarks
		min	max		
Motor Supply Voltage	V_M		44	V	
Driver Supply Voltage	V_{BB}	10	44	V	
Logic Supply Voltage	V_{DD}	3.0	5.5	V	The V_{DD} surge voltage should be 0.5V or lower.
REF Input Voltage	V_{REF}	0.1	1.0	V	The control current precision is degraded at 0.1V or lower.
Case Temperature	T_C		90	$^\circ\text{C}$	Temperature at Pin-11 Lead (Without heatsink)


Electrical Characteristics

($V_{DD}=5V, V_{BB}=24V, T_a=25^\circ\text{C}$, unless otherwise specified)

Parameter	Symbol	Ratings								Unit	
		SLA7060M			SLA7061M			SLA7062M			
		min	typ	max	min	typ	max	min	max		
Main Supply Current	I_{BB}			15			15		15	mA	
	Conditions	In operation			In operation			In operation			
	Conditions	Sleep mode			Sleep mode			Sleep mode			
Logic Supply Current	I_{DD}			4			4		4	mA	
Output MOSFET Breakdown Voltage	$V_{(BR)DS}$	100			100			100			V
Output MOSFET ON Resistance	$R_{DS(ON)}$	$V_{BB}=44V, I_D=1mA$			$V_{BB}=44V, I_D=1mA$			$V_{BB}=44V, I_D=1mA$			
Output MOSFET Diode Forward Voltage	V_F		0.7			0.25			0.18	V	
Maximum Clock Frequency	Conditions	$I_D=1A$			$I_D=2A$			$I_D=3A$			
	Conditions	$I_F=1A$			$I_F=2A$			$I_F=3A$			
	Conditions	$I_F=1A$			$I_F=2A$			$I_F=3A$			
Logic Input Voltage	f_{clk}	250			250			250		kHz	
	Conditions	When Clock Duty = 50%			When Clock Duty = 50%			When Clock Duty = 50%			
	Conditions	$V_{DD} \cdot 0.25$			$V_{DD} \cdot 0.25$			$V_{DD} \cdot 0.25$			
Logic Input Current	V_{IL}	$V_{DD} \cdot 0.75$			$V_{DD} \cdot 0.75$			$V_{DD} \cdot 0.75$		V	
	V_{IH}		+1			+1		+1			
	Conditions	Clock, Reset, CW/CCW, Sync			Clock, Reset, CW/CCW, Sync			Clock, Reset, CW/CCW, Sync			
REF Input Voltage	I_{ILM}		-50			-50			-50	μA	
	I_{IH}		+1			+1		+1			
	Conditions	M1, M2			M1, M2			M1, M2			
REF Input Current	V_{REF}	0		1.5	0		1.5	0		V	
	Conditions	Normal-operation current control			Normal-operation current control			Normal-operation current control			
	Conditions	Output OFF (sleep)			Output OFF (sleep)			Output OFF (sleep)			
Mo Output Voltage	I_{REF}		+10			+10			+10	μA	
	Conditions	$I_{MOL}=1.5mA$			$I_{MOL}=1.5mA$			$I_{MOL}=1.5mA$			
	Conditions	$I_{MOH}=-1.5mA$			$I_{MOH}=-1.5mA$			$I_{MOH}=-1.5mA$			
Mo Output Current	V_{MOL}	$V_{DD}-1.25$			$V_{DD}-1.25$			$V_{DD}-1.25$		V	
	Conditions	$I_{MOH}=-1.5mA$			$I_{MOH}=-1.5mA$			$I_{MOH}=-1.5mA$			
	Conditions	$I_{MOH}=-1.5mA$			$I_{MOH}=-1.5mA$			$I_{MOH}=-1.5mA$			
Sense Terminal Inflow Current	I_{MOL}			3			3		3	mA	
	I_{MOH}	-3			-3			-3			
	Conditions	$I_{MOH}=-1.5mA$			$I_{MOH}=-1.5mA$			$I_{MOH}=-1.5mA$			
Sense Voltage	I_{SENSE}		+10			+10			+10	μA	
	Conditions	When $V_{REF} = 1V$ in Mode F			When $V_{REF} = 1V$ in Mode F			When $V_{REF} = 1V$ in Mode F			
	Conditions	When $V_{REF} = 1V$ in Mode F			When $V_{REF} = 1V$ in Mode F			When $V_{REF} = 1V$ in Mode F			
Step Reference Current Ratio	V_{SENSE}	0.95	1.00	1.05	0.95	1.00	1.05	0.95	1.00	1.05	%
	Mode F		100			100			100		
	Mode E		98.1			98.1			98.1		
	Mode D		95.7			95.7			95.7		
	Mode C		92.4			92.4			92.4		
	Mode B		88.2			88.2			88.2		
	Mode A		83.1			83.1			83.1		
	Mode 9		77.3			77.3			77.3		
	Mode 8		70.7			70.7			70.7		
	Mode 7		63.4			63.4			63.4		
	Mode 6		55.5			55.5			55.5		
	Mode 5		47.1			47.1			47.1		
	Mode 4		38.2			38.2			38.2		
Mode 3		29			29			29			
Mode 2		19.5			19.5			19.5			
Mode 1		9.8			9.8			9.8			
Switching Time	Conditions	$V_{REF} \pm V_{SENSE} = 100\%, V_{REF} = 0.1$ to 1.0V			$V_{REF} \pm V_{SENSE} = 100\%, V_{REF} = 0.1$ to 1.0V			$V_{REF} \pm V_{SENSE} = 100\%, V_{REF} = 0.1$ to 1.0V			
	Conditions	2.0			2.0			2.0			
	Conditions	Clock \rightarrow OutON			Clock \rightarrow OutON			Clock \rightarrow OutON			
PWM Minimum ON Time	T_{OFFC}		1.5			1.5			1.5	μs	
	Conditions	Clock \rightarrow OutOFF			Clock \rightarrow OutOFF			Clock \rightarrow OutOFF			
	Conditions	Clock \rightarrow OutOFF			Clock \rightarrow OutOFF			Clock \rightarrow OutOFF			
Chopping OFF Time	$T_{ON(min)}$		1.8			1.8			1.8	μs	
	Conditions	Mode 1 to F			Mode 1 to F			Mode 1 to F			
	Conditions	Mode 1 to F			Mode 1 to F			Mode 1 to F			
Chopping OFF Time	T_{OFF1}		12			12			12	μs	
	Conditions	Mode 8 to F			Mode 8 to F			Mode 8 to F			
	Conditions	Mode 8 to F			Mode 8 to F			Mode 8 to F			
Chopping OFF Time	T_{OFF2}		9			9			9	μs	
	Conditions	Mode 4 to 7			Mode 4 to 7			Mode 4 to 7			
	Conditions	Mode 4 to 7			Mode 4 to 7			Mode 4 to 7			
Chopping OFF Time	T_{OFF3}		7			7			7	μs	
	Conditions	Mode 1 to 3			Mode 1 to 3			Mode 1 to 3			
	Conditions	Mode 1 to 3			Mode 1 to 3			Mode 1 to 3			

The direction in which current flows out of the product is regarded as negative.


Internal Block Diagram



Pin Assignment


Pin No.	Symbol	Function
1	OutA	Phase A output
2		
3	OutĀ	Phase Ā output
4		
5	SenseA	Phase A current sense
6	V _{DD}	Logic supply
7	REF	Control current setting & output OFF control input
8	Reset	Internal logic reset input
9	CW/CCW	Normal/reverse control input
10	Clock	Step Clock input
11	GND	Device GND
12	M2	Excitation mode setting input
13	M1	
14	M0	2-phase excitation state monitor output
15	Sync	PWM control signal input
16	V _{BB}	Driver supply (motor supply)
17	SenseB	Phase B current sense
18	OutB̄	Phase B̄ output
19		
20	OutB	Phase B output
21		

Typical Connection Diagram



External Dimensions

(Unit : mm)



PG001M Serial Signal Generator IC for SLA7042M and SLA7044M

Absolute Maximum Ratings

(T_a=25°C)

Parameter	Symbol	Ratings	Unit
Supply voltage	V _{DD}	-0.5 to 7	V
Input voltage	V _I	-0.5 to V _{DD} +0.5	V
Input current	I _I	±10	mA
Output voltage	V _O	-0.5 to V _{DD} +0.5	V
Output current	I _O	±15	mA
Power dissipation	P _D	200	mW
Operating temperature	T _{OP}	-20 to +85	°C
Storage temperature	T _{STG}	-40 to +150	°C

Electrical Characteristics

(T_a=25°C)

Parameter	Symbol	Conditions	Ratings			Units	
			min	typ	max		
DC characteristics	Supply voltage	V _{DD}	4.5		5.5	V	
	Supply current	I _{DD}	V _{DD} =5.5V	0.35	0.45	mA	
	Output voltage	V _{OH}	V _{DD} =5V, I _O =±3mA	4.5		0.4	V
		V _{OL}					
	Input current	I _I	V _{DD} =5V, V _I =0 or 5V			±1	µA
	Input voltage	V _{IH}	V _{DD} =5V	3.5		5	V
		V _{IL}		-0.3		1.5	
Input hysteresis voltage	V _H	V _{DD} =5V		1		V	
Input capacity	C _I	V _{DD} =5V		5	10	pF	
AC characteristics	Internal oscillation frequency	F	V _{DD} =5V	1.5		MHz	
	Propagation delay time	T _{CS}	See Fig.1.	50		100	ns
		T _{CC}		430		550	
	Rise and fall time	T _r	V _{DD} =5V, C _L =15pF See Fig.2.	20			ns
		T _f		20			
	CLOCK IN terminal	V _{CIH}	H level time, V _{DD} =5V	4.5			µs
	Input clock time	V _{CIL}	L level time, V _{DD} =5V	0.5			
	Reset setting time (A)	t _{sR}	From/To CLOCK_IN ↑ See Fig.3.	100			ns
Stabilization time after reset input (B)	t _{psR}	See Fig.3.				ns	
Signal setting time (C)	t _{sS}	From/To CLOCK_IN ↑ See Fig.3.	100			ns	
Stabilization time after signal input (D)	t _{psS}	See Fig.3.				ns	

Fig. 1




Fig.2







Fig. 3 Timing conditions



Typical Connection Diagram



Internal Block Diagram



Input and Output Function Correlation Table


Mode	Input			Input Output				
	CLOCK_IN	CW/CCW	RESET	MO	CLOCK_OUT	STROBE	DATA_A	DATA_B
CW	[Waveform]	L	H	[Waveform]	[Waveform]	[Waveform]	CW	CW
CCW	[Waveform]	H	H	[Waveform]	[Waveform]	[Waveform]	CCW	CCW
RESET	[Waveform]	x	L	[Waveform]	[Waveform]	[Waveform]	Output Mode 4 or 7 Output Mode	Input Mode 4 or 7 Output Mode

x : Immaterial
 * : MO outputs L level while CLOCK_IN is H level when output mode is 4:4 (7:7), 4:4 (7:7), 4:4 (7:7), or 4:4 (7:7).
 Modes in brackets () are for 2-2 phase VC:H.

Excitation Selection Table

Excitation method	Input		Output current mode of SLA7042M/7044M								
	Excitation mode selection		0	1	2	3	4	5	6	7	Torque vector
	VC	MS1 MS2	0%	20%	40%	55.5%	71.4%	83%	91%	100%	
2-2 Phase Full Step	H	L L	-	-	-	-	-	-	-	-	141%
	L	L L	-	-	-	-	O	-	-	-	100%
1-2 Phase Half Step	x	H L	O	-	-	-	O	-	-	O	100%
W1-2 Phase 1/4 Step	x	L H	O	-	O	-	O	-	O	O	100%
2W1-2 Phase 1/8 Step	x	H H	O	O	O	O	O	O	O	O	100%

Output Mode Vs Output Pulse




Output Mode Sequence

Excitation method	CW/CCW	CLOCK MO	RESET																																	
			1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32		
2-2 Phase Full Step (1) (VC:H)	CW	DATA_A	7	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	H	L	
		DATA_B	7	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=
	CCW	DATA_A	7	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	
		DATA_B	7	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=
2-2 Phase Full Step (2) (VC:L)	CW	DATA_A	4	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	
		DATA_B	4	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=
	CCW	DATA_A	4	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=
		DATA_B	4	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=
1-2 Phase Half Step	CW	DATA_A	4	=	=	0	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	
		DATA_B	4	=	=	7	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=
	CCW	DATA_A	4	=	=	7	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=
		DATA_B	4	=	=	0	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=	=
W1-2 Phase 1/4 Step	CW	DATA_A	4	=	6	=	7	=	6	=	4	=	2	=	0	=	2	=	4	=	6	=	7	=	6	=	4	=	2	=	0	=	2	=	4	
		DATA_B	4	=	6	=	7	=	6	=	4	=	2	=	0	=	2	=	4	=	6	=	7	=	6	=	4	=	2	=	0	=	2	=	4	
	CCW	DATA_A	4	=	6	=	7	=	6	=	4	=	2	=	0	=	2	=	4	=	6	=	7	=	6	=	4	=	2	=	0	=	2	=	4	
		DATA_B	4	=	6	=	7	=	6	=	4	=	2	=	0	=	2	=	4	=	6	=	7	=	6	=	4	=	2	=	0	=	2	=	4	
2W1-2 Phase 1/8 Step	CW	DATA_A	4	3	2	1	0	1	2	3	4	5	6	7	7	6	5	4	3	2	1	0	1	2	3	4	5	6	7	7	6	5	4	3	2	
		DATA_B	4	5	6	7	7	6	5	4	3	2	1	0	1	2	3	4	5	6	7	7	6	5	4	3	2	1	0	1	2	3	4	5	6	
	CCW	DATA_A	4	5	6	7	7	6	5	4	3	2	1	0	1	2	3	4	5	6	7	7	6	5	4	3	2	1	0	1	2	3	4	5	6	
		DATA_B	4	3	2	1	0	1	2	3	4	5	6	7	7	6	5	4	3	2	1	0	1	2	3	4	5	6	7	7	6	5	4	3	2	

= : No output

External Dimensions

(Unit : mm)



SLA7611M Star Connection/Delta Connection

Absolute Maximum Ratings

(T_a=25°C)

Parameter	Symbol	Ratings	Unit	Remarks
Main Supply Voltage	V _{BB}	36	V	
Logic Supply Voltage	V _{CC}	7	V	
Output Current	I _{O (Ave)}	3	A	
	I _{O (Peak)}	6	A	tw < 1ms
Logic Input Voltage	V _{IN}	-0.3 to V _{CC} +0.3	V	
REF Input Voltage	V _{REF}	-0.3 to V _{CC} +0.3	V	
PFD Input Voltage	V _{PFD}	-0.3 to V _{CC} +0.3	V	
Sense Voltage	V _{RS}	-2 to 2	V	
Power Dissipation	P _D	4	W	Without heatsink
Junction Temperature	T _J	150	°C	
Operating Ambient Temperature	T _a	-20 to 85	°C	
Storage Temperature	T _{stg}	-30 to 150	°C	


Recommended Operating Conditions

Parameter	Symbol	Ratings	Unit	Remarks
Main Supply Voltage	V _{BB}	10 to 30	V	
Logic Supply Voltage	V _{CC}	3 to 5.5	V	The VCC surge voltage should be 0.5V or lower.
REF Input Voltage	V _{REF}	0.2 to V _{CC}	V	The control current precision is degraded at 0.2V or lower.
Case Temperature	T _c	110max	°C	Temperature at Pin-10 Lead (without heatsink)

Electrical Characteristics (T_a = 25°C, V_{BB} = 24V, V_{CC} = 5V, unless otherwise specified)

Parameter	Symbol	Ratings			Unit	Remarks
		min	typ	max		
Main Supply Current	I _{BB}			20	mA	
Logic Supply Current	I _{CC}			10	mA	
Charge Pump Voltage	V _{CP}		V _{BB} +5		V	
Output Withstand Voltage	V _O	36			V	
Output MOS FET ON Resistance (total of the upper and lower values)	R _{DS(on)}			0.8	Ω	I _{OS} =3A
Output MOS FET Diode Forward Voltage	V _{SD}			1.5	V	I _{SD} =3A
Logic Input Voltage	V _{IL}			V _{CC} ×0.25	V	
	V _{IH}	V _{CC} ×0.75			V	
Logic Input Current	I _{IL}		±1		μA	Excluding E _{na}
	I _{IH}		±1		μA	
Maximum Clock Frequency	F _{clock}			100	kHz	
PFD Input Current	I _{PFD}		±10		μA	
RC Terminal Inflow Current	I _{RC}		200		μA	
PFD Input Voltage	V _{PFDs}	1.7		V _{CC}	V	Slow Decay
	V _{PFDm}	0.7		1.3	V	Mixed Decay
	V _{PFDf}			0.3	V	Fast Decay
Sense Voltage	V _{RS}		V _{REF} ×0.2		V	Steady-state
REF Input Voltage	V _{REF}	0		V _{CC}	V	
REF Input Current	I _{REF}		±10		μA	
PWM OFF Time	T _{OFF}		1.1×R _L ×C _t		μs	
Thermal Protection Circuit Activation Temperature	T _J		150		°C	
Hysteresis of Thermal Protection Circuit Activation Temperature	ΔT _J		10		°C	
Switching Time	T _{ONC}		2.5		μs	Clock→Out
	T _{OFFC}		2		μs	Clock→Out


Internal Block Diagram



Pin Assignment (Function Table)


Pin No.	Symbol	Function
1	Sense	Current sense
2	Out U	Phase U output
3	V _{CC}	Logic supply
4	RC	PWM OFF time setting
5	PFD	Mixed Decay ratio setting
6	REF	Control current setting
7	Reset	Internal logic reset
8	Ena	Output Enable/Disable control
9	V _{BB}	Main supply (motor supply)
10	GND	Device GND
11	Out V	Phase V output
12	CW/CCW	Forward/reverse control
13	Clock	Step Clock
14	F/H	Full/half step control
15	CP2	Charge pump capacitor 2
16	CP1	Charge pump capacitor 1
17	Out W	Phase W output
18	V _b	Boost charge pump

Typical Connection Diagram



External Dimensions

(Unit : mm)




1-3 ICs for Switching Mode Power Supplies

STR-A6100 Series

■ Features

- **PRC [Pulse Ratio Control]: (8 μ s fixed off-time, variable on-time)**
 Low-EMI noise operation thanks to the quasi-jittering operation that varies the switching frequency within a range from about 63kHz to 120kHz according to load variations.
- **Auto burst standby: (Power consumption at no load <100mW at AC264V)**
 Enables very low power consumption at no load.
 Typical results of a 5W universal input power supply: Pin= 35mW at AC110V
 Pin=43mW at AC220V
- **Auto bias function**
 This function stabilizes operation during Auto Burst Standby mode, by controlling stably the hiccup mode caused by UVLO. The Auto Bias function forces the IC to turn on before the V_{CC} voltage drops down to V_{CC}(OFF), thereby stabilizing the entire power supply operation.
- **Startup circuit**
 600V BCD process allows direct connection of the STARTUP pin to the rectified high voltage rail. This reduces component count and improves overall efficiency.
- **Current mode control**
- **Leading edge blanking**
 Requires no external Low-pass filter circuit preventing the malfunction due to the surge current at turn-on.
- **Built-in Power MOSFET guaranteeing avalanche energy capability**
 Thus, surge absorber circuit can be simplified and also no VDSS derating is required.
- **Versatile protecting functions**
 - Over current protection ----- Pulse by pulse
 - Over voltage protection ----- With latch
 - Overload protection ----- Auto restart
 - Thermal shutdown ----- With latch



■ Applications


- Battery Charger ----- Cell Phone, Digital Still Camera, Camcorder, Shaver, Emergency light, Guidance light, etc.
- Standby Power Supply ----- CRT TV, Projection TV, LCD TV, PDP TV, Desktop PC, LBP, Audio system, etc.
- Compact SMPS ----- Inkjet printer, DVD Player/Recorder, VCR, Set Top Box, etc. (SMPS: Switching Mode Power Supply)
- Auxiliary Power Supply for Controller-- Air conditioner, Refrigerator, Washer, Dish Washer, etc.

■ Lineup

Part Number	V _{DSS}	R _{DS(ON)}	V _{IN(AC)}	P _{out}
STR-A6131	500V	3.95 Ω	100V/120V	12W
STR-A6132		2.62 Ω	100V/120V	16W
STR-A6153E	650V	1.90 Ω	230V/85V to 264V	24W/20W
STR-A6151		3.95 Ω	230V/85V to 264V	16W/12W
STR-A6159		6.00 Ω	230V/85V to 264V	13W/12W
STR-A6169	800V	19.20 Ω	230V/85V to 264V	8W/5W


■ Typical Connection Diagram (STR-A6159)

(5W Universal input, single output power supply)



■ Electrical Characteristics (STR-A6159)

(Power supply characteristics at input of 85VAC to 264VAC and 5V 1A output)



Transistor

Application Note	148
2-1 Transistor	149
Selection Guide	149
• V_{CE0-Ic}	149
• Audio Transistor	150
• Switching Transistor	151
Specifications List by Part Number	152
2-2 MOS FET	160
Selection Guide	160
• By V_{DSS}	160
Specifications List by Part Number	162
2-3 Transistor and MOS FET Array	166
Specifications List by Part Number	166
Specifications List by Application	170
• Sink Driver Array	170
• Source Driver Array	174
• Motor Driver Array	176
• Array for CRT Monitor S-Distortion Correction Circuit	182
Package Type (Dimensions)	187

Application Note

Since reliability can be affected adversely by improper storage environment or handling methods during Characteristic tests, please observe the following cautions.

■ Cautions for Storage

- Ensure that storage conditions comply with the normal temperature (5 to 35°C) and the normal relative humidity (around 40 to 75%), and avoid storage locations that experience high temperature and humidity, or extreme changes in temperature or humidity.
- Avoid locations where dust or harmful gases are present, and avoid direct sunlight.
- Reinspect the devices for rust in leads and solderability after stored for a long time.

■ Cautions for Characteristic Tests and Handling

On characteristics test at incoming inspection, etc, take good care to avoid the surge voltages from the test equipment, the short circuit at terminals, or the wrong connection.

■ Silicone Grease

When using a heatsink, please coat thinly and evenly the back surface of the device and both surfaces of the insulating plate with silicone grease to lower the thermal resistance between the device and the heatsink. Please select proper silicone grease carefully since the oil in some grease products may penetrate the device and result in an extremely short device life.

Recommended Silicone Grease

- G-746 (Shin-Etsu Chemical)
- YG6260 (GE Toshiba Silicones)
- SC102 (Dow Corning Toray Silicone)

■ Mounting Torque

When mounting torque is insufficient, thermal resistance increases, and so heat radiation effect is decreased. When the torque is excessive, the screw may be broken, the heatsink may be deformed, and the device frame may be distorted, resulting in the device damage. Recommended mounting torque per package is as follows:

● Mounting Torque Table

Package	Screw Torque
MT-25 (TO-220)	0.490 to 0.686 N•m (5 to 7kgf•cm)
FM20 (TO-220 Full Mold)	
MT-100 (TO-3P)	0.686 to 0.882 N•m (7 to 9kgf•cm)
FM100 (TO-3P Full Mold)	
MT-200 (two-point mount)	
2GR (one-point mount)	0.588 to 0.784 N•m (6 to 8kgf•cm)
SLA	

* When the surface of a heatsink where Full Mold package is to be mounted is not flat due to the burred metal bracket for screwing around the mounting hole of the heatsink, the resin of the package might be cracked even if the torque is lower than the recommended value.

* When a screw is fastened with an air driver for the Full Mold package, a large impact is generated at the time of stop, and the resin may crack even if the torque is lower than the recommended value. An electric driver, therefore, should be used instead of an air driver.

■ Heatsink

A larger contact area between the device and the heatsink is required for more effective heat radiation. To ensure a larger contact area, minimize mounting holes. And select a heatsink with a surface smooth enough and free from burrs and slivers.

■ Soldering Temperature

In general, the device mounted on a printed circuit board is subjected to high temperatures from flow solder in a solder bath, or, from a soldering iron at hand soldering.

The testing method and test conditions (JIS-C-7021 standards) for a device's heat resistance to soldering are:

At a distance of 1.5mm from the device's main body, apply 260°C for 10 seconds, and 350°C for 3 seconds.

Please observe these limits and finish soldering in as short a time as possible.

■ Antistatic measure for power MOSFET arrays

- When handling the device, body grounding is necessary. Wear a wrist strap with a 1 MΩ resistor close to the body in the wrist strap to prevent electric shock.
- Use a conductive tablemat and a floor mat at the device-handling workbench and ground them properly.
- When using a curve tracer or other measuring equipment, ground them as well.
- In soldering, ground the soldering iron tip and the solder bath to prevent a leakage voltage from damaging the device.
- As an antistatic measure for device containers, use Sanken shipping containers or a conductive containers, or use aluminum foils. Since reliability can be affected adversely by improper storage environment or handling methods during Characteristic tests, please observe the following cautions.

Selection Guide

$V_{CEO}-I_c$

Collector-Emitter Voltage $V_{CEO}(V)$	800		C3678 C4020 C4299 C4304 C4445 C4908		C3679 C4300		C3680 C4301 C5002 C5003		C5124									
	600		C5249									C4706 C5924						
	550		C4517 C4517A C5239		C4518 C4518A C5287 C5586				C3927 C4557									
	500					C3830 C4907			C3831									
	450							C5830										
	400				C4073 C4418 C4662 C5130		C3832 C3890 C4130 C4546		C4138 C4296	C3833 C4297 C5071		C4139 C4298 C4434				C4140		
	380					D2141												
	300	C2023 C5333																
	250					D2017												
	230											A1294 C3263 A2151A C6011A			A1295 C3264			
	200	A1668 C4382	D2016		C5271 D2557 D2558							A1493 C3857 A2151 C6011			A1494 C3858			
	180	A1859A C4883A										A1386A A1492 A1673 C3519A C3856 C4388			A1216 C2922			
	160											A1215 A1386 C2921 C3519						
	150	A1667 A1859 C4381 C4883						B1559 B1587 D2389 D2438	A1186 B1560 B1588 C2837 D2390 D2439	B1570 D2401	A1303 A1860 C3284 C4886	B1647 B1649 D2560 D2562			B1648 D2561			
	140								A1695 A1909 C4468 C5101									
	120			D2015		D1769 D1785 D2045	C3834 C3835 C4153	A1694 A1908 C4467 C5100	B1259 D2081					B1382 B1420 D2082				B1383 D2083
	110					B1659 B1685 B1686 B1687 D2589 D2641 D2642 D2643												
	100					B1258												
	80		C3852A	A1488A C3851A D2014		A1693 A1725 A1726 A1907 C4466 C4511 C4512 C5099												
60		C3852	A1262 A1488 B1257 C3179 C3851 D1796							A1568 B1351 B1352 C4065								
50		C4495						A2042 C4024	A1567 A1746 C4064		C4131							
40										C5370								
		2	3	4	5	6	7	8	10	12	14	15	16	17	18	25		

Collector Current $I_c(A)$

Audio Transistor

Output Transistor

P _c (W)	I _c (A)	V _{CE0} (V)	Chip						Package Type
			Single Transistor				Darlington		
			General		LAPT				
30	6	80	2SA1725	2SC4511					TO-220F
	6	110					2SB1686	2SD2642	TO-220F
50	6	80	2SA1726	2SC4512					TO-220
	6	110					2SB1659	2SD2589	TO-220
60	6	80	2SA1693	2SC4466					TO-3P
	6	80	2SA1907	2SC5099					TO-3PF
	6	110					2SB1685	2SD2641	TO-3P
	6	110					2SB1687	2SD2643	TO-3PF
75	8	120	2SA1908	2SC5100					TO-3PF
	8	150					2SB1587	2SD2438	TO-3PF
80	8	120	2SA1694	2SC4467					TO-3P
	10	140	2SA1909	2SC5101					TO-3PF
	8	150					2SB1559	2SD2389	TO-3P
	10	150					2SB1588	2SD2439	TO-3PF
	14	150			2SA1860	2SC4886			TO-3PF
85	15	150					2SB1649	2SD2562	TO-3PF
	15	180	2SA1673	2SC4388					TO-3PF
100	10	140	2SA1695	2SC4468					TO-3P
	10	150			2SA1186	2SC2837			TO-3P
	10	150					2SB1560	2SD2390	TO-3P
125	14	150			2SA1303	2SC3284			TO-3P
130	15	150					2SB1647	2SD2560	TO-3P
	15	160			2SA1386	2SC3519			TO-3P
	15	180	2SA1492	2SC3856					TO-3P
	15	180			2SA1386A	2SC3519A			TO-3P
	15	230			2SA1294	2SC3263			TO-3P
150	12	150					2SB1570	2SD2401	MT-200 (fixed at two points)
	15	160			2SA1215	2SC2921			MT-200 (fixed at two points)
	15	200	2SA1493	2SC3857					MT-200 (fixed at two points)
160	15	200	2SA2151	2SC6011					TO-3P
	15	230	2SA2151A	2SC6011A					TO-3P
200	17	150					2SB1648	2SD2561	MT-200 (fixed at two points)
	17	180			2SA1216	2SC2922			MT-200 (fixed at two points)
	17	200	2SA1494	2SC3858					MT-200 (fixed at two points)
	17	230			2SA1295	2SC3264			MT-200 (fixed at two points)

LAPT: Multi-Emitter for High Frequency

Output Transistor with Temperature Compensating Function (Refer to our Web site for applications)

Part Number		P _c (W)	I _c (A)	V _{CE0} (V)	Package Type
SAP09P	SAP09N	80	10	150	SAP (Original 5-pin power package)
SAP10P	SAP10N	100	12	150	SAP (Original 5-pin power package)
SAP15P	SAP15N	150	15	160	SAP (Original 5-pin power package)

Driver and Temperature Compensating Transistor

Part Number		P _c (W)	V _{CE0} (V)	I _c (A)	h _{FE} (min)	f _T (MHz)	Package Type	Remarks
2SC4495		25	50	3	500	40	TO-220F	For temperature compensation
2SA1859	2SC4883	20	150	2	60	60/120	TO-220F	Driver
2SA1859A	2SC4883A	20	180	2	60	60/120	TO-220F	Driver
2SA1667	2SC4381	25	150	2	60	20/15	TO-220F	Driver
2SA1668	2SC4382	25	200	2	60	20/15	TO-220F	Driver

Refer to our Web site for the h_{FE} ranks.

Switching Transistor

■DC-DC Converter

Part Number	V _{CB0} (V)	V _{CE0} (V)	I _c (A)	P _c (W)	Package Type
2SC5370	60	40	12	30	TO-220F
2SC4024	100	50	10	35	TO-220F
2SC4131			15	60	TO-3PF
2SC4153	200	120	7	30	TO-220F
2SC3834				50	TO-220
2SC3835				70	TO-3P

■For AC100V Input

Part Number	V _{CB0} (V)	V _{CE0} (V)	I _c (A)	P _c (W)	Package Type		
2SC5271	250	200	5	30	TO-220F		
2SC4073				30	TO-220F		
2SC4418				30	TO-220F		
2SC4662				30	TO-220F		
2SC3890			7	30	TO-220F		
2SC4130				30	TO-220F		
2SC3832			50	TO-220			
2SC4296			500	400	10	75	TO-3PF
2SC4138						80	TO-3P
2SC4297					12	75	TO-3PF
2SC3833						100	TO-3P
2SC5071						100	TO-3P
2SC4298						80	TO-3PF
2SC4139			15	120	TO-3P		
2SC4434				120	TO-3P		
2SC4140			18	TO-3P			
2SC5130	600	400	5	30	TO-220F		
2SC4546			7	30	TO-220F		
2SC4907		500	6	30	TO-220F		
2SC3830			50	TO-220			
2SC3831		10	100	TO-3P			
2SC5249		600	3	35	TO-220F		

■For AC200V Input

Part Number	V _{CB0} (V)	V _{CE0} (V)	I _c (A)	P _c (W)	Package Type	
2SC4517	900	550	3	30	TO-220F	
2SC5239				50	TO-220	
2SC4518			5	35	TO-220F	
2SC5287				80	TO-3P	
2SC4557			10	80	TO-3PF	
2SC3927				120	TO-3P	
2SC5586		600	5	70	TO-3PF	
2SC4706			14	130	TO-3P	
2SC5924		800	800	3	90	TO-3PF
2SC4908					35	TO-220F
2SC4304					35	TO-220F
2SC4020					50	TO-220
2SC4445				60	60	TO-3PF
2SC4299					70	TO-3PF
2SC3678				80	80	TO-3P
2SC4300					75	TO-3PF
2SC3679	5			100	TO-3P	
2SC4301	7			80	TO-3PF	
2SC3680		120	TO-3P			
2SC4517A	1000	550	3	30	TO-220F	
2SC4518A			5	35	TO-220F	
2SC5002	1500	800	7	80	TO-3PF	
2SC5124			10	100	TO-3PF	

Specifications List by Part Number

Part Number	Applications	Absolute Maximum Ratings						I _{CBO}		h _{FE}		Conditions	
		V _{CB0}	V _{CE0}	I _c	P _c	I _{CBO}	Conditions	min	max	V _{CE}	I _c	Conditions	
		(V)	(V)	(A)	(W)								(μA)
2SA1186	Audio, general-purpose	-150	-150	-10	100	-100	-150	50	180	-4	-3		
2SA1215	Audio, general-purpose	-160	-160	-15	150	-100	-160	50	180	-4	-5		
2SA1216	Audio, general-purpose	-180	-180	-17	200	-100	-180	30	180	-4	-8		
2SA1262	Audio, general-purpose	-60	-60	-4	30	-100	-60	40		-4	-1		
2SA1294	Audio, general-purpose	-230	-230	-15	130	-100	-230	50	140	-4	-5		
2SA1295	Audio, general-purpose	-230	-230	-17	200	-100	-230	50	140	-4	-5		
2SA1303	Audio, general-purpose	-150	-150	-14	125	-100	-150	50	180	-4	-5		
2SA1386	Audio, general-purpose	-160	-160	-15	130	-100	-160	50	180	-4	-5		
2SA1386A	Audio, general-purpose	-180	-180	-15	130	-100	-180	50	180	-4	-5		
2SA1488	Audio, general-purpose	-60	-60	-4	25	-100	-60	40		-4	-1		
2SA1488A	Audio, general-purpose	-80	-80	-4	25	-100	-80	40		-4	-1		
2SA1492	Audio, general-purpose	-180	-180	-15	130	-100	-180	50	180	-4	-3		
2SA1493	Audio, general-purpose	-200	-200	-15	150	-100	-200	50	180	-4	-5		
2SA1494	Audio, general-purpose	-200	-200	-17	200	-100	-200	50	180	-4	-8		
2SA1567	DC motor driver, chopper regulator, general-purpose	-50	-50	-12	35	-100	-50	50		-1	-6		
2SA1568	DC motor driver, chopper regulator, general-purpose	-60	-60	±12	35	-100	-60	50		-1	-6		
2SA1667	TV vertical output, audio output driver, general-purpose	-150	-150	-2	25	-10	-150	60		-10	-0.7		
2SA1668	TV vertical output, audio output driver, general-purpose	-200	-200	-2	25	-10	-200	60		-10	-0.7		
2SA1673	Audio, general-purpose	-180	-180	-15	85	-10	-180	50	180	-4	-3		
2SA1693	Audio, general-purpose	-80	-80	-6	60	-10	-80	50	180	-4	-2		
2SA1694	Audio, general-purpose	-120	-120	-8	80	-10	-120	50	180	-4	-3		
2SA1695	Audio, general-purpose	-140	-140	-10	100	-10	-140	50	180	-4	-3		
2SA1725	Audio, general-purpose	-80	-80	-6	30	-10	-80	50	180	-4	-2		
2SA1726	Audio, general-purpose	-80	-80	-6	50	-10	-80	50	180	-4	-2		
2SA1746	Chopper regulator, switch, general-purpose	-70	-50	-12 (Pulse -20)	60	-10	-70	50		-1	-5		
2SA1859	Audio output driver, TV velocity modulation	-150	-150	-2	20	-10	-150	60	240	-10	-0.7		
2SA1859A	Audio output driver, TV velocity modulation	-180	-180	-2	20	-10	-180	60	240	-10	-0.7		
2SA1860	Audio, general-purpose	-150	-150	-14	80	-100	-150	50	180	-4	-5		
2SA1907	Audio, general-purpose	-80	-80	-6	60	-10	-80	50	180	-4	-2		
2SA1908	Audio, general-purpose	-120	-120	-8	75	-10	-120	50	180	-4	-3		
2SA1909	Audio, general-purpose	-140	-140	-10	80	-10	-140	50	180	-4	-3		
2SA2151	Audio, general-purpose	-200	-200	-15	160	-10	-200	50	180	-4	-3		
2SA2151A	Audio, general-purpose	-230	-230	-15	160	-10	-230	50	180	-4	-3		
2SA2042	Chopper regulator, switch, general-purpose	-50	-50	-10 (Pulse -20)	30	-10	-50	130	310	-2	-1		
2SB1257	Solenoid/relay/motor driver, general-purpose	-60	-60	-4 (Pulse -6)	25	-10	-60	2000		-4	-3		
2SB1258	Solenoid/relay/motor driver, general-purpose	-100	-100	-6 (Pulse -10)	30	-10	-100	1000		-2	-3		
2SB1259	Solenoid/relay/motor driver, general-purpose	-120	-120	-10 (Pulse -15)	30	-10	-120	2000		-4	-5		
2SB1351	Printer head/solenoid/relay/motor driver, general-purpose	-60	-60	-12 (Pulse -20)	30	-10	-60	2000		-4	-10		
2SB1352	Printer head/solenoid/relay/motor driver, general-purpose	-60	-60	-12 (Pulse -20)	60	-10	-60	2000		-4	-10		
2SB1382	Chopper regulator, DC motor driver, general-purpose	-120	-120	-16 (Pulse -26)	75	-10	-120	2000		-4	-8		
2SB1383	Chopper regulator, DC motor driver, general-purpose	-120	-120	-25 (Pulse -40)	120	-10	-120	2000		-4	-12		
2SB1420	Chopper regulator, DC motor driver, general-purpose	-120	-120	-16 (Pulse -26)	80	-10	-120	2000		-4	-8		
2SB1559	Audio, series regulator, general-purpose	-160	-150	-8	80	-100	-160	5000	30000	-4	-6		
2SB1560	Audio, series regulator, general-purpose	-160	-150	-10	100	-100	-160	5000	30000	-4	-7		
2SB1570	Audio, series regulator, general-purpose	-160	-150	-12	150	-100	-160	5000	30000	-4	-7		
2SB1587	Audio, series regulator, general-purpose	-160	-150	-8	75	-100	-160	5000	30000	-4	-6		
2SB1588	Audio, series regulator, general-purpose	-160	-150	-10	80	-100	-160	5000	30000	-4	-7		
2SB1647	Audio, series regulator, general-purpose	-150	-150	-15	130	-100	-150	5000	30000	-4	-10		
2SB1648	Audio, series regulator, general-purpose	-150	-150	-17	200	-100	-150	5000	30000	-4	-10		
2SB1649	Audio, series regulator, general-purpose	-150	-150	-15	85	-100	-150	5000	30000	-4	-10		
2SB1659	Audio, series regulator, general-purpose	-110	-110	-6	50	-100	-110	5000	30000	-4	-5		

Electrical Characteristics												Complementary	Package Type
V _{CE} (sat)	V _{BE} (sat)	Conditions			f _T	Switching Time			C _{ob}				
(V)	(V)	I _c	I _b	MHz	V _{CE}	I _E	t _{on}	t _{stg}		t _i			
max	max	(A)	(A)		(V)	(A)	(μs)	(μs)	(μs)	(pF)			
-2.0		-5	-0.5	60	-12	1	0.25typ	0.8typ	0.2typ	110typ	2SC2837	TO3P (MT-100)	
-2.0		-5	-0.5	50	-12	2	0.25typ	0.85typ	0.2typ	400typ	2SC2921	MT-200	
-2.0		-8	-0.8	40	-12	2	0.3typ	0.7typ	0.2typ	500typ	2SC2922	MT-200	
-0.6		-2	-0.2	15	-12	0.2	0.25typ	0.75typ	0.25typ	90typ	2SC3179	TO220 (MT-25)	
-2.0		-5	-0.5	35	-12	2	0.35typ	1.5typ	0.3typ	500typ	2SC3263	TO3P (MT-100)	
-2.0		-5	-0.5	35	-12	2	0.35typ	1.5typ	0.3typ	500typ	2SC3264	MT-200	
-2.0		-5	-0.5	50	-12	2	0.25typ	0.85typ	0.2typ	400typ	2SC3284	TO3P (MT-100)	
-2.0		-5	-0.5	40	-12	2	0.3typ	0.7typ	0.2typ	500typ	2SC3519	TO3P (MT-100)	
-2.0		-5	-0.5	40	-12	2	0.3typ	0.7typ	0.2typ	500typ	2SC3519A	TO3P (MT-100)	
-0.5		-2	-0.2	15	-12	0.2	0.25typ	0.75typ	0.25typ	90typ	2SC3851	TO220F (FM20)	
-0.5		-2	-0.2	15	-12	0.2	0.25typ	0.75typ	0.25typ	90typ	2SC3851A	TO220F (FM20)	
-2.0		-5	-0.5	20	-12	0.5	0.6typ	0.9typ	0.2typ	500typ	2SC3856	TO3P (MT-100)	
-3.0		-10	-1	20	-12	0.5	0.3typ	0.9typ	0.2typ	400typ	2SC3857	MT-200	
-2.5		-10	-1	20	-12	1	0.6typ	0.9typ	0.2typ	500typ	2SC3858	MT-200	
-0.35		-6	-0.3	40	-12	0.5	0.4typ	0.4typ	0.2typ	330typ	2SC4064	TO220F (FM20)	
-0.35		-6	-0.3	40	-12	0.5	0.4typ	0.4typ	0.2typ	330typ	2SC4065	TO220F (FM20)	
-1.0		-0.7	-0.07	20	-12	0.2	0.4typ	1.5typ	0.5typ	60typ	2SC4381	TO220F (FM20)	
-1.0		-0.7	-0.07	20	-12	0.2	0.4typ	1.5typ	0.5typ	60typ	2SC4382	TO220F (FM20)	
-2.0		-5	-0.5	20	-12	0.5	0.6typ	0.9typ	0.2typ	500typ	2SC4388	TO3PF (FM100)	
-1.5		-2	-0.2	20	-12	0.5	0.18typ	1.1typ	0.21typ	150typ	2SC4466	TO3P (MT-100)	
-1.5		-3	-0.3	20	-12	0.5	0.14typ	1.4typ	0.21typ	300typ	2SC4467	TO3P (MT-100)	
-0.5		-5	-0.5	20	-12	0.5	0.17typ	1.86typ	0.27typ	400typ	2SC4468	TO3P (MT-100)	
-0.5		-2	-0.2	20	-12	0.5	0.18typ	1.1typ	0.21typ	150typ	2SC4511	TO220F (FM20)	
-0.5		-2	-0.2	20	-12	0.5	0.18typ	1.1typ	0.21typ	150typ	2SC4512	TO220 (MT-25)	
-0.5	-1.2	-5	-0.08	25	-12	1	0.5typ	0.6typ	0.3typ	400typ		TO3PF (FM100)	
-1.0		-0.7	-0.07	60	-12	0.7	0.5typ	1typ	0.5typ	30typ	2SC4883	TO220F (FM20)	
-1.0		-0.7	-0.07	60	-12	0.7	0.5typ	1typ	0.5typ	30typ	2SC4883A	TO220F (FM20)	
-2.0		-5	-0.5	50	-12	2	0.25typ	0.85typ	0.2typ	400typ	2SC4886	TO3PF (FM100)	
-0.5		-12	-0.2	20	-12	0.5	0.18typ	1.1typ	0.21typ	150typ	2SC5099	TO3PF (FM100)	
-0.5		-3	-0.3	20	-12	0.5	0.14typ	1.4typ	0.21typ	300typ	2SC5100	TO3PF (FM100)	
-0.5		-5	-0.5	20	-12	0.5	0.17typ	1.86typ	0.27typ	400typ	2SC5101	TO3PF (FM100)	
-0.5		-5	-0.5	20	-12	-0.5	-	-	-	450typ	2SC6011	TO3P (MT-100)	
-0.5		-5	-0.5	20	-12	-0.5	-	-	-	450typ	2SC6011A	TO3P (MT-100)	
-0.5		-5	-0.1	60	-12	0.5	0.2typ	0.7typ	0.1typ	375typ		TO220F (FM20)	
-1.5	-2.0	-3	-0.006	200	-12	0.2	0.4typ	0.8typ	0.6typ	75typ	2SD2014	TO220F (FM20)	
-1.5	-2.0	-3	-0.006	100	-12	0.2	0.6typ	1.6typ	0.5typ	100typ	2SD1785	TO220F (FM20)	
-1.5	-2.0	-5	-0.01	100	-12	0.2	0.6typ	1.6typ	0.5typ	145typ	2SD2081	TO220F (FM20)	
-1.5	-2.0	-10	-0.02	130	-12	1	0.7typ	1.5typ	0.6typ	170typ		TO220F (FM20)	
-1.5	-2.0	-10	-0.02	130	-12	1	0.7typ	1.5typ	0.6typ	170typ		TO3PF (FM100)	
-1.5	-2.5	-8	-0.016	50	-12	1	0.8typ	1.8typ	1typ	350typ	2SD2082	TO3PF (FM100)	
-1.8	-2.5	-12	-0.024	50	-12	1	1typ	3typ	1typ	230typ	2SD2083	TO3P (MT-100)	
-1.5	-2.5	-8	-0.016	50	-12	1	1typ	3typ	1typ	350typ		TO3P (MT-100)	
-2.5	-3.0	-6	-0.006	65	-12	1	0.7typ	3.6typ	0.9typ	160typ	2SD2389	TO3P (MT-100)	
-2.5	-3.0	-7	-0.007	50	-12	2	0.8typ	3typ	1.2typ	230typ	2SD2390	TO3P (MT-100)	
-2.5	-3.0	-7	-0.007	50	-12	2	0.8typ	3typ	1.2typ	230typ	2SD2401	MT-200	
-2.5	-3.0	-6	-0.006	65	-12	1	0.7typ	3.6typ	0.9typ	160typ	2SD2438	TO3PF (FM100)	
-2.5	-3.0	-7	-0.007	50	-12	2	0.8typ	3typ	1.2typ	230typ	2SD2439	TO3PF (FM100)	
-2.5	-3.0	-10	-0.01	45	-12	2	0.7typ	1.6typ	1.1typ	320typ	2SD2560	TO3P (MT-100)	
-2.5	-3.0	-10	-0.01	45	-12	2	0.7typ	1.6typ	1.1typ	320typ	2SD2561	MT-200	
-2.5	-3.0	-10	-0.01	45	-12	2	0.7typ	1.6typ	1.1typ	320typ	2SD2562	TO3PF (FM100)	
-2.5	-3.0	-5	-0.005	100	-12	0.5	1.1typ	3.2typ	1.1typ	110typ	2SD2589	TO220 (MT-25)	

Part Number	Applications	Absolute Maximum Ratings						h _{FE}				
		V _{CB0}	V _{CEO}	I _c	P _c	I _{CB0}	Conditions		min	max	Conditions	
		(V)	(V)	(A)	(W)		(μA)	V _{CB}			I _c	V _{CE}
							(V)	(A)	(V)	(A)		
2SB1685	Audio, series regulator, general-purpose	-110	-110	-6	60	-100	-110	5000	30000	-4	-5	
2SB1686	Audio, series regulator, general-purpose	-110	-110	-6	30	-100	-110	5000	30000	-4	-5	
2SB1687	Audio, series regulator, general-purpose	-110	-110	-6	60	-100	-110	5000	30000	-4	-5	
2SC2023	Series regulator, switch, general-purpose	300	300	2	40	1mA	300	30		4	0.5	
2SC2837	Audio, general-purpose	150	150	10	100	100	150	50	180	4	3	
2SC2921	Audio, general-purpose	160	160	15	150	100	160	50	180	4	5	
2SC2922	Audio, general-purpose	180	180	17	200	100	180	30	180	4	8	
2SC3179	Audio, general-purpose	80	60	4	30	100	80	40		4	1	
2SC3263	Audio, general-purpose	230	230	15	130	100	230	50	140	4	5	
2SC3264	Audio, general-purpose	230	230	17	200	100	230	50	140	4	5	
2SC3284	Audio, general-purpose	150	150	14	125	100	150	50	180	4	5	
2SC3519	Audio, general-purpose	160	160	15	130	100	160	50	180	4	5	
2SC3519A	Audio, general-purpose	180	180	15	130	100	180	50	180	4	5	
2SC3678	Switching regulator, general-purpose	900	800	3 (Pulse 6)	80	100	800	10	30	4	1	
2SC3679	Switching regulator, general-purpose	900	800	5 (Pulse 10)	100	100	800	10	30	4	2	
2SC3680	Switching regulator, general-purpose	900	800	7 (Pulse 14)	120	100	800	10	30	4	3	
2SC3830	Switching regulator, general-purpose	600	500	6 (Pulse 12)	50	1mA	600	10	30	4	2	
2SC3831	Switching regulator, general-purpose	600	500	10 (Pulse 20)	100	1mA	600	10	30	4	5	
2SC3832	Switching regulator, general-purpose	500	400	7 (Pulse 14)	50	100	500	10	30	4	3	
2SC3833	Switching regulator, general-purpose	500	400	12 (Pulse 24)	100	100	500	10	30	4	7	
2SC3834	Humidifier, DC-DC converter, general-purpose	200	120	7 (Pulse 14)	50	100	200	70	220	4	3	
2SC3835	Humidifier, DC-DC converter, general-purpose	200	120	7 (Pulse 14)	70	100	200	70	220	4	3	
2SC3851	Audio, PPC high voltage power supply, general-purpose	80	60	4	25	100	80	40	320	4	1	
2SC3851A	Audio, PPC high voltage power supply, general-purpose	100	80	4	25	100	100	40	320	4	1	
2SC3852	Solenoid/motor driver/series regulator, general-purpose	80	60	3	25	10	80	500		4	0.5	
2SC3852A	Solenoid/motor driver/series regulator, general-purpose	100	80	3	25	10	100	500		4	0.5	
2SC3856	Audio, general-purpose	200	180	15	130	100	200	80	180	4	3	
2SC3857	Audio, general-purpose	200	200	15	150	100	200	50	180	4	5	
2SC3858	Audio, general-purpose	200	200	17	200	100	200	50	180	4	8	
2SC3890	Switching regulator, general-purpose	500	400	7 (Pulse 14)	30	100	500	10	30	4	3	
2SC3927	Switching regulator, general-purpose	900	550	10 (Pulse 15)	120	100	800	10	28	4	5	
2SC4020	Switching regulator, general-purpose	900	800	3 (Pulse 6)	50	100	800	10	30	4	0.7	
2SC4024	DC-DC converter, emergency lamp inverter, general-purpose	100	50	10	35	100	100	300	1600	4	1	
2SC4064	DC motor driver, general-purpose	50	50	12	35	100	50	50		1	6	
2SC4065	DC motor driver, general-purpose	60	60	±12	35	100	60	50		1	6	
2SC4073	Switching regulator, general-purpose	500	400	5 (Pulse 10)	30	100	500	10	30	4	2	
2SC4130	Switching regulator, general-purpose	500	400	7 (Pulse 14)	30	100	500	10	30	4	3	
2SC4131	DC-DC converter, emergency lamp inverter, general-purpose	100	50	15 (Pulse 20)	60	10	100	60	360	1	5	
2SC4138	Switching regulator, general-purpose	500	400	10 (Pulse 20)	80	100	500	10	30	4	6	
2SC4139	Switching regulator, general-purpose	500	400	15 (Pulse 30)	120	100	500	10	30	4	8	
2SC4140	Switching regulator, general-purpose	500	400	18 (Pulse 36)	130	100	500	10	30	4	10	
2SC4153	Humidifier, DC-DC converter, general-purpose	200	120	7 (Pulse 14)	30	100	200	70	220	4	3	
2SC4296	Switching regulator, general-purpose	500	400	10 (Pulse 20)	75	100	500	10	30	4	6	
2SC4297	Switching regulator, general-purpose	500	400	12 (Pulse 24)	75	100	500	10	30	4	7	
2SC4298	Switching regulator, general-purpose	500	400	15 (Pulse 30)	80	100	500	10	30	4	8	
2SC4299	Switching regulator, general-purpose	900	800	3 (Pulse 6)	70	100	800	10	30	4	1	
2SC4300	Switching regulator, general-purpose	900	800	5 (Pulse 10)	75	100	800	10	30	4	2	
2SC4301	Switching regulator, lighting inverter, general-purpose	900	800	7 (Pulse 14)	80	100	800	10	30	4	3	
2SC4304	Switching regulator, general-purpose	900	800	3 (Pulse 6)	35	100	800	10	30	4	0.7	
2SC4381	TV vertical output, audio output driver, general-purpose	150	150	2	25	10	150	60		10	0.7	
2SC4382	TV vertical output, audio output driver, general-purpose	200	200	2	25	10	200	60		10	0.7	

Electrical Characteristics												Complementary	Package Type
V _{CE} (sat)	V _{BE} (sat)	Conditions			f _T	Switching Time			C _{ob}				
(V)	(V)	I _c	I _b	MHz	V _{CE}	I _E	t _{on}	t _{sig}		t _f			
max	max	(A)	(A)		(V)	(A)	(μS)	(μS)	(μS)	(pF)			
-2.5	-3.0	-5	-0.005	100	-12	0.5	1.1typ	3.2typ	1.1typ	110typ	2SD2641	TO3P (MT-100)	
-2.5	-3.0	-5	-0.005	100	-12	0.5	1.1typ	3.2typ	1.1typ	110typ	2SD2642	TO220F (FM20)	
-2.5	-3.0	-5	-0.005	100	-12	0.5	1.1typ	3.2typ	1.1typ	110typ	2SD2643	TO3PF (FM100)	
1.0		1	0.2	10	12	-0.2	0.3typ	4typ	1typ	75typ		TO220 (MT-25)	
2.0		5	0.5	70	12	-1	0.2typ	1.4typ	0.35typ	60typ	2SA1186	TO3P (MT-100)	
2.0		5	0.5	60	12	-2	0.2typ	1.5typ	0.35typ	200typ	2SA1215	MT-200	
2.0		8	0.8	50	12	-2	0.2typ	1.3typ	0.45typ	250typ	2SA1216	MT-200	
0.6		2	0.2	15	12	-0.2	0.2typ	1.9typ	0.29typ	60typ	2SA1262	TO220 (MT-25)	
2.0		5	0.5	60	12	-2	0.3typ	2.4typ	0.5typ	250typ	2SA1294	TO3P (MT-100)	
2.0		5	0.5	60	12	-2	0.3typ	2.4typ	0.5typ	250typ	2SA1295	MT-200	
2.0		5	0.5	60	12	-2	0.2typ	1.5typ	0.35typ	200typ	2SA1303	TO3P (MT-100)	
2.0		5	0.5	50	12	-2	0.2typ	1.3typ	0.45typ	250typ	2SA1386	TO3P (MT-100)	
2.0		5	0.5	50	12	-2	0.2typ	1.3typ	0.45typ	250typ	2SA1386A	TO3P (MT-100)	
0.5	1.2	1	0.2	6	12	-0.3	1max	5max	1max	50typ		TO3P (MT-100)	
0.5	1.2	2	0.4	6	12	-0.5	1max	5max	1max	75typ		TO3P (MT-100)	
0.5	1.2	3	0.6	6	12	-2	1max	5max	1max	105typ		TO3P (MT-100)	
0.5	1.3	2	0.4	8	12	-0.5	1max	4.5max	0.5max	45typ		TO220 (MT-25)	
0.5	1.3	5	1	8	12	-1	1max	4.5max	0.5max	105typ		TO3P (MT-100)	
0.5	1.3	3	0.6	10	12	-0.5	1max	3max	0.5max	50typ		TO220 (MT-25)	
0.5	1.3	7	1.4	10	12	-1	1max	3max	0.5max	105typ		TO3P (MT-100)	
0.5	1.2	3	0.3	30	12	-0.5	0.5max	3max	0.5max	110typ		TO220 (MT-25)	
0.5	1.2	3	0.3	30	12	-0.5	0.5max	3max	0.5max	110typ		TO3P (MT-100)	
0.5		2	0.2	15	12	-0.2	0.2typ	1typ	0.3typ	60typ	2SA1488	TO220F (FM20)	
0.5		2	0.2	15	12	-0.2	0.2typ	1typ	0.3typ	60typ	2SA1488A	TO220F (FM20)	
0.5		2	0.05	15	12	-0.2	0.8typ	3typ	1.2typ	50typ		TO220F (FM20)	
0.5		2	0.05	15	12	-0.2	0.8typ	3typ	1.2typ	50typ		TO220F (FM20)	
2.0		5	0.5	20	12	-0.5	0.5typ	1.8typ	0.6typ	300typ	2SA1492	TO3P (MT-100)	
3.0		10	1	20	12	-0.5	0.3typ	2.4typ	0.4typ	250typ	2SA1493	MT-200	
2.5		10	1	20	12	-1	0.5typ	1.8typ	0.6typ	300typ	2SA1494	MT-200	
0.5	1.3	3	0.6	10	12	-0.5	1max	3max	0.5max	50typ		TO220F (FM20)	
0.5	1.2	5	1	6	12	-1	1max	5max	0.5max	105typ		TO3P (MT-100)	
0.5	1.2	0.7	0.14	6	12	-0.3	1max	5max	1max	40typ		TO220 (MT-25)	
0.5		5	0.1	24	12	-0.5	0.5typ	2typ	0.5typ	150typ		TO220F (FM20)	
0.35		6	0.3	40	12	-0.5	0.6typ	1.4typ	0.4typ	180typ	2SA1567	TO220F (FM20)	
0.35		6	1.3	24	12	-0.5	0.6typ	1.4typ	0.4typ	180typ	2SA1568	TO220F (FM20)	
0.5	1.3	2	0.4	10	12	-0.3	1max	3max	0.5max	30typ		TO220F (FM20)	
0.5	1.3	3	0.6	15	12	-0.5	1max	2.2max	0.5max	50typ		TO220F (FM20)	
0.5	1.2	5	0.08	18	12	-1	0.5typ	2typ	0.4typ	210typ		TO3PF (FM100)	
0.5	1.3	6	1.2	10	12	-0.7	1max	3max	0.5max	85typ		TO3P (MT-100)	
0.5		8	1.6	10	12	-1.5	1max	3max	0.5max	85typ		TO3P (MT-100)	
0.5	1.3	10	2	10	12	-2.0	1max	3max	0.5max	165typ		TO3P (MT-100)	
0.5	1.2	3	0.3	30	12	-0.5	0.5max	3max	0.5max	110typ		TO220F (FM20)	
0.5	1.3	6	1.2	10	12	-0.7	1max	3max	0.5max	85typ		TO3PF (FM100)	
0.5	1.3	7	1.4	10	12	-1	1max	3max	0.5max	105typ		TO3PF (FM100)	
0.5	1.3	8	1.6	10	12	-1.5	1max	3max	0.5max	85typ		TO3PF (FM100)	
0.5	1.2	1	0.2	6	12	-0.3	1max	5max	1max	50typ		TO3PF (FM100)	
0.5	1.2	2	0.4	6	12	-0.5	1max	5max	1max	75typ		TO3PF (FM100)	
0.5	1.2	3	0.6	6	12	-1	1max	5max	1max	105typ		TO3PF (FM100)	
0.5	1.2	7	0.14	15	12	-0.3	0.7max	4max	0.7max	50typ		TO220F (FM20)	
1.0		7	0.07	15	12	-0.2	1typ	3typ	1.5typ	35	2SA1667	TO220F (FM20)	
1.0		7	0.07	15	12	-0.2	1typ	3typ	1.5typ	35	2SA1668	TO220F (FM20)	

Part Number	Applications	Absolute Maximum Ratings						h _{FE}			
		V _{CB0}	V _{CEO}	I _c	P _c	I _{CB0}	Conditions		Conditions		
		(V)	(V)	(A)	(W)		(μA)	V _{CB}	min	max	V _{CE}
							(V)	(V)			(V)
2SC4388	Audio, general-purpose	200	180	15	85	10	200	50	180	4	3
2SC4418	Switching regulator, general-purpose	500	400	5 (Pulse 10)	30	100	500	10	30	4	1.5
2SC4434	Switching regulator, lighting inverter, general-purpose	500	400	15 (Pulse 30)	120	100	500	10	25	4	8
2SC4445	Switching regulator, general-purpose	900	800	3 (Pulse 6)	60	100	800	10	30	4	0.7
2SC4466	Audio, general-purpose	120	80	6	60	10	120	50	180	4	2
2SC4467	Audio, general-purpose	160	120	8	80	10	160	50	180	4	3
2SC4468	Audio, general-purpose	200	140	10	100	10	200	50	180	4	3
2SC4495	For audio temperature compensation, general-purpose	80	50	3	25	10	80	500		4	0.5
2SC4511	Audio, general-purpose	120	80	6	30	10	120	50	180	4	2
2SC4512	Audio, general-purpose	120	80	6	50	10	120	50	180	4	2
2SC4517	Switching regulator, general-purpose	900	550	3 (Pulse 6)	30	100	800	10	30	4	1
2SC4517A	Switching regulator, general-purpose	1000	550	3 (Pulse 6)	30	100	800	10	30	4	1
2SC4518	Switching regulator, lighting inverter, general-purpose	900	550	5 (Pulse 10)	35	100	800	10	25	4	1.8
2SC4518A	Switching regulator, lighting inverter, general-purpose	1000	550	5 (Pulse 10)	35	100	800	10	25	4	1.8
2SC4546	Switching regulator, lighting inverter, general-purpose	600	400	7 (Pulse 14)	30	100	600	10	25	4	3
2SC4557	Switching regulator, general-purpose	900	550	10 (Pulse 20)	80	100	800	10	28	4	5
2SC4662	Switching regulator, general-purpose	500	400	5 (Pulse 10)	30	100	500	10	30	4	1.5
2SC4706	Switching regulator, general-purpose	900	600	14 (Pulse 28)	130	100	800	10	25	4	7
2SC4883	Audio output driver, TV velocity modulation	150	150	2	20	10	150	60	240	10	0.7
2SC4883A	Audio output driver, TV velocity modulation	180	180	2	20	10	180	60	240	10	0.7
2SC4886	Audio, general-purpose	150	150	14	80	100	150	50	180	4	5
2SC4907	Switching regulator, general-purpose	600	500	6 (Pulse 12)	30	1	600	10	30	4	2
2SC4908	Switching regulator, general-purpose	900	800	3 (Pulse 6)	35	100	800	10	30	4	0.7
2SC5002	Display horizontal deflection output, switching regulator, general-purpose	1500	800	7 (Pulse 14)	80	100	1200	4	9	5	5
2SC5071	Switching regulator, general-purpose	500	400	12 (Pulse 24)	100	100	500	10	30	4	7
2SC5099	Audio, general-purpose	120	80	6	60	10	120	50	180	4	2
2SC5100	Audio, general-purpose	160	120	8	75	10	160	50	180	4	3
2SC5101	Audio, general-purpose	200	140	10	80	10	200	50	180	4	3
2SC5124	Display horizontal deflection output, switching regulator, general-purpose	1500	800	10 (Pulse 20)	100	100	1200	4	9	5	8
2SC5130	Switching regulator, general-purpose	600	400	5 (Pulse 10)	30	100	500	10	30	4	1.5
2SC5239	Switching regulator, general-purpose	900	550	3 (Pulse 6)	50	100	800	10	30	4	1
2SC5249	Switching regulator, general-purpose	600	600	3 (Pulse 6)	35	100	600	20	40	4	1
2SC5271	Resonant switching regulator, general-purpose	300	200	5 (Pulse 10)	30	100	300	10	30	2	2.5
2SC5287	Switching regulator, general-purpose	900	550	5 (Pulse 10)	80	100	800	10	25	4	1.8
2SC5333	Series regulator, switch, general-purpose	300	300	2	35	1	300	30		4	0.5
2SC5370	Emergency lamp inverter, general-purpose	60	40	12	30	10	60	70	400	2	6
2SC5586	Switching regulator, general-purpose	900	550	5 (Pulse 10)	70	100	800	10	25	4	1.8
2SC5830	Switching regulator, lighting inverter, general-purpose	1000	450	8 (Pulse 16)	35	1000	1000	10	30	5	4
2SC5924	Switching regulator, general-purpose	900	600	14 (Pulse 28)	90	100	800	10	25	4	7
2SC6011	Audio, general-purpose	200	200	15	160	10	200	50	180	4	3
2SC6011A	Audio, general-purpose	230	230	15	160	10	230	50	180	4	3
2SD1769	Solenoid/relay/motor driver/series regulator, general-purpose	120	120	6 (Pulse 10)	50	10	120	2000		2	3
2SD1785	Solenoid/relay/motor driver/series regulator, general-purpose	120	120	6 (Pulse 10)	30	10	120	2000		2	3
2SD1796	Solenoid/relay/motor driver, general-purpose	60±10	60±10	4	25	10	50	2000		4	3
2SD2014	Solenoid/relay/motor driver/series regulator, general-purpose	120	80	4	25	10	120	2000		2	3
2SD2015	Solenoid/relay/motor driver, general-purpose	150	120	4	25	10	150	2000		2	2
2SD2016	Igniter, relay, general-purpose	200	200	3	25	10	200	1000	15000	4	1
2SD2017	Solenoid/relay/motor driver, general-purpose	300	250	6	35	100	300	2000		2	2
2SD2045	Solenoid/motor driver, general-purpose	120	120	6 (Pulse 10)	50	10	120	2000		2	3
2SD2081	Solenoid/motor driver, general-purpose	120	120	10 (Pulse 15)	30	10	120	2000		4	5
2SD2082	Solenoid/motor driver, general-purpose	120	120	16 (Pulse 26)	75	10	120	2000		4	8

Electrical Characteristics												Complementary	Package Type
V _{CE} (sat)	V _{BE} (sat)	Conditions		f _T	Switching Time			C _{ob}					
		I _c	I _b		Conditions	t _{on}	t _{stg}		t _i				
(V)	(V)	(A)	(A)	MHz	V _{CE}	I _E	(μS)	(μS)	(μS)	(pF)			
max	max				(V)	(A)							
2.0		5	0.5	20	12	-0.5	0.5max	1.8max	0.6max	300	2SA1673	TO3PF (FM100)	
0.5	1.3	1.5	0.3	20	12	-0.3	1max	2.5max	0.5max	30		TO220F (FM20)	
0.7	1.3	8	1.6	10	12	-1.5	0.5typ	2typ	0.15typ	135		TO3P (MT-100)	
0.5	1.2	0.7	0.14	15	12	-0.3	0.7max	4max	0.7max	50		TO3PF (FM100)	
1.5		2	0.2	20	12	-0.5	0.16typ	2.6typ	0.34typ	110	2SA1693	TO3P (MT-100)	
1.5		3	0.3	20	12	-0.5	0.13typ	3.5typ	0.32typ	200	2SA1694	TO3P (MT-100)	
0.5		5	0.5	20	12	-0.5	0.24typ	4.32typ	0.4typ	250	2SA1695	TO3P (MT-100)	
0.5		4	0.02	40	12	-0.1	0.45typ	1.6typ	0.85typ	30		TO220F (FM20)	
0.5		2	0.2	20	12	-0.5	0.16typ	2.6typ	0.34typ	110	2SA1725	TO220F (FM20)	
0.5		5	0.2	20	12	-0.5	0.16typ	2.6typ	0.34typ	110	2SA1726	TO220 (MT-25)	
0.5	1.2	1	0.2	6	12	-0.25	0.7max	4max	0.5max	35		TO220F (FM20)	
0.5	1.2	1	0.2	6	12	-0.25	0.7max	4max	0.5max	35		TO220F (FM20)	
0.5	1.2	1.8	0.36	6	12	-0.35	0.7max	4max	0.5max	50		TO220F (FM20)	
0.5	1.2	1.8	0.36	6	12	-0.35	0.7max	4max	0.5max	50		TO220F (FM20)	
0.7	1.3	3	0.6	10	12	-0.5	0.5max	2max	0.15max	55		TO220F (FM20)	
0.5	1.2	5	1	6	12	-1	1max	5max	0.5max	105		TO3PF (FM100)	
0.5	1.3	1.5	0.3	20	12	-0.3	1max	2.5max	0.5max	30		TO220F (FM20)	
0.5	1.2	7	1.4	6	12	-1.5	1max	5max	0.7max	160		TO3P (MT-100)	
1.0		0.7	0.07	120	12	-0.7	0.5typ	1.5typ	0.5typ	30	2SA1859	TO220F (FM20)	
1.0		0.7	0.07	120	12	-0.7	0.5typ	1.5typ	0.5typ	30	2SA1859A	TO220F (FM20)	
2.0		5	0.5	60	12	-2	0.26typ	1.5typ	0.35typ	200	2SA1860	TO3PF (FM100)	
0.5	1.3	2	0.4	8	12	-0.5	1max	4.5max	0.5max	45		TO220F (FM20)	
0.5	1.2	0.7	0.14	6	12	-0.3	1max	5max	1max	40		TO220F (FM20)	
5.0	1.5	5	1.2	4	12	-0.5		4max	0.2max	100		TO3PF (FM100)	
0.5	1.3	7	1.4	10	12	-1	1max	3max	0.5max	105		TO3P (MT-100)	
0.5		2	0.2	20	12	-0.5	0.16typ	2.6typ	0.34typ	110	2SA1907	TO3PF (FM100)	
0.5		3	0.3	20	12	-0.5	0.13typ	3.5typ	0.32typ	200	2SA1908	TO3PF (FM100)	
0.5		5	0.5	20	12	-0.5	0.24typ	4.32typ	0.4typ	250	2SA1909	TO3PF (FM100)	
5	1.5	8	2	3	12	-1	0.1typ	4typ	0.2typ	130		TO3PF (FM100)	
0.5	1.3	1.5	0.3	20	12	-0.3	1max	2max	0.3max	30		TO220F (FM20)	
0.5	1.2	1	0.2	6	12	-0.25	0.7max	4max	0.5max	35		TO220 (MT-25)	
0.5	1.2	1	0.2	6	12	-0.3	1.0max	19max	1max	50		TO220F (FM20)	
1.0	1.5	2.5	0.5	10	12	-0.5	0.3max	1max	0.1max	45		TO220F (FM20)	
0.5	1.2	1.8	0.36	6	12	-0.35	0.7max	4max	0.5max	50		TO3P (MT-100)	
1.0		1	0.2	10	12	-0.2	0.3typ	4typ	1typ	75		TO220F (FM20)	
0.3	1.2	6	0.3	90	12	-3				120		TO220F (FM20)	
0.5	1.2	1.8	0.36	6	12	-0.35	0.7max	4max	0.5max	50		TO3PF (FM100)	
0.5	1.2	4	0.8	4	12	-0.25	1max	4max	0.4max	95		TO220F (FM20)	
0.5	1.2	7	1.4	6	12	-1.5	1max	5max	0.7max	160		TO3PF (FM100)	
0.5		5	0.5	20	12	-0.5	-	-	-	270	2SA2151	TO3P (MT-100)	
0.5		5	0.5	20	12	-0.5	-	-	-	270	2SA2151A	TO3P (MT-100)	
1.5	2.0	3	3mA	100	12	-0.2	0.5typ	5.5typ	1.5typ			TO220 (MT-25)	
1.5		2	3mA	100	12	-0.1	0.5typ	5.5typ	1.5typ	70	2SB1258	TO220F (FM20)	
1.5		3	10mA	60	12	-0.2	1typ	4typ	1.5typ	45		TO220F (FM20)	
1.5	2.0	3	3mA	75	12	-0.1	1typ	4typ	1.5typ	45	2SB1257	TO220F (FM20)	
1.5	2.0	2	2mA	40	12	-0.1	0.6typ	5typ	2typ	40		TO220F (FM20)	
1.5	2.0	1	1.5mA	90	12	-0.1				40		TO220F (FM20)	
1.5	2.0	2	2mA	20	12	-1	0.6typ	16typ	3typ	65		TO220F (FM20)	
1.5	2.0	3	3mA	50	12	-1	0.5typ	5.5typ	1.5typ	70		TO3PF (FM100)	
1.5	2.0	5	5mA	60	12	-0.5				95	2SB1259	TO220F (FM20)	
1.5	2.5	8	16mA	20	12	-1	0.6typ	7typ	1.5typ	210	2SB1382	TO3PF (FM100)	

Part Number	Applications	Absolute Maximum Ratings				I _{CBO}		h _{FE}			
		V _{CEO}	V _{CEO}	I _C	P _C	I _{CBO} (μA)	Conditions V _{CB} (V)	min	max	Conditions	
		(V)	(V)	(A)	(W)					V _{CE}	I _C
										(V)	(A)
2SD2083	Solenoid/motor driver, general-purpose	120	120	25 (Pulse 40)	120	10	120	2000		4	12
2SD2141	Igniter, solenoid, motor driver, general-purpose	380±50	380±50	6 (Pulse 10)	35	10	330	1500		2	3
2SD2389	Audio, series regulator, general-purpose	160	150	8	80	100	160	5000	30000	4	6
2SD2390	Audio, series regulator, general-purpose	160	150	10	100	100	160	5000	30000	4	7
2SD2401	Audio, series regulator, general-purpose	160	150	12	150	100	160	5000	30000	4	7
2SD2438	Audio, series regulator, general-purpose	160	150	8	75	100	160	5000	30000	4	6
2SD2439	Audio, series regulator, general-purpose	160	150	10	80	100	160	5000	30000	4	7
2SD2557	Series regulator, general-purpose	200	200	5	70	100	200	1500	6500	5	1
2SD2558	Series regulator, general-purpose	200	200	5	60	100	200	1500	6500	5	1
2SD2560	Audio, series regulator, general-purpose	150	150	15	130	100	150	5000	30000	4	10
2SD2561	Audio, series regulator, general-purpose	150	150	17	200	100	150	5000	30000	4	10
2SD2562	Audio, series regulator, general-purpose	150	150	15	85	100	150	5000	30000	4	10
2SD2589	Audio, series regulator, general-purpose	110	110	6	50	100	110	5000	30000	4	5
2SD2641	Audio, series regulator, general-purpose	110	110	6	60	100	110	5000	30000	4	5
2SD2642	Audio, series regulator, general-purpose	110	110	6	30	100	110	5000	30000	4	5
2SD2643	Audio, series regulator, general-purpose	110	110	6	60	100	110	5000	30000	4	5
SAP09N	Audio	150	150	10	80	100	150	5000	20000	4	6
SAP09P	Audio	-150	-150	-10	80	-100	-150	5000	20000	-4	-6
SAP10N	Audio	150	150	12	100	100	150	5000	20000	4	7
SAP10P	Audio	-150	-150	-12	100	-100	-150	5000	20000	-4	-7
SAP15N	Audio	160	150	15	150	100	160	5000	20000	4	10
SAP15P	Audio	-160	-150	-15	150	-100	-160	5000	20000	-4	-10

Electrical Characteristics												Complementary	Package Type
V _{CE} (sat)	V _{BE} (sat)	Conditions			f _T	Switching Time			C _{ob}				
(V)	(V)	I _c	I _b	MHz	V _{CE}	I _E	t _{on}	t _{stg}	t _r	(pF)			
max	max	(A)	(A)		(V)	(A)	(μS)	(μS)	(μS)				
1.8	2.5	12	24mA	20	12	-1	1typ	6typ	1typ	340	2SB1383	TO3P (MT-100)	
1.5		4	20mA	20	12	-0.5				95		TO220F (FM20)	
2.5	3.0	6	6mA	80	12	-1	0.6typ	10typ	0.9typ	85	2SB1559	TO3P (MT-100)	
2.5	3.0	7	7mA	55	12	-2	0.5typ	10typ	1.1typ	95	2SB1560	TO3P (MT-100)	
2.5	3.0	7	7mA	55	12	-2	0.5typ	10typ	1.1typ	95	2SB1570	MT-200	
2.5	3.0	6	6mA	80	12	-1	0.6typ	10typ	0.9typ	85	2SB1587	TO3PF (FM100)	
2.5	3.0	7	7mA	55	12	-2	0.5typ	10typ	1.1typ	95	2SB1588	TO3PF (FM100)	
1.5		1	5mA	15	10	-0.5				110		TO3P (MT-100)	
1.5		1	5mA	15	10	-0.5				110		TO3PF (FM100)	
2.5	3.0	10	10mA	70	12	-2	0.8typ	4typ	1.2typ	120	2SB1647	TO3P (MT-100)	
2.5	3.0	10	10mA	70	12	-2	0.8typ	4typ	1.2typ	120	2SB1648	MT-200	
2.5	3.0	10	10mA	70	12	-2	0.8typ	4typ	1.2typ	120	2SB1649	TO3PF (FM100)	
2.5	3.0	5	5mA	60	12	-0.5	0.8typ	6.2typ	1.1typ	55	2SB1659	TO220 (MT-25)	
2.5	3.0	5	5mA	60	12	-2	0.8typ	6.2typ	1.1typ	55	2SB1624	TO3P (MT-100)	
2.5	3.0	5	5mA	60	12	-0.5	0.8typ	6.2typ	1.1typ	55	2SB1626	TO220F (FM20)	
2.5	3.0	5	5mA	60	12	-0.5	0.8typ	6.2typ	1.1typ	55	2SB1625	TO3PF (FM100)	
2.0	2.5	6	6mA								SAP09P	2GR	
-2.0	-2.5	-6	-6mA								SAP09N	2GR	
2.0	2.5	7	7mA								SAP10P	2GR	
-2.0	-2.5	-7	-7mA								SAP10N	2GR	
2.0	2.5	10	10mA								SAP15P	2GR	
-2.0	-2.5	-10	-10mA								SAP15N	2GR	

Selection Guide

By V_{DSS}

V_{DSS} (V)	$R_{DS(ON)}$ (Ω) max	I_D (A)	P_D (W)	Part Number	Package Type
40	9m	± 60	60	FKV460S	TO220S (Surface-mount)
	11m	± 60	35	FKV560	TO220F (FM20)
50	11m	± 60	60	FKV560S	TO220S (Surface-mount)
	13m	± 50	35	FKV550T	TO220F (FM20)
	15m	± 50	35	FKV550N	TO220F (FM20)
60	4.7m	± 85	150	2SK3851*	TO3P (MT100)
	5.0m	± 80	80	2SK3724*	TO220S (Surface-mount)
	6.0m	± 70	90	2SK3710*	TO220S (Surface-mount)
	6.0m	± 70	130	2SK3711*	TO3P (MT100)
	6.0m	± 70	80	2SK3800	TO220S (Surface-mount)
	6.0m	± 70	100	2SK3801	TO3P (MT100)
	14m	± 60	60	FKV660S	TO220S (Surface-mount)
	20m	± 40	40	2SK2421	TO220F (FM20)
	28m	± 40	90	2SK1192	TO3PF (FM100)
	28m	± 30	40	2SK2420	TO220F (FM20)
	28m	± 30	40	2SK1191	TO220F (FM20)
	37m	± 25	35	2SK2419	TO220F (FM20)
	50m	± 22	35	2SK1190	TO220F (FM20)
	0.1	± 15	30	2SK1189	TO220F (FM20)
	0.1	± 15	30	2SK1712	TO220F (FM20)
	0.2	± 10	25	2SK1188	TO220F (FM20)
100	80m	± 20	35	2SK2779	TO220F (FM20)
	0.16	± 12	35	2SK1187	TO220F (FM20)
	0.175	± 12	30	2SK2778	TO220F (FM20)
	0.27	± 9	30	2SK1186	TO220F (FM20)
	0.54	± 5	25	2SK1185	TO220F (FM20)
150	95m	± 18	35	2SK3460	TO220F (FM20)
	0.20	± 12	30	2SK3332	TO220F (FM20)
200	0.175	± 18	35	2SK3003	TO220F (FM20)
	0.35	± 8	30	2SK3002*	TO220F (FM20)
	0.8	± 5	30	2SK1184	TO220F (FM20)
250	1.5	± 3	25	2SK1183	TO220F (FM20)
	0.25	± 18	35	2SK3004	TO220F (FM20)
450	0.30	± 18	85	2SK2706*	TO3PF (FM100)
	0.38	± 15	80	2SK2805*	TO3PF (FM100)
	0.57	± 13	40	2SK2704	TO220F (FM20)
	0.80	± 10	35	2SK2702*	TO220F (FM20)
	1.1	± 7	35	2SK2701	TO220F (FM20)
500	2.8	± 3	30	2SK2803	TO220F (FM20)
	0.4	± 13	85	2SK1181	TO3PF (FM100)
	0.6	± 10	85	2SK1180	TO3PF (FM100)
	0.85	± 8.5	85	2SK1179	TO220F (FM20)
	1.1	± 10	35	2SK3200	TO220F (FM20)
	1.5	± 5	30	2SK3199	TO220F (FM20)
600	3.0	± 2.5	30	2SK1177	TO220F (FM20)
	0.55	± 12	85	2SK2710A	TO3PF (FM100)
	0.85	± 8.5	85	2SK2709*	TO3PF (FM100)
	1.1	± 7	40	2SK2708	TO220F (FM20)
	1.85	± 4.5	35	2SK2707*	TO220F (FM20)
900	3.8	± 2	30	2SK2848	TO220F (FM20)
	3.0	± 5	35	2SK2945	TO220F (FM20)
-60	5.0	± 3	30	2SK2943	TO220F (FM20)
	0.28	± 8	30	2SJ425	TO220F (FM20)
	0.5	± 5	25	2SJ424*	TO220F (FM20)

*Under development

Specifications List by Part Number

Part Number	Absolute Maximum Ratings						I _{GSS}		I _{BSS}		V _{TH}				
	V _{DSS}	V _{GSS}	I _D	I _{D (pulse)}	P _D	E _{AS}	Conditions						Conditions		
							(nA)	V _{GS}	(μA)	V _{DS}	(V)	V _{DS}	I _D		
	(V)	(V)	(A)	(A)	(W)	(mJ)	max	(V)	min	max	(V)	min	max	(V)	(μA)
2SJ424*	-60	±20	±5	±20	25	-	±500	±20		-50	-60	-2.0	-4.0	-10	-250
2SJ425	-60	±20	±8	±32	30	-	±500	±20		-250	-60	-2.0	-4.0	-10	-250
2SK1177	500	±20	±2.5	±10	30	200	±500	±20		250	500	2.0	4.0	10	250
2SK1179	500	±20	±8.5	±34	85	400	±500	±20		250	500	2.0	4.0	10	250
2SK1180	500	±20	±10	±40	85	500	±500	±20		250	500	2.0	4.0	10	250
2SK1181	500	±20	±13	±52	85	660	±500	±20		250	500	2.0	4.0	10	250
2SK1183	200	±20	±3	±12	25	30	±500	±20		250	200	2.0	4.0	10	250
2SK1184	200	±20	±5	±20	30	67	±500	±20		250	200	2.0	4.0	10	250
2SK1185	100	±20	±5	±20	25	16	±500	±20		250	100	2.0	4.0	10	250
2SK1186	100	±20	±9	±36	30	32	±500	±20		250	100	2.0	4.0	10	250
2SK1187	100	±20	±12	±48	35	58	±500	±20		250	100	2.0	4.0	10	250
2SK1188	60	±20	±10	±40	25	2.1	±500	±20		250	60	2.0	4.0	10	250
2SK1189	60	±20	±15	±60	30	6.2	±500	±20		250	60	2.0	4.0	10	250
2SK1190	60	±20	±22	±88	35	17	±500	±20		250	60	2.0	4.0	10	250
2SK1191	60	±20	±30	±120	40	38	±500	±20		250	60	2.0	4.0	10	250
2SK1192	60	±20	±40	±160	90	38	±500	±20		250	60	2.0	4.0	10	250
2SK1712	60	±10	±15	±60	30	6.2	±500	±10		250	60	1.0	2.0	10	250
2SK2419	60	±20	±25	±100	35	26	±100	±20		100	60	2.0	4.0	10	250
2SK2420	60	±20	±30	±120	40	38	±100	±20		100	60	2.0	4.0	10	250
2SK2421	60	±20	±40	±160	40	60	±100	±20		100	60	2.0	4.0	10	1m
2SK2701	450	±30	±7	±28	35	130	±100	±30		100	450	2.0	4.0	10	1m
2SK2702*	450	±30	±10	±40	35	300	±100	±30		100	450	2.0	4.0	10	1m
2SK2704	450	±30	±13	±52	40	400	±100	±30		100	450	2.0	4.0	10	1m
2SK2706*	450	±30	±18	±72	85	700	±100	±30		100	450	2.0	4.0	10	1m
2SK2707*	600	±30	±4.5	±18	35	50	±100	±30		100	600	2.0	4.0	10	1m
2SK2708	600	±30	±7	±28	40	150	±100	±30		100	600	2.0	4.0	10	1m
2SK2709*	600	±30	±8.5	±34	85	300	±100	±30		100	600	2.0	4.0	10	1m
2SK2710A	600	±30	±12	±48	85	400	±100	±30		100	600	2.0	4.0	10	1m
2SK2778	100	±20	±12	±48	30	70	±100	±20		100	100	1.0	2.0	10	250
2SK2779	100	±20	±20	±80	35	200	±100	±20		100	100	1.0	2.0	10	250
2SK2803	450	±30	±3	±12	30	30	±100	±30		100	450	2.0	4.0	10	1m
2SK2805*	450	±30	±15	±60	80	550	±100	±30		100	450	2.0	4.0	10	1m
2SK2848	600	±30	±2	±8	30	10	±100	±30		100	600	2.0	4.0	10	250
2SK2943	900	±30	±3	±12	30	60	±100	±30		100	900	2.0	4.0	10	1m
2SK2945	900	±30	±5	±20	35	120	±100	±30		100	900	2.0	4.0	10	1m
2SK3002*	200	±20	±8	±32	30	55	±100	±20		100	200	2.0	4.0	10	1m
2SK3003	200	±20	±18	±72	35	120	±100	±20		100	200	2.0	4.0	10	1m
2SK3004	250	±20	±18	±72	35	120	±100	±20		100	250	2.0	4.0	10	1m
2SK3199	500	±30	±5	±20	30	35	±100	±30		100	500	2.0	4.0	10	1m
2SK3200	500	±30	±10	±40	35	50	±100	±30		100	500	2.0	4.0	10	1m
2SK3332	150	+20, -10	±12	±48	30	100	±100	+20, -10		100	150	1.0	2.0	10	250
2SK3460	150	+20, -10	±18	±72	35	180	±100	+20, -10		100	150	1.0	2.0	10	250
2SK3710*	60	±20	±70	±140	90	468	±10μ	±15		100	60	2.0	4.0	10	1m
2SK3711†	60	±20	±70	±140	130		±10μ	±15		100	60	2.0	4.0	10	1m
2SK3724*	60	±20	±80	±160	80	400	±10μ	±20		100	60	1.0	2.0	10	1m
2SK3800	40	±20	±70	±140	80	400	±10	±15		100	40	2.0	4.0	10	1m
2SK3801	40	±20	±70	±140	100	400	±10	±15		100	40	2.0	4.0	10	1m
2SK3851*	60	±20	±85	±280	150	280	±10μ	±20		100	60	2.0	3.0	10	1m
FKV460S	40	+20, -10	±60	±180	60		+10, -5μ	+20, -10		100	40	1.0	2.5	10	250
FKV550T	50	±20	±50	±150	35	150	±10μ	±20		100	50	1.0	2.5	10	250

*Under development

Electrical Characteristics																	Package Type
Re (yfs)		Conditions		Ciss (pF)	Crss (pF)	RDS (ON)											
						Conditions		Conditions		Conditions		Conditions					
(S)		Vds (V)	Id (A)			Vgs (V)	Vds (V)	(Ω)		Vgs (V)	Id (A)	(Ω)		Vgs (V)	Id (A)		
min	typ			typ	typ			typ	max			typ	max				
1.0	1.6	-10	-2.5	270		0	-25	0.35	0.5	-10	-2.5					TO220F (FM20)	
1.8	2.8	-10	-4	580		0	-25	0.2	0.28	-10	-4					TO220F (FM20)	
1.5	2.3	10	1.4	350		0	25	2.6	3.0	10	1.4					TO220F (FM20)	
5.1	7.7	10	4.5	1300		0	25	0.7	0.85	10	4.5					TO220F (FM20)	
6.1	9.2	10	5	1800		0	25	0.5	0.6	10	5					TO3PF (FM100)	
8.5	13	10	6.5	2700		0	25	0.35	0.4	10	6.5					TO3PF (FM100)	
0.8	1.2	10	1.5	140		0	25	1.2	1.5	10	1.5					TO220F (FM20)	
1.3	2.5	10	2.5	260		0	25	0.5	0.8	10	2.5					TO220F (FM20)	
1.5	1.7	10	2.5	180		0	25	0.41	0.54	10	2.5					TO220F (FM20)	
2.4	3.7	10	4.5	350		0	25	0.24	0.27	10	4.5					TO220F (FM20)	
4.4	6.5	10	6	650		0	25	0.12	0.16	10	6					TO220F (FM20)	
2.2	3.3	10	5	300		0	25	0.15	0.2	10	5					TO220F (FM20)	
4.2	6.2	10	8	640		0	25	0.07	0.1	10	8					TO220F (FM20)	
7.3	11	10	12	1300		0	25	40m	50m	10	12					TO220F (FM20)	
13	20	10	15	2500		0	25	21m	28m	10	15					TO220F (FM20)	
13	20	10	20	2500		0	25	21m	28m	10	20					TO3PF (FM100)	
5.6	8.4	10	8	820		0	25	0.07	0.1	10	8	0.12	0.14	4	8	TO220F (FM20)	
10	15	10	12	1300	200	0	25	31m	37m	10	12					TO220F (FM20)	
13	20	10	15	2200		0	25	21m	28m	10	15					TO220F (FM20)	
18	25	10	20	2400		0	25	17.5m	20m	10	20					TO220F (FM20)	
3.5	5	20	3.5	720	62	0	10	0.84	1.1	10	3.5					TO220F (FM20)	
5	7	20	5	1000	95	0	10	0.66	0.8	10	5					TO220F (FM20)	
6.0	9.0	20	6.5	1300	130	0	10	0.48	0.57	10	6.5					TO220F (FM20)	
10	15	20	9	2500	260	0	10	0.24	0.3	10	9					TO3PF (FM100)	
2.4	3.5	20	2	560	65	0	10	1.45	1.85	10	2					TO220F (FM20)	
4.0	6.0	20	3.5	950	120	0	10	0.85	1.1	10	3.5					TO220F (FM20)	
5.0	7.0	20	4	1200	150	0	10	0.65	0.85	10	4					TO3PF (FM100)	
7.5	11	20	6	1900	240	0	10	0.42	0.55	10	6					TO3PF (FM100)	
7	11	10	6	740	75	0	10	105m	175m	10	6	130m	220m	4	6	TO220F (FM20)	
12	20	10	10	1630	180	0	10	60m	80m	10	10	75m	95m	4	10	TO220F (FM20)	
1.5	2.1	20	1.5	340	26	0	10	2.1	2.8	10	1.5					TO220F (FM20)	
8.0	11.5	20	7.5	2100	210	0	10	0.30	0.38	10	7.5					TO3PF (FM100)	
1.2	1.7	20	1	290	30	0	10	3	3.8	10	1					TO220F (FM20)	
1.8	2.8	20	1.5	600	40	0	10	4	5	10	1.5					TO220F (FM20)	
2.0	4.5	20	2.5	880	70	0	10	2.3	3	10	2.5					TO220F (FM20)	
2.5	5.5	10	4	450	120	0	10	0.27	0.35	10	4					TO220F (FM20)	
7	11	10	9	850	250	0	10	130m	175m	10	9					TO220F (FM20)	
7	11	10	9	850	250	0	10	0.2	0.25	10	9					TO220F (FM20)	
3.5	5.2	20	2.5	650	110	0	10	1.2	1.5	10	2.5					TO220F (FM20)	
5.0	9.0	20	5	920	190	0	10	0.85	1.1	10	5					TO220F (FM20)	
6	11	10	6	870	210	0	10	0.15	0.2	10	6	0.17	0.23	4	6	TO220F (FM20)	
13	20	10	9	1900	420	0	10	70m	95m	10	9	80m	105m	4	9	TO220F (FM20)	
30	80	10	35	8000	1000	0	10	5m	6m	10	35					TO220S (Surface-mount)	
30	80	10	35	8000	1000	0	10	5m	6m	10	35					TO3P (MT100)	
				10600	1300	0	10	4m	5m	10	40					TO220S (Surface-mount)	
30	50	10	35	5100	860	0	10	5.0	6.0	10	35					TO220S (Surface-mount)	
30	50	10	35	5100	860	0	10	5.0	6.0	10	35					TO3P (MT100)	
30		10	42	11500	1100	0	10	4m	4.7m	10	42					TO3P (MT100)	
20		10	25	2800	600	0	10	7m	9m	10	25					TO220S (Surface-mount)	
20		10	25	2700	500	0	10	10m	13m	10	25					TO220F (FM20)	

Part Number	Absolute Maximum Ratings						I _{gss}		I _{oss}		V _{TH}				
	V _{DSS}	V _{GSS}	I _D	I _{D (pulse)}	P _D	E _{AS}	(nA)	Conditions	(μA)	V _{DS}	(V)		Conditions		
	(V)	(V)	(A)	(A)	(W)	(mJ)		V _{GS}					V _{DS}	V _{DS}	I _D
							max	(V)	min	max	(V)	min	max	(V)	(μA)
FKV550N	50	±20	±50	±150	35	150	±10μ	±20		100	50	3.0	4.2	10	250
FKV560	50	+20, -10	±60	±180	35		+10, -5μ	+20, -10		100	50	1.0	2.5	10	250
FKV560S	50	+20, -10	±60	±180	60		+10, -5μ	±20, -10		100	50	1.0	2.5	10	250
FKV660S	60	+20, -10	±60	±180	60		+10, -5μ	+20, -10		100	60	1.0	2.5	10	250

Electrical Characteristics																Package Type
R _e (yfs)		Conditions		C _{iss} (pF)	C _{rss} (pF)	Conditions		R _{DS(on)}				Conditions				
		V _{DS}	I _D			V _{GS}	V _{DS}	(Ω)		(Ω)		V _{GS}	I _D			
min	typ	(V)	(A)	typ	typ	(V)	(V)	typ	max	(V)	(A)	typ	max	(V)	(A)	
17		10	25	2000	500	0	10	12m	15m	10	25					TO220F (FM20)
20		10	25	2700	500	0	10	9m	11m	10	25					TO220F (FM20)
20		10	25	2700	500	0	10	9m	11m	10	25					TO220S (Surface-mount)
20		10	25	2500	150	0	10	11m	14m	10	25					TO220S (Surface-mount)

2-3 Transistor and MOS FET Array

Specifications List by Part Number

Part Number	Category	Circuit Count	V _{CE0} · V _{DSS} (V)	IC · ID (A)	hFE (min)	R _{DS(on)} max(Ω)	Package Type
SDA01	For source driver	4	-60	-1.5	2000		SMD16Pin
SDA05	For 3-phase motor driver	3	-60	-4	2000		SMD16Pin
SDC01	For sink driver	4	50	2	1000		SMD16Pin
SDC03	For sink driver	4	60±10	1.5	2000		SMD16Pin
SDC04	For sink driver	4	100±15	1.5	2000		SMD16Pin
SDC06	For sink driver	4	30 to 45	2	400		SMD16Pin
SDC07	For 3-phase motor driver	3	60	4	2000		SMD16Pin
SDH02	For sink driver	4	100	1.5	2000		SMD16Pin
SDH03	H bridge	4	+100/-60	±1.5	2000		SMD16Pin
SDK04	For sink driver	4	100	2		0.8	SMD16Pin
SLA4010	For sink driver	4	60±10	4	2000		SIP12Pin with heatsink
SLA4030	For sink driver	4	100	4	2000		SIP12Pin with heatsink
SLA4031	For sink driver	4	120	4	2000		SIP12Pin with heatsink
SLA4041	For sink driver	4	200	3	1000		SIP12Pin with heatsink
SLA4060	For sink driver	4	120	5	2000		SIP12Pin with heatsink
SLA4061	For sink driver	4	120	5	2000		SIP12Pin with heatsink
SLA4070	For source driver	4	-100	-5	1000		SIP12Pin with heatsink
SLA4071	For source driver	4	-100	-5	2000		SIP12Pin with heatsink
SLA4310	H bridge	4	±60	±4	80		SIP12Pin with heatsink
SLA4340	H bridge	4	±60	±4	2000		SIP12Pin with heatsink
SLA4390	H bridge	4	±100	±5	2000		SIP12Pin with heatsink
SLA4391	H bridge	4	±100	±5	1000		SIP12Pin with heatsink
SLA5001	For sink driver	4	100	5		0.3	SIP12Pin with heatsink
SLA5002	For sink driver	4	100	5		0.3	SIP12Pin with heatsink
SLA5003	For sink driver	4	200	5		0.9	SIP12Pin with heatsink
SLA5005	For source driver	4	-100	-5		0.7	SIP12Pin with heatsink
SLA5007	H bridge	4	±60	+5/-4		0.22/0.55	SIP12Pin with heatsink
SLA5008	H bridge	4	±100	+4/-3		0.6/1.3	SIP12Pin with heatsink
SLA5009	For 3-phase motor driver	6	±60	+5/-4		0.22/0.55	SIP12Pin with heatsink
SLA5011	For sink driver	5	60	5		0.22	SIP12Pin with heatsink
SLA5012	For source driver	5	-60	-5		0.3	SIP12Pin with heatsink
SLA5013	H bridge	4	±100	±5		0.3/0.7	SIP12Pin with heatsink
SLA5015	For source driver	5	-60	-4		0.55	SIP12Pin with heatsink
SLA5017	For 3-phase motor driver	6	±60	+5/-4		0.22/0.55	SIP12Pin with heatsink
SLA5021	For sink driver	5	100	5		0.19	SIP12Pin with heatsink
SLA5022	For 3-phase motor driver	6	±60	±6	2000	0.22	SIP12Pin with heatsink
SLA5023	For 3-phase motor driver	6	±100	±6	2000	0.55	SIP12Pin with heatsink
SLA5024	For source driver	4	-60	-4		0.55	SIP12Pin with heatsink
SLA5029	For sink driver	5	60	4		0.45	SIP12Pin with heatsink
SLA5031	For sink driver	4	60	5		0.22	SIP12Pin with heatsink
SLA5037	For sink driver	4	100	10		0.08	SIP12Pin with heatsink
SLA5040	For sink driver	4	100	4		0.6	SIP12Pin with heatsink
SLA5041	For sink driver	4	200	10		0.175	SIP12Pin with heatsink
SLA5042	For sink driver	5	100	5		0.185	SIP12Pin with heatsink
SLA5044	For sink driver	4	250	10		0.25	SIP12Pin with heatsink
SLA5046	For sink driver	5	200	7		0.35	SIP12Pin with heatsink
SLA5047	For sink driver	4	150	10		0.085	SIP12Pin with heatsink
SLA5049	For sink driver	5	250	7		0.5	SIP12Pin with heatsink
SLA5052	For sink driver	4	150	10		0.115	SIP12Pin with heatsink
SLA5054	For S-distortion correction	6	150	±7/±5/±7		0.105/0.44/0.2	SIP15Pin with heatsink
SLA5055	For S-distortion correction	5	150	±5/±7		0.44/0.2	SIP12Pin with heatsink
SLA5057	For S-distortion correction	6	200	±7/±7		0.175/0.35	SIP12Pin with heatsink
SLA5058	For sink driver	5	150	±7		0.2	SIP12Pin with heatsink
SLA5059	For 3-phase motor driver	6	±60	±4		0.55	SIP12Pin with heatsink
SLA5060	For 3-phase motor driver	6	±60	±6		0.22	SIP12Pin with heatsink

Part Number	Category	Circuit Count	$V_{CE0} \cdot V_{DSS}$ (V)	$I_C \cdot I_D$ (A)	hFE (min)	$R_{DS(ON)}$ max(Ω)	Package Type
SLA5061	For 3-phase motor driver	6	± 60	± 10		0.14	SIP12Pin with heatsink
SLA5064	For 3-phase motor driver	6	± 60	± 10		0.14	SIP12Pin with heatsink
SLA5065	For 5-phase motor driver	4	60	7		0.1	SIP15Pin with heatsink
SLA5068	For 5-phase motor driver	6	60	7		0.1	SIP15Pin with heatsink
SLA5070	For S-distortion correction	6	150	$\pm 7/\pm 7$		0.105/0.2	SIP15Pin with heatsink
SLA5072	For 3-phase motor driver	6	250	7		0.5	SIP15Pin with heatsink
SLA5073	For 5-phase motor driver	6	60	5		0.3	SIP15Pin with heatsink
SLA5074	For 5-phase motor driver	4	60	5		0.3	SIP15Pin with heatsink
SLA5075	For 3-phase motor driver	6	500	± 5		1.4	SIP15Pin with heatsink
SLA5077	For sink driver	4	150	± 10		0.2	SIP12Pin with heatsink
SLA5079	For 3-phase motor driver	3	-60	-10		0.14	SIP12Pin with heatsink
SLA5080	For 3-phase motor driver	3	60	10		0.14	SIP12Pin with heatsink
SLA5081	For S-distortion correction	5	150	$\pm 7/\pm 7$		0.105/0.2	SIP15Pin with heatsink
SLA5085	For sink driver	5	60	5		0.22	SIP12Pin with heatsink
SLA5086	For source driver	5	-60	-5		0.22	SIP12Pin with heatsink
SLA5088	For S-distortion correction	5	150	$\pm 5/\pm 7$		0.44/0.2	SIP15Pin with heatsink
SLA5089	For sink driver	4	200	10		0.12	SIP12Pin with heatsink
SLA5090	For sink driver	4	100	4		0.6	SIP12Pin with heatsink
SLA5094	For sink driver	5	200	7		0.35	SIP12Pin with heatsink
SLA5096	For 3-phase motor driver	6	55	8		0.08	SIP15Pin with heatsink
SLA5201	For 3-phase motor driver	6	600	7		1.85typ	SIP15Pin with heatsink
SLA6012	For 3-phase motor driver	6	± 60	± 4	2000		SIP12Pin with heatsink
SLA6020	For 3-phase motor driver	6	± 100	± 5	2000		SIP12Pin with heatsink
SLA6022	For 3-phase motor driver	6	± 80	± 5	2000		SIP12Pin with heatsink
SLA6023	For 3-phase motor driver	6	± 60	± 6	2000		SIP12Pin with heatsink
SLA6024	For 3-phase motor driver	6	± 60	± 8	2000		SIP12Pin with heatsink
SLA6026	For 3-phase motor driver	6	± 60	± 10	2000		SIP12Pin with heatsink
SLA8001	H bridge	4	± 60	± 12	50		SIP12Pin with heatsink
SMA4020	For source driver	4	-60	-4	2000		SIP12Pin
SMA4021	For source driver	4	-60	-3	2000		SIP12Pin
SMA4030	For sink driver	4	100	3	2000		SIP12Pin
SMA4032	For sink driver	4	100	3	2000		SIP12Pin
SMA4033	For sink driver	4	100	2	2000		SIP12Pin
SMA4036	For sink driver	6	120	2	2000		SIP12Pin
SMA5101	For sink driver	4	100	4		0.6	SIP12Pin
SMA5102	For sink driver	4	100	4		0.6	SIP12Pin
SMA5103	H bridge	4	± 60	+5/-4		0.22/0.55	SIP12Pin
SMA5104	For 3-phase motor driver	6	± 60	+5/-4		0.22/0.55	SIP12Pin
SMA5105	For sink driver	4	100	5		0.3	SIP12Pin
SMA5106	For sink driver	4	100	4		0.55	SIP12Pin
SMA5112	For 3-phase motor driver	6	250	7		0.5	SIP12Pin
SMA5114	For sink driver	4	60	3		0.25	SIP12Pin
SMA5117	For 3-phase motor driver	6	250	7		0.25	SIP12Pin
SMA5118	For 3-phase motor driver	6	500	± 5		1.4	SIP12Pin
SMA5125	For 3-phase motor driver	6	± 60	± 10		0.14	SIP12Pin
SMA5127	For 3-phase motor driver	6	± 60	± 4		0.55	SIP12Pin
SMA5130	For 3-phase motor driver	6	250	2.5	2000	0.9	SIP15Pin
SMA5131	For 3-phase motor driver	6	250	2		1.8	SIP12Pin
SMA5132	For 3-phase motor driver	6	500	1.5		4	SIP12Pin
SMA5133	For 3-phase motor driver	6	500	2.5		2	SIP12Pin
SMA6010	For 3-phase motor driver	6	± 60	± 4	2000		SIP12Pin
SMA6014	For 3-phase motor driver	6	± 60	± 2	1500/2000		SIP12Pin
SMA6080	For 3-phase motor driver	6	± 60	± 2	2000		SIP12Pin
SMA6511	For driving stepping motor with two supplies	5	100 \pm 15/-60	1.5/-3	2000		SIP12Pin
SMA6512	For driving stepping motor with two supplies	5	60 \pm 10/-60	1.5/-3	2000		SIP12Pin

Part Number	Category	Circuit Count	$V_{CE0} \cdot V_{DSS}$ (V)	IC · ID (A)	hFE (min)	$R_{DS(ON)}$ max(Ω)	Package Type
STA301A	For sink driver	3	60±10	4	1000		SIP8Pin
STA302A	For source driver/3-phase motor driver	3	-50	-4	1000		SIP8Pin
STA303A	For sink driver/3-phase motor driver	3	100	4	1000		SIP8Pin
STA304A	For 3-phase motor driver	3	550	1	200		SIP8Pin
STA305A	For 3-phase motor driver	3	-550	-1	200		SIP8Pin
STA308A	For source driver/3-phase motor driver	3	-120	-4	2000		SIP8Pin
STA309A	For source driver/3-phase motor driver	3	-250	-2.5	1000		SIP8Pin
STA312A	For sink driver	3	60	3	300		SIP8Pin
STA322A	For source driver	3	-50	-3	100		SIP8Pin
STA351A	For sink driver/3-phase motor driver	3	100	5	1000		SIP8Pin
STA352A	For source driver/3-phase motor driver	3	-100	-5	1000		SIP8Pin
STA371A	For sink driver	3	60±10	2	2000		SIP8Pin
STA401A	For sink driver	4	60±10	4	1000		SIP10Pin
STA402A	For source driver	4	-50	-4	1000		SIP10Pin
STA403A	For sink driver	4	100	4	1000		SIP10Pin
STA404A	For sink driver	4	200	3	1000		SIP10Pin
STA406A	For sink driver	4	60±10	6	2000		SIP10Pin
STA408A	For source driver	4	-120	-4	2000		SIP10Pin
STA412A	For sink driver	4	60	3	300		SIP10Pin
STA413A	For sink driver	4	35±5	3	500		SIP10Pin
STA421A	For source driver	4	-60	-3	40		SIP10Pin
STA431A	H bridge	4	±60	±3	40		SIP10Pin
STA434A	H bridge	4	±60	±4	1000		SIP10Pin
STA435A	For sink driver	4	65±15	4	1000		SIP10Pin
STA457C	H bridge	4	±60	±4	2000		SIP10Pin
STA458C	H bridge	4	±30	±5	40		SIP10Pin
STA460C	For sink driver	2	60±10	6	700		SIP10Pin
STA471A	For sink driver	4	60±10	2	2000		SIP10Pin
STA472A	For source driver	4	-60	-2	2000		SIP10Pin
STA473A	For sink driver	4	100	2	2000		SIP10Pin
STA475A	For sink driver	4	100±15	2	2000		SIP10Pin
STA481A	For sink driver	4	60±10	1	2000		SIP10Pin
STA485A	For sink driver	4	100±15	1	2000		SIP10Pin
STA491A	H bridge	4	±20	±7	80		SIP10Pin
STA492A	Half bridge	2	±20	±7	80		SIP10Pin
STA501A	For sink driver	4	60	5		0.2	SIP10Pin
STA506A	For sink driver	4	100	2		0.8	SIP10Pin
STA513A	For sink driver/3-phase motor driver	3	250	3.5		0.9	SIP10Pin
STA517A	For sink driver/3-phase motor driver	3	305	3		1.8	SIP10Pin
STA521A	For sink driver	4	200	±7		0.35	SIP10Pin
STA524A	For sink driver	3	200	±7		0.35	SIP10Pin

Specifications List by Application Sink Driver Array
●Built-in Avalanche Diode, between Collector and Base


Part Number	Circuit Count	V _{CE0} (V)/ V _{DSS} (V)	I _C (A)/ I _D (A)	h _{FE} (min)	R _{Ds(ON)} max (Ω)	Equivalent Circuit	Package Type
STA460C	2	60±10	6	700		1	SIP10Pin
STA371A	3	60±10	2	2000		2	SIP8Pin
STA301A	3	60±10	4	1000		2	SIP8Pin
SDC06	4	30 to 45	2	400		3	SMD16Pin
STA413A	4	35±5	3	500		4	SIP10Pin
STA481A	4	60±10	1	2000		5	SIP10Pin
SDC03	4	60±10	1.5	2000		6	SMD16Pin
STA471A	4	60±10	2	2000		5	SIP10Pin
STA401A	4	60±10	4	1000		5	SIP10Pin
SLA4010	4	60±10	4	2000		6	SIP12Pin with heatsink
STA406A	4	60±10	6	2000		5	SIP10Pin
STA435A	4	65±15	4	1000		7	SIP10Pin
STA485A	4	100±15	1	2000		5	SIP10Pin
SDC04	4	100±15	1.5	2000		6	SMD16Pin
STA475A	4	100±15	2	2000		5	SIP10Pin

●Built-in Flywheel Diode


Part Number	Circuit Count	V _{CE0} (V)/ V _{DSS} (V)	I _C (A)/ I _D (A)	h _{FE} (min)	R _{Ds(ON)} max (Ω)	Equivalent Circuit	Package Type
SMA5114	4	60	3		0.25	9	SIP12Pin
SLA5031	4	60	5		0.3	10	SIP12Pin with heatsink
SDH02	4	100	1.5	2000		11	SMD16Pin
SMA4033	4	100	2	2000		12	SIP12Pin
SMA4032	4	100	3	2000		12	SIP12Pin
SLA5040	4	100	4		0.6	10	SIP12Pin with heatsink
SMA5102	4	100	4		0.6	10	SIP12Pin
SMA5106	4	100	4		0.55	10	SIP12Pin
SLA5002	4	100	5		0.3	10	SIP12Pin with heatsink
SMA5105	4	100	5		0.3	10	SIP12Pin
SLA4031	4	120	4	2000		12	SIP12Pin with heatsink
SLA4061	4	120	5	2000		12	SIP12Pin with heatsink
SLA4041	4	200	3	1000		12	SIP12Pin with heatsink
SLA5003	4	200	5		0.9	10	SIP12Pin with heatsink
SMA4036	6	120	2	2000		13	SIP15Pin

●Equivalent Circuit (for Sink Driver)


①




②




③




④




⑤




⑥




⑦




⑨




⑩




⑪



⑫



⑬




●General-Purpose


Part Number	Circuit Count	V _{CE0} (V)/ V _{DSS} (V)	I _C (A)/ I _D (A)	h _{FE} (min)	R _{DS(ON)} max (Ω)	Equivalent Circuit	Package Type
STA312A	3	60	3	300		14	SIP8Pin
STA303A	3	100	4	100		15	SIP8Pin
STA524A	3	200	7		0.35	24	SIP10Pin
SDC01	4	50	2	1000		16	SMD16Pin
STA412A	4	60	3	300		17	SIP10Pin
STA501A	4	60	5		0.2	18	SIP10Pin
STA473A	4	100	2	2000		19	SIP10Pin
STA506A	4	100	2		0.8	18	SIP10Pin
SDK04	4	100	2		0.8	20	SMD16Pin
SMA4030	4	100	3	2000		21	SIP12Pin
STA403A	4	100	4	1000		19	SIP10Pin
SLA4030	4	100	4	2000		21	SIP12Pin with heatsink
SMA5101	4	100	4		0.6	20	SIP12Pin
SLA5001	4	100	5		0.3	20	SIP12Pin with heatsink
SLA5037	4	100	10		0.08	20	SIP12Pin with heatsink
SLA4060	4	120	5	2000		21	SIP12Pin with heatsink
SLA5047	4	150	10		0.085	20	SIP12Pin with heatsink
SLA5052	4	150	10		0.115	20	SIP12Pin with heatsink
SLA5077	4	150	±10		0.2	20	SIP12Pin with heatsink
STA404A	4	200	3	1000		19	SIP10Pin
STA521A	4	200	7		0.35	23	SIP10Pin
SLA5041	4	200	10		0.175	20	SIP10Pin
SLA5044	4	250	10		0.25	20	SIP12Pin with heatsink
SLA5089	4	200	10		0.12	20	SIP12Pin with heatsink
SLA5029	5	60	4		0.45	22	SIP12Pin with heatsink
SLA5011	5	60	5		0.22	22	SIP12Pin with heatsink
SLA5085	5	60	5		0.22	22	SIP12Pin with heatsink
SLA5021	5	100	5		0.19	22	SIP12Pin with heatsink
SLA5042	5	100	5		0.185	22	SIP12Pin with heatsink
SLA5058	5	150	±7		0.2	22	SIP12Pin with heatsink
SLA5046	5	200	7		0.35	22	SIP12Pin with heatsink
SLA5094	5	200	7		0.35	22	SIP12Pin with heatsink
SLA5049	5	250			0.5	22	SIP12Pin with heatsink

●Equivalent Circuit (for Sink Driver)


⑭




⑮




⑯




⑰




⑱




⑳




㉑




㉒



㉓



㉔



Specifications List by Application Source Driver Array

●Built-in Flywheel Diode


Part Number	Circuit Count	V _{CEO} (V)/ V _{DSS} (V)	I _c (A)/ I _D (A)	h _{FE} (min)	R _{DS(ON)} max (Ω)	Equivalent Circuit	Package Type
SMA4021	4	-60	-3	2000		1	SIP12Pin
SLA4071	4	-100	-5	2000		1	SIP12Pin with heatsink

●General-Purpose


Part Number	Circuit Count	V _{CEO} (V)/ V _{DSS} (V)	I _c (A)/ I _D (A)	h _{FE} (min)	R _{DS(ON)} max (Ω)	Equivalent Circuit	Package Type
STA322A	3	-50	-3	100		3	SIP8Pin
STA302A	3	-50	-4	1000		4	SIP8Pin
STA308A	3	-120	-4	2000		4	SIP8Pin
STA402A	4	-50	-4	1000		5	SIP10Pin
SDA01	4	-60	-1.5	2000		6	SMD16Pin
STA472A	4	-60	-2	2000		5	SIP10Pin
STA421A	4	-60	-3	40		7	SIP10Pin
SMA4020	4	-60	-4	2000		6	SIP12Pin
SLA5024	4	-60	-4		0.55	8	SIP12Pin with heatsink
SLA4070	4	-100	-5	1000		6	SIP12Pin with heatsink
SLA5005	4	-100	-5		0.7	8	SIP12Pin with heatsink
STA408A	4	-120	-4	2000		9	SIP10Pin
SLA5015	5	-60	-4		0.55	10	SIP12Pin with heatsink
SLA5012	5	-60	-5		0.3	10	SIP12Pin with heatsink
SLA5086	5	-60	-5		0.22	10	SIP12Pin with heatsink

●Equivalent Circuit (for Source Driver)


①




③




④




⑤




⑥




⑦




⑧



⑨



⑩




Specifications List by Application Motor Driver Array

●H Bridge


Part Number	Circuit Count	V _{CE0} (V)/ V _{DSS} (V)	I _C (A)/ I _D (A)	h _{FE} (min)	R _{DS(ON)} max (Ω)	Equivalent Circuit	Package Type
STA492A	2	±20	±7	45		1	SIP10Pin
STA458C	4	±30	±5	40		2	SIP10Pin
STA431A	4	±60	±3	40		3	SIP10Pin
STA434A	4	±60	±4	1000		4	SIP10Pin
STA457C	4	±60	±4	2000		5	SIP10Pin
SLA4310	4	±60	±4	80		6	SIP12Pin with heatsink
SLA4340	4	±60	±4	2000		4	SIP12Pin with heatsink
SLA5007	4	±60	+5/-4		0.22/0.55	7	SIP12Pin with heatsink
SMA5103	4	±60	+5/-4		0.22/0.55	7	SIP12Pin
SLA8001	4	±60	±12	50		2	SIP12Pin with heatsink
SDH03	4	+100/-60	±1.5	2000		8	SMD16Pin
SLA5008	4	±100	+4/-3		0.6/1.3	7	SIP12Pin with heatsink
SLA4390	4	±100	±5	2000		4	SIP12Pin with heatsink
SLA4391	4	±100	±5	1000		9	SIP12Pin with heatsink
SLA5013	4	±100	±5		0.3/0.7	7	SIP12Pin with heatsink
STA491A	4	±20	±7	45		10	SIP10Pin

●Equivalent Circuit (for Motor Driver)


①




⑥




②




⑦




③




⑧




④




⑨



⑤























⑩



●For 3-Phase Motor Driver

Part Number	Circuit Count	V _{CE0} (V)/ V _{BSS} (V)/ V _{CEs} (V)	I _c (A)/ I _D (A)	h _{FE} (min)	R _{DS(ON)} max (Ω)	Equivalent Circuit	Package Type
SDC07	3	60	4	2000		11	SMD16Pin
SLA5080	3	60	10		0.14	12	SIP12Pin with heatsink
STA303A	3	100	4	1000		13	SIP8Pin
STA351A	3	100	5	1000		13	SIP8PIN
STA513A	3	250	3.5		0.9	14	SIP10PIN
STA517A	3	305	3		1.8	14	SIP10PIN
STA304A	3	550	1	200		15	SIP8Pin
STA302A	3	-50	-4	1000		16	SIP8Pin
SDA05	3	-60	-4	2000		17	SMD16Pin
SLA5079	3	-60	-10		0.14	18	SIP12Pin with heatsink
STA352A	3	-100	-5	1000		16	SIP8Pin
STA309A	3	-250	-2.5	1000		16	SIP8Pin
STA305A	3	-550	-1	200		19	SIP8Pin
SLA5096	6	55	±8		80m	28	SIP15Pin with heatsink
SLA5059	6	60	±4		0.55	20	SIP12Pin with heatsink
SLA5060	6	60	±6		0.22	20	SIP12Pin with heatsink
SLA5061	6	60	±10		0.14	20	SIP12Pin with heatsink
SLA5064	6	60	±10		0.14	21	SIP12Pin with heatsink
SMA6014	6	±60	±2	1500/2000		22	SIP12Pin
SMA6080	6	±60	±2	2000		23	SIP12Pin
SMA6010	6	±60	±4	2000		23	SIP12Pin
SLA6012	6	±60	±4	2000		22	SIP12Pin with heatsink
SMA5127	6	±60	±4		0.55	20	SIP12Pin
SLA5009	6	±60	+5/-4		0.22/0.55	24	SIP12Pin with heatsink
SLA5017	6	±60	+5/-4		0.22/0.55	24	SIP12Pin with heatsink
SMA5104	6	±60	+5/-4		0.22/0.55	24	SIP12Pin
SLA5022	6	±60	±6	2000	0.22	25	SIP12Pin with heatsink
SLA6023	6	±60	±6	2000		22	SIP12Pin with heatsink
SLA6024	6	±60	±8	2000		22	SIP12Pin with heatsink
SLA6026	6	±60	±10	2000		22	SIP12Pin with heatsink
SMA5125	6	±60	±10		0.14	21	SIP12Pin
SLA6022	6	±80	±5	2000		22	SIP12Pin with heatsink
SLA6020	6	±100	±5	2000		23	SIP12Pin with heatsink
SLA5023	6	±100	±6	2000	0.55	25	SIP12Pin with heatsink
SMA5130	6	±250	±2.5	2000	0.9	30	SIP15Pin
SMA5131	6	250	2		1.8	27	SIP12Pin
SLA5072	6	250	7		0.5	26	SIP15Pin with heatsink
SMA5112	6	250	7		0.5	27	SIP12Pin
SMA5117	6	250	7		0.25	27	SIP12Pin
SMA5132	6	500	1.5		4	27	SIP12Pin
SMA5133	6	500	2.5		2	27	SIP12Pin
SLA5075	6	500	±5		1.4	26	SIP15Pin with heatsink
SMA5118	6	500	±5		1.4	27	SIP12Pin
SLA5201	6	600	7			29	SIP15Pin with heatsink

●Equivalent Circuit (for Motor Driver)



●For Driving Stepping Motor with Two Supplies


Part Number	Circuit Count	V _{CE0} (V)/ V _{DSS} (V)	I _C (A)/ I _D (A)	h _{FE} (min)	R _{DS(ON)} max (Ω)	Equivalent Circuit	Package Type
SMA6511	5	100±15/-60	1.5/-3	2000		31	SIP12Pin
SMA6512	5	60—10/-60	1.5/-3	2000		31	SIP12Pin

●For 5-Phase Motor Drive


Part Number	Circuit Count	V _{CE0} (V)/ V _{DSS} (V)	I _C (A)/ I _D (A)	h _{FE} (min)	R _{DS(ON)} max (Ω)	Equivalent Circuit	Package Type
SLA5074	4	60	5		0.3	32	SIP15Pin with heatsink
SLA5065	4	60	7		0.1	32	SIP15Pin with heatsink
SLA5073	6	60	5		0.3	28	SIP15Pin with heatsink
SLA5068	6	60	7		0.1	26	SIP15Pin with heatsink

●Equivalent Circuit (for Motor Driver)


②6




②8



③1



③2




Specifications List by Application *Array for CRT Monitor S-Distortion Correction Circuit*


Part Number	V _{BS}	Circuit Count	I _D (A)	R _{DS(ON)max} (Ω)	Equivalent Circuit	Package Type
SLA5037	100	4	10	0.08	1	SIP12Pin with heatsink
SLA5021		5	5	0.19	2	SIP12Pin with heatsink
SLA5042		5	5	0.185	2	SIP12Pin with heatsink
SLA5047	150	4	10	0.085	1	SIP12Pin with heatsink
SLA5052		4	10	0.115	1	SIP12Pin with heatsink
SLA5077		4	±10	0.2	1	SIP12Pin with heatsink
SLA5055		5	±5/±7	0.44/0.2	2	SIP12Pin with heatsink
SLA5058		5	±7	0.2	2	SIP12Pin with heatsink
SLA5081		5	±7/±7	0.105/0.2	2	SIP15Pin with heatsink
SLA5088		5	±5/±7	0.44/0.2	2	SIP15Pin with heatsink
SLA5054		6	±7/±5/±7	0.105/0.44/0.2	3	SIP15Pin with heatsink
SLA5070		6	±7/±7	0.105/0.2	3	SIP15Pin with heatsink
STA524A		200	3	±7	0.35	4
STA521A	4		±7	0.35	5	SIP10Pin
SLA5041	4		10	0.175	1	SIP12Pin with heatsink
SLA5089	4		10	0.12	1	SIP12Pin with heatsink
SLA5046	5		7	0.35	2	SIP12Pin with heatsink
SLA5094	5		7	0.35	2	SIP12Pin with heatsink
SLA5057	6		±7/±7	0.175/0.35	3	SIP15Pin with heatsink
SLA5044	250		4	10	0.25	1
SLA5049		5	7	0.5	2	SIP12Pin with heatsink

●Equivalent Circuit (for CRT Monitor S-Distortion Correction)


①




②




③



④














⑤





Specifications List by Application

Applications	Typical Connection Diagram	Part Number		
		Transistor		MOSFET
		Darlington	Single	
<ul style="list-style-type: none"> ● Solenoid ● Relay 		STA301A STA371A STA401A STA406A STA435A STA471A STA475A STA481A STA485A STA4010 SDC04 SDC03	STA460C STA413A SDC06	
		SLA4031 SLA4041 SLA4060 SMA4032 SMA4033 SMA4036 SDH02		SLA5002 SLA5003 SLA5031 SLA5040 SMA5102 SMA5105 SMA5106 SMA5114 SDK02
		SLA4071 SMA4021		SLA5006
		STA302A STA308A STA402A STA408A STA472A SLA4070 SMA4020 SDA01	STA322A STA421A	SLA5004 SLA5005 SLA5024

Applications		Typical Connection Diagram	Part Number			
			Transistor		MOSFET	
			Darlington	Single		
●DC Motor	Normal/Reverse Rotation Control		STA434A STA457C SLA4340 STA4390 SDH03	STA431A STA458C STA474A SLA4310 SLA8001		
	PWM Control		SLA4391		SLA5007 SLA5008 SLA5013 SLA5018 SMA5103	
●3-Phase DC Brushless Motor			STA302A+STA303A SMA6010 SLA6020 SDA05+SDC07 SMA6080 STA351A+STA352A			
	AC100V Direct Driver AC200V Direct Driver				SLA5072 SLA5075 SMA5112 SMA5117 SMA5118 SMA5131 SMA5132 SMA5133	
	AC200V Direct Driver		STA304A+STA305A			
	PWM Control			SLA6012 SLA6022 SLA6023 SLA6024 SLA6026 SMA6014		
				SLA5022 SLA5023 SMA5130 STA309A STA309A	+	STA513A STA517A
					SLA5009 SLA5010 SLA5017 SLA5059 SLA5060 SLA5061 SLA5064 SLA5079+SLA5080 SMA5104 SMA5125 SMA5127	

Applications		Typical Connection Diagram	Part Number		
			Transistor		MOSFET
			Darlington	Single	
●Stepping Motor	Constant Voltage Driver		STA401A STA406A STA435A STA471A STA475A STA481A STA485A SLA4010 SDC04 SDC03	STA460C STA413A SDC06	
	Two Supplies Driver		SMA6511 SMA6512		
	Bipolar Driver		STA473A STA472A STA408A STA404A STA403A STA402A SMA4030 SMA4020 SLA4070 SLA4060 SLA4030 SDA01	STA421A STA412A SDC01	STA506A STA505A STA504A STA501A SMA5101 SLA5024 SLA5005 SLA5004 SLA5001


Applications	Typical Connection Diagram	Part Number	
		N-CH	P-CH
●5-Phase Motor		SLA5011 SLA5029 SLA5065+SLA5068 SLA5073+SLA5074 SLA5085	SLA5012 SLA5015 SLA5086

Applications	Typical Connection Diagram	Part Number			
		100V	150V	200V	250V
●S-Distortion Correction		SLA5021 SLA5037 SLA5042	SLA5047 SLA5052 SLA5054 SLA5055 SLA5058 SLA5070 SLA5077 SLA5081 SLA5088	SLA5041 SLA5046 SLA5057 SLA5089 SLA5094 STA521A STA524A	SLA5044 SLA5049


Package Type (Dimensions)

Package Type (Dimensions)


• TO-220F




• TO-220




• TO-3P




• TO-3PF




• MT-200



• SAP




• TO-220S




(Unit:mm)


• STA 8 pin (SIP8Pin)




• STA 10 pin (SIP10Pin)




• SD 16 pin (SMD16Pin)




• SMA 12 pin (SIP12Pin)




• SMA 15 pin (SIP15Pin)



• SLA 12 pin (SIP 12 Pin with heatsink)



• SLA 15 pin (SIP 15 Pin with heatsink)



(Unit:mm)

Thyristor

Application Note	191
3-1 Thyristor	192
3-2 Triac	194
3-3 PNP Switch Element	196
Package Type (Dimensions)	198

Application Note

Since reliability can be affected adversely by improper storage environment or handling methods during Characteristic tests, please observe the following cautions.

■ Cautions for Storage

- Ensure that storage conditions comply with the normal temperature (5 to 35°C) and the normal relative humidity (around 40 to 75%), and avoid storage locations that experience high temperature and humidity, or extreme changes in temperature or humidity.
- Avoid locations where dust or harmful gases are present, and avoid direct sunlight.
- Reinspect the devices for rust in leads and solderability after stored for a long time.

■ Cautions for Characteristic Tests and Handling

On characteristics test at incoming inspection, etc, take good care to avoid the surge voltages from the test equipment, the short circuit at terminals, or the wrong connection.

■ Silicone Grease

When using a heatsink, please coat thinly and evenly the back surface of the device and both surfaces of the insulating plate with silicone grease to lower the thermal resistance between the device and the heatsink.

Please select proper silicone grease carefully since the oil in some grease products may penetrate the device and result in an extremely short device life.

Recommended Silicone Grease

- G-746 (Shin-Etsu Chemical)
- YG6260 (GE Toshiba Silicones)
- SC102 (Dow Corning Toray Silicone)

■ Mounting Torque

When mounting torque is insufficient, thermal resistance increases, and so heat radiation effect is decreased. When the torque is excessive, the screw may be broken, the heatsink may be deformed, and the device frame may be distorted, resulting in the device damage. Recommended mounting torque per package is as follows:

● Mounting Torque Table

Package	Screw Torque
MT-25 (TO-220)	0.490 to 0.686 N•m (5 to 7kgf•cm)
FM20 (TO-220 Full Mold)	
MT-100 (TO-3P)	0.686 to 0.882 N•m (7 to 9kgf•cm)
FM100 (TO-3P Full Mold)	
SLA	0.588 to 0.784 N•m (6 to 8kgf•cm)

- * When the surface of a heatsink where Full Mold package is to be mounted is not flat due to the burred metal bracket for screwing around the mounting hole of the heatsink, the resin of the package might be cracked even if the torque is lower than the recommended value.
- * When a screw is fastened with an air driver for the Full Mold package, a large impact is generated at the time of stop, and the resin may crack even if the torque is lower than the recommended value. An electric driver, therefore, should be used instead of an air driver.

■ Heatsink

A larger contact area between the device and the heatsink is required for more effective heat radiation. To ensure a larger contact area, minimize mounting holes. And select a heatsink with a surface smooth enough and free from burrs and slivers.

■ Soldering Temperature

In general, the device mounted on a printed circuit board is subjected to high temperatures from flow solder in a solder bath, or, from a soldering iron at hand soldering.

The testing method and test conditions (JIS-C-7021 standards) for a device's heat resistance to soldering are:

At a distance of 1.5mm from the device's main body, apply 260°C for 10 seconds, and 350°C for 3 seconds.

Please observe these limits and finish soldering in as short a time as possible.

Since reliability can be affected adversely by improper storage environment or handling methods during Characteristic tests, please observe the following cautions.

3-1 Thyristor

Thyristor

Part Number	Absolute Maximum Ratings													I _{RRM} I _{DRM} (mA) max	Conditions T _j (°C)
	V _{RSM} V _{DSM} (V)	V _{RRM} V _{DRM} (V)	I _T (AV) (A)	Conditions T _c (°C)	I _T (RMS) (50Hz) (A)	I _{TSM} 50Hz Single Half Sine Wave, Default T _j =125°C (A)	P _{GM} (W)	P _G (AV) (W)	V _{RGM} (V)	I _{FGM} (A)	T _j (°C)	T _{stg} (°C)			
TF321M	300	200	3.0	102	4.7	60	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF321M-A	300	200	3.0	87	4.7	60	5.0	0.5	5.0	2.0	-40 to +110	-40 to +125	1.0	110	
TF321S	300	200	3.0	93	4.7	60	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF521M	300	200	5.0	96	7.8	80	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF521S	300	200	5.0	87	7.8	80	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF821M	300	200	8.0	83	12.6	120	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF821S	300	200	8.0	74	12.6	120	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF341M	500	400	3.0	102	4.7	60	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF341M-A	500	400	3.0	87	4.7	60	5.0	0.5	5.0	2.0	-40 to +110	-40 to +125	1.0	110	
TF341S	500	400	3.0	93	4.7	60	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF541M	500	400	5.0	96	7.8	80	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF541S	500	400	5.0	87	7.8	80	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF541S-A	500	400	5.0	88	7.8	80	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF841M	500	400	8.0	83	12.6	120	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF841S	500	400	8.0	74	12.6	120	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
SLA0201	650	600	5 × 4		7.8	80	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF361M	700	600	3.0	102	4.7	60	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF361M-A	700	600	3.0	87	4.7	60	5.0	0.5	5.0	2.0	-40 to +110	-40 to +125	1.0	110	
TF361S	700	600	3.0	93	4.7	60	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF561M	700	600	5.0	96	7.8	80	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF561S	700	600	5.0	87	7.8	80	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF561S-A	700	600	5.0	88	7.8	80	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF861M	700	600	8.0	83	12.6	120	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	
TF861S	700	600	8.0	74	12.6	120	5.0	0.5	5.0	2.0	-40 to +125		2.0	125	

3-Pin Reverse Conducting Thyristor for HID Lamp Ignition

Part Number	Absolute Maximum Ratings											I _{DRM} (mA) max	Conditions T _j (°C)	V _{TM} (V) max	Conditions	
	V _{DRM} (V)	I _{TRM} (50Hz) (A)	di/dt (A/μs)	P _{GM} (W)	P _G (AV) (W)	V _{RGM} (V)	I _{FGM} (A)	I _{FRM} [*] (A)	T _j (°C)	T _{stg} (°C)	T _c (°C)				I _{TM} (A)	
TFC561D	600	430	1200	5.0	0.5	5.0	2.0	240	-40 to +125		1.0	125	1.4		10	

*: V_b≤430V, 100kcycle, W_p=1.3ms, T_a=125°C

Thyristor with Built-in Avalanche Diode

Part Number	Absolute Maximum Ratings													V _{BO}		
	V _{DRM} (V)	I _T (AV) (A)	Conditions T _c (°C)	I _T (RMS) (50Hz) (A)	I ² t t=2-10ms (A ² S)	P _{GM} (W)	P _G (AV) (W)	V _{RGM} (V)	I _{FGM} (A)	T _j (°C)	T _{stg} (°C)	I _{DRM} (mA) max	Conditions T _j (°C)	min	typ	max
TFD312S-C	20													27	30	33
TFD312S-K	100													115	125	135
TFD312S-L	120													140	150	160
TFD312S-M	145	3.0	92	4.7	18	5	0.5	5.0		-10 to +125	-40 to +125	1.0	125	163	175	187
TFD312S-N	170													185	200	215
TFD312S-O	190													210	225	240

Electrical Characteristics																Package Type
V _{TM} (V) max	Conditions		V _{GT}			I _{GT}			V _{GD} (V) min	T _J (°C)	Conditions		d _v /d _t (V/μs) typ	I _H (mA) typ	R _{th} (°C/W) max	
	T _c (°C)	I _{TM} (A)	(V)		(mA)		T _c (°C)	V _D (V)								
	typ	max	typ	max	typ	max	typ	max								
1.4	25	5		1.5	2.0	10	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	4.0	3.0	TO220
1.4	25	5		1.0		0.1	25	0.1	110	1/2V _{DRM}	20	110	1/2V _{DRM}	1.0	3.0	TO220
1.4	25	5	0.7	1.5	3.0	15	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	5.0	5.0	TO220F
1.4	25	10		1.5	3.0	15	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	4.0	3.0	TO220
1.4	25	10		1.5	3.0	15	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	4.0	4.0	TO220F
1.4	25	15		1.5	5.0	15	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	4.0	2.7	TO220
1.4	25	15		1.5	5.0	15	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	4.0	3.6	TO220F
1.4	25	5		1.5	2.0	10	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	4.0	3.0	TO220
1.4	25	5		1.0		0.1	25	0.1	110	1/2V _{DRM}	20	110	1/2V _{DRM}	1.0	3.0	TO220
1.4	25	5	0.7	1.5	3.0	15	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	5.0	5.0	TO220F
1.4	25	10		1.5	3.0	15	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	4.0	3.0	TO220
1.4	25	10		1.5	3.0	15	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	4.0	4.0	TO220F
1.4	25	10		1.5	0.03	0.2	25	0.1	125	1/2V _{DRM}	20	125	1/2V _{DRM}	4.0	4.0	TO220F
1.4	25	15		1.5	5.0	15	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	4.0	2.7	TO220
1.4	25	15		1.5	5.0	15	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	4.0	3.6	TO220F
1.4	25	10	0.7	1.5	5.0	10	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	4.0		SLA12Pin
1.4	25	5		1.5	2.0	10	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	4.0	3.0	TO220
1.4	25	5		1.0		0.1	25	0.1	110	1/2V _{DRM}	20	110	1/2V _{DRM}	1.0	3.0	TO220
1.4	25	5	0.7	1.5	3.0	15	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	5.0	5.0	TO220F
1.4	25	10		1.5	3.0	15	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	4.0	3.0	TO220
1.4	25	10		1.5	3.0	15	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	4.0	4.0	TO220F
1.4	25	10		1.5	0.03	0.2	25	0.1	125	1/2V _{DRM}	20	125	1/2V _{DRM}	4.0	4.0	TO220F
1.4	25	15		1.5	5.0	15	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	4.0	2.7	TO220
1.4	25	15		1.5	5.0	15	25	0.1	125	1/2V _{DRM}	50	125	1/2V _{DRM}	4.0	3.6	TO220F

Electrical Characteristics											Package Type	
V _{GT}		I _{GT}		Conditions T _c (°C)	V _{GD} (V) min	Conditions		I _H (mA) typ	R _{th} (°C/W) max	V _F (V) max		Conditions I _F (A)
(V)		(mA)				T _J (°C)	V _D (V)					
typ	max	typ	max			typ	max					
	1.5		20		0.1	125	480	10	4.0	1.4	10.0	TO220S

Electrical Characteristics														Package Type	
V _{TM} (V) max	Conditions		V _{GT}			I _{GT}			Conditions T _c (°C)	d _v /d _t		I _H (mA) max	R _{th} (°C/W) max		
	T _c (°C)	I _{TM} (A)	(V)		(mA)		(V/μs)			T _J (°C)	V _D (V)				
	typ	max	typ	max	min	max	min	typ		typ	max				
1.4		5.0		1	0.2	10				40	125	V _{DRM}	15	5.0	TO220F

3-2 Triac

Triac

Part Number	Absolute Maximum Ratings															
	V _{DRM} (V)	I _T (RMS) (A)		I _{TSM} (A)	Conditions T _c (°C)	P _{GM} (W)	P _G (AV) (W)	I _{GM} (A)	T _j (°C)	T _{stg} (°C)	I _{DRM1} (mA) max	Conditions	I _{DRM2} (mA) max	Conditions	V _{TM} (V) max	Conditions I _{TM} (A)
TMA34M-L ^{*1}	400	3		30		3	0.3	0.5	-40 to +125	0.1		2		1.5	4.5	
TMA34S-L	400	3	109	30		3	0.3	0.5	-40 to +125	0.1		2		1.5	4.5	
TM341S-R	400	3	109	30		3	0.3	0.5	-40 to +125	0.1		2		1.6	5	
TMA54M-L ^{*1}	400	5		50		5	0.5	2	-40 to +125	0.1		2		1.5	7	
TMA54S-L	400	5	102	50		5	0.5	2	-40 to +125	0.1		2		1.5	7	
TM541S-R	400	5	104	50		5	0.5	2	-40 to +125	0.1		2		1.6	7	
TMA84M-L ^{*1}	400	8		80		5	0.5	2	-40 to +125	0.1		2		1.5	12	
TMA84S-L	400	8	92	80		5	0.5	2	-40 to +125	0.1		2		1.5	12	
TMA104S-L	400	10	85	100		5	0.5	2	-40 to +125	0.1		2		1.5	14	
TM1041S-R	400	10	90	80		5	0.5	2	-40 to +125	0.1		2		1.6	14	
TMA124S-L	400	12	77	120		5	0.5	2	-40 to +125	0.1		2		1.5	17	
TM1241S-R	400	12	84	110		5	0.5	2	-40 to +125	0.1		2		1.6	16	
TMA164S-L	400	16	66	160		5	0.5	2	-40 to +125	0.1		2		1.45	20	
TMA164P-L	400	16	108	160		5	0.5	2	-40 to +125	0.1		2		1.4	20	
TMA164B-L	400	16	98	160		5	0.5	2	-40 to +125	0.1		2		1.4	20	
TMA204S-L	400	20	53	190		5	0.5	2	-40 to +125	0.1		2		1.4	20	
TM2541B-L	400	25	84	240		5	0.5	2	-40 to +125	0.1		2		1.3	20	
STA221A	400	1.0 × 4	97	10	125°C	1	0.1	0.5	-40 to +125	0.1		1		1.6	1.6	
STA203A	400	1.2 × 3	97	10	50Hz	1.2	0.1	0.5	-40 to +125	0.1	25°C	1	125°C	1.6	1.6	
TMA36M-L ^{*1}	600	3		30	1shot	3	0.3	0.5	-40 to +125	0.1	V _D =V _{DRM}	2	V _D =V _{DRM}	1.5	4.5	
TMA36S-L	600	3	109	30		3	0.3	0.5	-40 to +125	0.1		2		1.5	4.5	
TM361S-R	600	3	109	30		3	0.3	0.5	-40 to +125	0.1		2		1.6	5	
TMA56M-L ^{*1}	600	5		50		5	0.5	2	-40 to +125	0.1		2		1.5	7	
TMA56S-L	600	5	102	50		5	0.5	2	-40 to +125	0.1		2		1.5	7	
TM561S-R	600	5	104	50		5	0.5	2	-40 to +125	0.1		2		1.6	7	
TMA86M-L ^{*1}	600	8		80		5	0.5	2	-40 to +125	0.1		2		1.5	12	
TMA86S-L	600	8	92	80		5	0.5	2	-40 to +125	0.1		2		1.5	12	
TMA106S-L	600	10	85	100		5	0.5	2	-40 to +125	0.1		2		1.5	14	
TM1061S-R	600	10	90	90		5	0.5	2	-40 to +125	0.1		2		1.6	14	
TMA126S-L	600	12	77	120		5	0.5	2	-40 to +125	0.1		2		1.5	17	
TM1261S-R	600	12	84	110		5	0.5	2	-40 to +125	0.1		2		1.6	16	
TMA166S-L	600	16	66	160		5	0.5	2	-40 to +125	0.1		2		1.45	20	
TMA166P-L	600	16	108	160		5	0.5	2	-40 to +125	0.1		2		1.4	20	
TMA166B-L	600	16	98	160		5	0.5	2	-40 to +125	0.1		2		1.4	20	
TMA206S-L	600	20	53	190		5	0.5	2	-40 to +125	0.1		2		1.4	20	
TM2561B-L	600	25	84	240		5	0.5	2	-40 to +125	0.1		2		1.3	20	
TM583S-L	800	5	101	45		5	0.5	2	-40 to +125	0.1		2		1.6	7	
TM883S-L	800	8	91	80		5	0.5	2	-40 to +125	0.1		2		1.6	10	

*1: Under development

Electrical Characteristics ($T_j = 25^\circ\text{C}$, unless otherwise specified)

	V_{GT}			Conditions		I_{GT}			Conditions		V_{GD}		$(dv/dt)_c$		$R_{th(j-c)}$ ($^\circ\text{C/W}$) max	Package Type	
	Mode I (T2+, G+) (V) max	Mode II (T2+, G-) (V) max	Mode III (T2-, G-) (V) max	V_D (V)	R_L (Ω)	Mode I (T2+, G+) (mA) max	Mode II (T2+, G-) (mA) max	Mode III (T2-, G-) (mA) max	V_D (V)	R_L (Ω)	T_j ($^\circ\text{C}$)	V_o (V)	(V/us) min	Conditions (dv/dt) c (-A/ms)			T_j ($^\circ\text{C}$)
1.5	1.5	1.5	12	20	15/20	15/20	15/20	12	20	0.2	125	1/2V _{DRM}	5	1.5	125	-	TO220
1.5	1.5	1.5	12	20	15/20	15/20	15/20	12	20	0.2	125	1/2V _{DRM}	5	1.5	125	4.5	TO220F
1.8	1.2	1.2	20	40	12	12	12	20	40	0.1	125	1/2V _{DRM}	-			5	TO220F
1.5	1.5	1.5	12	20	15/20	15/20	15/20	12	20	0.2	125	1/2V _{DRM}	5	2.5	125	-	TO220
1.5	1.5	1.5	12	20	15/20	15/20	15/20	12	20	0.2	125	1/2V _{DRM}	5	2.5	125	4	TO220F
1.8	1.2	1.2	20	40	12	12	12	20	40	0.1	125	1/2V _{DRM}	-			4	TO220F
1.5	1.5	1.5	12	20	20/30	20/30	20/30	12	20	0.2	125	1/2V _{DRM}	10	4	125	-	TO220
1.5	1.5	1.5	12	20	20/30	20/30	20/30	12	20	0.2	125	1/2V _{DRM}	10	4	125	3.7	TO220F
1.5	1.5	1.5	12	20	20/30	20/30	20/30	12	20	0.2	125	1/2V _{DRM}	10	5	125	3.6	TO220F
2	1.2	1.2	20	40	7	7	7	20	40	0.1	125	1/2V _{DRM}	-			3.3	TO220F
1.5	1.5	1.5	12	20	20/30	20/30	20/30	12	20	0.2	125	1/2V _{DRM}	10	6	125	3.5	TO220F
1.8	1.2	1.2	20	40	8	8	8	20	40	0.1	125	1/2V _{DRM}	-			3	TO220F
1.5	1.5	1.5	12	20	20/30	20/30	20/30	12	20	0.2	125	1/2V _{DRM}	10	8	125	3.3	TO220F
1.5	1.5	1.5	12	20	30	30	30	12	20	0.2	125	1/2V _{DRM}	10	8	125	1.2	TO3P
1.5	1.5	1.5	12	20	30	30	30	12	20	0.2	125	1/2V _{DRM}	10	8	125	1.8	TO3PF
1.5	1.5	1.5	12	20	20/30	20/30	20/30	12	20	0.2	125	1/2V _{DRM}	10	10	125	3.2	TO220F
2	2	2	6	10	30	30	30	6	10	0.2	125	1/2V _{DRM}	10	4	125	1.5	TO3PF
3.5	1.2	1.2	6	10	3	3	3	6	10	0.2	125	1/2V _{DRM}	1		125	20	SIP10
3.5	1.2	1.2	6	10	3	3	3	6	10	0.2	125	1/2V _{DRM}	1		125	20	SIP8
1.5	1.5	1.5	12	20	15/20	15/20	15/20	12	20	0.2	125	1/2V _{DRM}	5	1.5	125	-	TO220
1.5	1.5	1.5	12	20	15/20	15/20	15/20	12	20	0.2	125	1/2V _{DRM}	5	1.5	125	4.5	TO220F
1.8	1.2	1.2	20	40	12	12	12	20	40	0.1	125	1/2V _{DRM}	-			5	TO220F
1.5	1.5	1.5	12	20	15/20	15/20	15/20	12	20	0.2	125	1/2V _{DRM}	5	2.5	125	-	TO220
1.5	1.5	1.5	12	20	15/20	15/20	15/20	12	20	0.2	125	1/2V _{DRM}	5	2.5	125	4	TO220F
1.8	1.2	1.2	20	40	12	12	12	20	40	0.1	125	1/2V _{DRM}	-			4	TO220F
1.5	1.5	1.5	12	20	20/30	20/30	20/30	12	20	0.2	125	1/2V _{DRM}	10	4	125	-	TO220
1.5	1.5	1.5	12	20	20/30	20/30	20/30	12	20	0.2	125	1/2V _{DRM}	10	4	125	3.7	TO220F
1.5	1.5	1.5	12	20	20/30	20/30	20/30	12	20	0.2	125	1/2V _{DRM}	10	5	125	3.6	TO220F
2	1.2	1.2	20	40	7	7	7	20	40	0.1	125	1/2V _{DRM}	-			3.3	TO220F
1.5	1.5	1.5	12	20	20/30	20/30	20/30	12	20	0.2	125	1/2V _{DRM}	10	6	125	3.5	TO220F
1.8	1.2	1.2	20	40	8	8	8	20	40	0.1	125	1/2V _{DRM}	-			3	TO220F
1.5	1.5	1.5	12	20	20/30	20/30	20/30	12	20	0.2	125	1/2V _{DRM}	10	8	125	3.3	TO220F
1.5	1.5	1.5	12	20	30	30	30	12	20	0.2	125	1/2V _{DRM}	10	8	125	1.2	TO3P
1.5	1.5	1.5	12	20	30	30	30	12	20	0.2	125	1/2V _{DRM}	10	8	125	1.8	TO3PF
1.5	1.5	1.5	12	20	20/30	20/30	20/30	12	20	0.2	125	1/2V _{DRM}	10	10	125	3.2	TO220F
2	2	2	6	10	30	30	30	6	10	0.2	125	1/2V _{DRM}	10	4	125	1.5	TO3PF
2	2	2	6	10	20	20	20	6	10	0.2	125	1/2V _{DRM}	5	2	125	4	TO220F
2	2	2	6	10	30	30	30	6	10	0.2	125	1/2V _{DRM}	10	4	125	3.6	TO220F

3-3 PNP Switch Element


PNPN Switch Elements List

Part Number	Absolute Maximum Ratings							
	V _{DRM}	I _T (RMS)	Conditions T _I (°C)	I _{TSM}	Conditions T _a /Wp/f (°C)/(μs)/(Hz)	diT/dt	T _J	T _{stg}
	(V)	(A)		(A)		(A/μs)	(°C)	(°C)
ET013	90	0.6	≤112	80		30	-40 to +125	
ET015	115	0.6	≤112	80		30	-40 to +125	
ET020	170	0.6	≤112	80	25/10/50	30	-40 to +125	
ET0141	115	0.6	≤112	80		30	-40 to +125	
ET0201	170	0.6	≤112	80		30	-40 to +125	


	Electrical Characteristics								Package Type
	V _{BO}			I _{BO}	I _{DRM}		V _T		
	(V) min	typ	max	(μ A) max	(μ A) max	Conditions V _D (V)	(V) max	Conditions I _T (A)	
	120		138	150			± 2.5	± 10	$\phi 2.7$ body/ $\phi 0.6$ lead
	142		157	100			± 2.5	± 10	$\phi 2.7$ body/ $\phi 0.6$ lead
	190		210	100			± 2.5	± 10	$\phi 2.7$ body/ $\phi 0.6$ lead
	134		146	100	10	V _{DRM}	± 2.5	± 10	$\phi 2.7$ body/ $\phi 0.6$ lead
	190		210	100	10	V _{DRM}	± 2.5	± 10	$\phi 2.7$ body/ $\phi 0.6$ lead

Package Type (Dimensions)


• TO220




• TO220F




• TO3P



• TO3PF




• TO-220S Straight




(Unit: mm)


• STA 10 pin




• STA 8 pin



• SLA 12 pin



• 2.7 Body/ ϕ 0.6 Lead













(Unit: mm)

Diode

Taping Specifications	202
Application Note	205
Marking Guide	206
4-1 Rectifier Diode	207
Surface-Mount	207
Thru-hole	207
Bridge	208
4-2 Fast Recovery Diode	209
Thru-hole	209
4-3 Ultrafast Recovery Diode	211
Surface-Mount	211
Thru-hole	211
4-4 Schottky Barrier Diode	214
General-Purpose	214
• Surface-Mount	214
• Thru-hole	214
Low VF "A Series"	215
• Surface-Mount	215
• Thru-hole	215
Low IR "E Series"	216
• Surface-Mount	216
• Thru-hole	216
Low VF/Low IR Balance "J Series"	216
• Surface-Mount	216
• Thru-hole	216
4-5 High Voltage Rectifier Diode	217
4-6 Damper Diode	218
Damper Diode	218
DM Damper Diode	219
4-7 Avalanche Diode with Built-in Thyristor	220
4-8 Power Zener Diode	221
4-9 Silicon Varistor	222
Package Type (Dimensions)	223

Taping Specifications

Taping name	Taping Type, Dimensions (mm)	Packing Dimensions (mm) and Packing Note	Quantity
<p>V</p> <p>To specify the taping type, add a suffix [V] to the end of the Part Number</p>	<p>Axial taping</p> 	<p>Reel</p> 	<p>5,000 pcs/reel (2.7φ body)</p> <p>3,000 pcs/reel (4φ body)</p>
<p>V1</p> <p>To specify the taping type, add a suffix [V1] to the end of the Part Number</p>	<p>Axial taping</p> 	<p>Ammunition (Ammo) pack</p> 	<p>2,000 pcs/box (2.7φ body)</p> <p>3,000 pcs/box (2.4φ body)</p> <p>1,000 pcs/box (4φ body)</p>
<p>V0</p> <p>To specify the taping type, add a suffix [V0] to the end of the Part Number</p>	<p>Axial taping</p> 	<p>Ammunition (Ammo) pack</p> 	<p>2,000 pcs/box (2.7φ body)</p> <p>3,000 pcs/box (2.4φ body)</p>
<p>V3</p> <p>To specify the taping type, add a suffix [V3] to the end of the Part Number</p>	<p>Axial taping</p> 	<p>Reel</p> 	<p>1,500 pcs/reel (5.2φ body)</p>
<p>V4</p> <p>To specify the taping type, add a suffix [V4] to the end of the Part Number</p>	<p>Axial taping</p> 	<p>Ammunition (Ammo) pack</p> 	<p>1,000 pcs/box (5.2φ body)</p>

Taping name	Taping Type, Dimensions (mm)	Packing Dimensions (mm) and Packing Note	Quantity
<p>W</p> <p>To specify the taping type, add a suffix [W] to the end of the Part Number</p>	<p>Radial taping</p>	<p>Ammunition (Ammo) pack</p>	<p>4,000 pcs/box (2.7φ body) (0.6φ lead only)</p>
<p>WS</p> <p>To specify the taping type, add a suffix [WS] to the end of the Part Number</p>	<p>Radial taping (for A0 series)</p>	<p>Ammunition (Ammo) pack</p>	<p>2,500 pcs/box (2.4φ body)</p>
<p>WK</p> <p>To specify the taping type, add a suffix [WK] to the end of the Part Number</p>	<p>Radial taping (for A0 series)</p>		<p>2,500 pcs/box (2.4φ body)</p>

Surface-Mount Taping Specifications

Taping Name	Taping Type, Dimensions (mm)	Packing Dimensions (mm) and Packing Note	Quantity
SFP V To specify the taping type, add a suffix [V] to the end of the Part Number	Emboss taping <p>(1) Cathode is placed on the right, facing the direction where the tape is reeled out. (2) Device is placed in the embossed pocket with the mounting electrode down. (3) 150 to 200mm leader tape is attached to the tip of the tape. (4) 10 or more blank pockets are provided at both the beginning and the end of the tape. (5) It is possible to apply taping with the diode polarity reversed on demand (taping name VL).</p>	Reel <p>Part No., Lot No., Quantity, etc.</p>	1800 pcs/reel
	VL To specify the taping type, add a suffix [VL] to the end of the Part Number 	<p>Part Number Quantity Taping Name (Code) Lot No.</p> <p>Material Disc: Double-sided White Cardboard Core: Styrofoam</p>	3000 pcs/reel
VR To specify the taping type, add a suffix [VR] to the end of the Part Number 		3000 pcs/reel	
VR To specify the taping type, add a suffix [VR] to the end of the Part Number 		1000 pcs/reel	

High Voltage Rectifier Diode Taping Specifications


Taping Name	Taping Type, Dimensions (mm)	Packing Dimensions (mm) and Packing Note	Quantity
V1 To specify the taping type, add a suffix [V1] to the end of the Part Number Axial taping 	<p>Part Number Lot No. Quantity</p>	5000 pcs/reel	
VD To specify the taping type, add a suffix [VD] to the end of the Part Number Axial taping 	<p>Part Number Lot No. Quantity</p>	8000 pcs/reel	

Application Note

General Description

(1) Lead Forming

When forming leads, hold the lead wire on the main body's side so as to prevent stress from being applied to the main body.



(2) Mounting

To mount a frame-type diode on a heatsink, use its screw hole. Do not fix its resin body as the silicon chip may get broken.

(3) Temperature Measurement

For an axial type diode, measure the temperature of the lead wire on the main body side. The thermocouple to be used must be as thin as possible (approximately $\phi 0.125\text{mm}$).

(4) Temperature Rise Consideration

A diode's temperature increases due to losses from forward current, reverse current and reverse recovery time. In normal use, losses are mainly attributable to forward current and voltage. However, in high frequency circuits such as switching power supplies, losses due to reverse recovery time also occurs. Moreover, in diodes having large reverse currents like Schottky barrier diode losses due to reverse current cannot be disregarded. Forward loss tends to decrease at high temperatures. However, reverse loss tends to increase at high temperatures. Therefore, it is necessary to consider the ambient temperature when verifying operation.

(5) Inrush current

In a capacitor-input type rectifier circuit, inrush current flows when the power supply is switched on. The peak value of this inrush current shall be set less than peak forward surge current I_{FSM} ($I^2 t$ can also be obtained but set the minimum pulse width to 1 msec). The value of I_{FSM} is guaranteed for a single shot only. If the inrush current is repeated within a short period of time, the derating has to be taken into account.

(6) Peak value current

Considering normal use, limit of the peak value current must be set to 10 times of the average current I_F (AV). If the peak value increases, the diode's forward loss also increases. In this case, check the temperature rise.


- Carefully study the mounting method when the usage environment is prone to creeping discharge.

Surface-Mount Diode

(Part Number Type: SFP□-5□/6□)

Soldering (common to flow and reflow)

- Use rosin based flux. Never use acidic fluxes.
- To prevent a large thermal stress, preheat within 1 to 2 minutes at 150°C and solder within the usable range shown below.




- When using a soldering iron, make use of the following references:
Temperature of soldering Iron Tip:

Lower than 300°C
(Power of the soldering iron: 30W or lower)
The soldering tip must be as thin as possible.

Soldering time: Less than 10 seconds


Reference Copper Laminate Pattern when Mounting SFP Series

(Unit : mm)




Marking Guide

1 Axial (A0)




- Part Number (abbreviation)
The AM01 is indicated as "M."
- Class
Z: 200V None: 400V A: 600V
B: 800V C: 1000V
- Manufacturing date
First letter: Year (Last digit of year)
Second letter: Month (1 to 9, O, N, D)
- Cathode band: Continuous band
Color of the band: White (Yellow for AU02 series)

2 Axial (E0, E1)



- Part Number (abbreviation)
EM01, EM2, EM1 are indicated as MO, M2 and M1, respectively.
- Class
Z: 200V None: 400V A: 600V
B: 800V C: 1000V F: 1500V
But EU02A is indicated as A2 and EU2YX as Y.
- Manufacturing date
First letter: Year (Last digit of year)
Second letter: Month (1 to 9, O, N, D)
- Manufacturing period
• First 10 days of month
•• Middle 10 days of month
••• Last 10 days of month


3 Axial (R1, R2, R3, R4)



- Part Number: 2 set marking
- Manufacturing date and period: 2 set marking
First letter: Year (Last digit of year)
Second letter: Month (1 to 9, O, N, D)
• First 10 days of month
•• Middle 10 days of month
••• Last 10 days of month
- Cathode band
Color of the band:


White:	For Power Supply and SBD
Yellow:	For Medium speed
Red:	For Fast and ultrafast

4 RBV




- Part Number
- Lot No.
First letter: Year (Last digit of year)
Second letter: Month (1 to 9, O, N, D)
Third letter: A—First 10 days of month
B—Middle 10 days of month
C—Last 10 days of month
- Input/output marking
Laser marking or White ink marking

5 TO-220F type




- Part Number
FMU-12S is indicated as "FMU12S."
- Polarity: Rectifier Symbol
- Lot No.
First letter: Year (Last digit of year)
Second letter: Month (1 to 9, O, N, D)
Third and fourth letters: Day
Laser marking or White ink marking




- Part Number: Excluding last letter
FML-G12S is indicated as "FML-G12."
- Last letter of Part Number
- Polarity: Rectifier Symbol
- Lot No.
First letter: Year (Last digit of year)
Second letter: Month (1 to 9, O, N, D)
Third and fourth letters: Day
Laser marking or White ink marking


6 TO-3PF, FM80, FM100 type



- Part Number: Full name
- Polarity: Rectifier Symbol
- Lot No.
First letter: Year (Last digit of year)
Second letter: Month (1 to 9, O, N, D)
Third and fourth letters: Day
Laser marking or White ink marking




7 Surface-Mount (SFP)




- Part Number: abbreviation
SFPB-64 is indicated as "C4"
- Cathode band
- Lot No.
First letter: Year (Last digit of year)
Second letter: Month (1 to 9, O, N, D)

8 Surface-Mount (D pack)



- Part Number
- Polarity: Rectifier Symbol
- Lot No.
First letter: Lot code
Second letter: Year (Last digit of year)
Third letter: Month (A to M except I)

9 Surface-Mount (TO-220S)



- Part Number
- Polarity: Rectifier Symbol
- Lot No.
First letter: Year (Last digit of year)
Second letter: Month (A to M except I)
Third letter: Week

10 Silicon Varistor

Refer P222

4-1 Rectifier Diode

●Surface-Mount

V _{RM} (V)	I _F (AV) (A) <small>Values in parentheses are for the products with heatsinks</small>	Package	Part Number	I _{FSM} (A)	T _J (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _{R(H)} (μA)	T _a (°C)	R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
				50Hz <small>Single Half Sine Wave</small>					V _R =V _{RM} max	V _R =V _{RM} max			
200	0.9	Surface-Mount (SFP)	SFPM-52	30	-40 to +150		1.00	1.0	10	50	100	20	0.072
	1.0	Surface-Mount (SFP)	SFPM-62	45	-40 to +150		0.98	1.0	10	50	100	20	0.072
400	0.9	Surface-Mount (SFP)	SFPM-54	30	-40 to +150		1.0	1.0	10	50	100	20	0.072
	1.0	Surface-Mount (SFP)	SFPM-64	45	-40 to +150		0.98	1.0	10	50	100	20	0.072

●Thru-hole

V _{RM} (V)	I _F (AV) (A) <small>Values in parentheses are for the products with heatsinks</small>	Package Axial <small>(Body Diameter/Lead Diameter)</small>	Part Number	I _{FSM} (A)	T _J (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _{R(H)} (μA)	T _a (°C)	R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
				50Hz <small>Single Half Sine Wave</small>					V _R =V _{RM} max	V _R =V _{RM} max			
100	1.0	Axial(φ2.7/φ0.78)	EM 1Y	45	-40 to +150		0.97	1.0	10	50	100	17	0.3
	1.7(3.0)	Axial(φ6.5/φ1.4)	RM 4Y	200	-40 to +150		0.95	3.0	10	50	100	8	1.2
	20	FM80(Center-tap)	FMM-31S, R	120	-40 to +150		1.10	10	10	100	100	2.0	5.5
200	1.0	Axial(φ2.4/φ0.6)	AM01Z	35	-40 to +150		0.98	1.0	10	50	100	22	0.13
	1.0	Axial(φ2.7/φ0.6)	EM01Z	45	-40 to +150		0.97	1.0	10	50	100	20	0.2
	1.0	Axial(φ2.7/φ0.78)	EM 1Z	45	-40 to +150		0.97	1.0	10	50	100	17	0.3
	1.0	Axial(φ4.0/φ0.78)	RM 1Z	50	-40 to +150		0.95	1.0	5	50	100	15	0.4
	1.2	Axial(φ4.0/φ0.98)	RO 2Z	80	-40 to +150		0.92	1.5	10	50	100	12	0.61
	1.2	Axial(φ4.0/φ0.78)	RM 2Z	100	-40 to +150		0.91	1.5	10	50	100	12	0.6
	1.5	Axial(φ4.0/φ0.98)	RM 10Z	120	-40 to +150		0.91	1.5	10	50	100	15	0.4
	1.7(3.0)	Axial(φ6.5/φ1.4)	RM 4Z	200	-40 to +150		0.95	3.0	10	50	100	8	1.2
	10	TO-220F(Center-tap)	FMM-22S, R	100	-40 to +150		1.10	5.0	10	100	100	4.0	2.1
	20	FM80(Center-tap)	FMM-32S, R	120	-40 to +150		1.10	10	10	100	100	2.0	5.5
400	1.0	Axial(φ2.4/φ0.6)	AM01	35	-40 to +150		0.98	1.0	10	50	100	22	0.13
	1.0	Axial(φ2.7/φ0.6)	EM01	45	-40 to +150		0.97	1.0	10	50	100	20	0.2
	1.0	Axial(φ2.7/φ0.78)	EM 1	45	-40 to +150		0.97	1.0	10	50	100	17	0.3
	1.0	Axial(φ4.0/φ0.78)	RM 1	50	-40 to +150		0.95	1.0	5	50	100	15	0.4
	1.2	Axial(φ2.7/φ0.78)	EM 2	80	-40 to +150		0.92	1.2	10	50	100	17	0.3
	1.2	Axial(φ4.0/φ0.98)	RO 2	80	-40 to +150		0.92	1.5	10	50	100	12	0.61
	1.2	Axial(φ4.0/φ0.98)	RM 2	100	-40 to +150		0.91	1.5	10	50	100	12	0.6
	1.2	Axial(φ4.0/φ0.78)	RM 10	150	-40 to +150		0.91	1.5	10	50	100	15	0.4
	2.5	Axial(φ5.2/φ1.2)	RM 3	150	-40 to +150		0.95	2.5	10	100	150	10	1.0
	1.7(3.0)	Axial(φ6.5/φ1.4)	RM 4	200	-40 to +150		0.95	3.0	10	50	100	8	1.2
	10	TO-220F(Center-tap)	FMM-24S, R	100	-40 to +150		1.10	5.0	10	100	100	4.0	2.1
20	FM80(Center-tap)	FMM-34S, R	120	-40 to +150		1.10	10	10	100	100	2.0	5.5	
600	1.0	Axial(φ2.4/φ0.6)	AM01A	35	-40 to +150		0.98	1.0	10	50	100	22	0.13
	1.0	Axial(φ2.7/φ0.6)	EM01A	45	-40 to +150		0.97	1.0	10	50	100	20	0.2
	1.0	Axial(φ2.7/φ0.78)	EM 1A	45	-40 to +150		0.97	1.0	10	50	100	17	0.3
	1.0	Axial(φ4.0/φ0.78)	RM 1A	50	-40 to +150		0.95	1.0	5	50	100	15	0.4
	1.2	Axial(φ2.7/φ0.78)	EM 2A	80	-40 to +150		0.92	1.2	10	50	100	17	0.3
	1.2	Axial(φ4.0/φ0.98)	RO 2A	80	-40 to +150		0.92	1.5	10	50	100	12	0.61
	1.2	Axial(φ4.0/φ0.78)	RM 11A	100	-40 to +150		0.92	1.5	10	50	100	15	0.4
	1.2	Axial(φ4.0/φ0.98)	RM 2A	100	-40 to +150		0.91	1.5	10	50	100	12	0.6
	1.2	Axial(φ4.0/φ0.78)	RM 10A	150	-40 to +150		0.91	1.5	10	50	100	15	0.4
	2.5	Axial(φ5.2/φ1.2)	RM 3A	150	-40 to +150		0.95	2.5	10	100	100	10	1.0
	1.7(3.0)	Axial(φ6.5/φ1.4)	RM 4A	200	-40 to +150		0.95	3.0	10	50	100	8	1.2
	1.8(3.2)	Axial(φ6.5/φ1.4)	RM 4AM	350	-40 to +150		0.92	3.5	10	50	100	8	1.2
	10	TO-220F(Center-tap)	FMM-26S, R	100	-40 to +150		1.10	5.0	10	100	100	4.0	2.1
	20	FM80(Center-tap)	FMM-36S, R	120	-40 to +150		1.10	10	10	100	100	2.0	5.5
800	0.8	Axial(φ4.0/φ0.78)	RM 1B	40	-40 to +150		1.2	1.0	5	50	100	15	0.4
	1.0	Axial(φ2.7/φ0.78)	EM 1B	35	-40 to +150		0.97	1.0	20	100	100	17	0.3
	1.2	Axial(φ2.7/φ0.78)	EM 2B	80	-40 to +150		0.92	1.2	10	50	100	17	0.3
	1.2	Axial(φ4.0/φ0.98)	RO 2B	80	-40 to +150		0.92	1.5	10	50	100	12	0.61
	1.2	Axial(φ4.0/φ0.78)	RM 11B	100	-40 to +150		0.92	1.5	10	50	100	15	0.4
	1.2	Axial(φ4.0/φ0.98)	RM 2B	100	-40 to +150		0.91	1.5	10	50	100	12	0.6
	1.2	Axial(φ4.0/φ0.78)	RM 10B	150	-40 to +150		0.91	1.5	10	50	100	15	0.4
	2.5	Axial(φ5.2/φ1.2)	RM 3B	150	-40 to +150		0.95	2.5	10	100	150	10	1.0
	1.7(3.0)	Axial(φ6.5/φ1.4)	RM 4B	150	-40 to +150		0.95	3.0	10	50	100	8	1.2

4-1 Rectifier Diode

V _{RM} (V)	I _F (AV) (A) <small>Values in parentheses are for the products with heatsinks</small>	Package Axial <small>(Body Diameter/Lead Diameter)</small>	Part Number	I _{FSM} (A)	T _J (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _{R(H)} (μA)	T _a (°C)	R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
				50Hz <small>Single Half Sine Wave</small>					V _R =V _{RM} max	V _R =V _{RM} max			
1000	0.8	Axial(φ4.0/φ0.78)	RM 1C	40	-40 to +150		1.2	1.0	5	50	100	15	0.4
	1.0	Axial(φ2.7/φ0.78)	EM 1C	35	-40 to +150		0.97	1.0	20	100	100	17	0.3
	1.2	Axial(φ4.0/φ0.98)	RO 2C	80	-40 to +150		0.92	1.5	10	50	100	12	0.61
	1.2	Axial(φ4.0/φ0.78)	RM 11C	100	-40 to +150		0.92	1.5	10	50	100	15	0.4
	1.2	Axial(φ4.0/φ0.98)	RM 2C	100	-40 to +150		0.91	1.5	10	50	100	12	0.6
	2.0	Axial(φ5.2/φ1.2)	RM 3C	150	-40 to +150		0.95	2.5	10	100	150	10	1.0
	1.7(3.0)	Axial(φ6.5/φ1.4)	RM 4C	150	-40 to +150		0.95	3.0	10	50	100	8	1.2

● Bridge

V _{RM} (V)	I _F (AV) (A) <small>Values in parentheses are for the products with heatsinks</small>	Package	Part Number	I _{FSM} (A)	T _J (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _{R(H)} (μA)	T _a (°C)	R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
				50Hz <small>Single Half Sine Wave</small>					V _R =V _{RM} max	V _R =V _{RM} max			
60	4.0	RBV-40	RBV-406B*1	40	-40 to +150		0.62	2.0	2	55	150	5	4.25
100	4.0	RBV-40	RBV-401	80	-40 to +150		1.05	2.0	10	100	100	5.0	4.05
	6.0	RBV-60	RBV-601	120	-40 to +150		1.00	3.0	10	100	100	3.0	6.45
200	4.0	RBV-40	RBV-402	80	-40 to +150		1.05	2.0	10	100	100	5.0	4.05
	4.0	RBV-40	RBV-402L*2	80	-40 to +150		0.98	2.0	50	100	100	5.0	4.05
	6.0	RBV-60	RBV-602L*3	100	-40 to +150		1.0	3.0	250	1000	100	3.0	6.45
	6.0	RBV-60	RBV-602	120	-40 to +150		1.00	3.0	10	100	100	3.0	6.45
400	10	RBV-40	RBV-4102	80	-40 to +150		1.1	5.0	10	100	150(Tj)	2.0	4.05
	4.0	RBV-40	RBV-404	80	-40 to +150		1.10	2.0	10	100	100	5.0	4.05
	6.0	RBV-60	RBV-604	120	-40 to +150		1.05	3.0	10	100	100	3.0	6.45
	600	4.0	RBV-40	RBV-406	80	-40 to +150		1.10	2.0	10	100	100	5.0
4.0		RBV-40	RBV-406H	120	-40 to +150		0.92	2.0	10	100	100	5.0	4.05
4.0		RBV-40	RBV-406M	120	-40 to +150		1.00	2.0	10	100	100	5.0	4.05
6.0		RBV-60	RBV-606	120	-40 to +150		1.05	3.0	10	100	100	3.0	6.45
6.0		RBV-60	RBV-606H	140	-40 to +150		1.05	3.0	10	200	100	3.0	6.45
10		RBV-40	RBV-4106M	120	-40 to +150		1.00	5.0	10	100	100	2.0	4.05
13		RBV-60	RBV-1306	80	-40 to +150		1.20	6.5	10	100	100	1.5	6.45
15		RBV-60	RBV-1506S	150	-40 to +150		1.10	7.5	10	200	100	1.5	6.45
15		RBV-60	RBV-1506J	150	-40 to +150		1.10	7.5	10	200	150(Tj)	1.5	6.45
15		RBV-60	RBV-1506	200	-40 to +150		1.05	7.5	50	200	100	1.5	6.45
800	25	RBV-60	RBV-2506	350	-40 to +150		1.05	12.5	50	200	100	1.5	6.45
	4.0	RBV-40	RBV-408	100	-40 to +150		1.00	2.0	10	50	100	5.0	4.05
1000	6.0	RBV-60	RBV-608	170	-40 to +150		0.95	3.0	10	100	100	3.0	6.45
	4.0	RBV-40	RBV-40C	100	-40 to +150		1.00	2.0	10	50	100	5.0	4.05
	15	RBV-60	RBV-150C	200	-40 to +150		1.05	7.5	50	200	100(Tj)	1.5	6.45

*1: Schottky barrier diode

*2: Ultrafast recovery diode (trr=40ns)

*3: Ultrafast recovery diode (trr=50ns)

4-2 Fast Recovery Diode

●Thru-hole

V _{RM} (V)	I _F (AV) (A) <small>Values in parentheses are for the products with heatsinks</small>	Package Axial <small>Body Diameter/Lead Diameter</small>	Part Number	I _{FSM} (A) <small>50Hz Single Half-Sine Wave</small>	T _j (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _{R(H)} (μA)	T _a (°C)	trr ⁽¹⁾ (μs)	I _F /I _{RP} (mA)	trr ⁽²⁾ (μs)	I _F /I _{RP} (mA)	R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
									<small>V_R=V_{RM} max</small>	<small>V_R=V_{RM} max</small>							
100	1.2	Axial(φ2.7/φ0.78)	EU 2YX	25	-40 to +150	0.9	1.2	10	300	100	0.2	10/10	0.08	10/20	17	0.3	
	1.5	Axial(φ4.0/φ0.78)	RU 2YX	30	-40 to +150	0.95	1.5	10	300	100	0.2	10/10	0.08	10/20	15	0.4	
	2.0	Axial(φ4.0/φ0.98)	RU 3YX	50	-40 to +150	0.95	2.0	10	300	100	0.2	10/10	0.08	10/20	12	0.6	
	1.5(3.5)	Axial(φ5.2/φ1.2)	RU 30Y	80	-40 to +150	0.97	3.5	10	300	100	0.4	10/10	0.18	10/20	10	1.0	
	2.0(3.5)	Axial(φ6.5/φ1.4)	RU 4Y	70	-40 to +150	1.3	3.5	10	300	100	0.4	10/10	0.18	10/20	8	1.2	
	2.2(4.0)	Axial(φ6.5/φ1.4)	RU 4YX	70	-40 to +150	1.3	3.5	10	300	100	0.4	100/100	0.18	100/200	8	1.2	
	10	TO-220F(Center-tap)	FMU-21S, R	40	-40 to +150	1.5	5.0	50	500	100	0.4	100/100	0.18	100/200	4.0	2.1	
10	TO-220F-2Pin	FMU-G2YXS	100	-40 to +150	1.0	10	50	500	100	0.2	100/100	0.08	100/200	4.2	2.1		
200	0.25	Axial(φ2.7/φ0.6)	EU01Z	15	-40 to +150	2.5	0.25	10	150	100	0.4	10/10	0.18	10/20	20	0.2	
	0.25	Axial(φ2.7/φ0.78)	EU 1Z	15	-40 to +150	2.5	0.25	10	150	100	0.4	10/10	0.18	10/20	17	0.3	
	0.5	Axial(φ2.4/φ0.6)	AU01Z	15	-40 to +150	1.7	0.5	10	150	100	0.4	10/10	0.18	10/20	22	0.13	
	0.6	Axial(φ2.7/φ0.78)	EH 1Z	30	-40 to +150	1.35	0.6	10	200	150	4	10/10	1.3	10/20	17	0.3	
	0.6	Axial(φ4.0/φ0.78)	RH 1Z	35	-40 to +150	1.3	0.6	5	70	150	4	10/10	1.3	10/20	15	0.4	
	0.7	Axial(φ2.7/φ0.78)	ES 1Z	30	-40 to +150	2.5	0.8	10	200	100	1.5	10/10	0.6	10/20	17	0.3	
	0.7	Axial(φ2.7/φ0.6)	ES01Z	30	-40 to +150	2.5	0.8	10	200	100	1.5	10/10	0.6	10/20	20	0.2	
	0.8	Axial(φ2.4/φ0.6)	AU02Z	25	-40 to +150	1.3	0.8	10	250	100	0.4	10/10	0.18	10/20	22	0.13	
	1.0	Axial(φ2.7/φ0.6)	EU02Z	15	-40 to +150	1.4	1.0	10	300	100	0.4	10/10	0.18	10/20	20	0.2	
	1.0	Axial(φ2.7/φ0.78)	EU 2Z	15	-40 to +150	1.4	1.0	10	300	100	0.4	10/10	0.18	10/20	17	0.3	
	1.0	Axial(φ4.0/φ0.78)	RU 2Z	20	-40 to +150	1.5	1.0	10	300	100	0.4	10/10	0.18	10/20	15	0.4	
	1.5(3.5)	Axial(φ5.2/φ1.2)	RU 30Z	80	-40 to +150	0.97	3.5	10	300	100	0.4	10/10	0.18	10/20	10	1.0	
	2.0(3.5)	Axial(φ6.5/φ1.4)	RU 4Z	70	-40 to +150	1.3	3.5	10	300	100	0.4	10/10	0.18	10/20	8	1.2	
	5.0	TO-220F(Center-tap)	FMU-12S, R	30	-40 to +150	1.5	2.5	50	500	100	0.4	100/100	0.18	100/200	4.0	2.1	
	10	TO-220F(Center-tap)	FMU-22S, R	40	-40 to +150	1.5	5.0	50	500	100	0.4	100/100	0.18	100/200	4.0	2.1	
20	FM80(Center-tap)	FMU-32S, R	80	-40 to +150	1.5	10	50	500	100	0.4	100/100	0.18	100/200	2.0	5.5		
400	0.25	Axial(φ2.7/φ0.6)	EU01	15	-40 to +150	2.5	0.25	10	150	100	0.4	10/10	0.18	10/20	20	0.2	
	0.25	Axial(φ2.7/φ0.78)	EU 1	15	-40 to +150	2.5	0.25	10	150	100	0.4	10/10	0.18	10/20	17	0.3	
	0.25	Axial(φ4.0/φ0.78)	RU 1	15	-40 to +150	2.5	0.25	10	200	100	0.4	10/10	0.18	10/20	15	0.4	
	0.5	Axial(φ2.4/φ0.6)	AU01	15	-40 to +150	1.7	0.5	10	150	100	0.4	10/10	0.18	10/20	22	0.13	
	0.6	Axial(φ2.4/φ0.6)	AS01	20	-40 to +150	1.5	0.6	10	50	100	1.5	10/10	0.6	10/20	22	0.13	
	0.6	Axial(φ2.7/φ0.78)	EH 1	30	-40 to +150	1.35	0.6	10	200	150	4	10/10	1.3	10/20	17	0.3	
	0.7	Axial(φ2.7/φ0.78)	ES 1	30	-40 to +150	2.5	0.8	10	200	100	1.5	10/10	0.6	10/20	20	0.2	
	0.7	Axial(φ2.7/φ0.6)	ES01	30	-40 to +150	2.5	0.8	10	200	100	1.5	10/10	0.6	10/20	20	0.2	
	0.8	Axial(φ2.4/φ0.6)	AU02	25	-40 to +150	1.3	0.8	10	250	100	0.4	10/10	0.18	10/20	22	0.13	
	1.0	Axial(φ2.7/φ0.6)	EU02	15	-40 to +150	1.4	1.0	10	300	100	0.4	10/10	0.18	10/20	20	0.2	
	1.0	Axial(φ2.7/φ0.78)	EU 2	15	-40 to +150	1.4	1.0	10	300	100	0.4	10/10	0.18	10/20	17	0.3	
	1.1	Axial(φ4.0/φ0.78)	RU 2M	20	-40 to +150	1.2	1.1	10	300	100	0.4	10/10	0.18	10/20	15	0.4	
	1.5	Axial(φ4.0/φ0.98)	RU 3	20	-40 to +150	1.5	1.5	10	400	100	0.4	10/10	0.18	10/20	12	0.6	
	1.5	Axial(φ4.0/φ0.98)	RU 3M	50	-40 to +150	1.1	1.5	10	350	100	0.4	10/10	0.18	10/20	12	0.6	
	2.0	Axial(φ5.2/φ1.2)	RU 30	200	-40 to +150	0.95	2.0	10	300	100	0.4	100/100	0.18	100/200	10	1.0	
	3.0	Axial(φ5.2/φ1.2)	RU 31	150	-40 to +150	1.2	3.0	50	500	100		100/100	0.18	100/200	10	1.0	
	1.5(3.0)	Axial(φ6.5/φ1.4)	RU 4	50	-40 to +150	1.5	3.0	10	300	100	0.4	10/10	0.18	10/20	8	1.2	
	2.0(3.5)	Axial(φ6.5/φ1.4)	RU 4M	70	-40 to +150	1.3	3.5	10	300	100	0.4	100/100	0.18	100/200	8	1.2	
	5.0	TO-220F(Center-tap)	FMU-14S, R	30	-40 to +150	1.5	2.5	50	500	100	0.4	100/100	0.18	100/200	4.0	2.1	
	10	TO-220F(Center-tap)	FMU-24S, R	40	-40 to +150	1.5	5.0	50	500	100	0.4	100/100	0.18	100/200	4.0	2.1	
	20	FM80(Center-tap)	FMU-34S, R	80	-40 to +150	1.5	10	50	500	100	0.4	100/100	0.18	100/200	2.0	5.5	
600	0.25	Axial(φ2.7/φ0.6)	EU01A	15	-40 to +150	2.5	0.25	10	150	100	0.4	10/10	0.18	10/20	20	0.2	
	0.25	Axial(φ2.7/φ0.78)	EU 1A	15	-40 to +150	2.5	0.25	10	150	100	0.4	10/10	0.18	10/20	17	0.3	
	0.25	Axial(φ4.0/φ0.78)	RU 1A	15	-40 to +150	2.5	0.25	10	200	100	0.4	10/10	0.18	10/20	15	0.4	
	0.5	Axial(φ2.4/φ0.6)	AU01A	15	-40 to +150	1.7	0.5	10	150	100	0.4	10/10	0.18	10/20	22	0.13	
	0.6	Axial(φ4.0/φ0.78)	RF 1A	15	-40 to +150	2.0	0.6	10	200	100	0.4	10/10	0.18	10/20	15	0.4	
	0.6	Axial(φ2.4/φ0.6)	AS01A	20	-40 to +150	1.5	0.6	10	50	100	1.5	10/10	0.6	10/20	22	0.13	
	0.6	Axial(φ2.7/φ0.78)	EH 1A	30	-40 to +150	1.35	0.6	10	200	150	4	10/10	1.3	10/20	17	0.3	
	0.6	Axial(φ4.0/φ0.78)	RH 1A	35	-40 to +150	1.3	0.6	5	70	150	4	10/10	1.3	10/20	15	0.4	
	0.7	Axial(φ2.7/φ0.78)	ES 1A	30	-40 to +150	2.5	0.8	10	200	100	1.5	10/10	0.6	10/20	20	0.2	
	0.7	Axial(φ2.7/φ0.78)	ES01A	30	-40 to +150	2.5	0.8	10	200	100	1.5	10/10	0.6	10/20	20	0.2	
	0.7	Axial(φ4.0/φ0.78)	RS 1A	30	-40 to +150	2.5	0.8	10	200	100	1.5	10/10	0.6	10/20	20	0.4	

4-2 Fast Recovery Diode

V _{RM} (V)	I _F (AV) (A) <small>Values in parentheses are for the products with heatsinks</small>	Package Axial <small>Body Diameter/Lead Diameter</small>	Part Number	I _{FSM}	T _j (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R	I _R (H)	T _a (°C)	trr ⁽¹⁾		trr ⁽²⁾		R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
				50Hz Single Half Sine Wave					(μA)	(μA)		μs	I _F /I _{RP} (mA)	μs	I _F /I _{RP} (mA)		
									V _R =V _{RM} max	V _R =V _{RM} max							
600	0.8	Axial(φ2.4/φ0.6)	AU02A	25	-40 to +150	1.3	0.8	10	250	100	0.4	10/10	0.18	10/20	22	0.13	
	1.0	Axial(φ2.7/φ0.6)	EU02A	15	-40 to +150	1.4	1.0	10	300	100	0.4	10/10	0.18	10/20	20	0.2	
	1.0	Axial(φ2.7/φ0.78)	EU 2A	15	-40 to +150	1.4	1.0	10	300	100	0.4	10/10	0.18	10/20	17	0.3	
	1.0	Axial(φ4.0/φ0.78)	RU 2	20	-40 to +150	1.5	1.0	10	300	100	0.4	10/10	0.18	10/20	15	0.4	
	1.1	Axial(φ4.0/φ0.78)	RU 2AM	20	-40 to +150	1.2	1.1	10	300	100	0.4	10/10	0.18	10/20	15	0.4	
	1.5	Axial(φ4.0/φ0.98)	RU 3A	20	-40 to +150	1.5	1.5	10	400	100	0.4	10/10	0.18	10/20	12	0.6	
	1.5	Axial(φ4.0/φ0.78)	RU 20A	50	-40 to +150	1.1	1.5	10	350	100	0.4	10/10	0.18	10/20	15	0.4	
	1.5	Axial(φ4.0/φ0.98)	RU 3AM	50	-40 to +150	1.1	1.5	10	350	100	0.4	10/10	0.18	10/20	12	0.6	
	2.0	Axial(φ5.2/φ1.2)	RU 30A	200	-40 to +150	0.95	2.0	10	300	100	0.4	100/100	0.18	100/200	10	1.0	
	3.0	Axial(φ5.2/φ1.2)	RU 31A	150	-40 to +150	1.2	3.0	50	500	100	0.4	100/100	0.18	100/200	10	1.0	
	1.5(3.0)	Axial(φ6.5/φ1.4)	RU 4A	50	-40 to +150	1.5	3.0	10	300	100	0.4	10/10	0.18	10/20	8	1.2	
	2.0(3.5)	Axial(φ6.5/φ1.4)	RU 4AM	70	-40 to +150	1.3	3.5	10	300	100	0.4	100/100	0.18	100/200	8	1.2	
	5.0	TO-220F2Pin	FMU-G16S	30	-40 to +150	1.25	5.0	50	500	100	0.4	100/100	0.18	100/200	4.0	2.1	
	5.0	TO-220F(Center-tap)	FMU-16S, R	30	-40 to +150	1.5	2.5	50	500	100	0.4	100/100	0.18	100/200	4.0	2.1	
	5.0	TO-220F(Center-tap)	FMUP-2056	30	-40 to +150	1.5	2.5	50	500	100(T _j)	0.4	100/100	0.18	100/200	4.0	2.1	
10	TO-220F(Center-tap)	FMU-26S, R	40	-40 to +150	1.5	5.0	50	500	100	0.4	100/100	0.18	100/200	4.0	2.1		
10	TO-220F2Pin	FMU-G26S	40	-40 to +150	1.35	10	50	500	100	0.4	100/100	0.18	100/200	4.0	2.1		
20	FM80(Center-tap)	FMU-36S, R	80	-40 to +150	1.5	10	50	500	100	0.4	100/100	0.18	100/200	2.0	5.5		
800	0.25	Axial(φ4.0/φ0.78)	RU 1B	15	-40 to +150	2.5	0.25	10	200	100	0.4	10/10	0.18	10/20	15	0.4	
	0.6	Axial(φ4.0/φ0.78)	RF 1B	15	-40 to +150	2.0	0.6	10	200	100	0.4	10/10	0.18	10/20	15	0.4	
	0.6	Axial(φ4.0/φ0.78)	RH 1B	35	-40 to +150	1.3	0.6	5	70	150	4	10/10	1.3	10/20	15	0.4	
	0.7	Axial(φ4.0/φ0.78)	RS 1B	30	-40 to +150	2.5	0.8	10	200	100	1.5	10/10	0.6	10/20	20	0.4	
	1.0	Axial(φ4.0/φ0.78)	RU 2B	20	-40 to +150	1.5	1.0	10	300	100	0.4	10/10	0.18	10/20	15	0.4	
	1.1	Axial(φ4.0/φ0.98)	RU 3B	20	-40 to +150	1.5	1.0	10	400	100	0.4	10/10	0.18	10/20	12	0.6	
	1.5(3.0)	Axial(φ6.5/φ1.4)	RU 4B	50	-40 to +150	1.6	3.0	10	500	100	0.4	10/10	0.18	10/20	8	1.2	
1000	0.2	Axial(φ4.0/φ0.78)	RU 1C	15	-40 to +150	3.0	0.25	10	200	100	0.4	10/10	0.18	10/20	15	0.4	
	0.6	Axial(φ4.0/φ0.78)	RH 1C	35	-40 to +150	1.3	0.6	5	70	150	4	10/10	1.3	10/20	15	0.4	
	0.8	Axial(φ4.0/φ0.78)	RU 2C	20	-40 to +150	1.5	1.0	10	300	100	0.4	10/10	0.18	10/20	15	0.4	
	1.5	Axial(φ4.0/φ0.98)	RU 3C	20	-40 to +150	2.5	1.5	10	400	100	0.4	10/10	0.18	10/20	12	0.6	
	1.5(2.5)	Axial(φ6.5/φ1.4)	RU 4C	50	-40 to +150	1.6	3.0	50	500	100	0.4	100/100	0.18	100/200	8	1.2	
1300	1.0	Axial(φ4.0/φ0.98)	RH 2D	60	-40 to +150	1.0	1.0	10	500	100	4	10/10	1.3	100/200	12	0.6	
	1.2(1.5)	Axial(φ6.5/φ1.4)	RU 4D	50	-40 to +150	1.8	1.5	50	500	100	0.4	500/500	0.18	500/1000	8	1.2	
	1.5(2.5)	Axial(φ6.5/φ1.4)	RU 4DS	50	-40 to +150	1.8	3.0	50	500	100	0.4	500/500	0.18	500/1000	8	1.2	
1500	0.5	Axial(φ2.7/φ0.6)	ES01F	20	-40 to +150	2.0	0.5	10	200	100	1.5	10/10	0.6	10/20	20	0.2	
	0.5	Axial(φ2.7/φ0.78)	ES 1F	20	-40 to +150	2.0	0.5	10	200	100	1.5	10/10	0.6	10/20	17	0.3	
	0.8	Axial(φ4.0/φ0.78)	RH 10F	60	-40 to +150	1.0	1.0	10	500	100	4	10/10	1.3	100/200	15	0.4	
	1.0	Axial(φ4.0/φ0.98)	RH 2F	60	-40 to +150	1.0	1.0	10	500	100	4	10/10	1.3	100/200	12	0.6	
	2.0	Axial(φ5.2/φ1.2)	RS 3FS	50	-40 to +150	1.1	3.0	50	500	100	2	100/100	0.8	100/200	10	1.0	
	2.0	Axial(φ5.2/φ1.2)	RP 3F	50	-40 to +150	1.7	2.0	50	500	100	0.7	500/500	0.3	500/1000	10	1.0	
	2.5	Axial(φ5.2/φ1.2)	RH 3F	50	-40 to +150	1.3	2.5	50	500	100	4	100/100	1.3	100/200	10	1.0	
	1.5(2.5)	Axial(φ6.5/φ1.4)	RS 4FS	50	-40 to +150	1.5	3.0	50	500	100	1	100/100	0.4	100/200	8	1.2	
	2.5	Axial(φ6.5/φ1.4)	RH 4F	50	-40 to +150	1.5	2.5	10	350	100	4	100/100	1.3	100/200	8	1.2	
	5.0	TO-220F2Pin	FMQ-G1FS	50	-40 to +150	5.0	5.0	50	500	150	0.7	500/500	0.3	500/1000	4.0	2.1	
	10	TO-220F2Pin	FMQ-G2FS	50	-40 to +150	2.8	10	50	500	150(T _j)	0.5	500/500	0.2	500/1000	4.0	2.1	
	10	TO-220F2Pin	FMU-G2FS	50	-40 to +150	1.6	10	50	6000	150(T _j)	0.6	500/500	0.25	500/1000	4.0	2.1	
	10	TO-220F2Pin	FMQ-G2FLS	50	-40 to +150	1.8	10	50	500	150(T _j)	1.2	500/500	0.4	500/1000	4.0	2.1	
10	TO-220F2Pin	FMQ-G2FMS	50	-40 to +150	2.4	10	50	500	150	0.5	500/500	0.25	500/1000	4.0	2.1		
10	TO-3PF2Pin	FMQ-G5FMS	50	-40 to +150	2.4	10	50	500	100	0.5	500/500	0.2	500/1000	2	6.5		
10	TO-3PF2Pin	FMV-G5FS	50	-40 to +150	1.5	10	50	700	100	2.0	500/500	0.8	500/1000	2	6.5		
1600	2.5	Axial(φ5.2/φ1.2)	RH 3G	50	-40 to +150	1.3	2.5	50	500	100	4	100/100	1.3	100/200	10	1.0	
1700	10	TO-3PF2Pin	FMQ-G5GS	50	-40 to +150	2.7	10	100	500	100	0.5	500/500	0.2	500/1000	2	6.5	
1800	8.0	TO-3PF2Pin	FMP-G5HS	50	-40 to +150	2.0	8	25	250	100	1.0	500/500	0.4	500/1000	2	6.5	
	10	TO-3PF2Pin	FMR-G5HS	50	-40 to +150	1.6	10	20	200	100	1.8	500/500	0.7	500/1000	2	6.5	
2000	0.2	Axial(φ4.0/φ0.78)	RC 2	20	-40 to +150	2.0	0.2	10	300	100	4.0	10/10	1.3	10/20	15	0.4	

4-3 Ultrafast Recovery Diode

●Surface-Mount

V _{RM} (V)	I _F (A) (A) <small>Values in parentheses are for the products with heatsinks</small>	Package	Part Number	I _{FSM} (A)	T _j (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _R (H) (mA)	T _a (°C)	trr ⁽¹⁾ (ns)	I _F /I _{RP} (mA)	trr ⁽²⁾ (ns)	I _F /I _{RP} (mA)	R _{th(j-l)} (°C/W)	Mass (g)
				50Hz Single Half Sine Wave					V _R =V _{RM} max	V _R =V _{RM} max							
200	0.9	Surface-Mount (SFP)	SFPL-52	25	-40 to +150	0.98	1.0	10	1	150(T _j)	50	100/100	35	100/200	20	0.072	
	1.0	Surface-Mount (SFP)	SFPL-62	25	-40 to +150	0.98	2.0	10	1	150(T _j)	50	100/100	35	100/200	20	0.072	
	1.5	Surface-Mount (SFP)	SFPX-62	30	-40 to +150	0.98	1.5	10	2	150(T _j)	30	100/100	25	100/200	20	0.072	
	3.0	Surface-Mount (D pack)	SPX-G32S	50	-40 to +150	0.98	3.0	50	10	100	30	100/100	25	100/200	5.0	0.41	
	6.0	Surface-Mount (D pack)Center-tap	SPX-62S	80	-40 to +150	0.98	3.0	50	10	100	30	100/100	25	100/200	5.0	0.41	
	10.0	Surface-Mount (TO220S)	MPL-102S	65	-40 to +150	0.98	5.0	100	0.2	150	40	100/100	30	100/200	2.5	1.4	
300	2.0	Surface-Mount (TO220S)Center-tap	MP2-202S	110	-40 to +150	0.98	10.0	200	0.4	150	50	100/100	35	100/200	2.5	1.4	
	10.0	Surface-Mount (TO220S)Center-tap	MPX-2103	65	-40 to +150	1.3	5.0	50	15	150(T _j)	30	100/100	25	100/200	2.5	1.4	
400	1.0	Surface-Mount(SFP)	SFPL-64	25	-40 to +150	1.3	1.0	10	0.05	150	50	100/100	30	100/200	20	0.072	
600	30.0	Surface-Mount(TO220S)	MP3-306	180	-40 to +150	1.7	30.0	100	0.5	150(T _j)	150	500/500	70	500/1000	2.0	1.4	

●Thru-hole

V _{RM} (V)	I _F (A) (A) <small>Values in parentheses are for the products with heatsinks</small>	Package Axial (Body Diameter/Lead Diameter)	Part Number	I _{FSM} (A)	T _j (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _R (H) (mA)	T _a (°C)	trr ⁽¹⁾ (ns)	I _F /I _{RP} (mA)	trr ⁽²⁾ (ns)	I _F /I _{RP} (mA)	R _{th(j-l)} (°C/W)	Mass (g)
				50Hz Single Half Sine Wave					V _R =V _{RM} max	V _R =V _{RM} max							
70	1.0	Axial(φ2.4/φ0.6)	AG01Y	25	-40 to +150	1.2	1.0	100	0.5	100	100	100/100	50	100/200	22	0.13	
	1.0	Axial(φ2.7/φ0.6)	EG01Y	30	-40 to +150	1.2	1.0	100	0.5	100	100	100/100	50	100/200	20	0.2	
	1.1	Axial(φ2.7/φ0.78)	EG 1Y	30	-40 to +150	1.2	1.1	100	0.5	100	100	100/100	50	100/200	17	0.3	
	1.5	Axial(φ4.0/φ0.78)	RG 10Y	50	-40 to +150	1.1	1.5	500	2.5	100	100	100/100	50	100/200	15	0.4	
	1.5	Axial(φ4.0/φ0.98)	RG 2Y	50	-40 to +150	1.1	1.5	500	2.5	100	100	100/100	50	100/200	12	0.6	
	2.0(3.5)	Axial(φ6.5/φ1.4)	RG 4Y	100	-40 to +150	1.3	3.5	1000	5	100	100	100/100	50	100/200	8	1.2	
200	0.7	Axial(φ2.4/φ0.6)	AG01Z	15	-40 to +150	1.8	0.7	100	0.5	100	100	100/100	50	100/200	22	0.13	
	0.7	Axial(φ2.7/φ0.6)	EG01Z	15	-40 to +150	1.9	0.7	50	0.3	100	100	100/100	50	100/200	20	0.2	
	0.8	Axial(φ2.7/φ0.78)	EG 1Z	15	-40 to +150	1.7	0.8	50	0.3	100	100	100/100	50	100/200	17	0.3	
	1.0	Axial(φ2.4/φ0.6)	AL01Z	25	-40 to +150	0.98	1.0	100	0.5	100	50	100/100	35	100/200	22	0.13	
	1.0	Axial(φ2.7/φ0.6)	EN 01Z	50	-40 to +150	0.92	1.0	10	2	150(T _j)	100	100/100	50	100/200	20	0.2	
	1.2	Axial(φ4.0/φ0.78)	RG 10Z	50	-40 to +150	1.5	1.2	500	2.5	100	100	100/100	50	100/200	15	0.4	
	1.2	Axial(φ4.0/φ0.98)	RG 2Z	50	-40 to +150	1.5	1.5	500	2.5	100	100	100/100	50	100/200	12	0.6	
	1.5	Axial(φ2.7/φ0.78)	EL 1Z	20	-40 to +150	0.98	1.5	100	0.5	100	100	100/100	50	100/200	17	0.3	
	1.5	Axial(φ2.7/φ0.6)	EL02Z	25	-40 to +150	0.98	1.5	50	0.1	100	40	100/100	30	100/200	20	0.2	
	1.5	Axial(φ4.0/φ0.78)	RN 1Z	60	-40 to +150	0.92	1.5	20	3	150(T _j)	100	100/100	50	100/200	15	0.4	
	2.0	Axial(φ4.0/φ0.78)	RX 10Z	30	-40 to +150	0.98	2.0	50	3	150(T _j)	30	100/100	25	100/200	15	0.4	
	2.0	Axial(φ4.0/φ0.78)	RL 10Z	30	-40 to +150	0.98	2.0	50	0.1	100	50	100/100	35	100/200	15	0.4	
	2.0	Axial(φ4.0/φ0.98)	RL 2Z	30	-40 to +150	0.98	2.0	100	0.5	100	50	100/100	35	100/200	12	0.6	
	2.0	Axial(φ4.0/φ0.98)	RN 2Z	70	-40 to +150	0.92	2.0	50	4	150(T _j)	100	100/100	50	100/200	12	0.6	
	3.0	Axial(φ5.2/φ1.2)	RX 3Z	80	-40 to +150	0.98	3.0	50	10	100	30	100/100	25	100/200	10	1.0	
	3.0	Axial(φ5.2/φ1.2)	RN 3Z	80	-40 to +150	0.92	3.0	50	6	150(T _j)	100	100/100	50	100/200	10	0.6	
	1.0(3.0)	Axial(φ6.5/φ1.4)	RG 4Z	80	-40 to +150	1.7	3.0	1000	5	100	100	100/100	50	100/200	8	1.2	
	3.5	Axial(φ5.2/φ1.2)	RL 3Z	80	-40 to +150	0.95	3.5	50	0.2	100	50	100/100	35	100/200	10	1.0	
	3.5	Axial(φ6.5/φ1.4)	RL 4Z	80	-40 to +150	0.95	3.5	150	0.5	100	50	100/100	35	100/200	8	1.2	
	3.5	Axial(φ6.5/φ1.4)	RN 4Z	120	-40 to +150	0.92	3.5	50	6	150(T _j)	100	100/100	50	100/200	8	1.2	
	5.0	TO-220F(Center-tap)	FML-12S	35	-40 to +150	0.98	2.5	150	0.5	100	40	100/100	30	100/200	4.0	2.1	
	5.0	TO-220F(Center-tap)	FMG-12S, R	35	-40 to +150	1.8	2.5	500	1.5	100	100	100/100	50	100/200	4.0	2.1	
	5.0	TO-220F(Center-tap)	FMX-12S	35	-40 to +150	0.98	2.5	50	10	100	30	100/100	25	100/200	4.0	2.1	
	5.0	TO-220F2Pin	FMP-G12S	65	-40 to +150	1.15	5.0	50	0.5	100	150	100/100	70	100/200	4.0	2.1	
	5.0	TO-220F2Pin	FML-G12S	65	-40 to +150	0.98	5.0	250	1	100	40	100/100	30	100/200	4.0	2.1	
	5.0	TO-220F2Pin	FMX-G12S	65	-40 to +150	0.98	5.0	100	20	100	30	100/100	25	100/200	4.0	2.1	
	5.0	TO-220F2Pin	FMN-G12S	100	-40 to +150	0.92	5.0	100	10	150	100	100/100	50	100/200	4.0	2.1	
	10.0	TO-220F(Center-tap)	FML-22S	65	-40 to +150	0.98	5.0	250	1	100	40	100/100	30	100/200	4.0	2.1	
	10.0	TO-220F(Center-tap)	FMG-22S, R	65	-40 to +150	1.8	5.0	500	1.5	100	100	100/100	50	100/200	4.0	2.1	
	10.0	TO-220F(Center-tap)	FMX-22S	65	-40 to +150	0.98	5.0	100	20	100	30	100/100	25	100/200	4.0	2.1	
10.0	TO-220F2Pin	FML-G22S	150	-40 to +150	0.98	10.0	500	2	100	40	500/500	30	500/1000	4.0	2.1		
10.0	TO-220F2Pin	FMX-G22S	150	-40 to +150	0.98	10.0	200	50	100	30	500/500	25	500/1000	4.0	2.1		
15.0	TO-220F(Center-tap)	FMX-22SL	100	-40 to +150	0.98	7.5	150	30	100	30	500/500	25	500/1000	4.0	2.1		
20.0	FM80(Center-tap)	FML-32S	150	-40 to +150	0.98	10.0	600	2	100	40	100/100	30	100/200	2.0	5.5		
20.0	FM80(Center-tap)	FMG-32S, R	150	-40 to +150	1.8	10.0	1000	5	100	100	100/100	50	100/200	2.0	5.5		
20.0	FM80(Center-tap)	FMX-32S	150	-40 to +150	0.98	10.0	200	50	100	30	500/500	25	500/1000	2.0	5.5		

4-3 Ultrafast Recovery Diode

V _{RM} (V)	I _F (AV) (A) <small>Values in parentheses are for the products with heatsinks</small>	Package Axial (Body Diameter/Lead Diameter)	Part Number	I _{FSM} (A) 50Hz Single Half Sine Wave	T _j (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _R (H) (mA)	T _a (°C)	trr ^① (ns)	trr ^② (ns)		R _{th(j-l)} (°C/W)	Mass (g)
									V _R =V _{RM} max	V _R =V _{RM} max			I _F /I _{RP} (mA)	I _F /I _{RP} (mA)		
200	20.0	TO-220F2Pin	FM2-2202	110	-40 to +150	0.98	10.0	200	400	150(T _j)	50	100/100	35	100/200	4.0	2.1
	20.0	TO-220F2Pin	FMXA-2202S	100	-40 to +150	1.2	10.0	100	30	150	25	500/500	—	—	4.0	2.1
300	5.0	TO-220F(Center-tap)	FMG-13S, R	35	-40 to +150	1.8	2.5	500	1.5	100	100	100/100	50	100/200	4.0	2.1
	5.0	TO-220F(Center-tap)	FML-13S	40	-40 to +150	1.3	2.5	50	0.1	100	50	100/100	35	100/200	4.0	2.1
	5.0	TO-220F2Pin	FML-G13S	70	-40 to +150	1.3	5.0	100	0.2	100	50	100/100	35	100/200	4.0	2.1
	10.0	TO-220F(Center-tap)	FMG-23S, R	65	-40 to +150	1.8	5.0	500	1.5	100	100	100/100	50	100/200	4.0	2.1
	10.0	TO-220F(Center-tap)	FML-23S	70	-40 to +150	1.3	5.0	100	0.5	100	50	100/100	35	100/200	4.0	2.1
	20.0	FM80(Center-tap)	FML-33S	100	-40 to +150	1.3	10.0	200	1	100	50	500/500	35	500/1000	2.0	5.5
	20.0	FM80(Center-tap)	FMG-33S, R	150	-40 to +150	1.8	10.0	1000	5	100	100	100/100	50	100/200	2.0	5.5
	20.0	FM80(Center-tap)	FMX-33S	100	-40 to +150	1.3	10.0	200	1	100	50	500/500	35	500/1000	2.0	5.5
	20.0	TO-220F(Center-tap)	FMX-2203	100	-40 to +150	1.3	10.0	100	30	150	30	500/500	25	500/1000	4.0	2.1
	10.0	TO-220F(Center-tap)	FMX-23S	65	-40 to +150	1.3	5.0	50	15	150	30	100/100	25	100/200	4.0	2.1
	20.0	TO-220F2Pin	FMXA-2203S	100	-40 to +150	1.3	10.0	100	30	150	25	500/500	—	—	4.0	2.1
400	0.7	Axial(φ2.4/φ0.6)	AG01	15	-40 to +150	1.8	0.7	100	0.5	100	100	100/100	50	100/200	22	0.13
	0.7	Axial(φ2.7/φ0.6)	EG01	15	-40 to +150	2.0	0.7	50	0.3	100	100	100/100	50	100/200	20	0.2
	0.8	Axial(φ2.7/φ0.78)	EG 1	15	-40 to +150	1.8	0.8	50	0.3	100	100	100/100	50	100/200	17	0.3
	1.0	Axial(φ2.4/φ0.6)	AL01	20	-40 to +150	1.4	1.0	10	0.5	150(T _j)	50	100/100	35	100/200	22	0.13
	1.2	Axial(φ4.0/φ0.78)	RG 10	50	-40 to +150	1.8	1.5	500	2.5	100	100	100/100	50	100/200	15	0.4
	1.2	Axial(φ4.0/φ0.98)	RG 2	50	-40 to +150	1.8	1.5	500	2.5	100	100	100/100	50	100/200	12	0.6
	1.5	Axial(φ2.7/φ0.78)	EL 1	20	-40 to +150	1.3	1.5	10	0.05	100	100	100/100	50	100/200	17	0.3
	2.0	Axial(φ4.0/φ0.98)	RL 2	40	-40 to +150	1.3	2.0	10	0.1	150(T _j)	50	100/100	35	100/200	12	0.6
	3.5	Axial(φ5.2/φ1.2)	RL 3	80	-40 to +150	1.3	3.5	100	0.2	150(T _j)	50	100/100	35	100/200	10	1.0
	5.0	TO-220F(Center-tap)	FMG-14S, R	35	-40 to +150	2.0	2.5	500	1.5	100	100	100/100	50	100/200	4.0	2.1
	5.0	TO-220F(Center-tap)	FML-14S	40	-40 to +150	1.3	2.5	50	0.1	100	50	100/100	35	100/200	4.0	2.1
	5.0	TO-220F2Pin	FMX-G14S	70	-40 to +150	1.3	5.0	50	15	150	30	100/100	25	100/200	4.0	2.1
	5.0	TO-220F2Pin	FML-G14S	70	-40 to +150	1.3	5.0	100	0.2	100	50	100/100	35	100/200	4.0	2.1
	5.0	TO-220F2Pin	FMN-G14S	70	-40 to +150	1.0	5.0	50	10	150(T _j)	100	100/100	50	100/200	4.0	2.1
	8.0	TO-220F(Center-tap)	FMG-24S, R	65	-40 to +150	2.0	5.0	500	2.5	100	100	100/100	50	100/200	4.0	2.1
	10.0	TO-220F(Center-tap)	FML-24S	70	-40 to +150	1.3	5.0	100	0.2	100	50	100/100	35	100/200	4.0	2.1
	16.0	FM80(Center-tap)	FMG-34S, R	100	-40 to +150	2.0	10.0	1000	5	100	100	100/100	50	100/200	2.0	5.5
	20.0	FM80(Center-tap)	FML-34S	100	-40 to +150	1.3	10.0	200	0.4	100	50	500/500	35	500/1000	2.0	5.5
	1.0(3.0)	Axial(φ6.5/φ1.4)	RG 4	80	-40 to +150	1.8	3.0	500	2.5	100	100	100/100	50	100/200	8	1.2
	3.0	Axial(φ5.2/φ1.2)	RL 31	70	-40 to +150	1.3	3.0	50	0.1	150(T _j)	50	100/100	35	100/200	10	1.0
5.0	TO-220F2Pin	FMXA-1054S	50	-40 to +150	1.5	5.0	50	15	150	20	500/500	—	—	4.0	2.1	
600	0.5	Axial(φ2.7/φ0.6)	EG01A	10	-40 to +150	2.0	0.5	100	0.5	100	100	100/100	50	100/200	20	0.2
	0.5	Axial(φ2.4/φ0.6)	AG01A	15	-40 to +150	1.8	0.5	100	0.5	100	100	100/100	50	100/200	22	0.13
	0.6	Axial(φ2.7/φ0.78)	EG 1A	10	-40 to +150	2.0	0.6	100	0.5	100	100	100/100	50	100/200	17	0.3
	1.0	Axial(φ4.0/φ0.78)	RG 10A	50	-40 to +150	2.0	1.0	500	2.5	100	100	100/100	50	100/200	15	0.4
	1.0	Axial(φ4.0/φ0.98)	RG 2A	50	-40 to +150	2.0	1.0	500	2.5	100	100	100/100	50	100/200	12	0.6
	1.2	Axial(φ4.0/φ0.98)	RD 2A	30	-40 to +150	1.55	1.2	50	0.1	150(T _j)	50	100/100	35	100/200	12	0.6
	2.0	Axial(φ5.2/φ1.2)	RL 3A	60	-40 to +150	1.7	3.0	50	0.2	150(T _j)	50	100/100	35	100/200	10	1.0
	3.0	TO-220F(Two elements)	FMC-26U	50	-40 to +150	2.0	3.0	500	3	150(T _j)	70	500/500	35	500/1000	4.0	2.1
	3.0	Axial(φ6.5/φ1.4)	RL 4A	80	-40 to +150	1.5	3.0	50	0.1	150(T _j)	50	500/500	35	500/1000	8	1.2
	4.0	TO-220F2Pin	FMG-G26S	50	-40 to +150	2.5	4.0	500	3	100	100	100/100	50	100/200	4.0	2.1
	5.0	TO-220F2Pin	FMX-G16S	50	-40 to +150	1.5	5.0	50	15	150	30	100/100	25	100/200	4.0	2.1
	5.0	TO-220F2Pin	FML-G16S	50	-40 to +150	1.5	5.0	100	0.5	100	50	500/500	35	500/1000	4.0	2.1
	5.0	TO-220F2Pin	FMN-G16S	50	-40 to +150	1.2	5.0	50	10	150(T _j)	100	100/100	50	100/200	4.0	2.1
	6.0	TO-220F(Center-tap)	FMG-26S, R	50	-40 to +150	2.2	3.0	500	3	100	100	100/100	50	100/200	4.0	2.1
	8.0	FM80-2Pin	FMG-G36S	80	-40 to +150	2.5	8.0	500	3	100	100	500/500	50	500/1000	2.0	5.5
	10.0	TO-220F2Pin	FMX-G26S	100	-40 to +150	1.5	10.0	100	20	150	30	100/100	25	100/200	4.0	2.1
	10.0	TO-220F2Pin	FMD-G26S	100	-40 to +150	1.7	10.0	100	0.3	100	50	500/500	30	500/1000	4.0	2.1
	15.0	FM80(Center-tap)	FMG-36S, R	80	-40 to +150	2.2	7.5	1000	5	100	100	100/100	50	100/200	2.0	5.5
	20.0	FM80(Center-tap)	FML-36S	100	-40 to +150	1.7	10.0	100	0.3	100	65	500/500	35	500/1000	2.0	5.5
1.0(2.0)	Axial(φ6.5/φ1.4)	RG 4A	50	-40 to +150	2.0	2.0	500	2.5	100	100	100/100	50	100/200	8	1.2	
800	3.0	TO-220F(Two elements)	FMC-28U	50	-40 to +150	3.0	3.0	100	0.5	150(T _j)	70	500/500	35	500/1000	4.0	2.1
	3.0	TO-220F2Pin	FMC-G28S	50	-40 to +150	3.0	3.0	100	1	150(T _j)	70	500/500	35	500/1000	4.0	2.1

V _{RM} (V)	I _F (AV) (A)	Package Axial (Body Diameter/Lead Diameter)	Part Number	I _{FSM} (A)	T _j (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _R (H) (mA)	T _a (°C)	trr ^① (ns)	I _F /I _{RP} (mA)	trr ^② (ns)	I _F /I _{RP} (mA)	R _{th(j-l)} (°C/W)	Mass (g)
				50Hz Single Half Sine Wave				V _R =V _{RM} max	V _R =V _{RM} max								
800	5.0	TO-220F2Pin	FMC-G28SL	60	-40 to +150		3.0	3.0	200	2	150(T _j)	70	70	35	500/1000	4.0	2.1
1000	0.2	Axial(φ2.4/φ0.6)	AP01C	5	-40 to +150		4.0	4.0	100	0.5	100	200	200	80	100/200	22	0.13
	0.2	Axial(φ2.7/φ0.6)	EP01C	5	-40 to +150		4.0	4.0	5	0.05	100	200	200	80	100/200	20	0.2
	0.4	Axial(φ2.7/φ0.6)	RU 1P	10	-40 to +150		4.0	4.0	5	0.05	100	100	100	50	100/200	15	0.4
	0.5	Axial(φ4.0/φ0.78)	EG01C	10	-40 to +150		3.3	3.3	50	0.5	100	100	100	50	100/200	20	0.2
	0.7	Axial(φ4.0/φ0.78)	RG 1C	10	-40 to +150		3.3	3.3	20	0.25	100	100	100	50	100/200	15	0.4
	4.0	TO-220F2Pin	FMG-G2CS	30	-40 to +150		4.0	4.0	50	0.3	100	100	100	50	500/1000	4.0	2.1
	5.0	FM80-2Pin	FMG-G3CS	60	-40 to +150		3.5	3.5	100	0.5	100	150	150	70	500/1000	2.0	5.5
	1.0(2.0)	Axial(φ6.5/φ1.4)	RG 4C	60	-40 to +150		3.0	3.0	500	2.5	100	100	100	50	500/1000	8	1.2
1200	3.0	TO-220F2Pin(Two elements)	FMC-26UA	50	-40 to +150		4.0	4.0	500	3	150(T _j)	70	70	35	500/1000	4.0	2.1
1600	3.0	TO-220F2Pin(Two elements)	FMC-28UA	50	-40 to +150		6.0	6.0	100	0.5	150(T _j)	70	70	35	500/1000	4.0	2.1
2000	0.1	Axial(φ4.0/φ0.78)	RP 1H	5	-40 to +150		7.0	7.0	20	0.01	100	100	100	50	10/20	15	0.4

4-4 Schottky Barrier Diode

Standard

●Surface-Mount

V _{RM} (V)	I _F (AV) (A)	Package	Part Number	I _{FSM} (A)	T _J (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _R (H) (mA)	T _a (°C)	R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
				50Hz Single Half Sine Wave					V _R =V _{RM} max	V _R =V _{RM} max			
40	1.0	Surface-Mount (SFP)	SFPB-54	30	-40 to +150	0.55	1.0	1	35	150	20	0.072	
	2.0	Surface-Mount (SFP)	SFPB-64	60	-40 to +150	0.55	2.0	5	70	150	20	0.072	
	3.0	Surface-Mount (SFP)	SFPB-74	60	-40 to +150	0.5	2.0	5	100	150	20	0.072	
	3.0	Surface-Mount (D pack)	SPB-G34S	50	-40 to +150	0.55	3.0	3.5	100	150	5	0.29	
	5.0	Surface-Mount (D pack)	SPB-G54S	60	-40 to +150	0.55	5.0	5	175	150	5	0.29	
	6.0	Surface-Mount (D pack)Center-tap	SPB-64S	50	-40 to +150	0.55	3.0	3.5	100	150	5	0.29	
60	0.7	Surface-Mount(SFP)	SFPB-56	10	-40 to +150	0.62	0.7	1	30	150	20	0.072	
	2.0	Surface-Mount(SFP)	SFPB-66	25	-40 to +150	0.69	2.0	1	55	150	20	0.072	
	2.0	Surface-Mount(SFP)	SFPB-76	40	-40 to +150	0.62	2.0	2	70	150	20	0.072	
	5.0	Surface-Mount (D pack)	SPB-G56S	60	-40 to +150	0.7	5.0	3	125	150	5	0.29	
	1.5	Surface-Mount (SFP)	SFPW-56	25	-40 to +150	0.7	1.5	1	70	150	20	0.072	
90	0.7	Surface-Mount (SFP)	SFPB-59	10	-40 to +150	0.81	0.7	1	30	150	20	0.072	
	1.5	Surface-Mount (SFP)	SFPB-69	40	-40 to +150	0.81	1.5	2	55	150	20	0.072	
100	20	Surface-Mount (TO220S)Center-tap	MPE-220A	120	-40 to +150	0.85	10.0	1	100	150	2.5	1.04	

●Thru-hole

V _{RM} (V)	I _F (AV) (A)	Package Axial (Body Diameter/Lead Diameter)	Part Number	I _{FSM} (A)	T _J (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _R (H) (mA)	T _a (°C)	R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
				50Hz Single Half Sine Wave					V _R =V _{RM} max	V _R =V _{RM} max			
30	1.0	Axial(φ2.4/φ0.6)	AK 03	25	-40 to +150	0.55	1.0	1.0	35	150	22	0.13	
	1.0	Axial(φ2.7/φ0.6)	EK 03	40	-40 to +150	0.55	1.0	5.0	35	150	20	0.3	
	1.5	Axial(φ2.7/φ0.78)	EK 13	40	-40 to +150	0.55	2.0	5.0	70	150	17	0.3	
	1.7	Axial(φ4.0/φ0.78)	RK 13	60	-40 to +150	0.55	2.0	5	70	150	15	0.45	
	2.5	Axial(φ4.0/φ0.98)	RK 33	50	-40 to +150	0.55	2.5	5	100	150	12	0.6	
	3.0	Axial(φ6.5/φ1.4)	RK 43	80	-40 to +150	0.55	3.0	5	100	150	8	1.2	
	1.0	Axial(φ2.4/φ0.6)	AK 04	25	-40 to +150	0.55	1.0	1	35	150	22	0.13	
40	1.0	Axial(φ2.4/φ0.6)	AW 04	25	-40 to +150	0.58	1.0	5	35	150	22	0.13	
	1.0	Axial(φ2.7/φ0.6)	EK 04	40	-40 to +150	0.55	1.0	5	35	150	20	0.3	
	1.5	Axial(φ2.7/φ0.78)	EK 14	40	-40 to +150	0.55	2.0	5	70	150	17	0.3	
	1.7	Axial(φ4.0/φ0.78)	RK 14	60	-40 to +150	0.55	2.0	5	70	150	15	0.45	
	2.5	Axial(φ4.0/φ0.98)	RK 34	50	-40 to +150	0.55	2.5	5	100	150	12	0.6	
	3.0	TO-220F2Pin	FMB-G14	60	-40 to +150	0.55	3.0	5	100	150	4	2.1	
	3.0	Axial(φ6.5/φ1.4)	RK 44	80	-40 to +150	0.55	3.0	5	100	150	8	1.2	
	4.0	TO-220F(Center-tap)	FMB-24	50	-40 to +150	0.55	2.0	5	250	150	4	2.1	
	5.0	TO-220F2Pin	FMB-G14L	60	-40 to +150	0.55	5.0	5	175	150	4	2.1	
	6.0	TO-220F(Center-tap)	FMB-24M	60	-40 to +150	0.55	3.0	5	100	150	4	2.1	
	10	TO-220F(Center-tap)	FMB-24L	60	-40 to +150	0.55	5.0	5	175	150	4	2.1	
	10	TO-220F(Center-tap)	FMW-24L	100	-40 to +150	0.55	5.0	5	175	150	4	2.1	
	10	TO-220F2Pin	FMB-G24H	150	-40 to +150	0.55	10.0	10	350	150	4	2.1	
	12	FM80(Center-tap)	FMB-34S	75	-40 to +150	0.58	6	5	175	150	2	5.5	
	15	TO-220F(Center-tap)	FMB-24H	100	-40 to +150	0.55	7.5	7.5	250	150	4	2.1	
	15	TO-220F(Center-tap)	FMW-24H	120	-40 to +150	0.55	7.5	7.5	250	150	4	2.1	
	20	FM80(Center-tap)	FMB-34	150	-40 to +150	0.55	10.0	10	350	150	2	5.5	
20	TO-220F(Center-tap)	FMB-2204	150	-40 to +150	0.55	10	10	350	150	4	2.1		
20	TO-220F(Center-tap)	FMW-2204*	150	-40 to +150	0.55	10.0	10	350	150	4	2.1		
30	TO-220F(Center-tap)	FMB-2304	150	-40 to +150	0.55	15	15	500	150	4	2.1		
30	FM80(Center-tap)	FMB-34M	300	-40 to +150	0.55	15.0	20	500	150	2	5.5		
60	0.7	Axial(φ2.4/φ0.6)	AK 06	10	-40 to +150	0.62	0.7	1	30	150	22	0.13	
	0.7	Axial(φ2.7/φ0.6)	EK 06	10	-40 to +150	0.62	0.7	1	30	150	20	0.3	
	1.5	Axial(φ2.7/φ0.78)	EK 16	25	-40 to +150	0.62	1.5	1	55	150	17	0.3	
	1.5	Axial(φ4.0/φ0.78)	RK 16	25	-40 to +150	0.62	1.5	1	55	150	15	0.45	
	2.0	Axial(φ4.0/φ0.98)	RK 36	40	-40 to +150	0.62	2.0	2	70	150	12	0.6	
	3.5	Axial(φ6.5/φ1.4)	RK 46	70	-40 to +150	0.62	3.5	3	125	150	8	1.2	

*Under development

V _{RM} (V)	I _F (AV) (A)	Package Axial (Body Diameter/Lead Diameter)	Part Number	I _{FSM} (A)	T _J (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _R (H) (mA)	T _a (°C)	R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
				50Hz Single Half Sine Wave					V _R =V _{RM} max	V _R =V _{RM} max			
60	4.0	TO-220F(Center-tap)	FMB-26	40	-40 to +150		0.62	2.0	1	55	150	4	2.1
	6.0	TO-220F2Pin	FMB-G16L	50	-40 to +150		0.62	0.62	5	175	150	150	2.1
	10	TO-220F(Center-tap)	FMB-26L	50	-40 to +150		0.62	0.62	2.5	175	150	150	2.1
	15	FM80(Center-tap)	FMB-36	100	-40 to +150		0.62	0.62	5	275	150	150	5.5
	20	TO-220F(Center-tap)	FMB-2206	150	-40 to +150		0.7	0.7	8	275	150	150	2.1
	30	FM80(Center-tap)	FMB-36M	150	-40 to +150		0.62	0.62	10	525	150	150	5.5
	30	TO-220F(Center-tap)	FMB-2306	150	-40 to +150		0.7	0.7	8	400	150	150	2.1
90	15	TO-220F(Center-tap)	FMW-2156	100	-40 to +150		0.7	0.7	5	175	150	150	2.1
	0.7	Axial(φ2.4/φ0.6)	AK 09	10	-40 to +150		0.81	0.81	1	30	150	150	0.13
	0.7	Axial(φ2.7/φ0.6)	EK 09	10	-40 to +150		0.81	0.7	1	30	150	20	0.3
	1.5	Axial(φ2.7/φ0.78)	EK 19	40	-40 to +150		0.81	1.5	2	55	150	17	0.3
	1.5	Axial(φ4.0/φ0.78)	RK 19	40	-40 to +150		0.81	1.5	2	55	150	15	0.45
	2.0	Axial(φ4.0/φ0.98)	RK 39	50	-40 to +150		0.81	2.0	3	70	150	12	0.6
	3.5	Axial(φ6.5/φ1.4)	RK 49	60	-40 to +150		0.81	3.5	5	125	150	8	1.2
	4.0	TO-220F(Center-tap)	FMB-29	50	-40 to +150		0.81	2.0	3	70	150	4	2.1
	4.0	TO-220F2Pin	FMB-G19L	60	-40 to +150		0.81	4.0	5	125	150	4	2.1
	8.0	TO-220F(Center-tap)	FMB-29L	60	-40 to +150		0.81	4.0	5	125	150	4	2.1
	15	FM80(Center-tap)	FMB-39	60	-40 to +150		0.81	7.5	10	275	150	2	5.5
20	FM80(Center-tap)	FMB-39M	150	-40 to +150		0.81	10.0	15	400	150	2	5.5	

Low V_F "A Series"

●Surface-Mount

V _{RM} (V)	I _F (AV) (A)	Package	Part Number	I _{FSM} (A)	T _J (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _R (H) (mA)	T _a (°C)	R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
				50Hz Single Half Sine Wave					V _R =V _{RM} max	V _R =V _{RM} max			
30	1.0	Surface-Mount (SFP)	SFPA-53	30	-40 to +125		0.36	1.0	1.5	70	100	20	0.072
	2.0	Surface-Mount (SFP)	SFPA-63	40	-40 to +125		0.36	2.0	3.0	140	100	20	0.072
	3.0	Surface-Mount (SFP)	SFPA-73	50	-40 to +125		0.36	3.0	4.5	210	100	20	0.072

●Thru-hole

V _{RM} (V)	I _F (AV) (A)	Package Axial (Body Diameter/Lead Diameter)	Part Number	I _{FSM} (A)	T _J (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _R (H) (mA)	T _a (°C)	R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
				50Hz Single Half Sine Wave					V _R =V _{RM} max	V _R =V _{RM} max			
30	1.0	Axial(φ2.7/φ0.6)	EA 03*	30	-40 to +125		0.36	1.0	1.5	70	100	20	0.3
	2.0	Axial(φ4.0/φ0.78)	RA 13	40	-40 to +125		0.36	2.0	3.0	140	100	15	0.45

*Under development

Low IR “E Series”

● **Surface-Mount**

V _{RM} (V)	I _F (AV) (A)	Package Axial (Body Diameter/Lead Diameter)	Part Number	I _{FSM} (A)	T _J (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _R (H) (mA)	T _a (°C)	R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
				50Hz Single Half Sine Wave					V _R =V _{RM} max	V _R =V _{RM} max			
40	2.0	Surface-Mount (SFP)	SFPE-64	40	-40 to +150		0.6	2.0	0.2	70	150	20	0.072
	2.0	Axial(φ2.7/φ0.6)	EE 04*	40	-40 to +150		0.55	1.0	5	70	150	20	0.3

*Under development

● **Thru-hole**

V _{RM} (V)	I _F (AV) (A)	Package	Part Number	I _{FSM} (A)	T _J (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _R (H) (mA)	T _a (°C)	R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
				50Hz Single Half Sine Wave					V _R =V _{RM} max	V _R =V _{RM} max			
40	10	TO-220F(Center-tap)	FME-2104	80	-40 to +150		0.6	5.0	0.5	50	150	4	2.1
	15	TO-220F(Center-tap)	FME-24H	100	-40 to +150		0.6	7.5	0.75	75	150	4	2.1
60	10	TO-220F(Center-tap)	FME-2106	60	-40 to +150		0.72	5.0	1	35	150	4	2.1
100	20	TO-220F(Center-tap)	FME-220A	120	-40 to +150		0.85	10	1	100	150	4	2.1
	30	TO-220F(Center-tap)	FME-230A	150	-40 to +150		0.85	15	1.5	150	150	4	2.1
150	10	TO-220F(Center-tap)	FME-210B	100	-40 to +150		0.9	5	0.5	25	150	4	2.1
	20	TO-220F(Center-tap)	FME-220B	120	-40 to +150		0.9	10	1.0	50	150	4	2.1
	30	TO-220F(Center-tap)	FME-230B	150	-40 to +150		0.9	15	1.5	75	150	4	2.1

Low V_F/Low IR Balance “J Series”

● **Surface-Mount**

V _{RM} (V)	I _F (AV) (A)	Package	Part Number	I _{FSM} (A)	T _J (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _R (H) (mA)	T _a (°C)	R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
				50Hz Single Half Sine Wave					V _R =V _{RM} max	V _R =V _{RM} max			
30	1.0	Surface-Mount (compact)	MI1A3	12	-40 to +150		0.47	1.0	1.0	70	150(T _J)	70	0.011
	1.0	Surface-Mount (compact)	MI2A3*	12	-40 to +150		0.39	1.0	2.0	110	150(T _J)	70	0.011
	1.0	Surface-Mount (SFP)	SFPJ-53*	30	-40 to +150		0.45	1.0	1.0	35	150	20	0.072
	2.0	Surface-Mount (SFP)	SFPJ-63	40	-40 to +150		0.45	2.0	2.0	70	150	20	0.072
	3.0	Surface-Mount (SFP)	SFPJ-73	50	-40 to +150		0.45	3.0	3.0	100	150	20	0.072
	5.0	Surface-Mount (D pack)	SPJ-G53S*	100	-40 to +150		0.45	5.0	5.0	175	150	5	0.29
	6.0	Surface-Mount (D pack)Center-tap	SPJ-63S*	50	-40 to +150		0.45	3.0	3.0	100	150	5	0.29

*Under development

● **Thru-hole**

V _{RM} (V)	I _F (AV) (A)	Package Axial (Body Diameter/Lead Diameter)	Part Number	I _{FSM} (A)	T _J (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _R (H) (mA)	T _a (°C)	R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
				50Hz Single Half Sine Wave					V _R =V _{RM} max	V _R =V _{RM} max			
30	3.0	Axial(φ6.5/φ1.4)	RJ 43	50	-40 to +150		0.45	3.0	3	100	150	8	1.2
	10	TO-220F(Center-tap)	FMJ-23L	100	-40 to +150		0.45	5.0	5	175	150	4	2.1
	20	TO-220F(Center-tap)	FMJ-2203*	150	-40 to +150		0.47	10.0	10	350	150	4	2.1
	30	TO-220F(Center-tap)	FMJ-2303	150	-40 to +150		0.48	15.0	15	500	150	4	2.1

*Under development

4-5 High Voltage Rectifier Diode

Category	V _{RM} (kV)	Part Number	I _{F(AV)} (mA)	I _{FSM} (A)	T _c (°C)	T _{stg} (°C)	V _F (V) max	I _F (mA)	I _R (μA)	I _{R(H)} (μA)	T _a (°C)	trr ⁽¹⁾ (μs)		I _F /I _{RP} (mA)	Mass (g)	Package Type No.
				50Hz Single Half Sine Wave					V _R =V _{RM} max	V _R =V _{RM} max		T _a =100°C				
General-purpose	2	SHV-02	2.0	0.3	100	-40 to +120	16	10	1	3	100	0.18	—	10/10	0.13	1
	3	SHV-03S	2.0	0.3	100	-40 to +120	16	10	1	3	100	0.18	—	10/10	0.13	
	3	SHV-03	2.0	0.5	100	-40 to +120	16	10	1	3	100	0.18	—	10/10	0.16	
For general FBT	10	SHV-10	2.0	0.5	100	-40 to +120	40	10	1	3	100	0.18	—	10/10	0.33	3
	12	SHV-12	2.0	0.5	100	-40 to +120	45	10	1	3	100	0.18	—	10/10	0.33	
	14	SHV-14	2.0	0.5	100	-40 to +120	55	10	1	3	100	0.18	—	10/10	0.33	
	16	SHV-16	2.0	0.5	100	-40 to +120	60	10	1	3	100	0.18	—	10/10	0.33	4
	20	SHV-20	2.0	0.5	100	-40 to +120	75	10	1	3	100	0.18	—	10/10	0.33	
	24	SHV-24	2.0	0.5	100	-40 to +120	75	10	1	3	100	0.18	—	10/10	0.33	
For high frequency multilayer FBT	6	SHV-06EN	2.0	0.5	100	-40 to +120	24	10	1	3	100	0.15	0.20	10/10	0.17	5
	8	SHV-08EN	2.0	0.5	100	-40 to +120	30	10	1	3	100	0.15	0.20	10/10	0.17	
	10	SHV-10EN	2.0	0.5	100	-40 to +120	38	10	1	3	100	0.15	0.20	10/10	0.20	6
	12	SHV-12EN	2.0	0.5	100	-40 to +120	45	10	1	3	100	0.15	0.20	10/10	0.20	
For ultra-high frequency multilayer FBT	8	SHV-08DN	2.0	0.5	100	-40 to +120	30	10	1	3	100	0.15	0.20	10/10	0.17	5
	10	SHV-10DN	2.0	0.5	100	-40 to +120	38	10	1	3	100	0.15	0.20	10/10	0.20	6
	12	SHV-12DN	2.0	0.5	100	-40 to +120	45	10	1	3	100	0.15	0.20	10/10	0.20	
For general microwave oven	9	HVR-1X-40B	350	20	60(Ta)	-40 to +130	9	350	10	V _Z =9.5 to 15kV		—	—	—	2.5	7
For inverter microwave oven	8	UX-F5B	350	15	60(Ta)	-30 to +130	14	350	10	V _Z =8.5kVmin		0.15	—	100/100	2.5	
For ignition	2.5	SHV-05J	30	3	—	-40 to +150	5	10	10	V _Z =2.6 to 5.0(@I _R =100μA)				0.16	2	
	3.0	SHV-06JN	30	3	—	-40 to +150	6	10	10	V _Z =3.2 to 6.0(@I _R =100μA)				0.17	5	
	4.0	SHV-08J	30	3	—	-40 to +150	8	10	10	V _Z =4.5 to 8.0(@I _R =100μA)				0.29	8	
	15.0	SHV-30J	30	3	—	-40 to +150	30	10	10	V _Z =16.0 to 30.0(@I _R =100μA)				0.33	4	

4-6 Damper Diode

Damper Diode

●For TV

V _{RM} (V)	I _F (AV) (A) <small>Values in parentheses are for the products with heatsinks</small>	Package Axial <small>(Body Diameter/Lead Diameter)</small>	Part Number	I _{FSM} (A) <small>50Hz Single Half Sine Wave</small>	T _j (°C)	T _{stg} (°C)	V _F (V) max	I _R		T _a (°C)	trr ⁽¹⁾		trr ⁽²⁾		R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
								(μA) V _R =V _{RM} max	(mA) V _R =V _{RM} max		(μs) I _F /I _{RP} (mA)	(μs) I _F /I _{RP} (mA)				
1300	1.0	Axial(φ4.0/φ0.98)	RH 2D	60	-40 to +150	1.0	1.0	10	0.5	100	4.0	10/10	1.3	100/200	12	0.6
1500	0.8	Axial(φ4.0/φ0.78)	RH 10F	60	-40 to +150	1.0	1.0	10	0.5	100	4.0	10/10	1.3	100/200	15	0.44
	1.0	Axial(φ4.0/φ0.98)	RH 2F	60	-40 to +150	1.0	1.0	10	0.5	100	4.0	10/10	1.3	100/200	12	0.6
	2.0	Axial(φ5.2/φ1.2)	RS 3FS	50	-40 to +150	1.1	3.0	50	0.5	100	2.0	100/100	0.8	100/200	10	1.0
	2.5	Axial(φ5.2/φ1.2)	RH 3F	50	-40 to +150	1.3	2.5	50	0.5	100	4.0	100/100	1.3	100/200	10	1.0
	1.5(2.5)	Axial(φ6.5/φ1.4)	RS 4FS	50	-40 to +150	1.5	3.0	50	0.5	100	1.0	100/100	0.4	100/200	8	1.2
	2.5	Axial(φ6.5/φ1.4)	RH 4F	50	-40 to +150	1.5	2.5	10	0.35	100	4.0	100/100	1.3	100/200	8	1.2
1600	2.5	Axial(φ5.2/φ1.2)	RH 3G	50	-40 to +150	1.3	2.5	50	0.5	100	4.0	100/100	1.3	100/200	10	1.0
1700	6.0	TO-220F2Pin	FMV-G2GS	50	-40 to +150	1.5	6.0	50	3	150(T _j)	2.0	500/500	0.8	500/1000	4	2.1
1800	10	TO3PF2Pin	FMR-G5HS	50	-40 to +150	1.6	10	20	0.2	100	1.8	500/500	0.7	500/1000	2	6.5

●For CRT Monitor

V _{RM} (V)	I _F (AV) (A) <small>Values in parentheses are for the products with heatsinks</small>	Package Axial <small>(Body Diameter/Lead Diameter)</small>	Part Number	I _{FSM} (A) <small>50Hz Single Half Sine Wave</small>	T _j (°C)	T _{stg} (°C)	V _F (V) max	I _R		T _a (°C)	trr ⁽¹⁾		trr ⁽²⁾		R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
								(μA) V _R =V _{RM} max	(mA) V _R =V _{RM} max		(μs) I _F /I _{RP} (mA)	(μs) I _F /I _{RP} (mA)				
1300	1.2(1.5)	Axial(φ6.5/φ1.4)	RU 4D	50	-40 to +150	1.8	1.5	50	0.5	100	0.4	500/500	0.18	500/1000	8	1.2
	1.5(2.5)	Axial(φ6.5/φ1.4)	RU 4DS	50	-40 to +150	1.8	3.0	50	0.5	100	0.4	500/500	0.18	500/1000	8	1.2
1500	2.0	Axial(φ5.2/φ1.2)	RP 3F	50	-40 to +150	1.7	2.0	50	0.5	100	0.7	500/500	0.3	500/1000	10	1.0
	5.0	TO-220F2Pin	FMQ-G1FS	50	-40 to +150	2.0	5.0	50	0.5	150	0.7	500/500	0.3	500/1000	4	2.1
	5.0	TO-220F2Pin	FMP-G2FS	50	-40 to +150	2.0	5.0	50	0.5	100	0.7	500/500	0.3	500/1000	4	2.1
	5.0	TO-220F2Pin	FMQA-105FS	50	-40 to +150	1.7	5.0	50	0.5	150(T _j)	0.5	500/500	0.2	500/1000	4	2.1
	10	TO-220F2Pin	FMQ-G2FLS	50	-40 to +150	1.8	10.0	50	0.5	150(T _j)	1.2	500/500	0.4	500/1000	4	2.1
	10	TO-220F2Pin	FMU-G2FS	50	-40 to +150	1.6	10	50	6	150(T _j)	0.6	500/500	0.25	500/1000	4	2.1
	10	TO-220F2Pin	FMQ-G2FS	50	-40 to +150	2.8	10	50	0.5	150(T _j)	0.5	500/500	0.2	500/1000	4	2.1
	10	TO-220F2Pin	FMQ-G2FMS	50	-40 to +150	2.4	10	50	0.5	150	0.5	500/500	0.25	500/1000	4	2.1
	10	TO3PF2Pin	FMQ-G5FMS	50	-40 to +150	2.4	10	50	0.5	100	0.5	500/500	0.2	500/1000	2	6.5
	1700	10	TO3PF2Pin	FMQ-G5GS	50	-40 to +150	2.7	10	100	0.5	100	0.5	500/500	0.2	500/1000	2
1800	8.0	TO3PF2Pin	FMP-G5HS	50	-40 to +150	2.0	8.0	25	0.25	100	1.0	500/500	0.4	500/1000	2	6.5
	10	TO3PF2Pin	FMR-G5HS	50	-40 to +150	1.6	10	20	0.2	100	1.8	500/500	0.7	500/1000	2	6.5

●For CRT Monitor Correction

V _{RM} (V)	I _F (AV) (A) <small>Values in parentheses are for the products with heatsinks</small>	Package Axial <small>(Body Diameter/Lead Diameter)</small>	Part Number	I _{FSM} (A) <small>50Hz Single Half Sine Wave</small>	T _j (°C)	T _{stg} (°C)	V _F (V) max	I _R		T _a (°C)	trr ⁽¹⁾		trr ⁽²⁾		R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
								(μA) V _R =V _{RM} max	(mA) V _R =V _{RM} max		(μs) I _F /I _{RP} (mA)	(μs) I _F /I _{FP} (mA)				
1300	0.5	Axial(φ4.0/φ0.98)	RG 2A2	5	-40 to +150	3.5	0.5	100	0.5	100	0.1	100/100	0.05	100/200	12	0.6
1600	1.0	Axial(φ5.2/φ1.2)	RC 3B2	20	-40 to +150	3.6	1.0	100	0.5	100	0.07	500/500	0.035	500/1000	10	1.0

DM Damper Diode

●For TV

V _{RM} (V)	I _F (AV) (A)	Package	Part Number	I _{FSM} (A)	T _j (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _R (H) (mA)	T _a (°C)	trr ⁽¹⁾ (μs)	I _F /I _{RP} (mA)	trr ⁽²⁾ (μs)	I _F /I _{RP} (mA)	R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
				50Hz Single Half Sine Wave					V _R =V _{RM} max	V _R =V _{RM} max							
1500	5.0	TO3PF	FMV-3FU	50	-40 to +150	1.4	5.0	50	0.5	100	4.0	500/500	1.3	500/1000	2.0	6.5	
600												500/500		500/1000			
1700	5.0	TO3PF	FMV-3GU	50	-40 to +150	1.5	5.0	50	0.5	100	2.0	500/500	0.8	500/1000	2.0	6.5	
600												500/500		500/1000			
1800	5.0	TO3PF	FMV-3HU	50	-40 to +150	1.5	5.0	50	3	150	2.0	500/500	0.8	500/1000	2.0	6.5	
600												500/500		500/1000			

●For CRT Monitor

V _{RM} (V)	I _F (AV) (A)	Package	Part Number	I _{FSM} (A)	T _j (°C)	T _{stg} (°C)	V _F (V) max	I _F (A)	I _R (μA)	I _R (H) (μA)	T _a (°C)	trr ⁽¹⁾ (μs)	I _F /I _{RP} (mA)	trr ⁽²⁾ (μs)	I _F /I _{RP} (mA)	R _{th(j-l)} R _{th(j-c)} (°C/W)	Mass (g)
				50Hz Single Half Sine Wave					V _R =V _{RM} max	V _R =V _{RM} max							
1500	5.0	TO220F	FMP-2FUR	50	-40 to +150	2.0	5.0	50	3	150(T _j)	0.7	500/500	0.3	500/1000	4.0	2.1	
600										150(T _j)		0.1		500/500			500/1000
1500	5.0	TO220F	FMQ-2FUR	50	-40 to +150	1.4	5.0	50	2	150	2	500/500	0.8	500/1000	4.0	2.1	
600												1.65		5.0			50
1500	5.0	TO3PF	FMP-3FU	50	-40 to +150	2.0	5.0	50	0.5	100	0.7	500/500	0.3	500/1000	1.8	6.5	
600												2.5		5.0			50
1700	5.0	TO3PF	FMQ-3GU	50	-40 to +150	2.0	5.0	500	1	100	0.7	500/500	0.3	500/1000	1.8	6.5	
800												4.0		5.0			100

4-7 Avalanche Diode with Built-in Thyristor

V _Z (V)	I _{RDC} (V) (-10°C)	Part Number	I _{FSM} (A)	T _J (°C)	T _{stg} (°C)	I _R (μA) V _R =V _{RDC} max	I _{R(H)} (μA) V _R =V _{DC} max	T _a (°C)	γ (V/°C) typ	Mass (g)	Package
			50Hz Single Half Sine Wave								
27 to 33	20	RZ1030	30	-10 to +125	-40 to +150	10	50	100	0.03	0.44	Axial(φ4.0/φ0.78)
34 to 40	28	RZ1040	30	-10 to +125	-40 to +150	10	50	100	0.05	0.44	Axial(φ4.0/φ0.78)
50 to 60	40	RZ1055	30	-10 to +125	-40 to +150	10	50	100	0.07	0.44	Axial(φ4.0/φ0.78)
115 to 135	105	RZ1125	30	-10 to +125	-40 to +150	10	50	100	0.14	0.44	Axial(φ4.0/φ0.78)
140 to 160	125	RZ1150	30	-10 to +125	-40 to +150	10	50	100	0.18	0.44	Axial(φ4.0/φ0.78)
140 to 160	125	EZ0150	30	-10 to +125	-40 to +150	10	50	100	0.18	0.44	Axial(φ4.0/φ0.78)
150 to 165	138.7	RZ1155	30	-10 to +125	-40 to +150	10	50	100	0.18	0.2	Axial(φ2.7/φ0.6)
165 to 185	150	RZ1175	30	-10 to +125	-40 to +150	10	50	100	0.22	0.44	Axial(φ4.0/φ0.78)
185 to 215	180	RZ1200	30	-10 to +125	-40 to +150	10	50	100	0.30	0.44	Axial(φ4.0/φ0.78)
220 to 250	179.5	RZ1235	30	-10 to +125	-40 to +150	10	50	100	0.30	0.44	Axial(φ4.0/φ0.78)
235 to 265	190	RZ1250	30	-10 to +125	-40 to +150	10	50	100	0.30	0.44	Axial(φ4.0/φ0.78)


4-8 Power Zener Diode

V _Z (V) I _Z = 1mA, momentary	P _R (W)	(ms)	Package Axial (Body Diameter/Lead Diameter)	Part Number	V _{DC} (V)	I _{ZSM} (A) Single Rectangular Wave	(ms)	T _j (°C)	T _{stg} (°C)	I _R (μA) V _R =V _{DC} max	I _{R(H)} (μA) V _R =V _{DC} max	T _a (°C)	V _Z Temperature Coefficient (V/°C) I _Z =1mA	R _Z (Ω) I _Z =1.0 to 10A typ	V _F (V) max	I _F (A)	Mass (g)
28±3.0*	1500	5	Axial(φ10.0/φ1.3)	PZ 628	20	65	10	-40 to +150		500	1000	150	0.036*	0.05	0.95	5	2.6
28±3.0	50	5	Surface-Mount (SFP)	SFPZ-68	20	2	5	-40 to +150		10	1000	150	0.025	0.026	0.95	1	0.072
36±3.6	450	1	Surface-Mount (D pack)	SPZ-G36	30	(11)	10	-40 to +150		5	1000	150	0.03	0.24	0.98	3	0.29
27±3.0*	5		Surface-Mount	SZ-10N27	22	70	Figure1	-55 to +175		10	—	—	0.036*	0.08	1.0	6	2.55
27±3.0*	6		Surface-Mount	SZ-10NN27	22	90	Figure1	-55 to +175		10	—	—	0.036*	0.08	0.98	6	2.55


*I_Z=10mA

Figure1

SZ-10 IZSM Condition



SZ-10 External Dimensions (Unit: mm)













4-9 Silicon Varistor






●Symmetrical

V _F (V)	I _F (mA)	Part Number	I _F (μ A) max	V _F (V)	I _{TSM} (A)	T _J (°C)	T _{stg} (°C)	R _{th(j-l)} (°C/W)	Mass (g)	Package
					50Hz Single Half Sine Wave					
1.5max	1000	VR-60SS	20	0.2	15	-40 to +100		20	0.3	Axial(ϕ 2.7/ ϕ 0.6)
2.3 \pm 0.25	1	VR-61SS			7.5	-40 to +100		20	0.3	Axial(ϕ 2.7/ ϕ 0.6)
2.75 \pm 0.25	10									
3.1 \pm 0.25	70									
4.0max	100	SV-2SS	50	1.2		-40 to +100		20	0.3	Axial(ϕ 2.7/ ϕ 0.6)
2.0max	100	SV-3SS	50	0.6		-40 to +100		20	0.3	Axial(ϕ 2.7/ ϕ 0.6)
1.8 \pm 0.2	1	SV-4SS	50	0.9		-40 to +100		20	0.3	Axial(ϕ 2.7/ ϕ 0.6)
2.15 \pm 0.2	10									
2.4 \pm 0.25	30									

●Asymmetrical


V _F (V)	I _F (mA)	Part Number	I _F (μ A) max	I _{TSM} (A)	T _J (°C)	T _{stg} (°C)	I _R (μ A)	V _R (V)	R _{th(j-l)} (°C/W)	Mass (g)	Package
				50Hz Single Half Sine Wave							
1.2 \pm 0.2	1	SV 02YS	200	30	-40 to +130		10	100	20	0.3	Axial(ϕ 2.7/ ϕ 0.6)
1.5 \pm 0.25	70										
1.8 \pm 0.2	1	SV 03YS	150	16	-40 to +130		10	100	20	0.3	Axial(ϕ 2.7/ ϕ 0.6)
2.3 \pm 0.25	70										
2.35 \pm 0.2	1	SV 04YS	100	12	-40 to +130		10	100	20	0.3	Axial(ϕ 2.7/ ϕ 0.6)
3.0 \pm 0.3	70										
3.0 \pm 0.3	1	SV 05YS	80	10	-40 to +130		10	100	20	0.3	Axial(ϕ 2.7/ ϕ 0.6)
3.8 \pm 0.4	70										
3.5 \pm 0.4	1	SV 06YS	70	8	-40 to +130		10	100	20	0.3	Axial(ϕ 2.7/ ϕ 0.6)
4.5 \pm 0.45	70										

Part Number	VR-60SS	VR-61SS	SV-2SS	SV-3SS	SV-4SS
Display Color					
Internal Connection					


Part Number	SV 02YS	SV 03YS	SV 04YS	SV 05YS	SV 06YS
Internal Connection					

Package Type (Dimensions)


• No. 1 Surface-Mount (Compact)




• No. 2 Surface-Mount (SFP)




• No. 3 Surface-Mount (D pack)



• No. 4 Surface-Mount (D pack) Center-tap




• No. 5 Surface-Mount (TO263)




• No. 6 Surface-Mount (TO220S)


MPL-102S, MP2-202S




• No. 7 Surface-Mount (TO220S)




• No. 8 Surface-Mount (TO220S) Center-tap




• No. 9 Surface-Mount (SZ-10)



• No. 10 Axial (φ2.4/φ0.6)




• No. 11 Axial (φ2.7/φ0.6)




• No. 12 Axial (φ2.7/φ0.6)


Silicon Varistor (Symmetrical)




• No. 13 Axial ($\phi 2.7/\phi 0.78$)




• No. 14 Axial ($\phi 4.0/\phi 0.78$)




• No. 15 Axial ($\phi 4.0/\phi 0.98$)




• No. 16 Axial ($\phi 5.2/\phi 1.2$)




• No. 17 Axial ($\phi 6.5/\phi 1.4$)




• No. 18 Axial ($\phi 10.0/\phi 1.3$)




• No. 19 TO-220F (Two Elements)




• No. 20 TO-220F (Center-tap)




• No. 21 TO-220F2Pin




• No. 22 TO-220F2Pin (Two Elements)




• No. 23 FM80 (Center-tap)



• No. 24 TO3PF2Pin




• No. 25 RBV-40




a: Part Number
b: Lot No.

• No. 26 RBV-60




a: Part Number
b: Lot No.


• No. 27 High Voltage Rectifier Diode (External Dimensions 1)




• No. 28 High Voltage Rectifier Diode (External Dimensions 2)




• No. 29 High Voltage Rectifier Diode (External Dimensions 3)




• No. 30 High Voltage Rectifier Diode (External Dimensions 4)




• No. 31 High Voltage Rectifier Diode (External Dimensions 5)




• No. 32 High Voltage Rectifier Diode (External Dimensions 6)



• No. 33 High Voltage Rectifier Diode (External Dimensions 7)



• No. 34 High Voltage Rectifier Diode (External Dimensions 8)



LED

Application Note	228
Part Numbering Guide	230
Selection Guide	232
• Unicolor LED/Unicolor surface mount LED	232
Taping Specifications	233
5-1 Visible Light LED	236
5-1-1 Unicolor lamp	237
5-1-2 Bicolor lamp	245
5-1-3 Unicolor surface mount	247
5-1-4 Bicolor surface mount	249
5-1-5 Surface mount LED with Three Elements	250
5-2 Infrared LED	251
5-3 Ultraviolet Surface Mount LED	252
External Dimensions List	253

Application Note

Sanken Electric's light emitting diodes (LEDs) are all molded in resin molds. When using Sanken's LEDs, observe the following cautions:

Heat resistance of mold resin

Since an LED must emit internally generated light with high efficiency, a highly transparent resin is used for molding. To ensure high transparency, the molding material must be free from the additives (silica, glass fiber, and others) that are used to improve the heat and moisture resistance of other semiconductor components (such as transistors).

Since the resin used for LEDs generally has a low heat resistance, the following cautions must be fully considered.

Never apply an external force, stress, or excess vibration to the terminals (leads) at high temperature. The glass transition point of the epoxy resin used in LEDs is about 120 to 130°C. Beyond this temperature range, the coefficient of linear thermal expansion becomes more than double that at room temperature, and the resin softens as well.

Under this condition, an external force or stress may budge the terminals, and may result in disconnection of the internal wire. Figure 1 shows reference data for the disconnection temperature and terminal load for the SEL1010 Series.

- Do not apply heat beyond the absolute maximum rating of the storage temperature (100°C for ordinary LEDs, 90°C for surface-mount LEDs). (For soldering, see the soldering conditions.)


Mechanical strength

If an excessive mechanical force is applied between the lens resin and the terminals, the lens resin or internal connections may be damaged.

Figure 2 shows the fracture strength of the SEL1000 Series according to the direction of the force applied to the terminals. When aligning or forming the terminals after soldering, do not bend or twist them with a force beyond the limits shown in Figure 2.

Forming

1. Be sure to form terminals before soldering.
2. When forming the terminals, hold tightly them at a point closer to the lens resin than the forming position to prevent stress from being applied between the lens resin and the terminals.
3. Form the terminals only below the tie-bar cuts (protruding part of the terminals).
4. Make the forming pitch equal to the board hole pitch.



Overcurrent

Since an overcurrent may burn the LED, connect a protective resistor in series to prevent a current over 100 mA in the case of a single-pulse overcurrent (excluding infrared LED).

Figure 1 Disconnection temperature - Terminal load





Figure 2 Fracture strength



Moisture-proof packaging of Surface Mount LEDs

1. Influence of moisture absorption on resin of surface-mount LEDs

If the resin is unusually damp, solder dipping may cause interfacial peeling. This phenomenon, generally called "popcorn phenomenon", occurs when a drastic temperature change causes moisture in the resin to vaporize and to expand.

- Due to this peeling, the efficiency of light emission might worsen and the luminosity could lower.

2. Moisture-proof packaging

- Surface Mount LEDs are protected by a moisture-proof packaging (baked by Sanken) to minimize moisture absorption by the resin before use.
- Aluminum laminates with high moisture resistance are used for packaging.
- Silica gel packs are enclosed in each package to further improve moisture proof efficiency.

3. Storage after opening

- Once the package has been opened, solder dipping should be carried out within seven days.

(Pb-free devices should be reflowed within 48 hours after opening the package.)

4. Handling of Remaining Surface Mount LEDs

- If some Surface Mount LEDs have not been used, put them back into the moisture-proof packaging, seal the package completely and store it in a dry place.

Chemical resistance

For washing after soldering, the following chemicals are recommended:

- Isopropyl alcohol
- Ethyl alcohol

In addition, keep the dip time within five minutes and work at room temperature.

- Freon-substitute cleaning liquid

Depending on the constituents, the chemicals may discolor the resin. Make sure that there will be no problems before use.

Mounting method

Do not mount the LED in such a way that there is a residual stress between the terminal and lens resin.

Electrostatic discharge (ESD) precaution

The devices with GaN / InGaN as die ingredients are electrostatic-sensitive, so be careful in handling them. Especially when the voltage exceeding the absolute maximum ratings are applied to the devices, they may be damaged. (SK confirmed that the devices got damaged by around 40V.) Therefore, take complete measure against ESD and surge voltages.

Mounting

1. Mounting holes

- Please use the printed circuit board with the same mounting hole spacing as the LED lead pitch.

The recommended PCB hole diameters are as follows:

Lead diameter	PCB hole diameter
0.4x0.45mm	φ0.9 to 1.0
□ 0.5mm	φ1.0 to 1.1
□ 0.6mm	φ1.0 to 1.2

2. Direct mount type

(a) Printed circuit board






Single-sided board is recommended. When using a double-sided board, do not use thru-holes. If the direct mount type LEDs and the surface mount devices are on the same surface of the board, insert the LEDs after the adhesives of the surface mount devices are cured.

(b) Insertion condition

Make an insertion pressure lower but enough to insert properly. For cut and clinch, T pattern of Panaset is recommended. When using N pattern, make the clinching angle of the anode lead looser, but enough to hold the LED. Standard Manual insertion of direct-mount type Automatic insertion of direct-mount type.


Soldering conditions

Thru-hole type


		Standard	Manual contact mount insertion	Automatic contact mount insertion
Soldering iron	Temperature	Iron bit: 350°C or lower	Iron bit: 350°C or lower	—
	Time	3 sec. or shorter	3 sec. or shorter	—
	Position			—
Flow dip soldering	Preheat	90°C, 120 sec or shorter	90°C, 120 sec or shorter	90°C, 120 sec or shorter
	Temperature	Soldering Bath: 250°C or lower	Soldering Bath: 250°C or lower	Soldering Bath: 250°C or lower
	Time	5 sec. or shorter	3 sec. or shorter	3 sec. or shorter
	Position			

- The heat resistance of the mold-resin of the direct mount type is almost equal to that of the standard type. Be careful not to apply a load when the LED is heated.
- When thermally curing the adhesive of surface-mount components on the same board after LED mounting, keep the temperature of the curing oven below 120°C and the curing time to less than 60 seconds. (For soldering a Surface Mount LED, see the soldering conditions.)
- When the direct-mount-type LED is mounted by the automatic inserter, note that open circuit may occur depending on the conditions of insertion even under the above conditions.

Surface Mount LED (Please contact out sales office for SEC1005 and 1007.)




Surface Mount Type (Pb-free device)




Reference mounting pattern for Surface Mount LED

(Unit: mm)




Part Numbering Guide


Unicolor LED




Bicolor LED




Surface Mount LED



Infrared LED (1)



Infrared LED (2)



●Emitting color

	Color code	Emitting color	Chip material	Dominant wavelength (nm)	Peak wavelength (nm)	Spectrum Half Bandwidth (nm)
Standard type	6	High luminosity	GaAlAs	642	660	30
	1	Deep red	GaP	625	700	100
	2	Red	GaAsP	620	630	35
	8	Amber	GaAsP	605	610	33
	9	Orange	GaAsP	590	587	35
	7	Yellow	GaP	571	570	30
	4	Deep green/Green	GaP	564/567	558/560	20/20
	5	Pure green	GaP	559	555	20
Ultrahigh luminosity type	E	Blue	GaN	466	430	65
	6	Deep red	AlGaInP	639	650	20
	2	Red	AlGaInP	624/625	632/635	20/15
	8	Amber	AlGaInP	605/607	611/615	17/15
	B	Light Amber	AlGaInP	595/596	598/600	16/15
	9	Orange	AlGaInP	590/589	590/591	15/15
	7	Yellow	AlGaInP	571	572	15
	4	Green	AlGaInP	563	560	15
	D	Pure green	InGaN	530	525	35
	J	Blue green	InGaN	503/505	500/502	35/30
L	Aqua Blue	InGaN	495	492	35	
E	Blue	InGaN	470	468	25	

●Lens color

Lens color			
R	Diffused red	K	Transparent yellow
W	Diffused white	G	Diffused green
S	Transparent red	E	Transparent green
C	Water clear	B	Transparent blue
D	Diffused orange	BR	Transparent deep blue
A	Transparent orange	BP	Transparent Violet
Y	Diffused yellow	BQ	Transparent light deep blue

Selection Guide

Unicolor LEDs/Unicolor surface mount LEDs

Shape	Lens diameter	Feature	Direct mount	Series	Emitting color and dominant wavelength																	Page					
					Standard luminosity type										Ultrahigh luminosity type												
					High luminosity red	Deep red	Red	Amber	Orange	Yellow	Deep green/Green	Pure green	Blue	Ultrahigh luminosity deep red	Ultrahigh luminosity red	Ultrahigh luminosity amber	Ultrahigh luminosity light amber	Ultrahigh luminosity orange	Ultrahigh luminosity yellow	Ultrahigh luminosity green	Ultrahigh luminosity pure green		Ultrahigh luminosity blue green	Ultrahigh luminosity aqua blue	Ultrahigh luminosity blue		
					Color code⇒	6	1	2	8	9	7	4	5	E	6	2	8	B	9	7	4		D	J	L	E	
Dominant wavelength [nm]⇒	642	625	620	605	590	571	564/567	559	466	639	624/625	605/607	595/596	590/589	571	563	530	503/505	495	470							
Round	5φ	Standard	N	SEL1010	○	○	○	○	○	○	○	○											237				
			N	SEL1010M			○	○	○	○	○	○													237		
		Wide viewing angle	N	SEL1010XM												△	○	○	△	○	△	△	○	△	○	237	
		Narrow viewing angle	Y	SEL1050M		○		○	○		○	○				○							○*		○*	238	
		N	SEL1015	○																						238	
	Cylinder	N	SEL1011		○	○	○	○	○	○																238	
	5.6×4.6φ	Egg-shaped	N	SEL1053M							○				○	○										238	
	4φ	Standard	N	SEL4010		○	○	○	○	○	○	○														238	
		Wide viewing angle	Y	SEL4014		○	○	○	○	○	○	○															239
	3φ	Standard	Y	SEL6010		○	○	○	○	○	○	○	○														239
		Wide viewing angle	Y	SEL6014				○	○	○	○	○		△	○	○	○	△	○	△	△					△	239
		Narrow viewing angle	Y	SEL6015				○	○	○	○	○															240
		Standard	N	SEL2010	○	○	○	○	○	○	○	○	○	△	△		△	○	△	○	△	○	△	○	○	○	240
		Narrow viewing angle	N	SEL2015				○	○	○	○	○		○													240
		Cylinder	N	SEL2011		○				○	○													○			241
2φ	Standard	N	SEL4017		○		○	○	○	○	○															241	
Inverted cone	5φ	For lighting	N	SEL1013			○	○	○	○	○	○														241	
	3φ		Y	SEL6013							○	○			○											241	
	3φ		N	SEL2013	○			○	○	○	○	○															241
Rectangular	3×5	N	SEL1021		○		○	○	○	○	○															242	
	2.5×5	N	SEL1022				○	○	○	○	○															242	
	2×5	N	SEL1020		○	○	○	○	○	○	○															242	
	1×5	N	SEL1024		○		○	○	○	○	○															242	
	2×4	N	SEL4025				○	○	○	○	○	○														242	
	2×4	Y	SEL4026				○	○	○	○	○															243	
Bow shaped	4φ	N	SEL4027				○			○																243	
	3.1φ	N	SEL4028	○			○	○	○	○	○	○														243	
	3.1φ	Y	SEL4029				○	○	○	○	○															243	
	4φ	Y	SEL6027				○	○		○																243	
5mm pitch lead	Rectangular	Y	SEL5020	○			○	○	○	○	○	○	△	△	○	△	○	○	△	○					○	244	
	3φ	Narrow viewing angle	Y	SEL5021				○	○	○	○	○														244	
	Bow shaped	Wide viewing angle	Y	SEL5023				○	○	○	○	○	○	○	○	○	○		△						○*	244	
	5.6×4.6φ	Y	SEL5055				○		○	○																244	
Surface mount	Flat lens		SEC1001	○	○	○	○	○	○	○	○													○		248	
	Inner lens		SEC1003	○			○	○	○	○	○				○	○										248	
	1608 type		SEC1005											○	△			○					△		○	247	
	1608 type		SEC1007													△			△					△	△	247	
	Side view Flat lens		SEC4001				△	○	△	△	○	△	△									△			○	247	
	Side view inner lens		SEC4003				△	△	△	△	△	△	△									△			△	247	


Y ...Available ○ ...Available
 N ...Unavailable △ ...In preparation for mass production
 * ...Not for direct mount

Taping Specifications

Lamp Types

1. Straight lead type

2. Forming (5 mm pitch) type



Taping shape (unit: mm)

Taping availability


Series name	Forming (5 mm pitch) type							Straight type						With holder*			Quantity/ package	Page
	TP1	TP2	TP3	TP6	TP7	TP8	TP19	TP4	TP5	TP15	TP16	TP17	TP18	TH8F	TH10D	TH12E		
SEL1010	○	○	○			○	○										2500	237
SEL1010M	○	○	○	○	○	○											2500	237
SEL1010XM	○	○	○	○	○	○											2500	237
SEL1050M	○	○	○	○	○	○			○								2500	238
SEL1015		○	○			○	○										2500	238
SEL1011		○	○			○	○										2500	238
SEL1053M																	2500	238
SEL4010		○	○			○	○										3000	238
SEL4014	○	○	○	○	○	○			○								3000	239
SEL6010	Use SEL2010								○					○	○		4000	239
SEL6014		○	○			○	○		○								4000	239
SEL6015	Use SEL2015								○								4000	240
SEL2010	○	○	○	○	○	○											4000	240
SEL2015	○	○	○	○	○	○											4000	240
SEL2011	○	○	○	○	○	○	○										4000	241
SEL4017	○	○	○	○	○	○											4000	241
SEL1013		○	○			○	○										2500	241
SEL6013	Use SEL2013								○								4000	241
SEL2013	○	○	○	○	○	○											4000	241
SEL1021		○	○			○	○										2500	242
SEL1022		○	○			○	○										2500	242
SEL1020		○	○			○	○										3000	242
SEL1024		○	○			○	○										3000	242
SEL4025	○	○	○	○	○	○											6000	242
SEL4026	○	○	○	○	○	○		○									6000	243
SEL4027	○	○	○	○	○	○											6000	243
SEL4028	○	○	○	○	○	○											6000	243
SEL4029	○	○	○	○	○	○											6000	243
SEL6027	Use SEL4027								○								6000	243
SEL5020										○				○			4000	244
SEL5021										○							4000	244
SEL5023										○							4000	244
SEL5055										○							4000	244
SML1016/10016								○									2500	245
SML10051								○									2500	245
SML10060								○									6000	245
SML70020										○							4000	245
SML70023										○							4000	246
SML70055										○							3000	246
SID1010	○	○	○	○	○	○											2500	251
SID1010XM	○	○	○	○	○	○											2500	251
SID1050	○	○	○	○	○	○			○								2500	251
SID300/1003											○	○	○				2000	251
SID2010																	3000	251

* The quantity per package for taping with holder are 1200.

Taping with holder

Features

- Free from the trouble of attaching LEDs to holders.
- Radial taping of 5 mm-pitch lead: Available for any inserters.




Po: The cumulative pitch error is ±1.0 mm per 20 pitches.
 Dimensional tolerance: ±0.3
 Unit: mm


See the previous page for the part number and quantity per standard package.

Surface Mount Types

Unicolor SEC1001/1003 Series




Bicolor SEC2002/2004 Series




Quantity/package: 3000

SEC1005 series




SEC1007 series




Quantity/package: 4000

SECS2D68C




SECU3M06C




Quantity/package: 4000

SEC4001/SEC4003 series



Quantity/package: 3000

Reel specifications



General tolerance: ±0.2

5-1 Visible Light LED

Absolute Maximum Ratings

●Visible Light Unicolor Lamp

Parameter	Unit	Ratings					Conditions
		GaP	GaAsP	GaAlAs	AlGaInP	InGaN	
PD	mW	75			120		
IF	mA	30					
ΔIF	mA/°C	-0.45					25°C or higher
IFP	mA	100			70		f=1kHz, tw≤100μs
VR	V	3		5			
Top	°C	-30 to +85				-30 to +80	
Tstg	°C	-30 to +100					

●Visible Light Bicolor Lamp

Parameter	Unit	Ratings					Conditions
		GaP	GaAsP	GaAlAs	AlGaInP	InGaN	
PD	mW	75			120		Same conditions for simultaneous lighting
IF	mA	30					
ΔIF	mA/°C	-0.45					25°C or higher
IFP	mA	100			70		f=1kHz, tw≤100μs
VR	V	4		5			
Top	°C	-30 to +85					
Tstg	°C	-30 to +100					

●Visible Light Unicolor Surface Mount LED

Parameter	Unit	Ratings					Conditions
		GaP	GaAsP	GaAlAs	AlGaInP	InGaN	
IF	mA	30			20		
ΔIF	mA/°C	-0.45					25°C or higher
IFP	mA	100 ^{*1}			70 ^{*2}		f=1kHz, tw≤100μs
VR	V	3		5			
Top	°C	-30 to +85				-30 to +80	
Tstg	°C	-30 to +100					

*1: 70mA for SEC1005/1007 Series
*2: 50mA for SEC1005/1007 Series

●Visible Light Bicolor Surface Mount LED

Parameter	Unit	Ratings				Conditions
		SEC2008		SEC2002/2004		
		AlGaAs	InGaN			
PD	mW	65	50	75		
IF	mA	(Same as InGaN for simultaneous lighting)		(Same conditions for simultaneous lighting)		
IF	mA	25	15	30		
ΔIF	mA/°C	-0.40	-0.22	-0.45		25°C or higher
IFP	mA	50	35	70		f=1kHz, tw≤100μs
VR	V	5		4		
Top	°C	-30 to +80			-30 to +85	
Tstg	°C	-30 to +100				

●Visible Light Three Element Surface Mount LED

Parameter	Unit	Ratings				Conditions
		SECU3M02C		SECU3M06C		
		Red	Green/Blue	Red	Green/Blue	
PD	mW	75	120	75	60	When one chip lights up (same as green/blue for simultaneous lighting)
IF	mA	30		30	15	
ΔIF	mA/°C	-0.45		-0.45	-0.22	25°C or higher
IFP	mA	70	50	50	35	f=1kHz, tw≤100μs
VR	V	5				
Top	°C	-30 to +80				
Tstg	°C	-30 to +100				

5φ Round Standard LED (with Stopper) - External Dimensions 1

SEL1010 Series (Viewing angle 2θ 1/2 - Diffused lens: 60° typ, Transparent lens: 40° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage			Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V) TYP	MAX	Conditions IF (mA)	Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
SEL1110R	Deep red	Diffused red	2.0	2.5	10	2.8	5	700	10	625	10	100	10	GaP
SEL1110S	Deep red	Transparent red	2.0	2.5	10	4.5	5	700	10	625	10	100	10	GaP
SEL1110W	Deep red	Diffused white	2.0	2.5	10	2.8	5	700	10	625	10	100	10	GaP
SEL1610C	High-luminosity red	Water clear	1.75	2.2	10	300	20	660	10	642	10	30	10	GaAlAs
SEL1610W	High-luminosity red	Diffused white	1.75	2.2	10	250	20	660	10	642	10	30	10	GaAlAs
SEL1210R	Red	Diffused red	1.9	2.5	10	26	20	630	10	620	10	35	10	GaAsP
SEL1210S	Red	Transparent red	1.9	2.5	10	75	20	630	10	620	10	35	10	GaAsP
SEL1810A	Amber	Transparent orange	1.9	2.5	10	37	10	610	10	605	10	35	10	GaAsP
SEL1810D	Amber	Diffused orange	1.9	2.5	10	18	10	610	10	605	10	35	10	GaAsP
SEL1910A	Orange	Transparent orange	1.9	2.5	10	25	10	587	10	590	10	33	10	GaAsP
SEL1910D	Orange	Diffused orange	1.9	2.5	10	14	10	587	10	590	10	33	10	GaAsP
SEL1710K	Yellow	Transparent yellow	2.0	2.5	10	65	10	570	10	571	10	30	10	GaP
SEL1710Y	Yellow	Diffused yellow	2.0	2.5	10	22	10	570	10	571	10	30	10	GaP
SEL1410E	Green	Transparent green	2.0	2.5	10	84	20	560	10	567	10	20	10	GaP
SEL1410G	Green	Diffused green	2.0	2.5	10	32	20	560	10	567	10	20	10	GaP
SEL1510C	Pure green	Water clear	2.0	2.5	10	50	20	555	10	559	10	20	10	GaP

5φ Round Standard LED - External Dimensions 2

SEL1010M Series (Viewing angle 2θ 1/2 - Diffused lens: 60° typ, Transparent lens: 40° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage			Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V) TYP	MAX	Conditions IF (mA)	Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
SEL1210RM	Red	Diffused red	1.9	2.5	10	36	20	630	10	620	10	35	10	GaAsP
SEL1210SM	Red	Transparent red	1.9	2.5	10	75	20	630	10	620	10	35	10	GaAsP
SEL1810AM	Amber	Transparent orange	1.9	2.5	10	37	10	610	10	605	10	35	10	GaAsP
SEL1810DM	Amber	Diffused orange	1.9	2.5	10	18	10	610	10	605	10	35	10	GaAsP
SEL1910AM	Orange	Transparent orange	1.9	2.5	10	34	10	587	10	590	10	33	10	GaAsP
SEL1910DM	Orange	Diffused orange	1.9	2.5	10	19	10	587	10	590	10	33	10	GaAsP
SEL1710KM	Yellow	Transparent yellow	2.0	2.5	10	65	10	570	10	571	10	30	10	GaP
SEL1410EM	Green	Transparent green	2.0	2.5	10	84	20	560	10	567	10	20	10	GaP
SEL1410GM	Green	Diffused green	2.0	2.5	10	30	20	560	10	567	10	20	10	GaP
SEL1510CM	Pure green	Water clear	2.0	2.5	10	50	20	555	10	559	10	20	10	GaP

5φ Round Wide Viewing LED - External Dimensions 3

SEL1010XM Series (Viewing angle 2θ 1/2 - AlGaInP: 60° typ, InGaN: 30° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage			Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V) TYP	MAX	Conditions IF (mA)	Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
* SELU1610CXM-S	Ultra-high luminosity	Deep red	2.0	2.5	20	350	20	650	20	639	20	20	20	AlGaInP
SELU1210CXM		Red	2.0	2.5	20	280	20	635	20	625	20	15	20	AlGaInP
SELU1810CXM		Amber	2.0	2.5	20	570	20	615	20	607	20	15	20	AlGaInP
* SELU1B10CXM-S		Light amber	2.0	2.5	20	350	20	598	20	595	20	16	20	AlGaInP
SELU1910CXM		Orange	2.0	2.5	20	450	20	591	20	589	20	15	20	AlGaInP
* SELU1710CXM		Yellow	2.1	2.5	20	300	20	572	20	571	20	15	20	AlGaInP
* SELU1410CXM-S		Green	2.1	2.5	20	150	20	560	20	562	20	12	20	AlGaInP
SELU1D10CXM		Pure green	3.3	4.0	20	2000	20	525	20	530	20	35	20	InGaN
SELU1J10CXM		Blue green	3.3	4.0	20	1150	20	502	20	505	20	35	20	InGaN
* SELU1L10CXM		Aqua blue	3.3	4.0	20	750	20	492	20	495	20	35	20	InGaN
* SELS1E10CXM-M		Blue	3.7	4.2	20	1000	20	468	20	470	20	25	20	InGaN
SELU1E10CXM		Blue	3.3	4.0	20	600	20	468	20	470	20	35	20	InGaN

* Mass production in preparation

■5φ Round Narrow Viewing Angle LED - External Dimensions 4

SEL 1050M Series (available as Direct Mount) (Viewing angle 2θ 1/2 - Diffused lens: 30° typ, Transparent lens: 30° typ)

Part Number	Emitting Color		Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
				VF (V) TYP	MAX		Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
SEL1250RM	Red		Diffused red	1.9	2.5	10	48	20	630	10	620	10	35	10	GaAsP
SEL1250SM	Red		Transparent red	1.9	2.5	10	75	20	630	10	620	10	35	10	GaAsP
SEL1850AM	Amber		Transparent orange	1.9	2.5	10	90	20	610	10	605	10	35	10	GaAsP
SEL1850DM	Amber		Diffused orange	1.9	2.5	10	60	20	610	10	605	10	35	10	GaAsP
SEL1950KM	Orange		Transparent orange	1.9	2.5	10	96	20	587	10	590	10	33	10	GaAsP
SEL1450EKM	Green		Diffused green	2.0	2.5	10	190	20	560	10	567	10	20	10	GaP
SEL1450GM-YG	Green		Diffused green	2.0	2.5	10	120	20	560	10	567	10	20	10	GaP
SEL1550CM	Pure green		Water clear	2.0	2.5	10	72	20	555	10	559	10	20	10	GaP
SEL1E50CM-S	Blue		Water clear	4.0	4.6	10	80	10	430	10	466	10	65	10	GaN
SELU1250CM	Ultrahigh luminosity	Red	Water clear	2.0	2.5	20	900	20	635	20	625	20	15	20	AlGaInP
SELU1D50CM		Pure green	Water clear	3.3	4.0	20	6000	20	525	20	530	20	35	20	InGaN
SELU1E50CM		Blue	Water clear	3.3	4.0	20	1850	20	468	20	470	20	35	20	InGaN

■5φ Round Narrow Viewing Angle LED - External Dimensions 5

SEL 1015 Series (Viewing angle 2θ 1/2 - 20° typ)

Part Number	Emitting Color		Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
				VF (V) TYP	MAX		Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
SEL1615C	High luminosity red		Water clear	1.75	2.2	10	170	20	660	10	642	10	30	10	GaAlAs

■5φ Cylinder LED - External Dimensions 6

SEL 1011 Series

Part Number	Emitting Color		Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
				VF (V) TYP	MAX		Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
SEL1111R	Deep red		Diffused red	2.0	2.5	10	1.4	10	700	10	625	10	100	10	GaP
SEL1211R	Red		Diffused red	1.9	2.5	10	12	20	630	10	620	10	35	10	GaAsP
SEL1811D	Amber		Diffused orange	1.9	2.5	10	8.0	10	610	10	605	10	35	10	GaAsP
SEL1911D	Orange		Diffused orange	1.9	2.5	10	8.0	10	587	10	590	10	33	10	GaAsP
SEL1711Y	Yellow		Diffused yellow	2.0	2.5	10	13	10	570	10	571	10	30	10	GaP
SEL1411G	Green		Diffused green	2.0	2.5	10	30	20	560	10	567	10	20	10	GaP

■4.6 × 5.6φ Egg-Shaped LED - External Dimensions 7

SEL 1053M Series (Viewing angle 2θ 1/2 - AlGaInP: 30° typ/80° typ, GaP: 30° typ/80° typ)

Part Number	Emitting Color		Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
				VF (V) TYP	MAX		Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
SEL1453CEMKT	Green		Transparent green	2.0	2.5	10	140	20	560	10	567	10	20	10	GaP
SELU1253CMKT	Ultrahigh luminosity	Red	Water clear	2.0	2.5	20	200	20	635	20	625	20	15	20	AlGaInP
SELU1853CM-S		Amber	Water clear	2.0	2.5	20	550	20	611	20	605	20	17	20	AlGaInP

■4φ Round Standard LED - External Dimensions 8

SEL 4010 Series (Viewing angle 2θ 1/2 - Diffused lens: 60° typ, Transparent lens: 40° typ)

Part Number	Emitting Color		Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
				VF (V) TYP	MAX		Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
SEL4110R	Deep red		Diffused red	2.0	2.5	10	1.7	5	700	10	625	10	100	10	GaP
SEL4110S	Deep red		Transparent red	2.0	2.5	10	2.4	5	700	10	625	10	100	10	GaP
SEL4210R	Red		Diffused red	1.9	2.5	10	17	20	630	10	620	10	35	10	GaAsP
SEL4210S	Red		Transparent red	1.9	2.5	10	30	20	630	10	620	10	35	10	GaAsP
SEL4810A	Amber		Transparent orange	1.9	2.5	10	20	10	610	10	605	10	35	10	GaAsP
SEL4810D	Amber		Diffused orange	1.9	2.5	10	15	10	610	10	605	10	35	10	GaAsP
SEL4910A	Orange		Transparent orange	1.9	2.5	10	26	10	587	10	590	10	33	10	GaAsP
SEL4910D	Orange		Diffused orange	1.9	2.5	10	16	10	587	10	590	10	33	10	GaAsP
SEL4710K	Yellow		Transparent yellow	2.0	2.5	10	36	10	570	10	571	10	30	10	GaP
SEL4710Y	Yellow		Diffused yellow	2.0	2.5	10	14	10	570	10	571	10	30	10	GaP
SEL4410E	Green		Transparent green	2.0	2.5	10	87	20	560	10	567	10	20	10	GaP
SEL4410G	Green		Diffused green	2.0	2.5	10	34	20	560	10	567	10	20	10	GaP
SEL4510C	Pure green		Water clear	2.0	2.5	10	45	20	555	10	559	10	20	10	GaP
SELU4410CKT-S	Ultrahigh luminosity	Green	Water clear	2.1	2.5	20	170	20	560	20	562	20	12	20	AlGaInP

4φ Round Wide Viewing Angle LED - External Dimensions 9

SEL 4014 Series (available as Direct Mount) (Viewing angle 2θ 1/2 - Diffused lens: 60° typ, Transparent lens: 40° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Dominant Wavelength		Chip Material
			VF (V)			Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
			TYP	MAX										
SEL4114R	Deep red	Diffused red	2.0	2.5	10	2.8	10	700	10	625	10	100	10	GaP
SEL4114S	Deep red	Transparent red	2.0	2.5	10	3.8	10	700	10	625	10	100	10	GaP
SEL4214R	Red	Diffused red	1.9	2.5	10	24	20	630	10	620	10	35	10	GaAsP
SEL4214S	Red	Transparent red	1.9	2.5	10	40	20	630	10	620	10	35	10	GaAsP
SEL4814A	Amber	Transparent orange	1.9	2.5	10	20	10	610	10	605	10	35	10	GaAsP
SEL4814D	Amber	Diffused orange	1.9	2.5	10	15	10	610	10	605	10	35	10	GaAsP
SEL4914A	Orange	Transparent orange	1.9	2.5	10	26	10	587	10	590	10	33	10	GaAsP
SEL4914D	Orange	Diffused orange	1.9	2.5	10	11	10	587	10	590	10	33	10	GaAsP
SEL4714K	Yellow	Transparent yellow	2.0	2.5	10	38	10	570	10	571	10	30	10	GaP
SEL4714Y	Yellow	Diffused yellow	2.0	2.5	10	27	10	570	10	571	10	30	10	GaP
SEL4414E	Green	Transparent green	2.0	2.5	10	69	20	560	10	567	10	20	10	GaP
SEL4414G	Green	Diffused green	2.0	2.5	10	48	20	560	10	567	10	20	10	GaP
SEL4514C	Pure green	Water clear	2.0	2.5	10	26	20	555	10	559	10	20	10	GaP

3φ Round LED - External Dimensions 10

SEL 6010 Series (available as Direct Mount) (Viewing angle 2θ 1/2 - Diffused lens: 60° typ, Transparent lens: 40° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V)			Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
			TYP	MAX										
SEL6110R	Deep red	Diffused red	2.0	2.5	10	2.6	10	700	10	625	10	100	10	GaP
SEL6110S	Deep red	Transparent red	2.0	2.5	10	3.9	10	700	10	625	10	100	10	GaP
SEL6210R	Red	Diffused red	1.9	2.5	10	18	20	630	10	620	10	35	10	GaAsP
SEL6210S	Red	Transparent red	1.9	2.5	10	41	20	630	10	620	10	35	10	GaAsP
SEL6810A	Amber	Transparent orange	1.9	2.5	10	22	10	610	10	605	10	35	10	GaAsP
SEL6810D	Amber	Diffused orange	1.9	2.5	10	9.6	10	610	10	605	10	35	10	GaAsP
SEL6910A	Orange	Transparent orange	1.9	2.5	10	22	10	587	10	590	10	33	10	GaAsP
SEL6910D	Orange	Diffused orange	1.9	2.5	10	11	10	587	10	590	10	33	10	GaAsP
SEL6710K	Yellow	Transparent yellow	2.0	2.5	10	37	10	570	10	571	10	30	10	GaP
SEL6710Y	Yellow	Diffused yellow	2.0	2.5	10	11	10	570	10	571	10	30	10	GaP
SEL6410E	Green	Transparent green	2.0	2.5	10	90	20	560	10	567	10	20	10	GaP
SEL6410G	Green	Diffused green	2.0	2.5	10	30	20	560	10	567	10	20	10	GaP
SEL6510C	Pure green	Water clear	2.0	2.5	10	42	20	555	10	559	10	20	10	GaP
SEL6510G	Pure green	Diffused green	2.0	2.5	10	9.6	20	555	10	559	10	20	10	GaP
SEL6E10C	Blue	Water clear	4.0	4.8	20	60	20	430	20	466	20	65	20	GaN
SEL6910C-S	Ultrahigh luminosity	Orange	2.0	2.5	20	550	20	591	20	589	20	15	20	AlGaInP

3φ Round Wide Viewing Angle LED - External Dimensions 11

SEL 6014 Series (available as Direct Mount) (Viewing angle 2θ 1/2 - Transparent lens: 140° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material	
			VF (V)			Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)		
			TYP	MAX											
SEL6214S	Red	Transparent red	1.9	2.5	10	18	20	630	10	620	10	35	10	GaAsP	
SEL6814A	Amber	Transparent orange	1.9	2.5	10	9.0	10	610	10	605	10	35	10	GaAsP	
SEL6914A	Orange	Transparent orange	1.9	2.5	10	8.0	10	587	10	590	10	33	10	GaAsP	
SEL6914W	Orange	Diffused white	1.9	2.5	10	5.0	10	587	10	590	10	33	10	GaAsP	
SEL6714K	Yellow	Transparent yellow	2.0	2.5	10	66	20	570	10	571	10	30	10	GaP	
SEL6714W	Yellow	Diffused white	2.0	2.5	10	30	20	570	10	571	10	30	10	GaP	
SEL6414E	Green	Transparent green	2.0	2.5	10	42	20	560	10	567	10	20	10	GaP	
SEL6414E-TG	Deep green	Transparent green	2.0	2.5	10	18	20	558	10	564	10	20	10	GaP	
SEL6514C	Pure green	Water clear	2.0	2.5	10	12	20	555	10	559	10	20	10	GaP	
SELU6614C-S	Ultrahigh luminosity	Deep red	2.0	2.5	20	150	20	650	20	639	20	20	20	AlGaInP	
SELU6614W-S		Deep red	2.0	2.5	20	90	20	650	20	639	20	20	20	AlGaInP	
SELU6214C		Red	Water clear	2.0	2.5	20	180	20	635	20	625	20	15	20	AlGaInP
SELU6814C		Amber	Water clear	2.0	2.5	20	230	20	615	20	607	20	15	20	AlGaInP
SELS6B14C		Light amber	Water clear	2.0	2.5	20	120	20	600	20	596	20	15	20	AlGaInP
SELU6914C-S		Orange	Water clear	2.0	2.5	20	180	20	591	20	589	20	15	20	AlGaInP
SELU6714C		Yellow	Water clear	2.1	2.5	20	60	20	572	20	571	20	15	20	AlGaInP
SELU6414G-S		Green	Water clear	2.1	2.5	20	30	20	560	20	562	20	12	20	AlGaInP
SELS6D14C		Pure green	Water clear	3.3	4.0	20	300	20	518	20	525	20	35	20	InGaN
SELS6E14C-M		Blue	Water clear	3.7	4.2	20	70	20	468	20	470	20	25	20	InGaN

■3φ Round Narrow Viewing Angle LED - External Dimensions 12

SEL 6015 Series (available as Direct Mount) (Viewing angle 2θ 1/2 - Transparent lens: 30° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V) TYP	MAX		Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
SEL6215S	Red	Transparent red	1.9	2.5	10	45	20	630	10	620	10	35	10	GaAsP
SEL6915A	Orange	Transparent orange	1.9	2.5	10	60	20	587	10	590	10	33	10	GaAsP
SEL6715C	Yellow	Water clear	2.0	2.5	10	90	20	570	10	571	10	30	10	GaP
SEL6415E	Green	Transparent green	2.0	2.5	10	81	20	560	10	567	10	20	10	GaP
SEL6615C	Pure green	Water clear	2.0	2.5	10	44	20	555	10	559	10	20	10	GaP

■3φ Round Standard LED - External Dimensions 13

SEL 2010 Series (Viewing angle 2θ 1/2 - Diffused lens: 60° typ, Transparent lens: 40° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material	
			VF (V) TYP	MAX		Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)		
SEL2110R	Deep red	Diffused red	2.0	2.5	10	1.8	10	700	10	625	10	100	10	GaP	
SEL2110S	Deep red	Transparent red	2.0	2.5	10	4.0	10	700	10	625	10	100	10	GaP	
SEL2110W	Deep red	Diffused white	2.0	2.5	10	1.8	10	700	10	625	10	100	10	GaP	
SEL2610C	High luminosity red	Water clear	1.75	2.2	10	60	20	660	10	642	10	30	10	GaAlAs	
SEL2210R	Red	Diffused red	1.9	2.5	10	15	20	630	10	620	10	35	10	GaAsP	
SEL2210S	Red	Transparent red	1.9	2.5	10	40	20	630	10	620	10	35	10	GaAsP	
SEL2210W	Red	Diffused white	1.9	2.5	10	15	20	630	10	620	10	35	10	GaAsP	
SEL2810A	Amber	Transparent orange	1.9	2.5	10	22	10	610	10	605	10	35	10	GaAsP	
SEL2810D	Amber	Diffused orange	1.9	2.5	10	9.0	10	610	10	605	10	35	10	GaAsP	
SEL2910A	Orange	Transparent orange	1.9	2.5	10	16	10	587	10	590	10	33	10	GaAsP	
SEL2910D	Orange	Diffused orange	1.9	2.5	10	8.0	10	587	10	590	10	33	10	GaAsP	
SEL2710K	Yellow	Transparent yellow	2.0	2.5	10	40	10	570	10	571	10	30	10	GaP	
SEL2710Y	Yellow	Diffused yellow	2.0	2.5	10	14	10	570	10	571	10	30	10	GaP	
SEL2410E	Green	Transparent green	2.0	2.5	10	77	20	560	10	567	10	20	10	GaP	
SEL2410G	Green	Diffused green	2.0	2.5	10	20	20	560	10	567	10	20	10	GaP	
SEL2510C	Pure green	Water clear	2.0	2.5	10	43	20	555	10	559	10	20	10	GaP	
SEL2510G	Pure green	Diffused green	2.0	2.5	10	8.2	20	555	10	559	10	20	10	GaP	
SEL2E10C	Blue	Water clear	4.0	4.8	20	60	20	430	10	466	20	65	10	GaN	
SELU2610C-S	Ultrahigh luminosity	Deep red	Water clear	2.0	2.5	20	300	20	650	20	639	20	20	20	AlGaNIP
* SELU2210C-S		Red	Water clear	2.0	2.5	20	350	20	632	20	624	20	20	20	AlGaNIP
* SELU2810C-S		Amber	Water clear	2.0	2.5	20	400	20	611	20	605	20	17	20	AlGaNIP
* SELU2B10C-S		Light amber	Water clear	2.0	2.5	20	300	20	598	20	595	20	16	20	AlGaNIP
* SELU2910C-S		Orange	Water clear	2.0	2.5	20	350	20	591	20	589	20	15	20	AlGaNIP
* SELU2710C		Yellow	Water clear	2.1	2.5	20	270	20	572	20	571	20	15	20	AlGaNIP
* SELU2410C-S		Green	Water clear	2.1	2.5	20	100	20	560	20	562	20	12	20	AlGaNIP
SELU2D10C		Pure green	Water clear	3.3	4.0	20	1200	20	525	20	530	20	35	20	InGaN
* SELU2J10C		Blue green	Water clear	3.3	4.0	20	800	20	502	20	505	20	35	20	InGaN
SELU2L10C		Aqua blue	Water clear	3.3	4.0	20	600	20	492	20	495	20	35	20	InGaN
SELS2E10C		Blue	Water clear	3.7	4.3	20	300	20	468	20	470	20	26	20	InGaN
SELU2E10C		Blue	Water clear	3.3	4.0	20	400	20	468	20	470	20	25	20	InGaN

* Mass production in preparation

■3φ Round Narrow Viewing Angle LED - External Dimensions 14

SEL 2015 Series (Viewing angle 2θ 1/2 - Diffused lens: 50° typ, Transparent lens: 30° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material	
			VF (V) TYP	MAX		Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)		
SEL2215R	Red	Diffused red	1.9	2.5	10	38	20	630	10	620	10	35	10	GaAsP	
SEL2215S	Red	Transparent red	1.9	2.5	10	45	20	630	10	620	10	35	10	GaAsP	
SEL2815A	Amber	Transparent orange	1.9	2.5	10	80	20	610	10	605	10	35	10	GaAsP	
SEL2815D	Amber	Diffused orange	1.9	2.5	10	60	20	610	10	605	10	35	10	GaAsP	
SEL2915A	Orange	Transparent orange	1.9	2.5	10	81	20	587	10	590	10	33	10	GaAsP	
SEL2915D	Orange	Diffused orange	1.9	2.5	10	53	20	587	10	590	10	33	10	GaAsP	
SEL2715K	Yellow	Transparent yellow	2.0	2.5	10	130	20	570	10	571	10	30	10	GaP	
SEL2715Y	Yellow	Diffused yellow	2.0	2.5	10	110	20	570	10	571	10	30	10	GaP	
SEL2415E	Green	Transparent green	2.0	2.5	10	110	20	560	10	567	10	20	10	GaP	
SEL2415G	Green	Diffused green	2.0	2.5	10	72	20	560	10	567	10	20	10	GaP	
SEL2515C	Pure green	Water clear	2.0	2.5	10	52	20	555	10	559	10	20	10	GaP	
SELU2215R-S	Ultrahigh luminosity	Red	Diffused red	2.0	2.5	20	380	20	632	20	624	20	20	20	AlGaNIP

■3φ Cylinder LED - External Dimensions 15

SEL 2011 Series

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			V TYP	MAX		Iv (mcd) TYP	Conditions IF (mA)	λ _P (nm) TYP	Conditions IF (mA)	λ _d (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
SEL2111R	Deep red	Diffused red	2.0	2.5	10	0.7	10	700	10	625	10	100	10	GaP
SEL2911D	Orange	Diffused orange	1.9	2.5	10	3.3	10	587	10	590	10	33	10	GaAsP
SEL2411G	Green	Diffused green	2.0	2.5	10	18	20	560	10	567	10	20	10	GaP
SELS2J11W	Ultrahigh luminosity	Blue green	3.4	4.0	10	47	10	505	10	508	10	26	10	InGaP

■2φ Round Special Shaped LED - External Dimensions 16

SEL 4017 Series

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			V TYP	MAX		Iv (mcd) TYP	Conditions IF (mA)	λ _P (nm) TYP	Conditions IF (mA)	λ _d (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
SEL4117R	Deep red	Diffused red	2.0	2.5	10	1.1	10	700	10	625	10	100	10	GaP
SEL4817D	Amber	Diffused orange	1.9	2.5	10	7.5	10	610	10	605	10	35	10	GaAsP
SEL4917D	Orange	Diffused orange	1.9	2.5	10	7.5	10	587	10	590	10	33	10	GaAsP
SEL4717Y	Yellow	Diffused yellow	2.0	2.5	10	14	20	570	10	571	10	30	10	GaP
SEL4417G	Green	Diffused green	2.0	2.5	10	16	20	560	10	567	10	20	10	GaP

■5φ Inverted-Cone Lighting-Panel LED - External Dimensions 17

SEL 1013 Series

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			V TYP	MAX		Iv (mcd) TYP	Conditions IF (mA)	λ _P (nm) TYP	Conditions IF (mA)	λ _d (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
SEL1213C	Red	Water clear	1.9	2.5	10	7.0	20	630	10	620	10	35	10	GaAsP
SEL1813A	Amber	Transparent orange	1.9	2.5	10	8.0	20	610	10	605	10	35	10	GaAsP
SEL1913K	Orange	Transparent light orange	1.9	2.5	10	8.0	20	587	10	590	10	33	10	GaAsP
SEL1713K	Yellow	Transparent yellow	2.0	2.5	10	15	20	570	10	571	10	30	10	GaP
SEL1413E	Green	Transparent green	2.0	2.5	10	12	20	560	10	567	10	20	10	GaP
SEL1513E	Pure green	Transparent light green	2.0	2.5	10	5.0	20	555	10	559	10	20	10	GaP

■3φ Inverted-Cone Lighting-Panel LED - External Dimensions 18

SEL 6013 Series (available as Direct Mount)

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			V TYP	MAX		Iv (mcd) TYP	Conditions IF (mA)	λ _P (nm) TYP	Conditions IF (mA)	λ _d (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
SEL6413E	Green	Transparent green	2.0	2.5	10	14	20	560	10	567	10	20	10	GaP
SEL6413E-TG	Deep green	Transparent green	2.0	2.5	10	6.0	20	558	10	564	10	20	10	GaP
SEL6513C	Pure green	Water clear	2.0	2.5	10	5.0	20	555	10	559	10	20	10	GaP
SELU6213C-S	Ultrahigh luminosity	Red	2.0	2.5	20	30	20	632	20	624	20	20	20	AlGaInP
SELS6B13W	Light amber	Diffused white	2.0	2.5	20	60	20	600	20	596	20	15	20	AlGaInP

■3φ Inverted-Cone Lighting-Panel LED - External Dimensions 19

SEL 2013 Series

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			V TYP	MAX		Iv (mcd) TYP	Conditions IF (mA)	λ _P (nm) TYP	Conditions IF (mA)	λ _d (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
SEL2613CS-S	High luminosity red	Transparent light red	1.75	2.2	10	20	20	660	10	642	10	30	10	GaAlAs
SEL2213C	Red	Water clear	1.9	2.5	10	7.0	20	630	10	620	10	35	10	GaAsP
SEL2813A	Amber	Transparent orange	1.9	2.5	10	8.0	20	610	10	605	10	35	10	GaAsP
SEL2913K	Orange	Transparent light orange	1.9	2.5	10	8.0	20	587	10	590	10	33	10	GaAsP
SEL2713K	Yellow	Transparent yellow	2.0	2.5	10	17	20	570	10	571	10	30	10	GaP
SEL2413E	Green	Transparent green	2.0	2.5	10	14	20	560	10	567	10	20	10	GaP
SEL2413G	Green	Diffused green	2.0	2.5	10	12	20	560	10	567	10	20	10	GaP
SEL2513E	Pure green	Transparent green	2.0	2.5	10	5.0	20	555	10	559	10	20	10	GaP

3 × 5 Rectangular LED - External Dimensions 20

SEL 1021 Series

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V)	MAX		lv (mcd)	Conditions IF (mA)	λP (nm)	Conditions IF (mA)	λd (nm)	Conditions IF (mA)	Δλ (nm)	Conditions IF (mA)	
			TYP		TYP		TYP		TYP		TYP			
SEL1121R	Deep red	Diffused red	2.0	2.5	10	0.9	10	700	10	625	10	100	10	GaP
SEL1821D	Amber	Diffused orange	1.9	2.5	10	3.0	10	610	10	605	10	35	10	GaAsP
SEL1921D	Orange	Diffused orange	1.9	2.5	10	3.8	10	587	10	590	10	33	10	GaAsP
SEL1721Y	Yellow	Diffused yellow	2.0	2.5	10	7.0	10	570	10	571	10	30	10	GaP
SEL1421G	Green	Diffused green	2.0	2.5	10	12	20	560	10	567	10	20	10	GaP

2.5 × 5 Rectangular LED - External Dimensions 21

SEL 1022 Series

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V)	MAX		lv (mcd)	Conditions IF (mA)	λP (nm)	Conditions IF (mA)	λd (nm)	Conditions IF (mA)	Δλ (nm)	Conditions IF (mA)	
			TYP		TYP		TYP		TYP		TYP			
SEL1222R	Red	Diffused red	1.9	2.5	10	9.0	20	630	10	620	10	35	10	GaAsP
SEL1822D	Amber	Diffused orange	1.9	2.5	10	4.8	10	610	10	605	10	35	10	GaAsP
SEL1922D	Orange	Diffused orange	1.9	2.5	10	4.5	10	587	10	590	10	33	10	GaAsP
SEL1722K	Yellow	Transparent yellow	2.0	2.5	10	12	10	570	10	571	10	30	10	GaP
SEL1722Y	Yellow	Diffused yellow	2.0	2.5	10	7.8	10	570	10	571	10	30	10	GaP
SEL1422G	Green	Diffused green	2.0	2.5	10	7.2	20	560	10	567	10	20	10	GaP

2 × 5 Rectangular LED - External Dimensions 22

SEL 1020 Series

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V)	MAX		lv (mcd)	Conditions IF (mA)	λP (nm)	Conditions IF (mA)	λd (nm)	Conditions IF (mA)	Δλ (nm)	Conditions IF (mA)	
			TYP		TYP		TYP		TYP		TYP			
SEL1120R	Deep red	Diffused red	2.0	2.5	10	0.9	10	700	10	625	10	100	10	GaP
SEL1220R	Red	Diffused red	1.9	2.5	10	4.8	20	630	10	620	10	35	10	GaAsP
SEL1820D	Amber	Diffused orange	1.9	2.5	10	3.0	10	610	10	605	10	35	10	GaAsP
SEL1920D	Orange	Diffused orange	1.9	2.5	10	3.8	10	587	10	590	10	33	10	GaAsP
SEL1720Y	Yellow	Diffused yellow	2.0	2.5	10	7.0	10	570	10	571	10	30	10	GaP
SEL1420G	Green	Diffused green	2.0	2.5	10	11	20	560	10	567	10	20	10	GaP

1 × 5 Rectangular LED - External Dimensions 23

SEL 1024 Series

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V)	MAX		lv (mcd)	Conditions IF (mA)	λP (nm)	Conditions IF (mA)	λd (nm)	Conditions IF (mA)	Δλ (nm)	Conditions IF (mA)	
			TYP		TYP		TYP		TYP		TYP			
SEL1124R	Deep red	Diffused red	2.0	2.5	10	0.5	10	700	10	625	10	100	10	GaP
SEL1824D	Amber	Diffused orange	1.9	2.5	10	4.0	10	610	10	605	10	35	10	GaAsP
SEL1924D	Orange	Diffused orange	1.9	2.5	10	3.0	10	587	10	590	10	33	10	GaAsP
SEL1724Y	Yellow	Diffused yellow	2.0	2.5	10	6.0	10	570	10	571	10	30	10	GaP
SEL1424G	Green	Diffused green	2.0	2.5	10	15	20	560	10	567	10	20	10	GaP
SEL1E24W	Blue	Diffused white	4.0	4.8	20	10	20	430	10	466	10	65	10	GaN

2 × 4 Rectangular LED - External Dimensions 24

SEL 4025 Series

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V)	MAX		lv (mcd)	Conditions IF (mA)	λP (nm)	Conditions IF (mA)	λd (nm)	Conditions IF (mA)	Δλ (nm)	Conditions IF (mA)	
			TYP		TYP		TYP		TYP		TYP			
SEL4225C	Red	Water clear	1.9	2.5	10	12	20	630	10	620	10	35	10	GaAsP
SEL4225R	Red	Diffused red	1.9	2.5	10	5.4	20	630	10	620	10	35	10	GaAsP
SEL4825A	Amber	Transparent orange	1.9	2.5	10	5.4	10	610	10	605	10	35	10	GaAsP
SEL4825D	Amber	Diffused orange	1.9	2.5	10	4.0	10	610	10	605	10	35	10	GaAsP
SEL4925A	Orange	Transparent orange	1.9	2.5	10	4.5	10	587	10	590	10	33	10	GaAsP
SEL4925D	Orange	Diffused orange	1.9	2.5	10	4.0	10	587	10	590	10	33	10	GaAsP
SEL4725K	Yellow	Transparent yellow	2.0	2.5	10	13	10	570	10	571	10	30	10	GaP
SEL4725Y	Yellow	Diffused yellow	2.0	2.5	10	5.0	10	570	10	571	10	30	10	GaP
SEL4425E	Green	Transparent green	2.0	2.5	10	20	20	560	10	567	10	20	10	GaP
SEL4425G	Green	Diffused green	2.0	2.5	10	10	20	560	10	567	10	20	10	GaP
SEL4525C	Pure Green	Water clear	2.0	2.5	10	6.6	20	555	10	559	10	20	10	GaP

■2 × 4 Rectangular LED - External Dimensions 25

SEL4026 Series (available as Direct Mount)

Part Number	Emitting Color	Lens Color	Forward Voltage			Luminous Intensity			Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V)		Conditions IF (mA)	I _v (mcd)	Conditions IF (mA)	λ _P (nm)	Conditions IF (mA)	λ _d (nm)	Conditions IF (mA)	Δλ (nm)	Conditions IF (mA)		
			TYP	MAX											
SEL4226C	Red	Water clear	1.9	2.5	10	12	20	630	10	620	10	35	10	GaAsP	
SEL4226R	Red	Diffused red	1.9	2.5	10	10	20	630	10	620	10	35	10	GaAsP	
SEL4826A	Amber	Transparent orange	1.9	2.5	10	5.4	10	610	10	605	10	35	10	GaAsP	
SEL4826D	Amber	Diffused orange	1.9	2.5	10	4.5	10	610	10	605	10	35	10	GaAsP	
SEL4926A	Orange	Transparent orange	1.9	2.5	10	6.0	10	587	10	590	10	33	10	GaAsP	
SEL4926D	Orange	Diffused orange	1.9	2.5	10	4.5	10	587	10	590	10	33	10	GaAsP	
SEL4726K	Yellow	Transparent yellow	2.0	2.5	10	14	10	570	10	571	10	30	10	GaP	
SEL4726Y	Yellow	Diffused yellow	2.0	2.5	10	8.6	10	570	10	571	10	30	10	GaP	
SEL4426E	Green	Transparent green	2.0	2.5	10	20	20	560	10	567	10	20	10	GaP	
SEL4426G	Green	Diffused green	2.0	2.5	10	14	20	560	10	567	10	20	10	GaP	

■4φ Bow Shaped LED - External Dimensions 26

SEL4027 Series (Viewing angle 2θ 1/2 - 60° typ/110° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage			Luminous Intensity			Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V)		Conditions IF (mA)	I _v (mcd)	Conditions IF (mA)	λ _P (nm)	Conditions IF (mA)	λ _d (nm)	Conditions IF (mA)	Δλ (nm)	Conditions IF (mA)		
			TYP	MAX											
SEL4227C	Red	Water clear	1.9	2.5	10	15	20	630	10	620	10	35	10	GaAsP	
SEL4427EP	Green	Transparent green	2.0	2.5	10	19	20	560	10	567	10	20	10	GaP	

■4φ Bow Shaped LED - External Dimensions 27

SEL6027 Series (available as Direct Mount) (Viewing angle 2θ 1/2 - 40° typ/50° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage			Luminous Intensity			Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V)		Conditions IF (mA)	I _v (mcd)	Conditions IF (mA)	λ _P (nm)	Conditions IF (mA)	λ _d (nm)	Conditions IF (mA)	Δλ (nm)	Conditions IF (mA)		
			TYP	MAX											
SEL6227S	Red	Transparent red	1.9	2.5	10	14	20	630	10	620	10	35	10	GaAsP	
SEL6927A	Orange	Transparent orange	1.9	2.5	10	10	10	587	10	590	10	33	10	GaAsP	
SEL6427EP	Green	Transparent green	2.0	2.5	10	26	20	560	10	567	10	20	10	GaP	

■3.1φ Bow Shaped LED - External Dimensions 28

SEL4028 Series (Viewing angle 2θ 1/2 - 40° typ/50° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage			Luminous Intensity			Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V)		Conditions IF (mA)	I _v (mcd)	Conditions IF (mA)	λ _P (nm)	Conditions IF (mA)	λ _d (nm)	Conditions IF (mA)	Δλ (nm)	Conditions IF (mA)		
			TYP	MAX											
SEL4828C-S	High luminosity red	Water clear	1.75	2.2	10	50	20	660	10	642	10	30	10	GaAlAs	
SEL4228C	Red	Water clear	1.9	2.5	10	27	20	630	10	620	10	35	10	GaAsP	
SEL4828A	Amber	Transparent orange	1.9	2.5	10	14	10	610	10	605	10	35	10	GaAsP	
SEL4928A	Orange	Transparent orange	1.9	2.5	10	14	10	587	10	590	10	33	10	GaAsP	
SEL4728K	Yellow	Transparent yellow	2.0	2.5	10	30	10	570	10	571	10	30	10	GaP	
SEL4428E	Green	Transparent green	2.0	2.5	10	63	20	560	10	567	10	20	10	GaP	
SEL4428B-TG	Deep green	Transparent blue	2.0	2.5	10	18	20	558	10	564	10	20	10	GaP	
SEL4528C	Pure green	Water clear	2.0	2.5	10	30	20	555	10	559	10	20	10	GaP	

■3.1φ Bow Shaped LED - External Dimensions 29

SEL4029 Series (available as Direct Mount) (Viewing angle 2θ 1/2 - 60° typ/110° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage			Luminous Intensity			Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V)		Conditions IF (mA)	I _v (mcd)	Conditions IF (mA)	λ _P (nm)	Conditions IF (mA)	λ _d (nm)	Conditions IF (mA)	Δλ (nm)	Conditions IF (mA)		
			TYP	MAX											
SEL4229R	Red	Diffused red	1.9	2.5	10	21	20	630	10	620	10	35	10	GaAsP	
SEL4829A	Amber	Transparent orange	1.9	2.5	10	18	10	610	10	605	10	35	10	GaAsP	
SEL4929A	Orange	Transparent orange	1.9	2.5	10	18	10	587	10	590	10	33	10	GaAsP	
SEL4729KH	Yellow	Transparent yellow	2.0	2.5	10	60	10	570	10	571	10	30	10	GaP	
SEL4429E	Green	Transparent green	2.0	2.5	10	60	20	560	10	567	10	20	10	GaP	

■5mm Pitch Lead Rectangular LED- External Dimensions 30

SEL 5020 Series (available as Direct Mount) (Viewing angle 2θ 1/2 - 120° typ/160° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material	
			TYP	MAX		I_v (mcd)	Conditions IF (mA)	λ_P (nm)	Conditions IF (mA)	λ_d (nm)	Conditions IF (mA)	$\Delta\lambda$ (nm)	Conditions IF (mA)		
SEL5620C	High luminosity red	Water clear	1.75	2.2	10	25	10	660	10	642	10	30	10	GaAlAs	
SEL5220S	Red	Transparent red	1.9	2.5	10	20	20	630	10	620	10	35	10	GaAsP	
SEL5820A	Amber	Transparent orange	1.9	2.5	10	12	20	610	10	605	10	35	10	GaAsP	
SEL5920A	Orange	Transparent orange	1.9	2.5	10	12	20	587	10	590	10	33	10	GaAsP	
SEL5420E	Green	Transparent green	2.0	2.5	10	20	20	560	10	567	10	20	10	GaP	
SEL5520C	Pure green	Water clear	2.0	2.5	10	6.0	20	555	10	559	10	20	10	GaP	
SEL5E20C	Blue	Water clear	4.0	4.8	20	10	20	430	20	466	20	65	20	GaN	
* SELU5620C-S	Ultrahigh luminosity	Deep red	2.0	2.5	20	100	20	650	20	639	20	20	20	20	AlGaInP
* SELU5220C-S		Red	2.0	2.5	20	120	20	632	20	624	20	20	20	20	AlGaInP
SELU5820C-S		Amber	2.0	2.5	20	150	20	611	20	605	20	17	20	20	AlGaInP
* SELU5B20C		Light amber	2.0	2.5	20	120	20	600	20	596	20	15	20	20	AlGaInP
SELU5920C		Orange	2.0	2.5	20	130	20	591	20	589	20	15	20	20	AlGaInP
SELU5720C		Yellow	2.1	2.5	20	50	20	572	20	571	20	15	20	20	AlGaInP
* SELU5420C-S		Green	2.1	2.5	20	25	20	560	20	562	20	12	20	20	AlGaInP
SELU5D20C		Pure green	3.3	4.0	20	240	20	525	20	530	20	35	20	20	InGaN
SELU5E20C		Blue	3.3	4.0	20	100	20	468	20	470	20	25	20	20	InGaN

* Mass production in preparation

■5mm Pitch Lead 3φ Lens LED - External Dimensions 31

SEL 5021 Series (available as Direct Mount) (Viewing angle 2θ 1/2 - 40° typ/30° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			TYP	MAX		I_v (mcd)	Conditions IF (mA)	λ_P (nm)	Conditions IF (mA)	λ_d (nm)	Conditions IF (mA)	$\Delta\lambda$ (nm)	Conditions IF (mA)	
SEL5221S	Red	Transparent red	1.9	2.5	10	35	20	630	10	620	10	35	10	GaAsP
SEL5821A	Amber	Transparent orange	1.9	2.5	10	60	20	610	10	605	10	35	10	GaAsP
SEL5921A	Orange	Transparent orange	1.9	2.5	10	60	20	587	10	590	10	33	10	GaAsP
SEL5721C	Yellow	Water clear	2.0	2.5	10	90	20	570	10	571	10	30	10	GaP
SEL5421E	Green	Transparent green	2.0	2.5	10	95	20	560	10	567	10	20	10	GaP
SEL5521C	Pure green	Water clear	2.0	2.5	10	35	20	555	10	559	10	20	10	GaP

■5mm Pitch Lead Bow Shaped LED - External Dimensions 32

SEL 5023 Series (available as Direct Mount) (Viewing angle 2θ 1/2 - 60° typ/60° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material	
			TYP	MAX		I_v (mcd)	Conditions IF (mA)	λ_P (nm)	Conditions IF (mA)	λ_d (nm)	Conditions IF (mA)	$\Delta\lambda$ (nm)	Conditions IF (mA)		
SEL5223S	Red	Transparent red	1.9	2.5	10	25	20	630	10	620	10	35	10	GaAsP	
SEL5823A	Amber	Transparent orange	1.9	2.5	10	35	20	610	10	605	10	35	10	GaAsP	
SEL5923A	Orange	Transparent orange	1.9	2.5	10	35	20	587	10	590	10	33	10	GaAsP	
SEL5723C	Yellow	Water clear	2.0	2.5	10	60	20	570	10	571	10	30	10	GaP	
SEL5423E	Green	Transparent green	2.0	2.5	10	40	20	560	10	567	10	20	10	GaP	
SEL5523C	Pure green	Water clear	2.0	2.5	10	13	20	555	10	559	10	20	10	GaP	
SEL5E23C	Blue	Water clear	4.0	4.8	20	20	20	430	20	466	20	65	20	GaN	
SEL5223C	Ultrahigh luminosity	Red	2.0	2.5	20	100	20	635	20	625	20	15	20	20	AlGaInP
SEL5823C		Amber	2.0	2.5	20	130	20	615	20	607	20	15	20	20	AlGaInP
SELU5823C		Amber	2.0	2.5	20	185	20	615	20	607	20	15	20	20	AlGaInP
SEL55B23C		Light amber	2.0	2.5	20	135	20	600	20	596	20	15	20	20	AlGaInP
SEL5923C		Orange	2.0	2.5	20	145	20	591	20	589	20	15	20	20	AlGaInP
SELU5723C		Yellow	2.0	2.5	20	155	20	572	20	571	20	15	20	20	AlGaInP
* SELU5D23C		Pure green	3.3	4.0	20	440	20	525	20	530	20	35	20	20	InGaN
SELU5E23C		Blue	3.3	4.0	20	180	20	468	20	470	20	25	20	20	InGaN

* Mass production in preparation

■5mm Pitch Lead Egg-Shaped LED - External Dimensions 33

SEL 5055 Series (available as Direct Mount) (Viewing angle 2θ 1/2 - 80° typ/40° typ)

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			TYP	MAX		I_v (mcd)	Conditions IF (mA)	λ_P (nm)	Conditions IF (mA)	λ_d (nm)	Conditions IF (mA)	$\Delta\lambda$ (nm)	Conditions IF (mA)	
SEL5255S	Red	Transparent red	1.9	2.5	10	35	20	630	10	620	10	35	10	GaAsP
SEL5955A	Orange	Transparent orange	1.9	2.5	10	25	20	587	10	590	10	33	10	GaAsP
SEL5755C	Yellow	Water clear	2.0	2.5	10	140	20	570	10	571	10	30	10	GaP

5-1-2 Bicolor lamps

■5φ Round Standard Bicolor LED - External Dimensions 34

SML 1016/10016 Series

Part Number	Emitting Color	Lens Color	Forward Voltage			Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material	Remark
			VF (V)		Conditions IF (mA)	Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)		
			TYP	MAX											
SML11516C	A: Deep red	Water clear	2.0	2.5	10	15	20	700	10	625	10	100	10	GaP	Cathode common
	B: Pure green		2.0	2.5	10	50	20	555	10	559	10	20	10		
SML1516W	A: Deep red	Diffused white	2.0	2.5	10	6.0	20	700	10	625	10	100	10	GaP	Cathode common
	B: Pure green		2.0	2.5	10	20	20	555	10	559	10	20	10		
SML1216C	A: Red	Water clear	1.9	2.5	10	65	20	630	10	620	10	35	10	GaAsP	Cathode common
	B: Green		2.0	2.5	10	90	20	560	10	567	10	20	10		
SML1216W	A: Red	Diffused white	1.9	2.5	10	60	20	630	10	620	10	35	10	GaAsP	Cathode common
	B: Green		2.0	2.5	10	60	20	560	10	567	10	20	10		
SML1816W	A: Amber	Diffused white	1.9	2.5	10	50	20	610	10	605	10	35	10	GaAsP	Cathode common
	B: Green		2.0	2.5	10	60	20	560	10	567	10	20	10		
SML19416W	A: Orange	Diffused white	1.9	2.5	10	45	20	587	10	590	10	33	10	GaAsP	Cathode common
	B: Green		2.0	2.5	10	60	20	560	10	567	10	20	10		
SML16716CN	A: High-luminosity red	Water clear	1.7	2.2	10	100	20	660	10	642	10	30	10	GaAlAs	Common anode
	B: Yellow		2.4	3.0	10	140	20	570	10	571	10	30	10		
SML16716WN	A: High-luminosity red	Diffused white	1.7	2.2	10	50	20	660	10	642	10	30	10	GaAlAs	Common anode
	B: Yellow		2.4	3.0	10	70	20	570	10	571	10	30	10		
SMLU12E16C	A: Red	Water clear	2.0	2.5	20	500	20	632	20	624	20	20	20	AlGaInP	Cathode common
	B: Blue		3.3	4.0	20	400	20	468	20	470	20	25	20		
SMLU12E16W	A: Red	Diffused white	2.0	2.5	20	250	20	632	20	624	20	20	20	AlGaInP	Cathode common
	B: Blue		3.3	4.0	20	150	20	468	20	470	20	25	20		
SMLU12D16W	A: Red	Diffused white	2.0	2.5	20	250	20	632	20	624	20	20	20	AlGaInP	Cathode common
	B: Pure green		3.3	4.0	20	700	20	525	20	530	20	35	20		
SMLU18D16C	A: Amber	Water clear	2.0	2.5	20	800	20	611	20	605	20	17	20	AlGaInP	Cathode common
	B: Pure green		3.3	4.0	20	2000	20	525	20	530	20	35	20		
* SMLU18D16W	A: Amber	Diffused white	2.0	2.5	20	300	20	611	20	605	20	17	20	AlGaInP	Cathode common
	B: Pure green		3.3	4.0	20	500	20	525	20	530	20	35	20		
* SMLU18E16C	A: Amber	Water clear	2.0	2.5	20	800	20	611	20	605	20	17	20	AlGaInP	Cathode common
	B: Blue		3.3	4.0	20	400	20	470	20	470	20	25	20		

*Mass production in preparation

■5φ Round Bicolor LED - External Dimensions 35

SML 10051 Series

Part Number	Emitting Color	Lens Color	Forward Voltage			Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material	Remark
			VF (V)		Conditions IF (mA)	Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP			
			TYP	MAX											
SML12451W	A: Red	Diffused white	1.9	2.5	10	40	20	630	10	620	10	35	10	GaAsP	Cathode common
	B: Green		2.0	2.5	10	60	20	560	10	567	10	20	10		
SML16751WN	A: High-luminosity red	Diffused white	1.7	2.2	10	50	20	660	10	642	10	30	10	GaAlAs	Common anode
	B: Yellow		2.4	3.0	10	60	20	570	10	571	10	30	10		

■2.5 × 5 Rectangular Bicolor LED - External Dimensions 36

SML 10060 Series

Part Number	Emitting Color	Lens Color	Forward Voltage			Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material	Remark
			VF (V)		Conditions IF (mA)	Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP			
			TYP	MAX											
SML12460C	A: Red	Water clear	1.9	2.5	10	10	20	630	10	620	10	35	10	GaAsP	Cathode common
	B: Green		2.0	2.5	10	25	20	560	10	567	10	20	10		
SML19460C	A: Orange	Water clear	1.9	2.5	10	15	20	587	10	590	10	33	10	GaAsP	Cathode common
	B: Green		2.0	2.5	10	25	20	560	10	567	10	20	10		
SML16760CN	A: High-luminosity red	Water clear	1.7	2.2	10	30	20	660	10	642	10	30	10	GaAlAs	Common anode
	B: Yellow		2.4	3.0	10	40	20	570	10	571	10	30	10		

■3.3 × 6 Rectangular Bicolor LED - External Dimensions 37

SML 70020 Series (available as Direct Mount)

Part Number	Emitting Color	Lens Color	Forward Voltage			Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material	Remark
			VF (V)		Conditions IF (mA)	Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP			
			TYP	MAX											
SML72420C	A: Red	Water clear	1.9	2.5	10	15	20	630	10	620	10	35	10	GaAsP	Cathode common
	B: Green		2.0	2.5	10	20	20	560	10	567	10	20	10		
SML78420C	A: Amber	Water clear	1.9	2.5	10	10	20	610	10	605	10	35	10	GaAsP	Cathode common
	B: Green		2.0	2.5	10	20	20	560	10	567	10	20	10		
SML79420C	A: Orange	Water clear	1.9	2.5	10	10	20	587	10	590	10	33	10	GaAsP	Cathode common
	B: Green		2.0	2.5	10	20	20	560	10	567	10	20	10		

■3.3 × 6 Bow Shaped Bicolor LED - External Dimensions 38

SML 70023 Series (available as Direct Mount)

Part Number	Emitting Color	Lens Color	Forward Voltage			Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material	Remark
			VF (V)		Conditions IF (mA)	I _v (mcd) TYP	Conditions IF (mA)	λ _P (nm) TYP	Conditions IF (mA)	λ _d (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)		
			TYP	MAX											
SML72423C	A: Red	Water clear	1.9	2.5	10	25	20	630	10	620	10	35	10	GaAsP GaP	Cathode common
	B: Green		2.0	2.5		35	20	560	10	567	10	20	10		
SML72923C	A: Red	Water clear	1.9	2.5	10	25	20	630	10	620	10	35	10	GaAsP GaAsP	Cathode common
	B: Orange		1.9	2.5		10	25	20	587	10	590	10	33		
SML78423C	A: Amber	Water clear	1.9	2.5	10	25	20	610	10	605	10	35	10	GaAsP GaP	Cathode common
	B: Green		2.0	2.5		10	35	20	560	10	567	10	20		
SML79423C	A: Orange	Water clear	1.9	2.5	10	25	20	587	10	590	10	33	10	GaAsP GaP	Cathode common
	B: Green		2.0	2.5		10	35	20	560	10	567	10	20		
SMLS79723C	A: Ultrahigh luminosity orange	Water clear	2.0	2.5	10	150	20	590	10	590	10	15	10	AlGaInP GaP	Cathode common
	B: Yellow		2.0	2.5		10	40	20	570	10	571	10	30		
* SMLU72423C-S	A: Red	Water clear	2.0	2.5	10	120	20	635	20	625	20	15	20	AlGaInP AlGaInP	Cathode common
	B: Green		2.2	2.5		10	30	20	560	20	567	10	15		
* SMLU79423C-S	A: Orange	Water clear	2.0	2.5	10	150	20	590	20	590	10	15	20	AlGaInP AlGaInP	Cathode common
	B: Green		2.2	2.5		10	30	20	560	20	567	10	15		

*Mass production in preparation

■Egg-Shaped Bicolor LED - External Dimensions 39

SML 70055 Series (available as Direct Mount)

Part Number	Emitting Color	Lens Color	Forward Voltage			Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material	Remark
			VF (V)		Conditions IF (mA)	I _v (mcd) TYP	Conditions IF (mA)	λ _P (nm) TYP	Conditions IF (mA)	λ _d (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)		
			TYP	MAX											
SML72755C	A: Red	Water clear	1.9	2.5	10	45	20	630	10	620	10	35	10	GaAsP GaP	Cathode common
	B: Yellow		2.0	2.5		10	75	20	570	10	571	10	30		
SML79255C	A: Orange	Water clear	1.9	2.5	10	40	20	587	10	590	10	33	10	GaAsP GaAsP	Cathode common
	B: Red		2.0	2.5		10	45	20	630	10	620	10	35		
SML79455C	A: Orange	Water clear	1.9	2.5	10	45	20	587	10	590	10	33	10	GaAsP GaP	Cathode common
	B: Green		2.0	2.5		10	75	20	560	10	567	10	20		
SMLU72755C	A: Red	Water clear	2.0	2.5	10	160	20	635	10	625	20	15	10	AlGaInP AlGaInP	Cathode common
	B: Yellow		2.0	2.5		10	170	20	572	10	571	20	15		
SMLU78755C	A: Amber	Water clear	2.0	2.5	10	280	20	615	10	607	20	15	10	AlGaInP AlGaInP	Cathode common
	B: Yellow		2.0	2.5		10	170	20	572	10	571	20	15		

1.6 × 0.8 Miniature Surface Mount LED - External Dimensions 40

SEC 1005 Series

Part Number	Emitting Color		Lens Color	Forward Voltage			Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
				VF (V)		Conditions IF (mA)	Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
				TYP	MAX										
SECU1205C-S	Ultra-high luminosity	Red	Water clear	1.9	2.5	10	45	10	635	10	625	10	20	10	AlGaInP
SECU1805C-S		Amber	Water clear	1.9	2.5	10	50	10	615	10	607	10	17	10	AlGaInP
SECU1905C-S		Orange	Water clear	1.9	2.5	10	40	10	591	10	589	10	15	10	AlGaInP
SECU1D05C-S		Pure green	Water clear	3.3	4.0	10	196	10	528	10	533	10	35	10	InGaN
SECU1J05C		Blue green	Water clear	3.3	4.0	10	147	10	505	10	508	10	35	10	InGaN
SECU1E05C-S		Blue	Water clear	3.4	4.0	10	28	10	470	10	472	10	25	10	InGaN

*Mass production in preparation

1.6 × 0.8 Miniature Surface Mount LED - External Dimensions 41

SEC 1007 Series

Part Number	Emitting Color		Lens Color	Forward Voltage			Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
				VF (V)		Conditions IF (mA)	Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
				TYP	MAX										
SECS1B07C	Ultra-high luminosity	Light amber	Water clear	1.9	2.5	10	45	10	600	10	596	10	15	10	AlGaInP
SECU1707C		Yellow	Water clear	2.2	2.5	10	15	10	572	10	571	10	15	10	AlGaInP
SECU1D07C		Pure green	Water clear	3.6	4.3	10	84	10	528	10	533	10	35	10	InGaN
SECS1L07C		Aqua blue	Water clear	3.6	4.3	10	54	10	494	10	497	10	35	10	InGaN
SECS1E07C		Blue	Water clear	3.6	4.3	10	18	10	470	10	472	10	25	10	InGaN

*Mass production in preparation

Side View Surface Mount LED - External Dimensions 42

SEC 4001 Series

Part Number	Emitting Color		Lens Color	Forward Voltage			Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
				VF (V)		Conditions IF (mA)	Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
				TYP	MAX										
SEC4201C	Red	Water clear	1.9	2.5	10	10	20	630	10	620	10	35	10	GaAsP	
SEC4801C	Amber	Water clear	1.9	2.5	10	16	20	610	10	605	10	35	10	GaAsP	
SEC4901C	Orange	Water clear	1.9	2.5	10	13	20	587	10	590	10	33	10	GaAsP	
SEC4701C	Yellow	Water clear	2.0	2.5	10	25	20	570	10	571	10	30	10	GaP	
SEC4401C	Green	Water clear	2.0	2.5	10	22	20	560	10	567	10	20	10	GaP	
SEC4401E-TG	Deep green	Transparent green	2.0	2.5	10	11	20	558	10	564	10	20	10	GaP	
SEC4501C	Pure green	Water clear	2.0	2.5	10	8.0	20	555	10	559	10	20	10	GaP	
SEC4D01C	Ultra-high luminosity	Pure green	Water clear	3.3	4.0	20	150	20	525	20	530	20	35	20	InGaN
SEC4E01C	Ultra-high luminosity	Blue	Water clear	3.3	4.0	20	50	20	468	20	470	20	25	20	InGaN

*Mass production in preparation

Side View Surface Mount LED (Inner Lens Type) - External Dimensions 43

SEC 4003 Series

Part Number	Emitting Color		Lens Color	Forward Voltage			Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
				VF (V)		Conditions IF (mA)	Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
				TYP	MAX										
SEC4203C	Red	Water clear	1.9	2.5	10	15	20	630	10	620	10	35	10	GaAsP	
SEC4803C	Amber	Water clear	1.9	2.5	10	20	20	610	10	605	10	35	10	GaAsP	
SEC4903C	Orange	Water clear	1.9	2.5	10	15	20	587	10	590	10	33	10	GaAsP	
SEC4703C	Yellow	Water clear	2.0	2.5	10	35	20	570	10	571	10	30	10	GaP	
SEC4403C	Green	Water clear	2.0	2.5	10	33	20	560	10	567	10	20	10	GaP	
SEC4403E-TG	Deep green	Transparent green	2.0	2.5	10	15	20	558	10	564	10	20	10	GaP	
SEC4503C	Pure green	Water clear	2.0	2.5	10	10	20	555	10	559	10	20	10	GaP	
SEC4D03C	Ultra-high luminosity	Pure green	Water clear	3.3	4.0	20	300	20	525	20	530	20	35	20	InGaN
SEC4E03C	Ultra-high luminosity	Blue	Water clear	3.3	4.0	20	100	20	468	20	470	20	25	20	InGaN

*Mass production in preparation

■3.0 × 1.5 Surface Mount LED (Flat Lens Type) - External Dimensions 44

SEC 1001 Series

Part Number	Emitting Color		Lens Color	Forward Voltage		Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material	
				V _F (V) TYP	MAX	Conditions IF (mA)	I _v (mcd) TYP	Conditions IF (mA)	λ _P (nm) TYP	Conditions IF (mA)	λ _d (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP		Conditions IF (mA)
SEC1101C	Deep red		Water clear	2.0	2.5	10	1.5	20	700	10	625	10	100	10	GaP
SEC1601C	High luminosity red		Water clear	1.7	2.2	10	25	20	660	10	642	10	30	10	GaAlAs
SEC1201C	Red		Water clear	1.9	2.5	10	10	20	630	10	620	10	35	10	GaAsP
SEC1801C	Amber		Water clear	1.9	2.5	10	16	20	610	10	605	10	35	10	GaAsP
SEC1901C	Orange		Water clear	1.9	2.5	10	13	20	587	10	590	10	33	10	GaAsP
SEC1701C-YG	Yellow		Water clear	2.0	2.5	10	25	20	570	10	571	10	30	10	GaP
SEC1401C	Green		Water clear	2.0	2.5	10	22	20	560	10	567	10	20	10	GaP
SEC1401E-TG	Deep green		Transparent green	2.0	2.5	10	11	20	558	10	564	10	20	10	GaP
SEC1501C	Pure green		Water clear	2.0	2.5	10	8.0	20	555	10	559	10	20	10	GaP
SEC1E01C	Blue		Water clear	3.9	4.8	20	6.0	20	430	20	466	20	65	20	GaN
SECU1D01C	Ultrahigh luminosity	Pure green	Water clear	3.3	4.0	20	150	20	525	20	525	20	35	20	InGaN
SECU1E01C	Ultrahigh luminosity	Blue	Water clear	3.3	4.0	20	50	20	470	20	468	20	25	20	InGaN

■3.0 × 1.5 Surface Mount LED (Inner Lens Type) - External Dimensions 45

SEC 1003 Series

Part Number	Emitting Color		Lens Color	Forward Voltage		Luminous Intensity		Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material	
				V _F (V) TYP	MAX	Conditions IF (mA)	I _v (mcd) TYP	Conditions IF (mA)	λ _P (nm) TYP	Conditions IF (mA)	λ _d (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP		Conditions IF (mA)
SEC1603C	High luminosity red		Water clear	1.7	2.2	10	35	20	660	10	642	10	30	10	GaAlAs
SEC1203C	Red		Water clear	1.9	2.5	10	15	20	630	10	620	10	35	10	GaAsP
SEC1803C	Amber		Water clear	1.9	2.5	10	20	20	610	10	605	10	35	10	GaAsP
SEC1903C	Orange		Water clear	1.9	2.5	10	15	20	587	10	590	10	33	10	GaAsP
SEC1703C	Yellow		Water clear	2.0	2.5	10	35	20	570	10	571	10	30	10	GaP
SEC1403C	Green		Water clear	2.0	2.5	10	33	20	560	10	567	10	20	10	GaP
SEC1403E-TG	Deep green		Transparent green	2.0	2.5	10	15	20	558	10	564	10	20	10	GaP
SEC1503C	Pure green		Water clear	2.0	2.5	10	10	20	555	10	559	10	20	10	GaP
SECS1203C	Ultrahigh luminosity	Red	Water clear	1.9	2.5	20	100	20	635	20	625	20	15	20	AlGaInP
SECS1803C		Amber	Water clear	1.9	2.5	3	10	3	615	3	607	20	15	3	AlGaInP
SECS1903C		Orange	Water clear	1.9	2.5	20	70	20	590	20	590	20	15	20	AlGaInP

1.6 × 1.25 Bicolor Surface Mount LED - External Dimensions 46

SEC 2008 Series

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Iv (mcd) TYP	Conditions IF (mA)	Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V)	MAX				λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
			TYP											
SECS2D68C	A: Green	Water clear	3.8	4.3	10	48	10	518	10	530	10	35	10	InGaN
	B: Red		1.7	2.2	10	5	10	660	10	642	10	30	10	GaAlAs

3.0 × 2.5 Surface Mount LED with Two Elements (Flat Lens Type) - External Dimensions 47

SEC 2002 Series

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Iv (mcd) TYP	Conditions IF (mA)	Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V)	MAX				λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
			TYP											
SEC2762C-YG	A: High luminosity red	Water clear	1.7	2.2	10	20	20	660	10	642	10	30	10	GaAlAs
	B: Yellow		2.0	2.5	10	20	20	570	10	571	10	30	10	GaP
SEC2462C	A: High luminosity red	Water clear	1.7	2.2	10	20	20	660	10	642	10	30	10	GaAlAs
	B: Green		2.0	2.5	10	20	20	560	10	567	10	20	10	GaP
SEC2422C	A: Red	Water clear	1.9	2.5	10	10	20	630	10	620	10	35	10	GaAsP
	B: Green		2.0	2.5	10	20	20	560	10	567	10	20	10	GaP
SEC2492C	A: Orange	Water clear	1.9	2.5	10	10	20	587	10	590	10	33	10	GaAsP
	B: Green		2.0	2.5	10	20	20	560	10	567	10	20	10	GaP
SEC2592C	A: Orange	Water clear	1.9	2.5	10	10	20	587	10	590	10	33	10	GaAsP
	B: Pure green		2.0	2.5	10	5.0	20	555	10	559	10	20	10	GaP
SEC2442C	A: Green	Water clear	2.0	2.5	10	20	20	560	10	642	10	20	10	GaP
	B: Green		2.0	2.5	10	20	20	560	10	642	10	20	10	GaP
SEC2552C	A: Pure green	Water clear	2.0	2.5	10	5.0	20	555	10	559	10	20	10	GaP
	B: Pure green		2.0	2.5	10	5.0	20	555	10	559	10	20	10	GaP

3.0 × 2.5 Surface Mount LED with Two Elements (Inner Lens Type) - External Dimensions 48

SEC 2004 Series

Part Number	Emitting Color	Lens Color	Forward Voltage		Conditions IF (mA)	Iv (mcd) TYP	Conditions IF (mA)	Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material
			VF (V)	MAX				λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	
			TYP											
SEC2764C	A: High luminosity red	Water clear	1.7	2.2	10	50	20	660	10	642	10	30	10	GaAlAs
	B: Yellow		2.0	2.5	10	50	20	570	10	571	10	30	10	GaP
SEC2484C	A: Amber	Water clear	1.9	2.5	10	20	20	610	10	605	10	35	10	GaAsP
	B: Green		2.0	2.5	10	30	20	560	10	567	10	20	10	GaP
SEC2494C	A: Orange	Water clear	1.9	2.5	10	20	20	587	10	590	10	33	10	GaAsP
	B: Green		2.0	2.5	10	30	20	560	10	567	10	20	10	GaP
SEC2774C	A: Yellow	Water clear	2.0	2.5	10	50	20	570	10	571	10	30	10	GaP
	B: Yellow		2.0	2.5	10	50	20	570	10	571	10	30	10	GaP
SEC2554C	A: Pure green	Water clear	2.0	2.5	10	10	20	555	10	559	10	20	10	GaP
	B: Pure green		2.0	2.5	10	10	20	555	10	559	10	20	10	GaP

■Surface Mount LEDs with Three Elements - External Dimensions 49, 50

SEC3M00 Series

Part Number	Emitting Color	Lens Color	Forward Voltage			Luminous Intensity			Peak Wavelength		Dominant Wavelength		Spectrum Half Bandwidth		Chip Material	Remark
			VF (V) TYP	MAX	Conditions IF (mA)	Iv (mcd) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	λd (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)			
SECU3M02C	A: Blue	Water clear	3.3	4.0	20	34	20	470	20	470	20	25	20	InGaN	Anode common	
	B: Red		1.9	2.5	20	96	20	635	20	625	20	15	20	AlGaInP		
	C: Green		3.2	4.0	20	162	20	530	20	530	20	35	20	InGaN		
SECU3M06C	A: Blue	Water clear	3.3	4.0	10	38	10	471	10	468	10	25	10	InGaN	Anode common	
	B: Red		1.8	2.5	10	44	10	632	10	624	10	20	10	AlGaInP		
	C: Green		3.3	4.0	10	125	10	528	10	525	10	35	10	InGaN		

5-2 Infrared LED

Absolute Maximum Ratings

Parameter	Unit	Rated	Conditions
IF	mA	100	
ΔIF	mA/°C	-1.33	25°C or higher
IFP	mA	1000	f=1kHz, tw≤10μs
VR	V	5	
Top	°C	-30 to +85	
Tstg	°C	-30 to +100	

5φ Round Infrared LED - External Dimensions 51

SID1010M Series

Part Number	Lens Color	Forward Voltage		Conditions IF (mA)	Ie (mW/sr) TYP	Conditions	Peak Wavelength		Spectrum Half Bandwidth		Chip Material	Remark (Dimension A)
		V _F (V) TYP	MAX				λ _P (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)		
SID1010CM	Water clear	1.3	1.5	50	130	(Constant voltage) V _{CC} =3V, R=2.2Ω	940	50	50	50	GaAs	7.6±0.2
SID1K10CM	Water clear	1.3	1.5	50	200	(Constant voltage) V _{CC} =3V, R=2.2Ω	940	50	50	50	GaAs	7.6±0.2
SID1010CXM	Water clear	1.3	1.5	50	80	(Constant voltage) V _{CC} =3V, R=2.2Ω	940	50	50	50	GaAs	6.9±0.2
SID1K10CXM	Water clear	1.3	1.5	50	110	(Constant voltage) V _{CC} =3V, R=2.2Ω	940	50	50	50	GaAs	6.9±0.2

5φ Round Infrared LED - External Dimensions 52

SID1050M Series (available as Direct Mount)

Part Number	Lens Color	Forward Voltage		Conditions IF (mA)	Ie (mW/sr) TYP	Conditions	Peak Wavelength		Spectrum Half Bandwidth		Chip Material	Remark
		V _F (V) TYP	MAX				λ _P (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)		
SID1050CM	Water clear	1.3	1.5	50	250	(Constant voltage) V _{CC} =3V, R=2.2Ω	940	50	50	50	GaAs	-

5φ Round Infrared LED - External Dimensions 53

SID300/1003 Series

Part Number	Lens Color	Forward Voltage		Conditions IF (mA)	Ie (mW/sr) TYP	Conditions	Peak Wavelength		Spectrum Half Bandwidth		Chip Material	Remark (Dimension A)
		V _F (V) TYP	MAX				λ _P (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)		
SID303C	Water clear	1.3	1.5	50	80	(Constant voltage) V _{CC} =3V, R=2.2Ω	940	50	50	50	GaAs	3.0±0.5
SID313BP	Transparent light violet	1.3	1.5	50	130	(Constant voltage) V _{CC} =3V, R=2.2Ω	940	50	50	50	GaAs	3.6±0.5
SID1003BQ	Transparent light deep blue	1.3	1.5	50	180	(Constant voltage) V _{CC} =3V, R=2.2Ω	940	50	50	50	GaAs	3.6±0.5
SID307BR	Transparent deep blue	1.3	1.5	50	200	(Constant voltage) V _{CC} =3V, R=2.2Ω	940	50	50	50	GaAs	4.2±0.5
SID1G307C	Water clear	1.5	1.8	50	50	IF=50mA	850	50	40	50	GaAlAs	4.2±0.5
SID1G313C	Water clear	1.5	1.8	50	30	IF=50mA	850	50	40	50	GaAlAs	3.6±0.5

5φ Round Infrared LED - External Dimensions 54

SID 2010 Series

Part Number	Lens Color	Forward Voltage		Conditions IF (mA)	Ie (mW/sr) TYP	Conditions	Peak Wavelength		Spectrum Half Bandwidth		Chip Material	Remark
		V _F (V) TYP	MAX				λ _P (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)		
SID2010C	Water clear	1.3	1.5	50	7	IF=50mA	940	50	50	50	GaAs	-
SID2K10C	Water clear	1.3	1.5	50	14	IF=50mA	940	50	50	50	GaAs	-

3 × 1.5 Surface Mount Infrared LED (Inner Lens Type) - External Dimensions 55

SEC 1003C Series

Part Number	Lens Color	Forward Voltage		Conditions IF (mA)	Ie (mW/sr) TYP	Conditions	Peak Wavelength		Spectrum Half Bandwidth		Chip Material	Remark
		V _F (V) TYP	MAX				λ _P (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)		
SEC1G03C	Water clear	1.5	1.8	50	3	IF=50mA	850	50	40	40	GaAlAs	-

5-3 Ultraviolet Surface Mount LED

Absolute Maximum Ratings


Parameter	Unit	Ratings	Conditions
IF	mA	30	
ΔIF	mA/°C	-0.45	25°C or higher
IFP	mA	100	f=1kHz, tw≤10μs
IR	mA	100	Maximum rating of built-in zener diode
Top	°C	-30 to +85	
Tstg	°C	-30 to +100	

External dimensions	Part Number	Lens Color	Forward Voltage			Optical Power Output		Peak Wavelength		Spectrum Half Bandwidth		Electrostatic Withstand Voltage		Chip Material
			VF (V) TYP	MAX	Conditions IF (mA)	Po (mW) TYP	Conditions IF (mA)	λP (nm) TYP	Conditions IF (mA)	Δλ (nm) TYP	Conditions IF (mA)	(V) TYP	Conditions	
2.8 × 3.5	SECU1V0AC	Water clear	3.7	4.0	20	2.2	20	385	20	20	20	4000	100pF, 1.5kΩ	InGaN


External Dimensions List

External Dimensions List


• No. 1




• No. 2




• No. 3




• No. 4




• No. 5




• No. 6




• No. 7




• No. 8




• No. 9




• No. 10



• No. 11




• No. 12




(Unit: mm) (General tolerance: ± 0.3)

External Dimensions List


• No. 13




• No. 14




• No. 15




• No. 16




• No. 17




• No. 18




• No. 19




• No. 20




• No. 21




• No. 22



• No. 23




• No. 24




(Unit: mm) (General tolerance: ±0.3)

External Dimensions List


• No. 25




• No. 26




• No. 27




• No. 28




• No. 29




• No. 30




• No. 31



• No. 32




• No. 33




(Unit: mm) (General tolerance: ±0.3)

External Dimensions List


• No. 34




• No. 35




• No. 36




• No. 37




• No. 38




• No. 39



• No. 40




• No. 41




(Unit: mm) (General tolerance: ±0.3)

External Dimensions List


• No. 42




• No. 43




• No. 44




• No. 45




• No. 46




• No. 47



• No. 48




• No. 49




(Unit: mm) (General tolerance: ±0.3)

External Dimensions List


• No. 50




• No. 51




• No. 52




• No. 53




• No. 54



• No. 55



• No. 56



(Unit: mm) (General tolerance: ±0.3)

Ordering Information

Please place orders by integer multiples of the standard minimum package unit.

Series Name	Standard Minimum Package Unit	
	Bulk	Taping
DIP16Pin	100 pcs (4 sticks)	
DIP24Pin	90 pcs (6 sticks)	
DIP30Pin	85 pcs (5 sticks)	
DIP8Pin	100 pcs (2 sticks)	
SOP16Pin	94 pcs (2 sticks)	
SOP20Pin	111 pcs (3 sticks)	2000 pcs (one reel)
SOP24Pin	93 pcs (3 sticks)	
SOP8		1000 pcs (one reel)
SOT89-3		1000 pcs (one reel)
SOT89-5		1000 pcs (one reel)
SSOP-24		2800 pcs (one reel)
HSOP16		1400 pcs (one reel)
EQ32Pin	93 pcs (3 sticks)	800 pcs (one reel)
eTSSOP16Pin	96 pcs (1 stick)	4000 pcs (one reel)
eTSSOP28Pin	100 pcs (2 sticks)	4000 pcs (one reel)
PLCC44Pin	108 pcs (4 sticks)	450 pcs (one reel)
PS16Pin		1200 pcs (one reel)
PS4Pin		2000 pcs (one reel)
TO252-3		3000 pcs (one reel)
TO252-5		3000 pcs (one reel)
TO263-5		800 pcs (one reel)
TO220F-3 (FM205-3)	100 pcs	
TO220F-5 (FM205)	100 pcs	
EI-12.5 core (Non-packaged)	100 pcs	
EI-19 core (Non-packaged)	100 pcs	
SLA12Pin/15Pin/18Pin/21Pin	108 pcs (6 sticks)	
SMA12Pin/15Pin	144 pcs (8 sticks)	
STA8Pin	100 pcs	
STA10Pin	100 pcs	
TO220S (Straight)	100 pcs (2 sticks)	
TO220S (Surface-Mount)		1000 pcs (one reel)
TO220 (MT-25)	100 pcs	
TO220F (FM20)	100 pcs	
TO220F-2Pin	100 pcs	
TO3P (MT100)	100 pcs	
FM80	100 pcs	
FM80-2Pin	100 pcs	
TO3PF (FM100)	100 pcs	
TO3PF-2Pin	100 pcs	
MT-200	100 pcs	
SAP (2GR)	100 pcs	
Diode (ϕ 1.0body/ ϕ 1.5 lead)	100 pcs	
Diode (ϕ 2.4body/ ϕ 0.6 lead)	100 pcs	Refer to P234.
Diode (ϕ 2.7body/ ϕ 0.6 lead)	100 pcs	Refer to P234.
Diode (ϕ 2.7body/ ϕ 0.78 lead)	100 pcs	Refer to P234.
Diode (ϕ 4.0body/ ϕ 0.78 lead)	100 pcs	Refer to P234.
Diode (ϕ 4.0body/ ϕ 0.98 lead)	100 pcs	Refer to P234.
Diode (ϕ 5.2body/ ϕ 1.2 lead)	100 pcs	Refer to P234.
Diode (ϕ 6.5body/ ϕ 1.4 lead)	100 pcs	
Diode (Compact (surface-mount))		3000 pcs (one reel)
Diode (SFP (Surface-Mount))		1800 pcs (one reel)
Diode (RB-40)	100 pcs	
Diode (RB-60)	100 pcs	
SZ-10 (Surface-Mount)		750 pcs (one reel)
High voltage rectifier diode		Refer to P236.
Diode (D pack (surface-mount))		3000 pcs (one reel)
LED	100 pcs (bag)	Refer to P265.

Part Number Index in Alphanumeric Order

Part No.	Category	Description	Page
2SC5100	Transistor	For Audio (Single Emitter) and General Purpose	156
2SC5101	Transistor	For Audio (Single Emitter) and General Purpose	156
2SC5124	Transistor	For SMPS for 200VAC system, CRT Display Horizontal Deflection Output and General Purpose	156
2SC5130	Transistor	For SMPS for 100VAC system and General Purpose	156
2SC5239	Transistor	For SMPS for 200VAC system and General Purpose	156
2SC5249	Transistor	For SMPS for 100VAC system and General Purpose	156
2SC5271	Transistor	For SMPS for 100VAC system and General Purpose	156
2SC5287	Transistor	For SMPS for 200VAC system and General Purpose	156
2SC5333	Transistor	For General Purpose	156
2SC5370	Transistor	For DC-DC Converter and General Purpose (Low Vce(sat))	156
2SC5586	Transistor	For SMPS for 200VAC system and General Purpose	156
2SC5830	Transistor	For SMPS for 200VAC system and General Purpose	156
2SC5924	Transistor	For SMPS for 200VAC system and General Purpose	156
2SC6011	Transistor	For Audio (Single Emitter) and General Purpose	156
2SC6011A	Transistor	For Audio (Single Emitter) and General Purpose	156
2SD1769	Transistor	For General Purpose (Darlington)	156
2SD1785	Transistor	For General Purpose (Darlington)	156
2SD1796	Transistor	For General Purpose (Darlington)	156
2SD2014	Transistor	For General Purpose (Darlington)	156
2SD2015	Transistor	For General Purpose (Darlington)	156
2SD2016	Transistor	For General Purpose (Darlington)	156
2SD2017	Transistor	For General Purpose (Darlington)	156
2SD2045	Transistor	For General Purpose (Darlington)	156
2SD2081	Transistor	For General Purpose (Darlington)	156
2SD2082	Transistor	For General Purpose (Darlington)	156
2SD2083	Transistor	For General Purpose (Darlington)	158
2SD2141	Transistor	For General Purpose (Darlington)	158
2SD2389	Transistor	For Audio (Darlington) and General Purpose	158
2SD2390	Transistor	For Audio (Darlington) and General Purpose	158
2SD2401	Transistor	For Audio (Darlington) and General Purpose	158
2SD2438	Transistor	For Audio (Darlington) and General Purpose	158
2SD2439	Transistor	For Audio (Darlington) and General Purpose	158
2SD2557	Transistor	For General Purpose (Darlington)	158
2SD2558	Transistor	For General Purpose (Darlington)	158
2SD2560	Transistor	For Audio (Darlington) and General Purpose	158
2SD2561	Transistor	For Audio (Darlington) and General Purpose	158
2SD2562	Transistor	For Audio (Darlington) and General Purpose	158
2SD2589	Transistor	For Audio (Darlington) and General Purpose	158
2SD2641	Transistor	For Audio (Darlington) and General Purpose	158
2SD2642	Transistor	For Audio (Darlington) and General Purpose	158
2SD2643	Transistor	For Audio (Darlington) and General Purpose	158
2SJ424	Transistor	MOS FET	162
2SJ425	Transistor	MOS FET	162
2SK1177	Transistor	MOS FET	162
2SK1179	Transistor	MOS FET	162
2SK1180	Transistor	MOS FET	162
2SK1181	Transistor	MOS FET	162
2SK1183	Transistor	MOS FET	162
2SK1184	Transistor	MOS FET	162
2SK1185	Transistor	MOS FET	162
2SK1186	Transistor	MOS FET	162
2SK1187	Transistor	MOS FET	162
2SK1188	Transistor	MOS FET	162
2SK1189	Transistor	MOS FET	162
2SK1190	Transistor	MOS FET	162
2SK1191	Transistor	MOS FET	162
2SK1192	Transistor	MOS FET	162
2SK1712	Transistor	MOS FET	162
2SK2419	Transistor	MOS FET	162
2SK2420	Transistor	MOS FET	162
2SK2421	Transistor	MOS FET	162
2SK2701	Transistor	MOS FET	162
2SK2702	Transistor	MOS FET	162
2SK2704	Transistor	MOS FET	162

Part No.	Category	Description	Page
2SK2706	Transistor	MOS FET	162
2SK2707	Transistor	MOS FET	162
2SK2708	Transistor	MOS FET	162
2SK2709	Transistor	MOS FET	162
2SK2710A	Transistor	MOS FET	162
2SK2778	Transistor	MOS FET	162
2SK2779	Transistor	MOS FET	162
2SK2803	Transistor	MOS FET	162
2SK2805	Transistor	MOS FET	162
2SK2848	Transistor	MOS FET	162
2SK2943	Transistor	MOS FET	162
2SK2945	Transistor	MOS FET	162
2SK3002	Transistor	MOS FET	162
2SK3003	Transistor	MOS FET	162
2SK3004	Transistor	MOS FET	162
2SK3199	Transistor	MOS FET	162
2SK3200	Transistor	MOS FET	162
2SK3332	Transistor	MOS FET	162
2SK3460	Transistor	MOS FET	162
2SK3710	Transistor	MOS FET	162
2SK3711	Transistor	MOS FET	162
2SK3724	Transistor	MOS FET	162
2SK3800	Transistor	MOS FET	162
2SK3801	Transistor	MOS FET	162
2SK3851	Transistor	MOS FET	162
AG01	Diode	Ultrafast Recovery Diode (Axial)	212
AG01A	Diode	Ultrafast Recovery Diode (Axial)	212
AG01Y	Diode	Ultrafast Recovery Diode (Axial)	211
AG01Z	Diode	Ultrafast Recovery Diode (Axial)	211
AK 03	Diode	Schottky Barrier Diode (Axial)	214
AK 04	Diode	Schottky Barrier Diode (Axial)	214
AK 06	Diode	Schottky Barrier Diode (Axial)	214
AK 09	Diode	Schottky Barrier Diode (Axial)	215
AL01	Diode	Ultrafast Recovery Diode (Axial)	212
AL01Z	Diode	Ultrafast Recovery Diode (Axial)	211
AM01	Diode	Rectifier Diode (Axial)	207
AM01A	Diode	Rectifier Diode (Axial)	207
AM01Z	Diode	Rectifier Diode (Axial)	207
AP01C	Diode	Ultrafast Recovery Diode (Axial)	213
AS01	Diode	Fast Recovery Diode (Axial)	209
AS01A	Diode	Fast Recovery Diode (Axial)	209
AU01	Diode	Fast Recovery Diode (Axial)	209
AU01A	Diode	Fast Recovery Diode (Axial)	209
AU01Z	Diode	Fast Recovery Diode (Axial)	209
AU02	Diode	Fast Recovery Diode (Axial)	209
AU02A	Diode	Fast Recovery Diode (Axial)	210
AU02Z	Diode	Fast Recovery Diode (Axial)	209
AW 04	Diode	Schottky Barrier Diode (Axial)	214
EA 03	Diode	Schottky Barrier Diode (Axial)	215
EE 04	Diode	Schottky Barrier Diode (Surface Mount)	216
EG 1	Diode	Ultrafast Recovery Diode (Axial)	212
EG 1A	Diode	Ultrafast Recovery Diode (Axial)	212
EG 1Y	Diode	Ultrafast Recovery Diode (Axial)	211
EG 1Z	Diode	Ultrafast Recovery Diode (Axial)	211
EG01	Diode	Ultrafast Recovery Diode (Axial)	212
EG01A	Diode	Ultrafast Recovery Diode (Axial)	212
EG01C	Diode	Ultrafast Recovery Diode (Axial)	213
EG01Y	Diode	Ultrafast Recovery Diode (Axial)	211
EG01Z	Diode	Ultrafast Recovery Diode (Axial)	211
EH 1	Diode	Fast Recovery Diode (Axial)	209
EH 1A	Diode	Fast Recovery Diode (Axial)	209
EH 1Z	Diode	Fast Recovery Diode (Axial)	209
EK 03	Diode	Schottky Barrier Diode (Axial)	214
EK 04	Diode	Schottky Barrier Diode (Axial)	214

Part No.	Category	Description	Page	Part No.	Category	Description	Page
EK 06	Diode	Schottky Barrier Diode (Axial)	214	FMB-24M	Diode	Schottky Barrier Diode (Frame)	214
EK 09	Diode	Schottky Barrier Diode (Axial)	215	FMB-26	Diode	Schottky Barrier Diode (Frame)	215
EK 13	Diode	Schottky Barrier Diode (Axial)	214	FMB-26L	Diode	Schottky Barrier Diode (Frame)	215
EK 14	Diode	Schottky Barrier Diode (Axial)	214	FMB-29	Diode	Schottky Barrier Diode (Frame)	215
EK 16	Diode	Schottky Barrier Diode (Axial)	214	FMB-29L	Diode	Schottky Barrier Diode (Frame)	215
EK 19	Diode	Schottky Barrier Diode (Axial)	215	FMB-34	Diode	Schottky Barrier Diode (Frame)	214
EL 1	Diode	Ultrafast Recovery Diode (Axial)	212	FMB-34M	Diode	Schottky Barrier Diode (Frame)	214
EL 1Z	Diode	Ultrafast Recovery Diode (Axial)	211	FMB-34S	Diode	Schottky Barrier Diode (Frame)	214
EL02Z	Diode	Ultrafast Recovery Diode (Axial)	211	FMB-36	Diode	Schottky Barrier Diode (Frame)	215
EM 1	Diode	Rectifier Diode (Axial)	207	FMB-36M	Diode	Schottky Barrier Diode (Frame)	215
EM 1A	Diode	Rectifier Diode (Axial)	207	FMB-39	Diode	Schottky Barrier Diode (Frame)	215
EM 1B	Diode	Rectifier Diode (Axial)	207	FMB-39M	Diode	Schottky Barrier Diode (Frame)	215
EM 1C	Diode	Rectifier Diode (Axial)	208	FMB-G14	Diode	Schottky Barrier Diode (F2Pin)	214
EM 1Y	Diode	Rectifier Diode (Axial)	207	FMB-G14L	Diode	Schottky Barrier Diode (F2Pin)	214
EM 1Z	Diode	Rectifier Diode (Axial)	207	FMB-G16L	Diode	Schottky Barrier Diode (F2Pin)	215
EM 2	Diode	Rectifier Diode (Axial)	207	FMB-G19L	Diode	Schottky Barrier Diode (F2Pin)	215
EM 2A	Diode	Rectifier Diode (Axial)	207	FMB-G24H	Diode	Schottky Barrier Diode (F2Pin)	214
EM 2B	Diode	Rectifier Diode (Axial)	207	FMC-26U	Diode	Ultrafast Recovery Diode (Frame)	212
EM01	Diode	Rectifier Diode (Axial)	207	FMC-26UA	Diode	Ultrafast Recovery Diode (F2Pin)	213
EM01A	Diode	Rectifier Diode (Axial)	207	FMC-28U	Diode	Ultrafast Recovery Diode (Frame)	212
EM01Z	Diode	Rectifier Diode (Axial)	207	FMC-28UA	Diode	Ultrafast Recovery Diode (F2Pin)	213
EN 01Z	Diode	Ultrafast Recovery Diode (Axial)	211	FMC-G28S	Diode	Ultrafast Recovery Diode (F2Pin)	212
EP01C	Diode	Ultrafast Recovery Diode (Axial)	213	FMC-G28SL	Diode	Ultrafast Recovery Diode (F2Pin)	213
ES 1	Diode	Fast Recovery Diode (Axial)	209	FMD-G26S	Diode	Ultrafast Recovery Diode (F2Pin)	212
ES 1A	Diode	Fast Recovery Diode (Axial)	209	FME-2104	Diode	Schottky Barrier Diode (Frame)	216
ES 1F	Diode	Fast Recovery Diode (Axial)	210	FME-2106	Diode	Schottky Barrier Diode (Frame)	216
ES 1Z	Diode	Fast Recovery Diode (Axial)	209	FME-210B	Diode	Schottky Barrier Diode (Frame)	216
ES01	Diode	Fast Recovery Diode (Axial)	209	FME-220A	Diode	Schottky Barrier Diode (Frame)	216
ES01A	Diode	Fast Recovery Diode (Axial)	209	FME-220B	Diode	Schottky Barrier Diode (Frame)	216
ES01F	Diode	Fast Recovery Diode (Axial)	210	FME-230A	Diode	Schottky Barrier Diode (Frame)	216
ES01Z	Diode	Fast Recovery Diode (Axial)	209	FME-230B	Diode	Schottky Barrier Diode (Frame)	216
ET013	Thyristor	PNPN Switch	196	FME-24H	Diode	Schottky Barrier Diode (Frame)	216
ET0141	Thyristor	PNPN Switch	196	FMG-12S, R	Diode	Ultrafast Recovery Diode (Frame)	211
ET015	Thyristor	PNPN Switch	196	FMG-13S, R	Diode	Ultrafast Recovery Diode (Frame)	212
ET020	Thyristor	PNPN Switch	196	FMG-14S, R	Diode	Ultrafast Recovery Diode (Frame)	212
ET0201	Thyristor	PNPN Switch	196	FMG-22S, R	Diode	Ultrafast Recovery Diode (Frame)	211
EU 1	Diode	Fast Recovery Diode (Axial)	209	FMG-23S, R	Diode	Ultrafast Recovery Diode (Frame)	212
EU 1A	Diode	Fast Recovery Diode (Axial)	209	FMG-24S, R	Diode	Ultrafast Recovery Diode (Frame)	212
EU 1Z	Diode	Fast Recovery Diode (Axial)	209	FMG-26S, R	Diode	Ultrafast Recovery Diode (Frame)	212
EU 2	Diode	Fast Recovery Diode (Axial)	209	FMG-32S, R	Diode	Ultrafast Recovery Diode (Frame)	211
EU 2A	Diode	Fast Recovery Diode (Axial)	210	FMG-33S, R	Diode	Ultrafast Recovery Diode (Frame)	212
EU 2YX	Diode	Fast Recovery Diode (Axial)	209	FMG-34S, R	Diode	Ultrafast Recovery Diode (Frame)	212
EU 2Z	Diode	Fast Recovery Diode (Axial)	209	FMG-36S, R	Diode	Ultrafast Recovery Diode (Frame)	212
EU01	Diode	Fast Recovery Diode (Axial)	209	FMG-G26S	Diode	Ultrafast Recovery Diode (F2Pin)	212
EU01A	Diode	Fast Recovery Diode (Axial)	209	FMG-G2CS	Diode	Ultrafast Recovery Diode (F2Pin)	213
EU01Z	Diode	Fast Recovery Diode (Axial)	209	FMG-G36S	Diode	Ultrafast Recovery Diode (F2Pin)	212
EU02	Diode	Fast Recovery Diode (Axial)	209	FMG-G3CS	Diode	Ultrafast Recovery Diode (F2Pin)	213
EU02A	Diode	Fast Recovery Diode (Axial)	210	FMJ-2203	Diode	Schottky Barrier Diode (Frame)	216
EU02Z	Diode	Fast Recovery Diode (Axial)	209	FMJ-2303	Diode	Schottky Barrier Diode (Frame)	216
EZ0150	Diode	Avalanche Diode with Built-in Thyristor (Axial)	220	FMJ-23L	Diode	Schottky Barrier Diode (Frame)	216
FKV460S	Transistor	MOS FET	162	FML-12S	Diode	Ultrafast Recovery Diode (Frame)	211
FKV550N	Transistor	MOS FET	162	FML-13S	Diode	Ultrafast Recovery Diode (Frame)	212
FKV550T	Transistor	MOS FET	162	FML-14S	Diode	Ultrafast Recovery Diode (Frame)	212
FKV560	Transistor	MOS FET	162	FML-22S	Diode	Ultrafast Recovery Diode (Frame)	211
FKV560S	Transistor	MOS FET	162	FML-23S	Diode	Ultrafast Recovery Diode (Frame)	212
FKV660S	Transistor	MOS FET	162	FML-24S	Diode	Ultrafast Recovery Diode (Frame)	212
FM2-2202	Diode	Ultrafast Recovery Diode (F2Pin)	212	FML-32S	Diode	Ultrafast Recovery Diode (Frame)	211
FMB-2204	Diode	Schottky Barrier Diode (Frame)	214	FML-33S	Diode	Ultrafast Recovery Diode (Frame)	212
FMB-2206	Diode	Schottky Barrier Diode (Frame)	215	FML-34S	Diode	Ultrafast Recovery Diode (Frame)	212
FMB-2304	Diode	Schottky Barrier Diode (Frame)	214	FML-36S	Diode	Ultrafast Recovery Diode (Frame)	212
FMB-2306	Diode	Schottky Barrier Diode (Frame)	215	FML-G12S	Diode	Ultrafast Recovery Diode (F2Pin)	211
FMB-24	Diode	Schottky Barrier Diode (Frame)	214	FML-G13S	Diode	Ultrafast Recovery Diode (F2Pin)	212
FMB-24H	Diode	Schottky Barrier Diode (Frame)	214	FML-G14S	Diode	Ultrafast Recovery Diode (F2Pin)	212
FMB-24L	Diode	Schottky Barrier Diode (Frame)	214	FML-G16S	Diode	Ultrafast Recovery Diode (F2Pin)	212

Part Number Index in Alphanumeric Order

Part No.	Category	Description	Page
FML-G22S	Diode	Ultrafast Recovery Diode (F2Pin)	211
FMM-22S, R	Diode	Rectifier Diode (Frame)	207
FMM-24S, R	Diode	Rectifier Diode (Frame)	207
FMM-26S, R	Diode	Rectifier Diode (Frame)	207
FMM-31S, R	Diode	Rectifier Diode (Frame)	207
FMM-32S, R	Diode	Rectifier Diode (Frame)	207
FMM-34S, R	Diode	Rectifier Diode (Frame)	207
FMM-36S, R	Diode	Rectifier Diode (Frame)	207
FMN-G12S	Diode	Ultrafast Recovery Diode (F2Pin)	211
FMN-G14S	Diode	Ultrafast Recovery Diode (F2Pin)	212
FMN-G16S	Diode	Ultrafast Recovery Diode (F2Pin)	212
FMP-2FUR	Diode	Diode Modulation Damper Diode for CRT Display (Frame)	219
FMP-3FU	Diode	Diode Modulation Damper Diode for CRT Display (Frame)	219
FMP-G12S	Diode	Ultrafast Recovery Diode (F2Pin)	211
FMP-G2FS	Diode	Damper Diode for CRT Display(Frame)	218
FMP-G5HS	Diode	Damper Diode for CRT Display/Fast Recovery Diode (F2Pin)	218/210
FMQ-2FUR	Diode	Diode Modulation Damper Diode for CRT Display (Frame)	219
FMQ-3GU	Diode	Diode Modulation Damper Diode for CRT Display (Frame)	219
FMQA-105FS	Diode	Damper Diode for CRT Display(Frame)	218
FMQ-G1FS	Diode	Damper Diode for CRT Display/Fast Recovery Diode (F2Pin)	218/210
FMQ-G2FLS	Diode	Damper Diode for CRT Display/Fast Recovery Diode (F2Pin)	218/210
FMQ-G2FMS	Diode	Damper Diode for CRT Display/Fast Recovery Diode (F2Pin)	218/210
FMQ-G2FS	Diode	Damper Diode for CRT Display/Fast Recovery Diode (F2Pin)	218/210
FMQ-G5FMS	Diode	Damper Diode for CRT Display/Fast Recovery Diode (F2Pin)	218/210
FMQ-G5GS	Diode	Damper Diode for CRT Display/Fast Recovery Diode (F2Pin)	218/210
FMR-G5HS	Diode	Damper Diode for CRT TV and Display/Fast Recovery Diode (F2Pin)	218/210
FMU-12S, R	Diode	Fast Recovery Diode (Frame)	209
FMU-14S, R	Diode	Fast Recovery Diode (Frame)	201
FMU-16S, R	Diode	Fast Recovery Diode (Frame)	201
FMU-21S, R	Diode	Fast Recovery Diode (Frame)	209
FMU-22S, R	Diode	Fast Recovery Diode (Frame)	209
FMU-24S, R	Diode	Fast Recovery Diode (Frame)	210
FMU-26S, R	Diode	Fast Recovery Diode (Frame)	210
FMU-32S, R	Diode	Fast Recovery Diode (Frame)	209
FMU-34S, R	Diode	Fast Recovery Diode (Frame)	210
FMU-36S, R	Diode	Fast Recovery Diode (Frame)	210
FMU-G16S	Diode	Fast Recovery Diode (F2Pin)	210
FMU-G26S	Diode	Fast Recovery Diode (F2Pin)	210
FMU-G2FS	Diode	Damper Diode for CRT Display/Fast Recovery Diode (F2Pin)	218/210
FMU-G2YXS	Diode	Fast Recovery Diode (F2Pin)	209
FMUP-2056	Diode	Fast Recovery Diode (Frame)	210
FMV-3FU	Diode	Diode Modulation Damper Diode for CRT TV (Frame)	219
FMV-3GU	Diode	Diode Modulation Damper Diode for CRT TV (Frame)	219
FMV-3HU	Diode	Diode Modulation Damper Diode for CRT TV (Frame)	219
FMV-G2GS	Diode	Damper Diode for CRT TV (Frame)	218
FMV-G5FS	Diode	Fast Recovery Diode (F2Pin)	210
FMW-2156	Diode	Schottky Barrier Diode (Frame)	215
FMW-2204	Diode	Schottky Barrier Diode (Frame)	214
FMW-24H	Diode	Schottky Barrier Diode (Frame)	214
FMW-24L	Diode	Schottky Barrier Diode (Frame)	214
FMX-12S	Diode	Ultrafast Recovery Diode (Frame)	211
FMX-2203	Diode	Ultrafast Recovery Diode (Frame)	212
FMX-22S	Diode	Ultrafast Recovery Diode (Frame)	211
FMX-22SL	Diode	Ultrafast Recovery Diode (Frame)	211
FMX-23S	Diode	Ultrafast Recovery Diode (Frame)	212
FMX-32S	Diode	Ultrafast Recovery Diode (Frame)	211
FMX-33S	Diode	Ultrafast Recovery Diode (Frame)	212
FMXA-1054S	Diode	Ultrafast Recovery Diode (F2Pin)	212
FMXA-2202S	Diode	Ultrafast Recovery Diode (F2Pin)	212
FMXA-2203S	Diode	Ultrafast Recovery Diode (F2Pin)	212
FMX-G12S	Diode	Ultrafast Recovery Diode (F2Pin)	211
FMX-G14S	Diode	Ultrafast Recovery Diode (F2Pin)	212
FMX-G16S	Diode	Ultrafast Recovery Diode (F2Pin)	212
FMX-G22S	Diode	Ultrafast Recovery Diode (F2Pin)	211

Part No.	Category	Description	Page
FMX-G26S	Diode	Ultrafast Recovery Diode (F2Pin)	212
HVR-1X-40B	Diode	High-Voltage Rectifier Diode for Microwave Oven	217
MI1A3	Diode	Schottky Barrier Diode (Surface Mount)	216
MI2A3	Diode	Schottky Barrier Diode (Surface Mount)	216
MP2-202S	Diode	Ultrafast Recovery Diode (Surface Mount)	211
MP3-306	Diode	Ultrafast Recovery Diode (Surface Mount)	211
MPE-220A	Diode	Schottky Barrier Diode (Surface Mount)	211
MPL-102S	Diode	Ultrafast Recovery Diode (Surface Mount)	211
MPX-2103	Diode	Ultrafast Recovery Diode (Surface Mount)	211
PG001M	IC	2-phase Stepper Motor Unipolar Driver IC (Serial Signal Generator for SLA704xM)	140
PZ 628	Diode	Power Zener Diode (Axial)	221
RA 13	Diode	Schottky Barrier Diode (Axial)	215
RBV-1306	Diode	Rectifier Diode (Brigde)	207
RBV-1506	Diode	Rectifier Diode (Brigde)	207
RBV-1506J	Diode	Rectifier Diode (Brigde)	207
RBV-1506S	Diode	Rectifier Diode (Brigde)	207
RBV-150C	Diode	Rectifier Diode (Brigde)	207
RBV-2506	Diode	Rectifier Diode (Brigde)	207
RBV-401	Diode	Rectifier Diode (Brigde)	207
RBV-402	Diode	Rectifier Diode (Brigde)	207
RBV-402L	Diode	Rectifier Diode (Bridge, Ultrafast Recovery Diode)	207
RBV-404	Diode	Rectifier Diode (Brigde)	207
RBV-406	Diode	Rectifier Diode (Brigde)	207
RBV-406B	Diode	Rectifier Diode (Bridge, Schottky Barrier Diode)	207
RBV-406H	Diode	Rectifier Diode (Brigde)	207
RBV-406M	Diode	Rectifier Diode (Brigde)	207
RBV-408	Diode	Rectifier Diode (Brigde)	207
RBV-40C	Diode	Rectifier Diode (Brigde)	207
RBV-4102	Diode	Rectifier Diode (Brigde)	207
RBV-4106M	Diode	Rectifier Diode (Brigde)	207
RBV-601	Diode	Rectifier Diode (Brigde)	207
RBV-602	Diode	Rectifier Diode (Brigde)	207
RBV-602L	Diode	Rectifier Diode (Bridge, Ultrafast Recovery Diode)	207
RBV-604	Diode	Rectifier Diode (Brigde)	207
RBV-606	Diode	Rectifier Diode (Brigde)	207
RBV-606H	Diode	Rectifier Diode (Brigde)	207
RBV-608	Diode	Rectifier Diode (Brigde)	207
RC 2	Diode	Fast Recovery Diode (Axial)	210
RC 3B2	Diode	Damper Diode for CRT Display Compensation (Axial)	218
RD 2A	Diode	Ultrafast Recovery Diode (Axial)	212
RF 1A	Diode	Fast Recovery Diode (Axial)	209
RF 1B	Diode	Fast Recovery Diode (Axial)	210
RG 10	Diode	Ultrafast Recovery Diode (Axial)	212
RG 10A	Diode	Ultrafast Recovery Diode (Axial)	212
RG 10Y	Diode	Ultrafast Recovery Diode (Axial)	211
RG 10Z	Diode	Ultrafast Recovery Diode (Axial)	211
RG 1C	Diode	Ultrafast Recovery Diode (Axial)	213
RG 2	Diode	Ultrafast Recovery Diode (Axial)	212
RG 2A	Diode	Ultrafast Recovery Diode (Axial)	212
RG 2A2	Diode	Damper Diode for CRT Display Compensation (Axial)	218
RG 2Y	Diode	Ultrafast Recovery Diode (Axial)	211
RG 2Z	Diode	Ultrafast Recovery Diode (Axial)	211
RG 4	Diode	Ultrafast Recovery Diode (Axial)	212
RG 4A	Diode	Ultrafast Recovery Diode (Axial)	212
RG 4C	Diode	Ultrafast Recovery Diode (Axial)	213
RG 4Y	Diode	Ultrafast Recovery Diode (Axial)	211
RG 4Z	Diode	Ultrafast Recovery Diode (Axial)	211
RH 10F	Diode	Damper Diode for CRT TV/Fast Recovery Diode (Axial)	218/210
RH 1A	Diode	Fast Recovery Diode (Axial)	209
RH 1B	Diode	Fast Recovery Diode (Axial)	210
RH 1C	Diode	Fast Recovery Diode (Axial)	210
RH 1Z	Diode	Fast Recovery Diode (Axial)	209
RH 2D	Diode	Damper Diode for CRT TV/Fast Recovery Diode (Axial)	218/210
RH 2F	Diode	Damper Diode for CRT TV/Fast Recovery Diode (Axial)	218/210

Part No.	Category	Description	Page	Part No.	Category	Description	Page
RH 3F	Diode	Damper Diode for CRT TV/Fast Recovery Diode (Axial)	218/210	RS 1A	Diode	Fast Recovery Diode (Axial)	209
RH 3G	Diode	Damper Diode for CRT TV/Fast Recovery Diode (Axial)	218/210	RS 1B	Diode	Fast Recovery Diode (Axial)	210
RH 4F	Diode	Damper Diode for CRT TV/Fast Recovery Diode (Axial)	218/210	RS 3FS	Diode	Damper Diode for CRT TV/Fast Recovery Diode (Axial)	218/210
RJ 43	Diode	Schottky Barrier Diode (Axial)	216	RS 4FS	Diode	Damper Diode for CRT TV/Fast Recovery Diode (Axial)	218/210
RK 13	Diode	Schottky Barrier Diode (Axial)	214	RU 1	Diode	Fast Recovery Diode (Axial)	209
RK 14	Diode	Schottky Barrier Diode (Axial)	214	RU 1A	Diode	Fast Recovery Diode (Axial)	210
RK 16	Diode	Schottky Barrier Diode (Axial)	214	RU 1B	Diode	Fast Recovery Diode (Axial)	210
RK 19	Diode	Schottky Barrier Diode (Axial)	215	RU 1C	Diode	Fast Recovery Diode (Axial)	210
RK 33	Diode	Schottky Barrier Diode (Axial)	214	RU 1P	Diode	Ultrafast Recovery Diode (Axial)	210
RK 34	Diode	Schottky Barrier Diode (Axial)	214	RU 2	Diode	Fast Recovery Diode (Axial)	210
RK 36	Diode	Schottky Barrier Diode (Axial)	214	RU 20A	Diode	Fast Recovery Diode (Axial)	210
RK 39	Diode	Schottky Barrier Diode (Axial)	215	RU 2AM	Diode	Fast Recovery Diode (Axial)	210
RK 43	Diode	Schottky Barrier Diode (Axial)	214	RU 2B	Diode	Fast Recovery Diode (Axial)	210
RK 44	Diode	Schottky Barrier Diode (Axial)	214	RU 2C	Diode	Fast Recovery Diode (Axial)	210
RK 46	Diode	Schottky Barrier Diode (Axial)	214	RU 2M	Diode	Fast Recovery Diode (Axial)	210
RK 49	Diode	Schottky Barrier Diode (Axial)	215	RU 2YX	Diode	Fast Recovery Diode (Axial)	209
RL 10Z	Diode	Ultrafast Recovery Diode (Axial)	211	RU 2Z	Diode	Fast Recovery Diode (Axial)	209
RL 2	Diode	Ultrafast Recovery Diode (Axial)	212	RU 3	Diode	Fast Recovery Diode (Axial)	209
RL 2Z	Diode	Ultrafast Recovery Diode (Axial)	211	RU 30	Diode	Fast Recovery Diode (Axial)	209
RL 3	Diode	Ultrafast Recovery Diode (Axial)	212	RU 30A	Diode	Fast Recovery Diode (Axial)	210
RL 31	Diode	Ultrafast Recovery Diode (Axial)	212	RU 30Y	Diode	Fast Recovery Diode (Axial)	209
RL 3A	Diode	Ultrafast Recovery Diode (Axial)	212	RU 30Z	Diode	Fast Recovery Diode (Axial)	209
RL 3Z	Diode	Ultrafast Recovery Diode (Axial)	211	RU 31	Diode	Fast Recovery Diode (Axial)	209
RL 4A	Diode	Ultrafast Recovery Diode (Axial)	212	RU 31A	Diode	Fast Recovery Diode (Axial)	210
RL 4Z	Diode	Ultrafast Recovery Diode (Axial)	211	RU 3A	Diode	Fast Recovery Diode (Axial)	210
RM 1	Diode	Rectifier Diode (Axial)	207	RU 3AM	Diode	Fast Recovery Diode (Axial)	210
RM 10	Diode	Rectifier Diode (Axial)	207	RU 3B	Diode	Fast Recovery Diode (Axial)	210
RM 10A	Diode	Rectifier Diode (Axial)	207	RU 3C	Diode	Fast Recovery Diode (Axial)	210
RM 10B	Diode	Rectifier Diode (Axial)	207	RU 3M	Diode	Fast Recovery Diode (Axial)	209
RM 10Z	Diode	Rectifier Diode (Axial)	207	RU 3YX	Diode	Fast Recovery Diode (Axial)	209
RM 11A	Diode	Rectifier Diode (Axial)	207	RU 4	Diode	Fast Recovery Diode (Axial)	209
RM 11B	Diode	Rectifier Diode (Axial)	207	RU 4A	Diode	Fast Recovery Diode (Axial)	210
RM 11C	Diode	Rectifier Diode (Axial)	208	RU 4AM	Diode	Fast Recovery Diode (Axial)	210
RM 1A	Diode	Rectifier Diode (Axial)	207	RU 4B	Diode	Fast Recovery Diode (Axial)	210
RM 1B	Diode	Rectifier Diode (Axial)	207	RU 4C	Diode	Fast Recovery Diode (Axial)	210
RM 1C	Diode	Rectifier Diode (Axial)	208	RU 4D	Diode	Damper Diode for CRT TV/Fast Recovery Diode (Axial)	210
RM 1Z	Diode	Rectifier Diode (Axial)	207	RU 4DS	Diode	Damper Diode for CRT TV/Fast Recovery Diode (Axial)	210
RM 2	Diode	Rectifier Diode (Axial)	207	RU 4M	Diode	Fast Recovery Diode (Axial)	209
RM 2A	Diode	Rectifier Diode (Axial)	207	RU 4Y	Diode	Fast Recovery Diode (Axial)	209
RM 2B	Diode	Rectifier Diode (Axial)	207	RU 4YX	Diode	Fast Recovery Diode (Axial)	209
RM 2C	Diode	Rectifier Diode (Axial)	208	RU 4Z	Diode	Fast Recovery Diode (Axial)	209
RM 2Z	Diode	Rectifier Diode (Axial)	207	RX 10Z	Diode	Ultrafast Recovery Diode (Axial)	209
RM 3	Diode	Rectifier Diode (Axial)	207	RX 3Z	Diode	Ultrafast Recovery Diode (Axial)	211
RM 3A	Diode	Rectifier Diode (Axial)	207	RZ1030	Diode	Avalanche Diode with Built-in Thyristor (Axial)	220
RM 3B	Diode	Rectifier Diode (Axial)	207	RZ1040	Diode	Avalanche Diode with Built-in Thyristor (Axial)	220
RM 3C	Diode	Rectifier Diode (Axial)	208	RZ1055	Diode	Avalanche Diode with Built-in Thyristor (Axial)	220
RM 4	Diode	Rectifier Diode (Axial)	207	RZ1125	Diode	Avalanche Diode with Built-in Thyristor (Axial)	220
RM 4A	Diode	Rectifier Diode (Axial)	207	RZ1150	Diode	Avalanche Diode with Built-in Thyristor (Axial)	220
RM 4AM	Diode	Rectifier Diode (Axial)	207	RZ1155	Diode	Avalanche Diode with Built-in Thyristor (Axial)	220
RM 4B	Diode	Rectifier Diode (Axial)	207	RZ1175	Diode	Avalanche Diode with Built-in Thyristor (Axial)	220
RM 4C	Diode	Rectifier Diode (Axial)	208	RZ1200	Diode	Avalanche Diode with Built-in Thyristor (Axial)	220
RM 4Y	Diode	Rectifier Diode (Axial)	207	RZ1235	Diode	Avalanche Diode with Built-in Thyristor (Axial)	220
RM 4Z	Diode	Rectifier Diode (Axial)	207	RZ1250	Diode	Avalanche Diode with Built-in Thyristor (Axial)	220
RN 1Z	Diode	Ultrafast Recovery Diode (Axial)	211	SAI01	IC	Surface mount Switching Regulator IC	64
RN 2Z	Diode	Ultrafast Recovery Diode (Axial)	211	SAI02	IC	Surface mount Switching Regulator IC	64
RN 3Z	Diode	Ultrafast Recovery Diode (Axial)	211	SAI03	IC	Surface mount Switching Regulator IC	64
RN 4Z	Diode	Ultrafast Recovery Diode (Axial)	211	SAI06	IC	Surface mount Switching Regulator IC	64
RO 2	Diode	Rectifier Diode (Axial)	207	SAP09N	Transistor	For Audio with Temperature Compensation (Darlington)	158
RO 2A	Diode	Rectifier Diode (Axial)	207	SAP09P	Transistor	For Audio with Temperature Compensation (Darlington)	158
RO 2B	Diode	Rectifier Diode (Axial)	207	SAP10N	Transistor	For Audio with Temperature Compensation (Darlington)	158
RO 2C	Diode	Rectifier Diode (Axial)	208	SAP10P	Transistor	For Audio with Temperature Compensation (Darlington)	158
RO 2Z	Diode	Rectifier Diode (Axial)	207	SAP15N	Transistor	For Audio with Temperature Compensation (Darlington)	158
RP 1H	Diode	Ultrafast Recovery Diode (Axial)	213	SAP15P	Transistor	For Audio with Temperature Compensation (Darlington)	158
RP 3F	Diode	Damper Diode for CRT Display/Fast Recovery Diode (Axial)	218/210	SDA01	Transistor	Arrey for Source Drive General Purpose (Surface Mount)	174

Part Number Index in Alphanumeric Order

Part No.	Category	Description	Page
SDA05	Transistor	Array for 3-Phase Motor Drive (Surface Mount)	178
SDC01	Transistor	Array for Sink Drive General Purpose (Surface Mount)	172
SDC03	Transistor	Array for Sink Drive with Built-in Avalanche Diode(btw C & E)(Surface Mount)	170
SDC04	Transistor	Array for Sink Drive with Built-in Avalanche Diode(btw C & E)(Surface Mount)	170
SDC06	Transistor	Array for Sink Drive with Built-in Avalanche Diode(btw C & E)(Surface Mount)	170
SDC07	Transistor	Array for 3-Phase Motor Drive (Surface Mount)	178
SDH02	Transistor	Array for Sink Drive with Built-in Flywheel Diode (Surface Mount)	170
SDH03	Transistor	Array for H-Bridge Motor Drive (Surface Mount)	176
SDI02	IC	Surface mount Dual Output Switching Regulator IC	100
SDK03M	IC	2-phase Stepper Motor Unipolar Driver IC (Surface Mount)	132
SDK04	Transistor	Array for Sink Drive General Purpose (Surface Mount)	172
SEC1101C	LED	3x1.5 Surface Mount LED	248
SEC1201C	LED	3x1.5 Surface Mount LED	248
SEC1203C	LED	3x1.5 Surface Mount Inner Lens TypeLED	248
SEC1401C	LED	3x1.5 Surface Mount LED	248
SEC1401E-TG	LED	3x1.5 Surface Mount LED	248
SEC1403C	LED	3x1.5 Surface Mount Inner Lens TypeLED	248
SEC1403E-TG	LED	3x1.5 Surface Mount Inner Lens TypeLED	248
SEC1501C	LED	3x1.5 Surface Mount LED	248
SEC1503C	LED	3x1.5 Surface Mount Inner Lens TypeLED	248
SEC1601C	LED	3x1.5 Surface Mount LED	248
SEC1603C	LED	3x1.5 Surface Mount Inner Lens TypeLED	248
SEC1701C-YG	LED	3x1.5 Surface Mount LED	248
SEC1703C	LED	3x1.5 Surface Mount Inner Lens TypeLED	248
SEC1801C	LED	3x1.5 Surface Mount LED	248
SEC1803C	LED	3x1.5 Surface Mount Inner Lens TypeLED	248
SEC1901C	LED	3x1.5 Surface Mount LED	248
SEC1903C	LED	3x1.5 Surface Mount Inner Lens TypeLED	248
SEC1E01C	LED	3x1.5 Surface Mount LED	248
SEC1G03C	LED	3x1.5 Infrared Surface Mount Inner Lens Type LED	251
SEC2422C	LED	3x2.5 Surface Mount 2-element LED	249
SEC2442C	LED	3x2.5 Surface Mount 2-element LED	249
SEC2462C	LED	3x2.5 Surface Mount 2-element LED	249
SEC2484C	LED	3x2.5 Surface Mount Inner Lens Type 2-element LED	249
SEC2492C	LED	3x2.5 Surface Mount 2-element LED	249
SEC2494C	LED	3x2.5 Surface Mount Inner Lens Type 2-element LED	249
SEC2552C	LED	3x2.5 Surface Mount 2-element LED	249
SEC2554C	LED	3x2.5 Surface Mount Inner Lens Type 2-element LED	249
SEC2592C	LED	3x2.5 Surface Mount 2-element LED	249
SEC2762C-YG	LED	3x2.5 Surface Mount 2-element LED	249
SEC2764C	LED	3x2.5 Surface Mount Inner Lens Type 2-element LED	249
SEC2774C	LED	3x2.5 Surface Mount Inner Lens Type 2-element LED	249
SEC4201C	LED	Side-view Surface Mount LED	247
SEC4203C	LED	Side-view Surface Mount Inner Lens Type LED	247
SEC4401C	LED	Side-view Surface Mount LED	247
SEC4401E-TG	LED	Side-view Surface Mount LED	247
SEC4403C	LED	Side-view Surface Mount Inner Lens Type LED	247
SEC4403E-TG	LED	Side-view Surface Mount Inner Lens Type LED	247
SEC4501C	LED	Side-view Surface Mount LED	247
SEC4503C	LED	Side-view Surface Mount Inner Lens Type LED	247
SEC4701C	LED	Side-view Surface Mount LED	247
SEC4703C	LED	Side-view Surface Mount Inner Lens Type LED	247
SEC4801C	LED	Side-view Surface Mount LED	247
SEC4803C	LED	Side-view Surface Mount Inner Lens Type LED	247
SEC4901C	LED	Side-view Surface Mount LED	247
SEC4903C	LED	Side-view Surface Mount Inner Lens Type LED	247
SECS1203C	LED	3x1.5 Surface Mount Inner Lens Type LED	248
SECS1803C	LED	3x1.5 Surface Mount Inner Lens Type LED	248
SECS1903C	LED	3x1.5 Surface Mount Inner Lens Type LED	248
SECS1B07C	LED	1.6x0.8 Miniature Surface Mount LED (t=0.7mm)	247
SECS1E07C	LED	1.6x0.8 Miniature Surface Mount LED (t=0.7mm)	247
SECS1L07C	LED	1.6x0.8 Miniature Surface Mount LED (t=0.7mm)	247
SECS2D68C	LED	1.6x1.25 Bicolor Surface Mount LED	247
SECU1205C-S	LED	1.6x0.8 Miniature Surface Mount LED (t=0.55mm)	247

Part No.	Category	Description	Page
SECU1707C	LED	1.6x0.8 Miniature Surface Mount LED (t=0.7mm)	247
SECU1805C-S	LED	1.6x0.8 Miniature Surface Mount LED (t=0.55mm)	247
SECU1905C-S	LED	1.6x0.8 Miniature Surface Mount LED (t=0.55mm)	247
SECU1D01C	LED	3x1.5 Surface Mount LED	248
SECU1D05C-S	LED	1.6x0.8 Miniature Surface Mount LED (t=0.55mm)	247
SECU1D07C	LED	1.6x0.8 Miniature Surface Mount LED (t=0.7mm)	247
SECU1E01C	LED	3x1.5 Surface Mount LED	248
SECU1E05C-S	LED	1.6x0.8 Miniature Surface Mount LED (t=0.55mm)	247
SECU1J05C	LED	1.6x0.8 Miniature Surface Mount LED (t=0.55mm)	247
SECU1V0AC	LED	2.8x3.5 Ultraviolet Surface Mount LED	252
SECU3M02C	LED	Surface Mount 3-element LED	250
SECU3M06C	LED	Surface Mount 3-element LED	250
SECU4D01C	LED	Side-view Surface Mount LED	247
SECU4D03C	LED	Side-view Surface Mount Inner Lens Type LED	247
SECU4E01C	LED	Side-view Surface Mount LED	247
SECU4E03C	LED	Side-view Surface Mount Inner Lens Type LED	247
SEL1110R	LED	5φ Round Standard LED (With Stopper)	237
SEL1110S	LED	5φ Round Standard LED (With Stopper)	237
SEL1110W	LED	5φ Round Standard LED (With Stopper)	237
SEL1111R	LED	5φ Cylindrical LED	238
SEL1120R	LED	2x5 Rectangular Type LED	242
SEL1121R	LED	3x5 Rectangular Type LED	242
SEL1124R	LED	1x5 Rectangular Type LED	242
SEL1210R	LED	5φ Round Standard LED (With Stopper)	237
SEL1210RM	LED	5φ Round Standard LED	237
SEL1210S	LED	5φ Round Standard LED (With Stopper)	237
SEL1210SM	LED	5φ Round Standard LED	237
SEL1211R	LED	5φ Cylindrical LED	238
SEL1213C	LED	5φ Inverted-cone LED for Lighting panel	241
SEL1220R	LED	2x5 Rectangular Type LED	242
SEL1222R	LED	2.5x5 Rectangular Type LED	242
SEL1250RM	LED	5φ Round Narrow-viewing-angle LED, Direct mount available	238
SEL1250SM	LED	5φ Round Narrow-viewing-angle LED, Direct mount available	238
SEL1410E	LED	5φ Round Standard LED (With Stopper)	237
SEL1410EM	LED	5φ Round Standard LED	237
SEL1410G	LED	5φ Round Standard LED (With Stopper)	237
SEL1410GM	LED	5φ Round Standard LED	237
SEL1411G	LED	5φ Cylindrical LED	238
SEL1413E	LED	5φ Inverted-cone LED for Lighting panel	241
SEL1420G	LED	2x5 Rectangular Type LED	242
SEL1421G	LED	3x5 Rectangular Type LED	242
SEL1422G	LED	2.5x5 Rectangular Type LED	242
SEL1424G	LED	1x5 Rectangular Type LED	242
SEL1450EKM	LED	5φ Round Narrow-viewing-angle LED, Direct mount available	238
SEL1450GM-YG	LED	5φ Round Narrow-viewing-angle LED, Direct mount available	238
SEL1453CEMKT	LED	4.6x5.6φ Egg-shaped LED	238
SEL1510C	LED	5φ Round Standard LED (With Stopper)	237
SEL1510CM	LED	5φ Round Standard LED	237
SEL1513E	LED	5φ Inverted-cone LED for Lighting panel	241
SEL1550CM	LED	5φ Round Narrow-viewing-angle LED, Direct mount available	238
SEL1610C	LED	5φ Round Standard LED (With Stopper)	237
SEL1610W	LED	5φ Round Standard LED (With Stopper)	237
SEL1615C	LED	5φ Round Narrow-viewing-angle LED	238
SEL1710K	LED	5φ Round Standard LED (With Stopper)	237
SEL1710KM	LED	5φ Round Standard LED	237
SEL1710Y	LED	5φ Round Standard LED (With Stopper)	237
SEL1711Y	LED	5φ Cylindrical LED	238
SEL1713K	LED	5φ Inverted-cone LED for Lighting panel	241
SEL1720Y	LED	2x5 Rectangular Type LED	242
SEL1721Y	LED	3x5 Rectangular Type LED	242
SEL1722K	LED	2.5x5 Rectangular Type LED	242
SEL1722Y	LED	2.5x5 Rectangular Type LED	242
SEL1724Y	LED	1x5 Rectangular Type LED	242
SEL1810A	LED	5φ Round Standard LED (With Stopper)	237

Part No.	Category	Description	Page
SEL1810AM	LED	5φ Round Standard LED	237
SEL1810D	LED	5φ Round Standard LED (With Stopper)	237
SEL1810DM	LED	5φ Round Standard LED	237
SEL1811D	LED	5φ Cylindrical LED	238
SEL1813A	LED	5φ Inverted-cone LED for Lighting panel	241
SEL1820D	LED	2×5 Rectangular Type LED	242
SEL1821D	LED	3×5 Rectangular Type LED	242
SEL1822D	LED	2.5×5 Rectangular Type LED	242
SEL1824D	LED	1×5 Rectangular Type LED	242
SEL1850AM	LED	5φ Round Narrow-viewing-angle LED, Direct mount available	238
SEL1850DM	LED	5φ Round Narrow-viewing-angle LED, Direct mount available	238
SEL1910A	LED	5φ Round Standard LED (With Stopper)	237
SEL1910AM	LED	5φ Round Standard LED	237
SEL1910D	LED	5φ Round Standard LED (With Stopper)	237
SEL1910DM	LED	5φ Round Standard LED	237
SEL1911D	LED	5φ Cylindrical LED	238
SEL1913K	LED	5φ Inverted-cone LED for Lighting panel	241
SEL1920D	LED	2×5 Rectangular Type LED	242
SEL1921D	LED	3×5 Rectangular Type LED	242
SEL1922D	LED	2.5×5 Rectangular Type LED	242
SEL1924D	LED	1×5 Rectangular Type LED	242
SEL1950KM	LED	5φ Round Narrow-viewing-angle LED, Direct mount available	238
SEL1E24W	LED	1×5 Rectangular Type LED	242
SEL1E50CM-S	LED	5φ Round Narrow-viewing-angle LED, Direct mount available	238
SEL2110R	LED	3φ Round Type LED	240
SEL2110S	LED	3φ Round Type LED	240
SEL2110W	LED	3φ Round Type LED	240
SEL2111R	LED	3φ Cylindrical LED	241
SEL2210R	LED	3φ Round Type LED	240
SEL2210S	LED	3φ Round Type LED	240
SEL2210W	LED	3φ Round Type LED	240
SEL2213C	LED	3φ Inverted-cone LED for Lighting panel	241
SEL2215R	LED	3φ Round Type Narrow-viewing-angle LED	240
SEL2215S	LED	3φ Round Type Narrow-viewing-angle LED	240
SEL2410E	LED	3φ Round Type LED	240
SEL2410G	LED	3φ Round Type LED	240
SEL2411G	LED	3φ Cylindrical LED	241
SEL2413E	LED	3φ Inverted-cone LED for Lighting panel	241
SEL2413G	LED	3φ Inverted-cone LED for Lighting panel	241
SEL2415E	LED	3φ Round Type Narrow-viewing-angle LED	240
SEL2415G	LED	3φ Round Type Narrow-viewing-angle LED	240
SEL2510C	LED	3φ Round Type LED	240
SEL2510G	LED	3φ Round Type LED	240
SEL2513E	LED	3φ Inverted-cone LED for Lighting panel	241
SEL2515C	LED	3φ Round Type Narrow-viewing-angle LED	240
SEL2610C	LED	3φ Round Type LED	240
SEL2613CS-S	LED	3φ Inverted-cone LED for Lighting panel	241
SEL2710K	LED	3φ Round Type LED	240
SEL2710Y	LED	3φ Round Type LED	240
SEL2713K	LED	3φ Inverted-cone LED for Lighting panel	241
SEL2715K	LED	3φ Round Type Narrow-viewing-angle LED	240
SEL2715Y	LED	3φ Round Type Narrow-viewing-angle LED	240
SEL2810A	LED	3φ Round Type LED	240
SEL2810D	LED	3φ Round Type LED	240
SEL2813A	LED	3φ Inverted-cone LED for Lighting panel	241
SEL2815A	LED	3φ Round Type Narrow-viewing-angle LED	240
SEL2815D	LED	3φ Round Type Narrow-viewing-angle LED	240
SEL2910A	LED	3φ Round Type LED	240
SEL2910D	LED	3φ Round Type LED	240
SEL2911D	LED	3φ Cylindrical LED	241
SEL2913K	LED	3φ Inverted-cone LED for Lighting panel	241
SEL2915A	LED	3φ Round Type Narrow-viewing-angle LED	240
SEL2915D	LED	3φ Round Type Narrow-viewing-angle LED	240
SEL2E10C	LED	3φ Round Type LED	240

Part No.	Category	Description	Page
SEL4110R	LED	4φ Round Type LED	238
SEL4110S	LED	4φ Round Type LED	238
SEL4114R	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL4114S	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL4117R	LED	2φ Round Type LED	241
SEL4210R	LED	4φ Round Type LED	238
SEL4210S	LED	4φ Round Type LED	238
SEL4214R	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL4214S	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL4225C	LED	2×4 Rectangular Type LED	242
SEL4225R	LED	2×4 Rectangular Type LED	242
SEL4226C	LED	2×4 Rectangular Type LED, Direct mount available	243
SEL4226R	LED	2×4 Rectangular Type LED, Direct mount available	243
SEL4227C	LED	4φ Bow-shaped LED	243
SEL4228C	LED	3.1φ Bow-Shaped Type LED	243
SEL4229R	LED	3.1φ Bow-Shaped Type LED, Direct mount available	243
SEL4410E	LED	4φ Round Type LED	238
SEL4410G	LED	4φ Round Type LED	238
SEL4414E	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL4414G	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL4417G	LED	2φ Round Type LED	241
SEL4425E	LED	2×4 Rectangular Type LED	242
SEL4425G	LED	2×4 Rectangular Type LED	242
SEL4426E	LED	2×4 Rectangular Type LED, Direct mount available	243
SEL4426G	LED	2×4 Rectangular Type LED, Direct mount available	243
SEL4427EP	LED	4φ Bow-shaped LED	243
SEL4428B-TG	LED	3.1φ Bow-Shaped Type LED	243
SEL4428E	LED	3.1φ Bow-Shaped Type LED	243
SEL4429E	LED	3.1φ Bow-Shaped Type LED, Direct mount available	243
SEL4510C	LED	4φ Round Type LED	238
SEL4514C	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL4525C	LED	2×4 Rectangular Type LED	242
SEL4528C	LED	3.1φ Bow-Shaped Type LED	243
SEL4710K	LED	4φ Round Type LED	238
SEL4710Y	LED	4φ Round Type LED	238
SEL4714K	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL4714Y	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL4717Y	LED	2φ Round Type LED	241
SEL4725K	LED	2×4 Rectangular Type LED	242
SEL4725Y	LED	2×4 Rectangular Type LED	242
SEL4726K	LED	2×4 Rectangular Type LED, Direct mount available	243
SEL4726Y	LED	2×4 Rectangular Type LED, Direct mount available	243
SEL4728K	LED	3.1φ Bow-Shaped Type LED	243
SEL4729KH	LED	3.1φ Bow-Shaped Type LED, Direct mount available	243
SEL4810A	LED	4φ Round Type LED	238
SEL4810D	LED	4φ Round Type LED	238
SEL4814A	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL4814D	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL4817D	LED	2φ Round Type LED	241
SEL4825A	LED	2×4 Rectangular Type LED	242
SEL4825D	LED	2×4 Rectangular Type LED	242
SEL4826A	LED	2×4 Rectangular Type LED, Direct mount available	243
SEL4826D	LED	2×4 Rectangular Type LED, Direct mount available	243
SEL4828A	LED	3.1φ Bow-Shaped Type LED	243
SEL4828C-S	LED	3.1φ Bow-Shaped Type LED	243
SEL4829A	LED	3.1φ Bow-Shaped Type LED, Direct mount available	243
SEL4910A	LED	4φ Round Type LED	238
SEL4910D	LED	4φ Round Type LED	238
SEL4914A	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL4914D	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL4917D	LED	2φ Round Type LED	241
SEL4925A	LED	2×4 Rectangular Type LED	242
SEL4925D	LED	2×4 Rectangular Type LED	242
SEL4926A	LED	2×4 Rectangular Type LED, Direct mount available	243

Part Number Index in Alphanumeric Order

Part No.	Category	Description	Page
SEL4926D	LED	2x4 Rectangular Type LED, Direct mount available	243
SEL4928A	LED	3.1φ Bow-Shaped Type LED	243
SEL4929A	LED	3.1φ Bow-Shaped Type LED, Direct mount available	243
SEL5220S	LED	5mm Pitch Lead Rectangular LED, Direct mount available	244
SEL5221S	LED	5mm Pitch Lead 3φ Lens-type LED, Direct mount available	244
SEL5223S	LED	5mm Pitch Lead Bow-shaped LED, Direct mount available	244
SEL5255S	LED	5mm Pitch Lead Egg-shaped LED, Direct mount available	244
SEL5420E	LED	5mm Pitch Lead Rectangular LED, Direct mount available	244
SEL5421E	LED	5mm Pitch Lead 3φ Lens-type LED, Direct mount available	244
SEL5423E	LED	5mm Pitch Lead Bow-shaped LED, Direct mount available	244
SEL5520C	LED	5mm Pitch Lead Rectangular LED, Direct mount available	244
SEL5521C	LED	5mm Pitch Lead 3φ Lens-type LED, Direct mount available	244
SEL5523C	LED	5mm Pitch Lead Bow-shaped LED, Direct mount available	244
SEL5620C	LED	5mm Pitch Lead Rectangular LED, Direct mount available	244
SEL5721C	LED	5mm Pitch Lead 3φ Lens-type LED, Direct mount available	244
SEL5723C	LED	5mm Pitch Lead Bow-shaped LED, Direct mount available	244
SEL5755C	LED	5mm Pitch Lead Egg-shaped LED, Direct mount available	244
SEL5820A	LED	5mm Pitch Lead Rectangular LED, Direct mount available	244
SEL5821A	LED	5mm Pitch Lead 3φ Lens-type LED, Direct mount available	244
SEL5823A	LED	5mm Pitch Lead Bow-shaped LED, Direct mount available	244
SEL5920A	LED	5mm Pitch Lead Rectangular LED, Direct mount available	244
SEL5921A	LED	5mm Pitch Lead 3φ Lens-type LED, Direct mount available	244
SEL5923A	LED	5mm Pitch Lead Bow-shaped LED, Direct mount available	244
SEL5955A	LED	5mm Pitch Lead Egg-shaped LED, Direct mount available	244
SEL5E20C	LED	5mm Pitch Lead Rectangular LED, Direct mount available	244
SEL5E23C	LED	5mm Pitch Lead Bow-shaped LED, Direct mount available	244
SEL6110R	LED	3φ Round Type LED, Direct mount available	239
SEL6110S	LED	3φ Round Type LED, Direct mount available	239
SEL6210R	LED	3φ Round Type LED, Direct mount available	239
SEL6210S	LED	3φ Round Type LED, Direct mount available	239
SEL6214S	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL6215S	LED	3φ Round Type Narrow-viewing-angle LED, Direct mount available	240
SEL6227S	LED	4φ Bow-shaped LED, Direct mount available	243
SEL6410E	LED	3φ Round Type LED, Direct mount available	239
SEL6410G	LED	3φ Round Type LED, Direct mount available	239
SEL6413E	LED	3φ Inverted-cone LED for Lighting panel, Direct mount available	241
SEL6413E-TG	LED	3φ Inverted-cone LED for Lighting panel, Direct mount available	241
SEL6414E	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL6414E-TG	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL6415E	LED	3φ Round Type Narrow-viewing-angle LED, Direct mount available	240
SEL6427EP	LED	4φ Bow-shaped LED, Direct mount available	243
SEL6510C	LED	3φ Round Type LED, Direct mount available	239
SEL6510G	LED	3φ Round Type LED, Direct mount available	239
SEL6513C	LED	3φ Inverted-cone LED for Lighting panel, Direct mount available	241
SEL6514C	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL6615C	LED	3φ Round Type Narrow-viewing-angle LED, Direct mount available	240
SEL6710K	LED	3φ Round Type LED, Direct mount available	239
SEL6710Y	LED	3φ Round Type LED, Direct mount available	239
SEL6714K	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL6714W	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL6715C	LED	3φ Round Type Narrow-viewing-angle LED, Direct mount available	240
SEL6810A	LED	3φ Round Type LED, Direct mount available	239
SEL6810D	LED	3φ Round Type LED, Direct mount available	239
SEL6814A	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL6910A	LED	3φ Round Type LED, Direct mount available	239
SEL6910D	LED	3φ Round Type LED, Direct mount available	239
SEL6914A	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL6914W	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SEL6915A	LED	3φ Round Type Narrow-viewing-angle LED, Direct mount available	240
SEL6927A	LED	4φ Bow-shaped LED, Direct mount available	243
SEL6E10C	LED	3φ Round Type LED, Direct mount available	239
SELS1E10CXM-M	LED	5φ Round Wide-viewing-angle LED	237
SELS2E10C	LED	3φ Round Type LED	240
SELS2J11W	LED	3φ Cylindrical LED	241

Part No.	Category	Description	Page
SELS5223C	LED	5mm Pitch Lead Bow-shaped LED, Direct mount available	244
SELS5823C	LED	5mm Pitch Lead Bow-shaped LED, Direct mount available	244
SELS5923C	LED	5mm Pitch Lead Bow-shaped LED, Direct mount available	244
SELS5B23C	LED	5mm Pitch Lead Bow-shaped LED, Direct mount available	244
SELS6B13W	LED	3φ Inverted-cone LED for Lighting panel, Direct mount available	241
SELS6B14C	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SELS6D14C	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SELS6E14C-M	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SELU1210CXM	LED	5φ Round Wide-viewing-angle LED	237
SELU1250CM	LED	5φ Round Narrow-viewing-angle LED, Direct mount available	238
SELU1253CMKT	LED	4.6x5.6φ Egg-shaped LED	238
SELU1410CXM-S	LED	5φ Round Wide-viewing-angle LED	237
SELU1610CXM-S	LED	5φ Round Wide-viewing-angle LED	237
SELU1710CXM	LED	5φ Round Wide-viewing-angle LED	237
SELU1810CXM	LED	5φ Round Wide-viewing-angle LED	237
SELU1853CM-S	LED	4.6x5.6φ Egg-shaped LED	238
SELU1910CXM	LED	5φ Round Wide-viewing-angle LED	237
SELU1B10CXM-S	LED	5φ Round Wide-viewing-angle LED	237
SELU1D10CXM	LED	5φ Round Wide-viewing-angle LED	237
SELU1D50CM	LED	5φ Round Narrow-viewing-angle LED, Direct mount available	238
SELU1E10CXM	LED	5φ Round Wide-viewing-angle LED	237
SELU1E50CM	LED	5φ Round Narrow-viewing-angle LED, Direct mount available	238
SELU1J10CXM	LED	5φ Round Wide-viewing-angle LED	237
SELU1L10CXM	LED	5φ Round Wide-viewing-angle LED	237
SELU2210C-S	LED	3φ Round Type LED	240
SELU2215R-S	LED	3φ Round Type Narrow-viewing-angle LED	240
SELU2410C-S	LED	3φ Round Type LED	240
SELU2610C-S	LED	3φ Round Type LED	240
SELU2710C	LED	3φ Round Type LED	240
SELU2810C-S	LED	3φ Round Type LED	240
SELU2910C-S	LED	3φ Round Type LED	240
SELU2B10C-S	LED	3φ Round Type LED	240
SELU2D10C	LED	3φ Round Type LED	240
SELU2E10C	LED	3φ Round Type LED	240
SELU2J10C	LED	3φ Round Type LED	240
SELU2L10C	LED	3φ Round Type LED	240
SELU4410CKT-S	LED	4φ Round Type LED	238
SELU5220C-S	LED	5mm Pitch Lead Rectangular LED, Direct mount available	244
SELU5420C-S	LED	5mm Pitch Lead Rectangular LED, Direct mount available	244
SELU5620C-S	LED	5mm Pitch Lead Rectangular LED, Direct mount available	244
SELU5720C	LED	5mm Pitch Lead Rectangular LED, Direct mount available	244
SELU5723C	LED	5mm Pitch Lead Bow-shaped LED, Direct mount available	244
SELU5820C-S	LED	5mm Pitch Lead Rectangular LED, Direct mount available	244
SELU5823C	LED	5mm Pitch Lead Bow-shaped LED, Direct mount available	244
SELU5920C	LED	5mm Pitch Lead Rectangular LED, Direct mount available	244
SELU5B20C	LED	5mm Pitch Lead Rectangular LED, Direct mount available	244
SELU5D20C	LED	5mm Pitch Lead Rectangular LED, Direct mount available	244
SELU5D23C	LED	5mm Pitch Lead Bow-shaped LED, Direct mount available	244
SELU5E20C	LED	5mm Pitch Lead Rectangular LED, Direct mount available	244
SELU5E23C	LED	5mm Pitch Lead Bow-shaped LED, Direct mount available	244
SELU6213C-S	LED	3φ Inverted-cone LED for Lighting panel, Direct mount available	241
SELU6214C	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SELU6414G-S	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SELU6614C-S	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SELU6614W-S	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SELU6714C	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SELU6814C	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SELU6910C-S	LED	3φ Round Type LED, Direct mount available	239
SELU6914C-S	LED	3φ Round Type Wide-viewing-angle LED, Direct mount available	239
SFPA-53	Diode	Schottky Barrier Diode (Surface Mount)	215
SFPA-63	Diode	Schottky Barrier Diode (Surface Mount)	215
SFPA-73	Diode	Schottky Barrier Diode (Surface Mount)	215
SFPB-54	Diode	Schottky Barrier Diode (Surface Mount)	214
SFPB-56	Diode	Schottky Barrier Diode (Surface Mount)	214

Part No.	Category	Description	Page	Part No.	Category	Description	Page
SFPB-59	Diode	Schottky Barrier Diode (Surface Mount)	214	SI-3018LUS	IC	Surface mount Linear Regulator IC	8
SFPB-64	Diode	Schottky Barrier Diode (Surface Mount)	214	SI-3025B	IC	Linear Regulator IC	32
SFPB-66	Diode	Schottky Barrier Diode (Surface Mount)	214	SI-3025F	IC	Linear Regulator IC	38
SFPB-69	Diode	Schottky Barrier Diode (Surface Mount)	214	SI-3025KD	IC	Surface mount Linear Regulator IC	24
SFPB-74	Diode	Schottky Barrier Diode (Surface Mount)	214	SI-3025KF	IC	Linear Regulator IC	42
SFPB-76	Diode	Schottky Barrier Diode (Surface Mount)	214	SI-3025KM	IC	Surface mount Linear Regulator IC	20
SFPE-64	Diode	Schottky Barrier Diode (Surface Mount)	216	SI-3025KMS	IC	Surface mount Linear Regulator IC	18
SFPJ-53	Diode	Schottky Barrier Diode (Surface Mount)	216	SI-3025KS	IC	Surface mount Linear Regulator IC	16
SFPJ-63	Diode	Schottky Barrier Diode (Surface Mount)	216	SI-3025LSA	IC	Surface mount Linear Regulator IC	14
SFPJ-73	Diode	Schottky Barrier Diode (Surface Mount)	216	SI-3025LU	IC	Surface mount Linear Regulator IC	10
SFPL-52	Diode	Ultrafast Recovery Diode (Surface Mount)	211	SI-3025LUS	IC	Surface mount Linear Regulator IC	8
SFPL-62	Diode	Ultrafast Recovery Diode (Surface Mount)	211	SI-3025ZD	IC	Surface mount Linear Regulator IC	30
SFPL-64	Diode	Ultrafast Recovery Diode (Surface Mount)	211	SI-3025ZF	IC	Linear Regulator IC	60
SFPM-52	Diode	Rectifier Diode (Surface Mount)	207	SI-3033C	IC	Linear Regulator IC	48
SFPM-54	Diode	Rectifier Diode (Surface Mount)	207	SI-3033HM	IC	Surface mount Linear Regulator IC	12
SFPM-62	Diode	Rectifier Diode (Surface Mount)	207	SI-3033KD	IC	Surface mount Linear Regulator IC	24
SFPM-64	Diode	Rectifier Diode (Surface Mount)	207	SI-3033KF	IC	Linear Regulator IC	42
SFPW-56	Diode	Schottky Barrier Diode (Surface Mount)	214	SI-3033KM	IC	Surface mount Linear Regulator IC	20
SFPX-62	Diode	Ultrafast Recovery Diode (Surface Mount)	211	SI-3033KMS	IC	Surface mount Linear Regulator IC	18
SFPX-63	Diode	Ultrafast Recovery Diode (Surface Mount)	211	SI-3033KS	IC	Surface mount Linear Regulator IC	16
SFPZ-68	Diode	Power Zener Diode (Surface Mount)	221	SI-3033LSA	IC	Surface mount Linear Regulator IC	14
SHV-02	Diode	High-Voltage Rectifier Diode	217	SI-3033LU	IC	Surface mount Linear Regulator IC	10
SHV-03	Diode	High-Voltage Rectifier Diode	217	SI-3033LUS	IC	Surface mount Linear Regulator IC	8
SHV-03S	Diode	High-Voltage Rectifier Diode	217	SI-3033ZD	IC	Surface mount Linear Regulator IC	30
SHV-05J	Diode	High-Voltage Rectifier Diode for Automotive Ignition Coil	217	SI-3033ZF	IC	Linear Regulator IC	60
SHV-06EN	Diode	High-Voltage Rectifier Diode	217	SI-3050C	IC	Linear Regulator IC	48
SHV-06JN	Diode	High-Voltage Rectifier Diode for Automotive Ignition Coil	217	SI-3050F	IC	Linear Regulator IC	38
SHV-08DN	Diode	High-Voltage Rectifier Diode	217	SI-3050HM	IC	Surface mount Linear Regulator IC	12
SHV-08EN	Diode	High-Voltage Rectifier Diode	217	SI-3050J	IC	Linear Regulator IC	58
SHV-08J	Diode	High-Voltage Rectifier Diode for Automotive Ignition Coil	217	SI-3050KD	IC	Surface mount Linear Regulator IC	24
SHV-10	Diode	High-Voltage Rectifier Diode	217	SI-3050KF	IC	Linear Regulator IC	42
SHV-10DN	Diode	High-Voltage Rectifier Diode	217	SI-3050KM	IC	Surface mount Linear Regulator IC	20
SHV-10EN	Diode	High-Voltage Rectifier Diode	217	SI-3050KMS	IC	Surface mount Linear Regulator IC	18
SHV-12	Diode	High-Voltage Rectifier Diode	217	SI-3050LSA	IC	Surface mount Linear Regulator IC	14
SHV-12DN	Diode	High-Voltage Rectifier Diode	217	SI-3050LU	IC	Surface mount Linear Regulator IC	10
SHV-12EN	Diode	High-Voltage Rectifier Diode	217	SI-3050LUS	IC	Surface mount Linear Regulator IC	8
SHV-14	Diode	High-Voltage Rectifier Diode	217	SI-3050N	IC	Linear Regulator IC	34
SHV-16	Diode	High-Voltage Rectifier Diode	217	SI-3050R	IC	Linear Regulator IC	52
SHV-20	Diode	High-Voltage Rectifier Diode	217	SI-3051N	IC	Linear Regulator IC	46
SHV-24	Diode	High-Voltage Rectifier Diode	217	SI-3052N	IC	Linear Regulator IC	54
SHV-30J	Diode	High-Voltage Rectifier Diode for Automotive Ignition Coil	217	SI-3052V	IC	Linear Regulator IC	56
SI-3002KWD	IC	Surface mount Dual Output Switching Regulator IC	110	SI-3053N	IC	Linear Regulator IC	34
SI-3002KWF	IC	Dual Output Switching Regulator IC	108	SI-3090C	IC	Linear Regulator IC	48
SI-3002KWM	IC	Surface mount Dual Output Switching Regulator IC	112	SI-3090F	IC	Linear Regulator IC	38
SI-3003KWD	IC	Surface mount Dual Output Switching Regulator IC	110	SI-3090HM	IC	Surface mount Linear Regulator IC	12
SI-3003KWF	IC	Dual Output Switching Regulator IC	108	SI-3090J	IC	Linear Regulator IC	58
SI-3003KWM	IC	Surface mount Dual Output Switching Regulator IC	112	SI-3090KD	IC	Surface mount Linear Regulator IC	24
SI-3010KD	IC	Surface mount Linear Regulator IC	24	SI-3090KF	IC	Linear Regulator IC	42
SI-3010KF	IC	Linear Regulator IC	42	SI-3090KM	IC	Surface mount Linear Regulator IC	20
SI-3010KM	IC	Surface mount Linear Regulator IC	20	SI-3090KMS	IC	Surface mount Linear Regulator IC	18
SI-3010LLSL	IC	Surface mount Linear Regulator IC	28	SI-3090N	IC	Linear Regulator IC	34
SI-3011ZD	IC	Surface mount Linear Regulator IC	30	SI-3091N	IC	Linear Regulator IC	46
SI-3011ZF	IC	Linear Regulator IC	60	SI-3092N	IC	Linear Regulator IC	54
SI-3012KD	IC	Surface mount Linear Regulator IC	24	SI-3120C	IC	Linear Regulator IC	48
SI-3012KM	IC	Surface mount Linear Regulator IC	20	SI-3120F	IC	Linear Regulator IC	38
SI-3012KS	IC	Surface mount Linear Regulator IC	16	SI-3120HM	IC	Surface mount Linear Regulator IC	12
SI-3012LU	IC	Surface mount Linear Regulator IC	10	SI-3120J	IC	Linear Regulator IC	58
SI-3018KD	IC	Surface mount Linear Regulator IC	24	SI-3120KD	IC	Surface mount Linear Regulator IC	24
SI-3018KF	IC	Linear Regulator IC	42	SI-3120KF	IC	Linear Regulator IC	42
SI-3018KM	IC	Surface mount Linear Regulator IC	20	SI-3120KM	IC	Surface mount Linear Regulator IC	20
SI-3018KMS	IC	Surface mount Linear Regulator IC	18	SI-3120KMS	IC	Surface mount Linear Regulator IC	18
SI-3018KS	IC	Surface mount Linear Regulator IC	16	SI-3120N	IC	Linear Regulator IC	34
SI-3018LSA	IC	Surface mount Linear Regulator IC	14	SI-3121N	IC	Linear Regulator IC	46
SI-3018LU	IC	Surface mount Linear Regulator IC	10	SI-3122N	IC	Linear Regulator IC	54

Part Number Index in Alphanumeric Order

Part No.	Category	Description	Page
SI-3122V	IC	Linear Regulator IC	56
SI-3123N	IC	Linear Regulator IC	36
SI-3150C	IC	Linear Regulator IC	48
SI-3150F	IC	Linear Regulator IC	38
SI-3150J	IC	Linear Regulator IC	58
SI-3150KD	IC	Surface mount Linear Regulator IC	24
SI-3150KF	IC	Linear Regulator IC	42
SI-3150KM	IC	Surface mount Linear Regulator IC	20
SI-3150KMS	IC	Surface mount Linear Regulator IC	18
SI-3150N	IC	Linear Regulator IC	34
SI-3151N	IC	Linear Regulator IC	46
SI-3152N	IC	Linear Regulator IC	54
SI-3152V	IC	Linear Regulator IC	56
SI-3153N	IC	Linear Regulator IC	36
SI-3157B	IC	Linear Regulator IC	32
SI-3157F	IC	Linear Regulator IC	38
SI-3200HM	IC	Surface mount Linear Regulator IC	12
SI-3240C	IC	Linear Regulator IC	48
SI-3240F	IC	Linear Regulator IC	38
SI-3241N	IC	Linear Regulator IC	46
SI-8010GL	IC	Switching Regulator IC	82
SI-8011NVS	IC	Surface mount Synchronous-rectification Switching Regulator Control IC	86
SI-8015JF	IC	Switching Regulator IC	80
SI-8025JF	IC	Switching Regulator IC	80
SI-8033JD	IC	Surface mount Switching Regulator IC	68
SI-8033JF	IC	Switching Regulator IC	80
SI-8033RD	IC	Surface mount Switching Regulator IC	76
SI-8033S	IC	Switching Regulator IC	84
SI-8033SD	IC	Surface mount Switching Regulator IC	70
SI-8033W	IC	Surface mount Switching Regulator IC	66
SI-8050E	IC	Switching Regulator IC	78
SI-8050JD	IC	Surface mount Switching Regulator IC	68
SI-8050JF	IC	Switching Regulator IC	80
SI-8050RD	IC	Surface mount Switching Regulator IC	76
SI-8050S	IC	Switching Regulator IC	84
SI-8050SD	IC	Surface mount Switching Regulator IC	70
SI-8050W	IC	Surface mount Switching Regulator IC	66
SI-8090JD	IC	Surface mount Switching Regulator IC	68
SI-8090JF	IC	Switching Regulator IC	80
SI-8090S	IC	Switching Regulator IC	84
SI-8120E	IC	Switching Regulator IC	78
SI-8120JD	IC	Surface mount Switching Regulator IC	68
SI-8120JF	IC	Switching Regulator IC	80
SI-8120S	IC	Switching Regulator IC	84
SI-8150S	IC	Switching Regulator IC	84
SI-8401L	IC	Switchig Type Regulator IC with Coil	94
SI-8402L	IC	Switchig Type Regulator IC with Coil	94
SI-8403L	IC	Switchig Type Regulator IC with Coil	94
SI-8501L	IC	Switchig Type Regulator IC with Coil	94
SI-8502L	IC	Switchig Type Regulator IC with Coil	94
SI-8503L	IC	Switchig Type Regulator IC with Coil	94
SI-8504L	IC	Switchig Type Regulator IC with Coil	94
SI-8511NVS	IC	Surface mount Synchronous-rectification Switching Regulator Control IC	88
SID1003BQ	LED	5 ϕ Round Infrade LED	251
SID1010CM	LED	5 ϕ Round Infrade LED	251
SID1010CXM	LED	5 ϕ Round Infrade LED	251
SID1050CM	LED	5 ϕ Round Infrade LED, Direct mount available	251
SID1G307C	LED	5 ϕ Round Infrade LED	251
SID1G313C	LED	5 ϕ Round Infrade LED	251
SID1K10CM	LED	5 ϕ Round Infrade LED	251
SID1K10CXM	LED	5 ϕ Round Infrade LED	251
SID2010C	LED	3 ϕ Round Infrade LED	251
SID2K10C	LED	3 ϕ Round Infrade LED	251
SID303C	LED	5 ϕ Round Infrade LED	251

Part No.	Category	Description	Page
SID307BR	LED	5 ϕ Round Infrade LED	251
SID313BP	LED	5 ϕ Round Infrade LED	251
SLA0201	Thyristor	Thyristor Array	192
SLA3002M	IC	3-Output Switching Regulator IC	114
SLA3004M	IC	3-Output Switching Regulator IC	114
SLA3005M	IC	4-Output Switching Regulator IC	116
SLA3006M	IC	4-Output Switching Regulator IC	116
SLA3007M	IC	4-Output Switching Regulator IC	116
SLA4010	Transistor	Arrey for Sink Drive with Built-in Avalanche Diode (btwn C & E)	170
SLA4030	Transistor	Arrey for Sink Drive General Purpose	172
SLA4031	Transistor	Array for Sink Drive with Built-in Flywheel Diode	170
SLA4041	Transistor	Array for Sink Drive with Built-in Flywheel Diode	170
SLA4060	Transistor	Arrey for Sink Drive General Purpose	172
SLA4061	Transistor	Array for Sink Drive with Built-in Flywheel Diode	170
SLA4070	Transistor	Arrey for Source Drive General Purpose	174
SLA4071	Transistor	Array for Source Drive with Built-in Flywheel Diode	174
SLA4310	Transistor	Array for H-Bridge Motor Drive	176
SLA4340	Transistor	Array for H-Bridge Motor Drive	176
SLA4390	Transistor	Array for H-Bridge Motor Drive	176
SLA4391	Transistor	Array for H-Bridge Motor Drive	176
SLA5001	Transistor	Arrey for Sink Drive General Purpose	172
SLA5002	Transistor	Array for Sink Drive with Built-in Flywheel Diode	170
SLA5003	Transistor	Array for Sink Drive with Built-in Flywheel Diode	170
SLA5005	Transistor	Arrey for Source Drive General Purpose	174
SLA5007	Transistor	Array for H-Bridge Motor Drive	176
SLA5008	Transistor	Array for H-Bridge Motor Drive	176
SLA5009	Transistor	Array for 3-Phase Motor Drive	178
SLA5011	Transistor	Arrey for Sink Drive General Purpose	172
SLA5012	Transistor	Arrey for Source Drive General Purpose	174
SLA5013	Transistor	Array for H-Bridge Motor Drive	176
SLA5015	Transistor	Arrey for Source Drive General Purpose	174
SLA5017	Transistor	Array for 3-Phase Motor Drive	178
SLA5021	Transistor	Arrey for Sink Drive General Purpose and S-Distortion Correction Switch for CRT Display	172/182
SLA5022	Transistor	Array for 3-Phase Motor Drive	178
SLA5023	Transistor	Array for 3-Phase Motor Drive	178
SLA5024	Transistor	Arrey for Source Drive General Purpose	174
SLA5029	Transistor	Arrey for Sink Drive General Purpose	172
SLA5031	Transistor	Array for Sink Drive with Built-in Flywheel Diode	170
SLA5037	Transistor	Arrey for Sink Drive General Purpose and S-Distortion Correction Switch for CRT Display	172/182
SLA5040	Transistor	Array for Sink Drive with Built-in Flywheel Diode	170
SLA5041	Transistor	Arrey for Sink Drive General Purpose and S-Distortion Correction Switch for CRT Display	172/182
SLA5042	Transistor	Arrey for Sink Drive General Purpose and S-Distortion Correction Switch for CRT Display	172/182
SLA5044	Transistor	Arrey for Sink Drive General Purpose and S-Distortion Correction Switch for CRT Display	172/182
SLA5046	Transistor	Arrey for Sink Drive General Purpose and S-Distortion Correction Switch for CRT Display	172/182
SLA5047	Transistor	Arrey for Sink Drive General Purpose and S-Distortion Correction Switch for CRT Display	172/182
SLA5049	Transistor	Arrey for Sink Drive General Purpose and S-Distortion Correction Switch for CRT Display	172/182
SLA5052	Transistor	Arrey for Sink Drive General Purpose and S-Distortion Correction Switch for CRT Display	172/182
SLA5054	Transistor	S-Distortion Correction Switch for CRT Display	182
SLA5055	Transistor	S-Distortion Correction Switch for CRT Display	182
SLA5057	Transistor	Arrey for Sink Drive General Purpose and S-Distortion Correction Switch for CRT Display	172/182
SLA5058	Transistor	Arrey for Sink Drive General Purpose and S-Distortion Correction Switch for CRT Display	172/182
SLA5059	Transistor	Array for 3-Phase Motor Drive	178
SLA5060	Transistor	Array for 3-Phase Motor Drive	178
SLA5061	Transistor	Array for 3-Phase Motor Drive	178
SLA5064	Transistor	Array for 3-Phase Motor Drive	178
SLA5065	Transistor	Array for 5-Phase Motor Drive	180
SLA5068	Transistor	Array for 5-Phase Motor Drive	180
SLA5070	Transistor	Array for "S" Distortion Correction Switch of CRT Display	182
SLA5072	Transistor	Array for 3-Phase Motor Drive	178
SLA5073	Transistor	Array for 5-Phase Motor Drive	180
SLA5074	Transistor	Array for 5-Phase Motor Drive	180
SLA5075	Transistor	Array for 3-Phase Motor Drive	178
SLA5077	Transistor	Arrey for Sink Drive General Purpose and S-shape Correction Switch for CRT Display	172/182
SLA5079	Transistor	Array for 3-Phase Motor Drive	178

Part No.	Category	Description	Page	Part No.	Category	Description	Page
SLA5080	Transistor	Array for 3-Phase Motor Drive	178	SMA7029M	IC	2-phase Stepper Motor Unipolar Driver IC	122
SLA5081	Transistor	Array for "S" Distortion Correction Switch of CRT Display	182	SMA7036M	IC	2-phase Stepper Motor Unipolar Driver IC	124
SLA5085	Transistor	Array for Sink Drive General Purpose	172	SML11516C	LED	5 ϕ Round Standard Bicolor LED	245
SLA5086	Transistor	Array for Source Drive General Purpose	174	SML1216C	LED	5 ϕ Round Standard Bicolor LED	245
SLA5088	Transistor	S-Distortion Correction Switch for CRT Display	182	SML1216W	LED	5 ϕ Round Standard Bicolor LED	245
SLA5089	Transistor	Array for "S" Distortion Correction Switch of CRT Display	172/182	SML12451W	LED	5 ϕ Round Bicolor LED	245
SLA5094	Transistor	Array for "S" Distortion Correction Switch of CRT Display	172/182	SML12460C	LED	2.5x5 Rectangular Type Bicolor LED	245
SLA5096	Transistor	Array for 3-Phase Motor Drive	178	SML1516W	LED	5 ϕ Round Standard Bicolor LED	245
SLA5201	Transistor	Array for 3-Phase Motor Drive	178	SML16716CN	LED	5 ϕ Round Standard Bicolor LED	245
SLA6012	Transistor	Array for 3-Phase Motor Drive	178	SML16716WN	LED	5 ϕ Round Standard Bicolor LED	245
SLA6020	Transistor	Array for 3-Phase Motor Drive	178	SML16751WN	LED	5 ϕ Round Bicolor LED	245
SLA6022	Transistor	Array for 3-Phase Motor Drive	178	SML16760CN	LED	2.5x5 Rectangular Type Bicolor LED	245
SLA6023	Transistor	Array for 3-Phase Motor Drive	178	SML1816W	LED	5 ϕ Round Standard Bicolor LED	245
SLA6024	Transistor	Array for 3-Phase Motor Drive	178	SML19416W	LED	5 ϕ Round Standard Bicolor LED	245
SLA6026	Transistor	Array for 3-Phase Motor Drive	178	SML19460C	LED	2.5x5 Rectangular Type Bicolor LED	245
SLA7022MU	IC	2-phase Stepper Motor Unipolar Driver IC	122	SML72420C	LED	3.3x6 Rectangular Type Bicolor LED, Direct mount available	245
SLA7024M	IC	2-phase Stepper Motor Unipolar Driver IC	126	SML72423C	LED	3.3x6 Bow-Shaped Type Bicolor LED, Direct mount available	246
SLA7026M	IC	2-phase Stepper Motor Unipolar Driver IC	126	SML72755C	LED	Egg-shaped Bicolor LED, Direct mount available	246
SLA7027MU	IC	2-phase Stepper Motor Unipolar Driver IC	126	SML72923C	LED	3.3x6 Bow-Shaped Type Bicolor LED, Direct mount available	246
SLA7029M	IC	2-phase Stepper Motor Unipolar Driver IC	122	SML78420C	LED	3.3x6 Rectangular Type Bicolor LED, Direct mount available	245
SLA7031M	IC	2-phase Stepper Motor Unipolar Driver IC	128	SML78423C	LED	3.3x6 Bow-Shaped Type Bicolor LED, Direct mount available	246
SLA7032M	IC	2-phase Stepper Motor Unipolar Driver IC	128	SML79255C	LED	Egg-shaped Bicolor LED, Direct mount available	246
SLA7033M	IC	2-phase Stepper Motor Unipolar Driver IC	128	SML79420C	LED	3.3x6 Rectangular Type Bicolor LED, Direct mount available	245
SLA7042M	IC	2-phase Stepper Motor Unipolar Driver IC	134	SML79423C	LED	3.3x6 Bow-Shaped Type Bicolor LED, Direct mount available	246
SLA7044M	IC	2-phase Stepper Motor Unipolar Driver IC	134	SML79455C	LED	Egg-shaped Bicolor LED, Direct mount available	246
SLA7050M	IC	2-phase Stepper Motor Unipolar Driver IC	130	SMLS79723C	LED	3.3x6 Bow-Shaped Type Bicolor LED, Direct mount available	246
SLA7051M	IC	2-phase Stepper Motor Unipolar Driver IC	130	SMLU12D16W	LED	5 ϕ Round Standard Bicolor LED	245
SLA7052M	IC	2-phase Stepper Motor Unipolar Driver IC	130	SMLU12E16C	LED	5 ϕ Round Standard Bicolor LED	245
SLA7060M	IC	2-phase Stepper Motor Unipolar Driver IC	138	SMLU12E16W	LED	5 ϕ Round Standard Bicolor LED	245
SLA7061M	IC	2-phase Stepper Motor Unipolar Driver IC	138	SMLU18D16C	LED	5 ϕ Round Standard Bicolor LED	245
SLA7062M	IC	2-phase Stepper Motor Unipolar Driver IC	138	SMLU18D16W	LED	5 ϕ Round Standard Bicolor LED	245
SLA7065M	IC	2-phase Stepper Motor Unipolar Driver IC	136	SMLU18E16C	LED	5 ϕ Round Standard Bicolor LED	245
SLA7066M	IC	2-phase Stepper Motor Unipolar Driver IC	136	SMLU72423C-S	LED	3.3x6 Bow-Shaped Type Bicolor LED, Direct mount available	246
SLA7067M	IC	2-phase Stepper Motor Unipolar Driver IC	136	SMLU72755C	LED	Egg-shaped Bicolor LED, Direct mount available	246
SLA7611M	IC	3-phase Stepper Motor Driver IC	142	SMLU78755C	LED	Egg-shaped Bicolor LED, Direct mount available	246
SLA8001	Transistor	Array for H-Bridge Motor Drive	176	SMLU79423C-S	LED	3.3x6 Bow-Shaped Type Bicolor LED, Direct mount available	246
SMA4020	Transistor	Array for Source Drive General Purpose	174	SPB-64S	Diode	Schottky Barrier Diode (Surface Mount)	214
SMA4021	Transistor	Array for Source Drive with Built-in Flywheel Diode	174	SPB-G34S	Diode	Schottky Barrier Diode (Surface Mount)	214
SMA4030	Transistor	Array for Sink Drive General Purpose	172	SPB-G54S	Diode	Schottky Barrier Diode (Surface Mount)	214
SMA4032	Transistor	Array for Sink Drive with Built-in Flywheel Diode	170	SPB-G56S	Diode	Schottky Barrier Diode (Surface Mount)	214
SMA4033	Transistor	Array for Sink Drive with Built-in Flywheel Diode	170	SPI-8001TW	IC	Surface mount Dual Output Switching Regulator IC	104
SMA4036	Transistor	Array for Sink Drive with Built-in Flywheel Diode	170	SPI-8002TW	IC	Surface mount Dual Output Switching Regulator IC	104
SMA5101	Transistor	Array for Sink Drive General Purpose	172	SPI-8010A	IC	Surface mount Switching Regulator IC	72
SMA5102	Transistor	Array for Sink Drive with Built-in Flywheel Diode	170	SPJ-63S	Diode	Schottky Barrier Diode (Surface Mount)	216
SMA5103	Transistor	Array for H-Bridge Motor Drive	176	SPJ-G53S	Diode	Schottky Barrier Diode (Surface Mount)	216
SMA5104	Transistor	Array for 3-Phase Motor Drive	178	SPX-62S	Diode	Ultrafast Recovery Diode (Surface Mount)	211
SMA5105	Transistor	Array for Sink Drive with Built-in Flywheel Diode	170	SPX-G32S	Diode	Ultrafast Recovery Diode (Surface Mount)	211
SMA5106	Transistor	Array for Sink Drive with Built-in Flywheel Diode	170	SPZ-G36	Diode	Power Zener Diode (Surface Mount)	221
SMA5112	Transistor	Array for 3-Phase Motor Drive	178	STA203A	Thyristor	Triac Array	194
SMA5114	Transistor	Array for Sink Drive with Built-in Flywheel Diode	170	STA221A	Thyristor	Triac Array	194
SMA5117	Transistor	Array for 3-Phase Motor Drive	178	STA301A	Transistor	Array for Sink Drive with Built-in Avalanche Diode (btwn C & E)	170
SMA5118	Transistor	Array for 3-Phase Motor Drive	178	STA302A	Transistor	Array for Source Drive General Purpose and 3-Phase Motor Drive	174/178
SMA5125	Transistor	Array for 3-Phase Motor Drive	178	STA303A	Transistor	Array for Sink Drive General Purpose and 3-Phase Motor Drive	172/178
SMA5127	Transistor	Array for 3-Phase Motor Drive	178	STA304A	Transistor	Array for 3-Phase Motor Drive	178
SMA5130	Transistor	Array for 3-Phase Motor Drive	178	STA305A	Transistor	Array for 3-Phase Motor Drive	178
SMA5131	Transistor	Array for 3-Phase Motor Drive	178	STA308A	Transistor	Array for Source Drive General Purpose	174
SMA5132	Transistor	Array for 3-Phase Motor Drive	178	STA309A	Transistor	Array for 3-Phase Motor Drive	178
SMA5133	Transistor	Array for 3-Phase Motor Drive	178	STA312A	Transistor	Array for Sink Drive General Purpose	172
SMA6010	Transistor	Array for 3-Phase Motor Drive	178	STA322A	Transistor	Array for Source Drive General Purpose	174
SMA6014	Transistor	Array for 3-Phase Motor Drive	178	STA351A	Transistor	Array for 3-Phase Motor Drive	178
SMA6080	Transistor	Array for 3-Phase Motor Drive	178	STA352A	Transistor	Array for 3-Phase Motor Drive	178
SMA6511	Transistor	Array for Stepper Motor drive with dual supply voltage switch	180	STA371A	Transistor	Array for Sink Drive with Built-in Avalanche Diode (btwn C & E)	170
SMA6512	Transistor	Array for Stepper Motor drive with dual supply voltage switch	180	STA401A	Transistor	Array for Sink Drive with Built-in Avalanche Diode (btwn C & E)	170
SMA7022MU	IC	2-phase Stepper Motor Unipolar Driver IC	122	STA402A	Transistor	Array for Source Drive General Purpose	174

Part Number Index in Alphanumeric Order

Part No.	Category	Description	Page
STA403A	Transistor	Arrey for Sink Drive General Purpose	172
STA404A	Transistor	Arrey for Sink Drive General Purpose	172
STA406A	Transistor	Arrey for Sink Drive with Built-in Avalanche Diode (btwn C & E)	170
STA408A	Transistor	Arrey for Source Drive General Purpose	174
STA412A	Transistor	Arrey for Sink Drive General Purpose	172
STA413A	Transistor	Arrey for Sink Drive with Built-in Avalanche Diode (btwn C & E)	170
STA421A	Transistor	Arrey for Source Drive General Purpose	172
STA431A	Transistor	Array for H-Bridge Motor Drive	176
STA434A	Transistor	Array for H-Bridge Motor Drive	176
STA435A	Transistor	Arrey for Sink Drive with Built-in Avalanche Diode (btwn C & E)	170
STA457C	Transistor	Array for H-Bridge Motor Drive	176
STA458C	Transistor	Array for H-Bridge Motor Drive	176
STA460C	Transistor	Arrey for Sink Drive with Built-in Avalanche Diode (btwn C & E)	170
STA471A	Transistor	Arrey for Sink Drive with Built-in Avalanche Diode (btwn C & E)	170
STA472A	Transistor	Arrey for Source Drive General Purpose	174
STA473A	Transistor	Arrey for Sink Drive General Purpose	173
STA475A	Transistor	Arrey for Sink Drive with Built-in Avalanche Diode (btwn C & E)	170
STA481A	Transistor	Arrey for Sink Drive with Built-in Avalanche Diode (btwn C & E)	170
STA485A	Transistor	Arrey for Sink Drive with Built-in Avalanche Diode (btwn C & E)	170
STA491A	Transistor	Array for H-Bridge Motor Drive	176
STA492A	Transistor	Array for H-Bridge Motor Drive	176
STA501A	Transistor	Arrey for Sink Drive General Purpose	172
STA506A	Transistor	Arrey for Sink Drive General Purpose	172
STA513A	Transistor	Array for 3-Phase Motor Drive	178
STA517A	Transistor	Array for 3-Phase Motor Drive	178
STA521A	Transistor	Array for "S" Distortion Correction Switch of CRT Display	182
STA524A	Transistor	Array for "S" Distortion Correction Switch of CRT Display	182
STA801M	IC	Dual Output Switching Regulator IC	98
STA802M	IC	Dual Output Switching Regulator IC	98
STA811M	IC	Switchig Type Regulator IC with Built-in Flywheel Diode	90
STA821M	IC	Switchig Type Regulator IC with Built-in Flywheel Diode	92
STR-A6131	IC	SMPS Primary Switcher	144
STR-A6132	IC	SMPS Primary Switcher	144
STR-A6151	IC	SMPS Primary Switcher	144
STR-A6153E	IC	SMPS Primary Switcher	144
STR-A6159	IC	SMPS Primary Switcher	144
STR-A6169	IC	SMPS Primary Switcher	144
SV 02YS	Diode	Asymmetrical Type Solicon Varistor (Axial)	222
SV 03YS	Diode	Asymmetrical Type Solicon Varistor (Axial)	222
SV 04YS	Diode	Asymmetrical Type Solicon Varistor (Axial)	222
SV 05YS	Diode	Asymmetrical Type Solicon Varistor (Axial)	222
SV 06YS	Diode	Asymmetrical Type Solicon Varistor (Axial)	222
SV-2SS	Diode	Symmetrical Type Solicon Varistor (Axial)	222
SV-3SS	Diode	Symmetrical Type Solicon Varistor (Axial)	222
SV-4SS	Diode	Symmetrical Type Solicon Varistor (Axial)	222
SZ-10N27	Diode	Power Zener Diode (Surface Mount)	221
SZ-10NN27	Diode	Power Zener Diode (Surface Mount)	221
TF321M	Thyristor	Thyristor	192
TF321M-A	Thyristor	Thyristor	192
TF321S	Thyristor	Thyristor	192
TF341M	Thyristor	Thyristor	192
TF341M-A	Thyristor	Thyristor	192
TF341S	Thyristor	Thyristor	192
TF361M	Thyristor	Thyristor	192
TF361M-A	Thyristor	Thyristor	192
TF361S	Thyristor	Thyristor	192
TF521M	Thyristor	Thyristor	192
TF521S	Thyristor	Thyristor	192
TF541M	Thyristor	Thyristor	192
TF541S	Thyristor	Thyristor	192
TF541S-A	Thyristor	Thyristor	192
TF561M	Thyristor	Thyristor	192
TF561S	Thyristor	Thyristor	192
TF561S-A	Thyristor	Thyristor	192

Part No.	Category	Description	Page
TF821M	Thyristor	Thyristor	192
TF821S	Thyristor	Thyristor	192
TF841M	Thyristor	Thyristor	192
TF841S	Thyristor	Thyristor	192
TF861M	Thyristor	Thyristor	192
TF861S	Thyristor	Thyristor	192
TFC561D	Thyristor	Thyristor with built-in Reverse Diode for HID Lamp Ignition	192
TFD312S-C	Thyristor	Thyristor with built-in Avalanche Diode	192
TFD312S-K	Thyristor	Thyristor with built-in Avalanche Diode	192
TFD312S-L	Thyristor	Thyristor with built-in Avalanche Diode	192
TFD312S-M	Thyristor	Thyristor with built-in Avalanche Diode	192
TFD312S-N	Thyristor	Thyristor with built-in Avalanche Diode	192
TFD312S-O	Thyristor	Thyristor with built-in Avalanche Diode	192
TM1041S-R	Thyristor	Triac	194
TM1061S-R	Thyristor	Triac	194
TM1241S-R	Thyristor	Triac	194
TM1261S-R	Thyristor	Triac	194
TM2541B-L	Thyristor	Triac	194
TM2561B-L	Thyristor	Triac	194
TM341S-R	Thyristor	Triac	194
TM361S-R	Thyristor	Triac	194
TM541S-R	Thyristor	Triac	194
TM561S-R	Thyristor	Triac	194
TM583S-L	Thyristor	Triac	194
TM883S-L	Thyristor	Triac	194
TMA104S-L	Thyristor	Triac	194
TMA106S-L	Thyristor	Triac	194
TMA124S-L	Thyristor	Triac	194
TMA126S-L	Thyristor	Triac	194
TMA164B-L	Thyristor	Triac	194
TMA164P-L	Thyristor	Triac	194
TMA164S-L	Thyristor	Triac	194
TMA166B-L	Thyristor	Triac	194
TMA166P-L	Thyristor	Triac	194
TMA166S-L	Thyristor	Triac	194
TMA204S-L	Thyristor	Triac	194
TMA206S-L	Thyristor	Triac	194
TMA34M-L	Thyristor	Triac	194
TMA34S-L	Thyristor	Triac	194
TMA36M-L	Thyristor	Triac	194
TMA36S-L	Thyristor	Triac	194
TMA54M-L	Thyristor	Triac	194
TMA54S-L	Thyristor	Triac	194
TMA56M-L	Thyristor	Triac	194
TMA56S-L	Thyristor	Triac	194
TMA84M-L	Thyristor	Triac	194
TMA84S-L	Thyristor	Triac	194
TMA86M-L	Thyristor	Triac	194
TMA86S-L	Thyristor	Triac	194
UX-F5B	Diode	High-Voltage Rectifier Diode for Inverter Type Microwave Oven	217
VR-60SS	Diode	Symmetrical Type Solicon Varistor (Axial)	222
VR-61SS	Diode	Symmetrical Type Solicon Varistor (Axial)	222

Discontinued Products and Service Parts (NND)

The shapes and electrical characteristics of the following products may be changed. When using them, check if they can be installed properly and also evaluate them.

Discontinued products

Part No.	Alternative	Category
2SA744	2SA1694	Transistor
2SA745	2SA1695	Transistor
2SA746	2SA1695	Transistor
2SA747	2SA1695	Transistor
2SA764	2SA1725	Transistor
2SA765	2SA1726	Transistor
2SA807	2SA1693	Transistor
2SA808	2SA1694	Transistor
2SA878	-	Transistor
2SA892	2SB1351	Transistor
2SA907	2SA1215	Transistor
2SA908	2SA1216	Transistor
2SA909	2SA1295	Transistor
2SA971	-	Transistor
2SA980	2SA1694	Transistor
2SA981	2SA1694	Transistor
2SA982	2SA1694	Transistor
2SA1067	-	Transistor
2SA1068	-	Transistor
2SA1102	2SA1693	Transistor
2SA1103	2SA1694	Transistor
2SA1104	2SA1694	Transistor
2SA1105	2SA1695	Transistor
2SA1106	2SA1695	Transistor
2SA1116	2SA1493	Transistor
2SA1117	2SA1494	Transistor
2SA1135	2SA1693	Transistor
2SA1169	2SA1493	Transistor
2SA1170	2SA1494	Transistor
2SA1187	-	Transistor
2SA1205	2SA1746	Transistor
2SA1355	2SA1262, 1488	Transistor
2SA1901	2SA1488	Transistor
2SB622	-	Transistor
2SB711	2SB1259, 1351	Transistor
2SB712	2SB1259, 1351	Transistor
2SB1005	2SB1257	Transistor
2SB1476	2SB1685	Transistor
2SB1586	2SB1687	Transistor
2SB1620	-	Transistor
2SB1624	2SB1685	Transistor
2SB1625	2SB1687	Transistor
2SB1626	2SB1686	Transistor
2SC1107	2SC3179, 3851	Transistor
2SC1108	2SC3851A	Transistor
2SC1109	2SC3179, 3851	Transistor
2SC1110	2SC3851A	Transistor
2SC1111	2SC4467~ 4468	Transistor
2SC1112	2SC4467~ 4468	Transistor
2SC1113	2SC4511~ 4512	Transistor
2SC1114	-	Transistor
2SC1115	2SC4468	Transistor
2SC1116	2SC4468	Transistor
2SC1402	2SC4467~ 4468	Transistor
2SC1403	2SC4467~ 4468	Transistor
2SC1436	-	Transistor
2SC1437	-	Transistor
2SC1440	-	Transistor
2SC1441	-	Transistor
2SC1442	-	Transistor
2SC1443	-	Transistor

Part No.	Alternative	Category
2SC1444	2SC4511~ 4512	Transistor
2SC1445	2SC4511~ 4512	Transistor
2SC1454	-	Transistor
2SC1477	-	Transistor
2SC1504	2SC2023	Transistor
2SC1577	2SC3833, 3831	Transistor
2SC1578	2SC3833, 3831	Transistor
2SC1579	2SC4706	Transistor
2SC1580	2SC4706	Transistor
2SC1584	2SC2921- 2922, 3264	Transistor
2SC1585	2SC2921- 2922, 3264	Transistor
2SC1586	2SC3264	Transistor
2SC1618	2SC4466- 4467	Transistor
2SC1619	2SC4466- 4467	Transistor
2SC1629	2SD2045	Transistor
2SC1664	2SD2642	Transistor
2SC1768	-	Transistor
2SC1777	-	Transistor
2SC1783	-	Transistor
2SC1786	-	Transistor
2SC1828	2SC3832, 3830	Transistor
2SC1829	-	Transistor
2SC1830	2SD2082, 2083	Transistor
2SC1831	-	Transistor
2SC1832	-	Transistor
2SC1888	2SC3852, 3852A	Transistor
2SC1889	2SC3852, 3852A	Transistor
2SC2022	2SC2023	Transistor
2SC2147	-	Transistor
2SC2198	2SC4024	Transistor
2SC2199	2SC4131	Transistor
2SC2256	-	Transistor
2SC2260	2SC4467	Transistor
2SC2261	2SC4467	Transistor
2SC2262	2SC4467	Transistor
2SC2302	2SC3832	Transistor
2SC2303	2SC3833	Transistor
2SC2304	2SC3833	Transistor
2SC2305	-	Transistor
2SC2306	2SC4140	Transistor
2SC2307	2SC3833	Transistor
2SC2317	2SD2016	Transistor
2SC2354	2SC2023	Transistor
2SC2364	-	Transistor
2SC2365	2SC3831	Transistor
2SC2491	2SC4024	Transistor
2SC2492	-	Transistor
2SC2493	-	Transistor
2SC2577	2SC4466	Transistor
2SC2578	2SC4467	Transistor
2SC2579	2SC4467	Transistor
2SC2580	2SC4468	Transistor
2SC2581	2SC4468	Transistor
2SC2607	2SC3857	Transistor
2SC2608	2SC3858	Transistor
2SC2665	2SC4466	Transistor
2SC2723	2SC4140	Transistor
2SC2761	-	Transistor
2SC2773	2SC3857	Transistor
2SC2774	2SC3858	Transistor
2SC2809	-	Transistor

Discontinued Products and Service Parts (NND)

Part No.	Alternative	Category
2SC2810A	2SC4518	Transistor
2SC2825	2SD2045	Transistor
2SC2838	-	Transistor
2SC2900	-	Transistor
2SC3409	2SC3679	Transistor
2SC3520	2SC4140	Transistor
2SC3706	-	Transistor
2SC3909	2SC3680	Transistor
2SC4023	2SC5124	Transistor
2SC4199	2SC5124	Transistor
2SC4199A	2SC5124	Transistor
2SC4302	2SC4301	Transistor
2SC4303	2SC5002	Transistor
2SC4303A	2SC5002	Transistor
2SC4327	-	Transistor
2SC4494	2SC4495	Transistor
2SC4756	2SC5002	Transistor
2SC4820	2SC4518	Transistor
2SD15	2SC4468	Transistor
2SD16	2SC4468	Transistor
2SD17	2SC4468	Transistor
2SD18	2SC4468	Transistor
2SD80	2SC4466, 4467	Transistor
2SD81	2SC4466, 4467	Transistor
2SD82	2SC4466, 4467	Transistor
2SD83	2SC4466, 4467	Transistor
2SD84	2SC4466, 4467	Transistor
2SD90	2SC3179, 3851, 3851A	Transistor
2SD91	2SC3179, 3851, 3851A	Transistor
2SD92	2SC3179, 3851, 3851A	Transistor
2SD93	2SC3179, 3851, 3851A	Transistor
2SD94	2SC3179, 3851, 3851A	Transistor
2SD163	2SC4468	Transistor
2SD164	2SC4468	Transistor
2SD165	2SC4468	Transistor
2SD166	2SC4468	Transistor
2SD201	2SC4466, 4467	Transistor
2SD202	2SC4466, 4467	Transistor
2SD203	2SC4466, 4467	Transistor
2SD211	2SC4468	Transistor
2SD212	2SC4468	Transistor
2SD213	2SC4468	Transistor
2SD214	2SC4468	Transistor
2SD219	2SC3179, 3851, 3851A	Transistor
2SD219F	2SC3179, 3851, 3851A	Transistor
2SD220	2SC3179, 3851, 3851A	Transistor
2SD220F	2SC3179, 3851, 3851A	Transistor
2SD221	2SC3179, 3851, 3851A	Transistor
2SD221F	2SC3179, 3851, 3851A	Transistor
2SD222	2SC3179, 3851, 3851A	Transistor
2SD223	2SC3179, 3851, 3851A	Transistor
2SD224	2SC3179, 3851, 3851A	Transistor
2SD236	2SC3179, 3851, 3851A	Transistor
2SD237	2SC3179, 3851, 3851A	Transistor
2SD238	2SC3179, 3851, 3851A	Transistor
2SD241	2SC3179, 3851, 3851A	Transistor
2SD242	2SC3179, 3851, 3851A	Transistor
2SD243	2SC3179, 3851, 3851A	Transistor
2SD244	2SC3179, 3851, 3851A	Transistor
2SD256	2SC3179, 3851, 3851A	Transistor
2SD257	2SC3179, 3851, 3851A	Transistor
2SD258	2SC3179, 3851, 3851A	Transistor
2SD259	2SC3179, 3851, 3851A	Transistor
2SD419	2SD1769, 1785	Transistor
2SD420	2SD1769, 1785	Transistor

Part No.	Alternative	Category
2SD421	2SD1769, 1785	Transistor
2SD556	2SC4468	Transistor
2SD557	2SC4468	Transistor
2SD593	2SC4020	Transistor
2SD594	2SC4020	Transistor
2SD605	-	Transistor
2SD606	-	Transistor
2SD614	2SD1769, 1785	Transistor
2SD615	2SD1769, 1785	Transistor
2SD617	2SD2082	Transistor
2SD721	2SD2081	Transistor
2SD722	2SD2081	Transistor
2SD807	2SC3679	Transistor
2SD810	2SC4024	Transistor
2SD971	-	Transistor
2SD972	2SD1796	Transistor
2SD1031	2SD1769, 1785	Transistor
2SD1170	2SD2045	Transistor
2SD1532	2SD2015	Transistor
2SD2231	2SD2641	Transistor
2SD2437	2SD2643	Transistor
2SD2488	-	Transistor
2SJ426	-	MOSFET
2SK979	-	MOSFET
2SK1193	-	MOSFET
2SK1343	-	MOSFET
2SK1367	2SK3199	MOSFET
2SK1368	2SK2701	MOSFET
2SK1369	2SK2704	MOSFET
2SK1370	2SK2706	MOSFET
2SK1711	2SK2778	MOSFET
2SK1713	-	MOSFET
2SK1714	-	MOSFET
2SK1715	-	MOSFET
2SK2156A	-	MOSFET
2SK2207	2SK2943	MOSFET
2SK2208	2SK2945	MOSFET
2SK2238	2SK2803	MOSFET
2SK2239	2SK3199	MOSFET
2SK2240	2SK3199	MOSFET
2SK2241	2SK2702	MOSFET
2SK2242	2SK2702	MOSFET
2SK2243	2SK2702	MOSFET
2SK2244	2SK2704	MOSFET
2SK2245	2SK2705	MOSFET
2SK2804	2SK3199	MOSFET
CTB-23L	FMB-24L	Schottky-barrier diode
CTB-24	FMB-24	Schottky-barrier diode
CTB-24L	FMB-24L	Schottky-barrier diode
CTB-3154	-	Schottky-barrier diode
CTB-3204	-	Schottky-barrier diode
CTB-33	FMB-33	Schottky-barrier diode
CTB-33S	FMB-33S	Schottky-barrier diode
CTB-34	FMB-34	Schottky-barrier diode
CTB-34D	FMB-34M	Schottky-barrier diode
CTB-34M	FMB-34M	Schottky-barrier diode
CTB-34S	FMB-34S	Schottky-barrier diode
CTB-34T	FMB-34	Schottky-barrier diode
CTG-12S	FMG-12S	Ultrafast Recovery Diode
CTG-14R	FMG-14R	Ultrafast Recovery Diode
CTG-14S	FMG-14S	Ultrafast Recovery Diode
CTG-21R	FMG-22R	Ultrafast Recovery Diode
CTG-21S	FMG-22S	Ultrafast Recovery Diode
CTG-22R	FMG-22R	Ultrafast Recovery Diode
CTG-22S	FMG-22S	Ultrafast Recovery Diode

Part No.	Alternative	Category
CTG-23R	FMG-23R	Ultrafast Recovery Diode
CTG-23S	FMG-23S	Ultrafast Recovery Diode
CTG-24R	FMG-24R	Ultrafast Recovery Diode
CTG-24S	FMG-24S	Ultrafast Recovery Diode
CTG-24U	FMG-24U	Ultrafast Recovery Diode
CTG-26S	FMG-26S	Ultrafast Recovery Diode
CTG-2TR	FMG-22S	Ultrafast Recovery Diode
CTG-2TS	FMG-24U	Ultrafast Recovery Diode
CTG-31R	FMG-32R	Ultrafast Recovery Diode
CTG-31S	FMG-32S	Ultrafast Recovery Diode
CTG-32R	FMG-32R	Ultrafast Recovery Diode
CTG-32S	FMG-32S	Ultrafast Recovery Diode
CTG-32U	FMG-33U	Ultrafast Recovery Diode
CTG-33R	FMG-33R	Ultrafast Recovery Diode
CTG-33S	FMG-33S	Ultrafast Recovery Diode
CTG-34R	FMG-34R	Ultrafast Recovery Diode
CTG-34S	FMG-34S	Ultrafast Recovery Diode
CTG-34U	FMG-34U	Ultrafast Recovery Diode
CTG-3TS	FMG-32S	Ultrafast Recovery Diode
CTG-G12S	FML-G12S	Ultrafast Recovery Diode
CTL-12S	FML-12S	Ultrafast Recovery Diode
CTL-21S	FML-21S	Ultrafast Recovery Diode
CTL-22S	FML-22S	Ultrafast Recovery Diode
CTL-32S	FML-32S	Ultrafast Recovery Diode
CTL-33S	FML-33S	Ultrafast Recovery Diode
CTL-34S	FML-34S	Ultrafast Recovery Diode
CTL-G12S	FML-G12S	Ultrafast Recovery Diode
CTM-21R	FMM-22R	Rectifier diode
CTM-21S	FMM-22S	Rectifier diode
CTM-22R	FMM-22R	Rectifier diode
CTM-22S	FMM-22S	Rectifier diode
CTM-22U	FMM-24U	Rectifier diode
CTM-24R	FMM-24R	Rectifier diode
CTM-24S	FMM-24S	Rectifier diode
CTM-26R	FMM-26R	Rectifier diode
CTM-26S	FMM-26S	Rectifier diode
CTM-26U	-	Rectifier diode
CTM-31R	FMM-31R	Rectifier diode
CTM-31S	FMM-31S	Rectifier diode
CTM-32R	FMM-32R	Rectifier diode
CTM-32S	FMM-32S	Rectifier diode
CTM-34R	FMM-34R	Rectifier diode
CTM-34S	FMM-34S	Rectifier diode
CTM-36R	FMM-36R	Rectifier diode
CTM-36S	FMM-36S	Rectifier diode
CTP-G2FR	FMP-G2FS	Damper diode
CTS-3FU	FMP-3FU	Damper diode
CTS-G3FR	FMQ-G5FMS	Damper diode
CTU-12R	FMU-12R	Fast Recovery Diode
CTU-12S	FMU-12S	Fast Recovery Diode
CTU-21R	FMU-21R	Fast Recovery Diode
CTU-21S	FMU-21S	Fast Recovery Diode
CTU-22R	FMU-22R	Fast Recovery Diode
CTU-22S	FMU-22S	Fast Recovery Diode
CTU-24R	FMU-24R	Fast Recovery Diode
CTU-24S	FMU-24S	Fast Recovery Diode
CTU-26R	FMU-26R	Fast Recovery Diode
CTU-26S	FMU-26S	Fast Recovery Diode
CTU-31R	FMU-32R	Fast Recovery Diode
CTU-31S	FMU-32S	Fast Recovery Diode
CTU-32R	FMU-32R	Fast Recovery Diode
CTU-32S	FMU-32S	Fast Recovery Diode
CTU-34R	FMU-34R	Fast Recovery Diode
CTU-34S	FMU-34S	Fast Recovery Diode
CTU-36R	FMU-36R	Fast Recovery Diode

Part No.	Alternative	Category
CTU-36S	FMU-36S	Fast Recovery Diode
CTU-38R	-	Fast Recovery Diode
CTU-38S	-	Fast Recovery Diode
CTU-G26R	FMU-G26S	Fast Recovery Diode
CTU-G2DR	FMU-G2FS	Fast Recovery Diode
CTU-G3DR	-	Fast Recovery Diode
CTX-12SL	FMX-12SL	Ultrafast Recovery Diode
EK 02	-	Schottky-barrier diode
EK 12	-	Schottky-barrier diode
EP01Z	-	Fast Recovery Diode
ET014	ET0141	PNPN switch element
FMB-22L	-	Schottky-barrier diode
FMB-23L	-	Schottky-barrier diode
FMB-32	-	Schottky-barrier diode
FMB-32M	-	Schottky-barrier diode
FMB-G12L	-	Schottky-barrier diode
FMB-G22H	-	Schottky-barrier diode
FMS-3FUM	-	Damper diode
RBA-1002	RBV-4102	Rectifier diode
RBA-1004B	-	Rectifier diode
RBA-401	RBV-401	Rectifier diode
RBA-402	RBV-402	Rectifier diode
RBA-402L	RBV-402L	Rectifier diode
RBA-404B	RBV-404B	Rectifier diode
RBA-406B	RBV-406B	Rectifier diode
SDC01	SDC03	Surface-mount transistor array for sink driver
SDK01M	SDK03M	2-phase stepper motor unipolar driver IC
SEL1112R	SEL4117R	2φ round special shape deep red LED lamp
SEL1123R	SEL1124R	1x5 rectangular type deep red LED lamp
SEL1131R	-	Triangle-type deep red LED lamp
SEL1132R	-	Triangle-type deep red LED lamp
SEL1134R	-	Triangle-type deep red LED lamp
SEL1142R	-	2x2 rectangular type deep red LED lamp
SEL1215R	-	5φ round narrow view angle red LED lamp
SEL1310E	SEL1410E	5φ round green LED lamp
SEL1310G	SEL1410G	5φ round green LED lamp
SEL1311G	SEL1411G	5φ cylinder green LED lamp
SEL1312G	SEL4417G	2φ round special shape green LED lamp
SEL1320G	SEL1420G	2x5 rectangular type green LED lamp
SEL1321G	SEL1421G	3x5 rectangular type green LED lamp
SEL1323G	SEL1424G	1x5 rectangular type green LED lamp
SEL1324G	SEL1424G	1x5 rectangular type green LED lamp
SEL1331G	-	Triangle green LED lamp
SEL1332G	-	Triangle green LED lamp
SEL1334G	-	Triangle green LED lamp
SEL1342G	-	2x2 rectangular type green LED lamp
SEL1650CM	-	5φ round narrow view angle GaAlAs red LED lamp
SEL1723Y	SEL1724Y	1x5 rectangular type yellow LED lamp
SEL1731Y	-	Triangle yellow LED lamp
SEL1742Y	-	2x2 rectangular type yellow LED lamp
SEL1823D	SEL1824D	1x5 rectangular type amber LED lamp
SEL1842D	-	2x2 rectangular type amber LED lamp
SEL1915C	-	5φ round narrow view angle orange LED lamp
SEL1923D	SEL1924D	1x5 rectangular type orange LED lamp
SEL1942D	-	2x2 rectangular type orange LED lamp
SEL1E10CM	SELU1E10CXM/SELU1E50CM	5φ round blue LED lamp
SEL2310E	SEL2410E	3φ round green LED lamp
SEL2310G	SEL2410G	3φ round green LED lamp
SEL2311G	SEL2411G	3φ cylinder green lamp
SEL3110R	SEL2110R/SEL6210R	3φ round red LED lamp
SEL3110S	SEL2110S/SEL6210S	3φ round red LED lamp
SEL3210R	SEL2210R/SEL6210R	3φ round red LED lamp
SEL3210S	SEL2210S/SEL6210S	3φ round red LED lamp
SEL3213C	SEL2213C	3φ for Lighting panel red LED lamp
SEL3410E	SEL2410E/SEL6410E	3φ round green LED lamp

Discontinued Products and Service Parts (NND)

Part No.	Alternative	Category
SEL3410G	SEL2410G	3 ϕ round green LED lamp
SEL3413E	SEL2413E	3 ϕ for Lighting panel green LED lamp
SEL3510C	SEL2510C/SEL6510C	3 ϕ round pure green LED lamp
SEL3510G	SEL2510G/SEL6510G	3 ϕ round pure green LED lamp
SEL3710K	SEL2710K/SEL6710K	3 ϕ round yellow LED lamp
SEL3710Y	SEL2710Y/SEL6710Y	3 ϕ round yellow LED lamp
SEL3713K	SEL2713K	3 ϕ for Lighting panel yellow LED lamp
SEL3810A	SEL2910A/SEL6810A	3 ϕ round amber LED lamp
SEL3810D	SEL2910D/SEL6810D	3 ϕ round amber LED lamp
SEL3813A	SEL2813A	3 ϕ for Lighting panel amber LED lamp
SEL3910A	SEL2910A/SEL6910A	3 ϕ round orange LED lamp
SEL3910D	SEL2910D/SEL6910D	3 ϕ round orange LED lamp
SEL3913K	SEL2913K	3 ϕ for Lighting panel orange LED lamp
SEL3E10C	SELU2E10C	3 ϕ round blue LED lamp
SEL4225RM	SEL4225R	2x4 rectangular red LED lamp
SEL4310E	SEL4410E	4 ϕ round green LED lamp
SEL4310G	SEL4410G	4 ϕ round green LED lamp
SEL4427E	SEL4427EP	Bow-shaped green LED lamp
SI-3018LS	SI-3018LSA	Surface-mount linear regulator IC
SI-3018LS	SI-3018LSA	Surface-mount linear regulator IC
SI-3025LS	SI-3025LSA	Surface-mount linear regulator IC
SI-3025LS	SI-3025LSA	Surface-mount linear regulator IC
SI-3033LS	SI-3033LSA	Surface-mount linear regulator IC
SI-3052P	SI-3050J	Linear regulator IC
SI-3122P	SI-3120J	Linear regulator IC
SI-3152P	SI-3150J	Linear regulator IC
SI-3242P	-	Linear regulator IC
SI-7115B	SLA7032M	2-phase stepper motor unipolar driver IC
SI-7200E	-	Stepper motor driver IC
SI-7200M	-	2-phase stepper motor bipolar driver IC
SI-7201A	-	Stepper motor driver IC
SI-7202A	-	Stepper motor driver IC
SI-7230E	-	Stepper motor driver IC
SI-7230M	-	2-phase stepper motor bipolar driver IC
SI-7235E	-	Stepper motor driver IC
SI-7300A	SLA7032M	2-phase stepper motor unipolar driver IC
SI-7330A	SLA7033M	2-phase stepper motor unipolar driver IC
SI-7500A	-	5-phase stepper motor driver IC
SI-7600D	SI-7600	3-phase stepper motor driver IC
SI-8011	-	Switching regulator IC
SI-8012	-	Switching regulator IC
SI-8013	-	Switching regulator IC
SI-8014	-	Switching regulator IC
SI-8020	-	Control IC for 2-pack type switching regulator
SI-8021	-	Control IC for 2-pack type switching regulator
SI-8022	-	Control IC for 2-pack type switching regulator
SI-8023	-	Control IC for 2-pack type switching regulator
SI-8100D	-	Switching regulator IC
SI-8211L	-	Switching regulator IC with coil
SI-8213L	-	Switching regulator IC with coil
SID1010BXM	-	Infrared LED
SID1010CM2	-	Infrared LED
SID1H10CXM	-	Infrared LED
SID1K10CM2	-	Infrared LED
SLA3001M	-	3-output type regulator IC
SLA7022M	SLA7022MU	2-phase stepper motor unipolar driver IC
SLA7027M	SLA7027MU	2-phase stepper motor unipolar driver IC
SLH30	-	LED accessory
SLH50	-	LED accessory
SLS34	-	LED accessory
SLS36	-	LED accessory
SLS54	-	LED accessory
SMA5126	-	MOSFET array
SMA7022M	SMA7022MU	2-phase stepper motor unipolar driver IC
STR2005	SI-8050S	Switching regulator IC

Part No.	Alternative	Category
STR2012	SI-8120S	Switching regulator IC
STR2013	-	Switching regulator IC
STR2015	SI-8150S	Switching regulator IC
STR2024	-	Switching regulator IC
STR7001	-	Power stage IC for 2-pack type switching regulator
STR7002	-	Power stage IC for 2-pack type switching regulator
STR7003	-	Power stage IC for 2-pack type switching regulator
STR7101	-	Power stage IC for 2-pack type switching regulator
STR7102	-	Power stage IC for 2-pack type switching regulator
STR7103	-	Power stage IC for 2-pack type switching regulator
STR9005	-	Linear regulator IC
STR9012	-	Linear regulator IC
STR9015	-	Linear regulator IC
TF320M	TF321M	Thyristor
TF320M-A	TF321M-A	Thyristor
TF325P	-	Thyristor
TF620M	TF861M	Thyristor
TF640M	TF841M	Thyristor
TFD312M	TFD312S SIRI-ZU	Thyristor with built-in avalanche diode
TFD315M	TFD312S	Thyristor with built-in avalanche diode
TFH341S	-	High-speed thyristor
TFH361S	-	High-speed thyristor
TGH340M	-	High-speed thyristor
TM1041M-L	TM1041S-L	Triac
TM1061M-L	TM1061S-L	Triac
TM1241M-L	TM1241S-L	Triac
TM1261M-L	TM1261S-L	Triac
TM1262B-R	-	Triac
TM1641M-L	TM1641S-L	Triac
TM1661M-L	TM1661S-L	Triac

■ Service Parts (Not for New Design)

Part No.	Alternative	Category
2SA768	2SA1262, 1488, 1488A	Transistor
2SA769	2SA1262, 1488, 1488A	Transistor
2SA770	2SA1725, 1726	Transistor
2SA771	2SA1725, 1726	Transistor
2SA957	2SA1667, 1668	Transistor
2SA958	2SA1667, 1668	Transistor
2SA1489	2SA1693	Transistor
2SA1490	2SA1694	Transistor
2SA1491	2SA1695	Transistor
2SA1643	2SA1725	Transistor
2SA1670	2SA1907	Transistor
2SA1671	2SA1908	Transistor
2SA1672	2SA1909	Transistor
2SB1621	-	Transistor
2SB1624	2SB1685	Transistor
2SB1625	2SB1687	Transistor
2SB1626	2SB1686	Transistor
2SC1826	2SC3179, 3851, 3851A	Transistor
2SC1827	2SC3179, 3851, 3851A	Transistor
2SC1983	2SC3852, 3852A	Transistor
2SC1984	2SC3852, 3852A	Transistor
2SC1985	2SC4511, 4512	Transistor
2SC1986	2SC4511, 4512	Transistor
2SC2167	2SC4381, 4382	Transistor
2SC2168	2SC4381, 4382	Transistor
2SC2315	2SD2642	Transistor
2SC2316	2SD2642	Transistor
2SC2810	2SC3890	Transistor
2SC3300	2SC4131	Transistor
2SC3853	2SC4466	Transistor
2SC3854	2SC4467	Transistor
2SC3855	2SC4468	Transistor
2SC4385	2SC5099	Transistor
2SC4386	2SC5100	Transistor
2SC4387	2SC5101	Transistor
2SC4503	2SD2083	Transistor
2SC4558	2SD2642	Transistor
2SC4820	2SC4518	Transistor
2SC5003	-	Transistor
2SD2493	2SD2641	Transistor
2SD2494	2SD2643	Transistor
2SD2495	2SD2642	Transistor
2SK1366	2SK2803	MOSFET
FML-11S	-	Ultrafast Recovery Diode
FML-21S	-	Ultrafast Recovery Diode
FML-G26S	FMD-G26S	Ultrafast Recovery Diode
FMU-11S	-	Fast Recovery Diode
FMU-31R	-	Fast Recovery Diode
FMU-32U	-	Fast Recovery Diode
PZ 127	-	Power zener diode
PZ 427	-	Power zener diode
RL 2A	RD 2A	Ultrafast Recovery Diode
SAP08N	SAP09N	Transistor
SAP08P	SAP09P	Transistor
SHV-08UK	-	High-voltage rectifier diode
SHV-10K	-	High-voltage rectifier diode
SHV-10UK	-	High-voltage rectifier diode
SHV-12K	-	High-voltage rectifier diode
SHV-12UK	-	High-voltage rectifier diode
SHV-16KM	-	High-voltage rectifier diode
SHV-16UK	-	High-voltage rectifier diode

Part No.	Alternative	Category
STA341M	-	Transistor array
STA342M	-	Transistor array
STA414A	-	Transistor array for sink drive

MEMO



Sanken Electric Co., Ltd.

1-11-1 Nishi-Ikebukuro, Toshima-ku, Tokyo
Tel: 81-3-3986-6164
Fax: 81-3-3986-8637

Overseas Sales Offices

● **Asia**

Singapore

Sanken Electric Singapore Pte. Ltd.

150 Beach Road, #14-03
The Gateway West
Singapore 189720, Singapore
Tel: 65-6291-4755
Fax: 65-6297-1744

China

Sanken Electric Hong Kong Co., Ltd.

Suite 1026 Ocean Centre, Canton Road, Tsimshatsui,
Kowloon, Hong Kong
Tel: 852-2735-5262
Fax: 852-2735-5494

Sanken Electric (Shanghai) Co., Ltd.

Room 3202, Maxdo Centre, Xingyi Road 8
Changning district, Shanghai, China
Tel: 86-21-5208-1177
Fax: 86-21-5208-1757

Korea

Sanken Electric Korea Co., Ltd.

MIRAE ASSET LIFE BLDG., 6F
168, Kongduk-dong, Mapo-ku, Seoul, 121-705, Korea
Tel: 82-2-714-3700
Fax: 82-2-3272-2145

Taiwan

Taiwan Sanken Electric Co., Ltd.

Room 1801, 18th Floor, 88 Jung Shiau East Road,
Sec. 2, Taipei 100, Taiwan R.O.C.
Tel: 886-2-2356-8161
Fax: 886-2-2356-8261

● **North America**

Allegro MicroSystems, Inc.

115 Northeast Cutoff, Worcester, MA 01615
General Information
Tel: (508)853-5000
Fax: (508)853-3353

● **Europe**

Allegro MicroSystems Europe Limited

Balfour House, Churchfield Road Walton-on-Thames,
Surrey KT12 2TD, U.K.
Tel: 44-1932-253355
Fax: 44-1932-246622

● This is notification that you, as purchaser of the products/technology, are not allowed to perform any of the following:

1. Resell or retransfer these products/technology to any party intending to disturb international peace and security.
2. Use these products/technology yourself for activities disturbing international peace and security.
3. Allow any other party to use these products/technology for activities disturbing international peace and security.

Also, as purchaser of these products/technology, you agree to follow the procedures for the export or transfer of these products/technology, under the Foreign Exchange and Foreign Trade Law, when you export or transfer the products/technology abroad.