

LA1230

Monolithic Linear Integrated Circuit
FM IF SYSTEM

The LA1230 is a high density monolithic IC developed by SANYO for use in FM IF system, and it provides most of the functions required in FM IF stages of an FM tuner.

In the block diagram shown on page 6, an internal functional block diagram of the LA1230 and its peripheral circuits for general application are given.

The IF amplifier/limiter stage consists of six stages of dual-ended differential amplifiers having good AMR characteristic, and a signal meter drive stage coupled in parallel with the amplifier/limiter stage is composed of three stages of level detectors and a drive circuit for extending the linearity range of the signal meter deflection.

The FM detector stage consists of a double-balanced quadrature detector circuit and has an AF preamplifier and a muting control circuit as auxiliary circuits. The muting drive stage contains a level detector responsive to S/N in the carrier signal under a low signal input condition, a circuit to detect a DC output signal of an S-curve supplied from the FM detector during tuning-off operation, and a drive circuit, and operates to reduce interstation noise and other noises such as transient sound which would be caused by muting operations (in conventional circuitry).


The AFC output and tuning meter drive stage have an additional clamp circuit which clamps the output voltage to a level of $\pm 0.7V$, thereby improving the AFC operation range, variations from the tuning meter deflection and symmetrical characteristics for the above.

A DC-stabilized circuit having approximately constant current consumption against a power supply voltage variation of 8.5V to 16V is also added.

Functions

1. IF amplification and limitation
2. Quadrature detector
3. AF preamplifier
4. Muting operation at low signal input
5. Muting operation at tuning in/off operation
6. Signal meter drive output
7. AFC and FM tuning meter drive output
8. Delayed AGC drive output
9. Multipath output

Case Outline 3006
(unit:mm)



Features

1. High limiting sensitivity : (12uV typ.)
 2. Low distortion : (*0.1% typ.)
 3. High demodulation output (350mV typ.)
 4. Muting circuit with less transient noise.
 5. Signal meter drive output proportional to signal input level in dB.
 6. Tuning meter drive output having good symmetry.
 7. Band limitable, clamped AFC output
 8. Delayed AGC drive output for Front End circuit.
 9. Stabilized DC circuit for operating voltage range of 9 to 14 V.
- * Distortion ratio depends upon phase linearity of the phase-shift circuit used.

These specifications are subject to change without notice.

TOKYO SANYO ELECTRIC CO., LTD. SEMICONDUCTOR DIVISION

www.DataSheet4U.com

